

## ARCAL N2-2

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 300-15-027ALBNL-ARC Issue date: 2-6-2022 Revision date: 17-11-2022 Supersedes version of: 2-6-2022 Version: 1.1

## Warning



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name SDS no : ARCAL N2-2

Consumer use.

## no : 300-15-027ALBNL-ARC

## 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses

Industrial and professional uses. Perform risk assessment prior to use.
 Contact supplier for more information on uses.
 Industrial and professional use for chemical analysis, calibration, (routine) quality control, laboratory use, under controlled conditions.

Uses advised against

Uses other than those listed above are not supported, contact your supplier for more information on other uses.

#### 1.3. Details of the supplier of the safety data sheet

#### THE NETHERLANDS:

AIR LIQUIDE BV De Witbogt 1 5652 AG Eindhoven the Netherlands-Nederland

#### BELGIUM:

L'AIR LIQUIDE BELGE S.A./N.V. Avenue de Bourget / Bourgetlaan 44 1130 Bruxelles-Brussel Belgium-Belgique-België

#### LUXEMBURG:

L'AIR LIQUIDE LUXEMBOURG S.A. ZONE P.E.D.-B.P.20 L-4801 RODANGE Luxemburg

infosafetydatasheet.albv@airliquide.com www.airliquide-benelux.com

#### 1.4. Emergency telephone number

Emergency telephone number

: NL: +31 (0)40 250 35 03 / BE: +32 (0)2 431 72 00 / LUX: +352 50 62 63 1



## ARCAL N2-2

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 300-15-027ALBNL-ARC

Country	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 1120 Bruxelles/Brussel	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)
Luxembourg	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 1120 Bruxelles/Brussel	+352 8002 5500	Free telephone number with a 24/7 access. Experts answer all urgency questions on dangerous products in French, or German
Netherlands	Nationaal Vergiftigingen Informatie Centrum	Huispostnummer B.00.118 Postbus 85500 3508 GA Utrecht	+31 88 755 80 00	Only for the purpose of informing medical personnel in cases of acute intoxications

## **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

## Classification according to Regulation (EC) No. 1272/2008 [CLP]

classification according	to Regulation (LC) NO. 12	
Physical hazards	Gases under pressure : Co	Compressed gas H280
2.2. Label elements		
Labelling according to R	egulation (EC) No. 1272/20	008 [CLP]
Hazard pictograms (CLP)	:	GHS04
Signal word (CLP)	:	: Warning
Hazard statements (CLP) Precautionary statements		: H280 - Contains gas under pressure; may explode if heated.
- Storage	:	: P403 - Store in a well-ventilated place.
2.3. Other hazards		
		Asphyxiant in high concentrations.
		Not classified as PBT or vPvB.
		The substance/mixture has no endocrine disrupting properties.

## **SECTION 3: Composition/information on ingredients**

#### 3.1. Substances

Not established.



ARCAL N2-2

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 300-15-027ALBNL-ARC

### 3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Argon	CAS-No.: 7440-37-1 EC-No.: 231-147-0 EC Index-No.: REACH-no: *1	98	Press. Gas (Comp.), H280
Nitrogen	CAS-No.: 7727-37-9 EC-No.: 231-783-9 EC Index-No.: REACH-no: *1	1,8 – 2,2	Press. Gas (Comp.), H280

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

\*1: Listed in Annex IV / V REACH, exempted from registration.

\*3: Registration not required: Substance manufactured or imported < 1t/y.

## SECTION 4: First aid measures

## 4.1. Description of first aid measures

- Inhalation	: Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact	: Adverse effects not expected from this product.
- Eye contact	: Adverse effects not expected from this product.
- Ingestion	: Ingestion is not considered a potential route of exposure.
4.2 Most important symptoms and effects, both acute and delayed	

4.2. Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation. See section 11.

#### 4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
- Suitable extinguishing media	: Water spray or fog. Product does not burn, use fire control measures appropriate for the surrounding fire.
- Unsuitable extinguishing media	: Do not use water jet to extinguish.
5.2. Special hazards arising from the substance of	or mixture
Specific hazards Hazardous combustion products	<ul><li>Exposure to fire may cause containers to rupture/explode.</li><li>None.</li></ul>
5.3. Advice for firefighters	
Specific methods	<ul> <li>Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.</li> <li>If possible, stop flow of product.</li> <li>Use water spray or fog to knock down fire fumes if possible.</li> <li>Move containers away from the fire area if this can be done without risk.</li> </ul>



ARCAL N2-2

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 300-15-027ALBNL-ARC

Special protective equipment for fire fighters	<ul> <li>In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.</li> <li>Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.</li> <li>Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.</li> </ul>

### SECTION 6: Accidental release measures

For non-emergency personnel	: Act in accordance with local emergency plan.
0 71	Try to stop release.
	Evacuate area.
	Ensure adequate air ventilation.
	Prevent from entering sewers, basements and workpits, or any place where its
	accumulation can be dangerous.
	Stay upwind.
	See section 8 of the SDS for more information on personal protective equipment.
For emergency responders	: Wear self-contained breathing apparatus when entering area unless atmosphere is proved
	to be safe.
	Oxygen detectors should be used when asphyxiating gases may be released.
	See section 5.3 of the SDS for more information.
6.2. Environmental precautions	
	Try to stop release.
6.3. Methods and material for containment and cle	paning up
	Ventilate area.
6.4. Reference to other sections	
	See also sections 8 and 13.

# SECTION 7: Handling and storage 7.1. Precautions for safe handling Safe use of the product : Do not breathe gas. Avoid release of product into work area. The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations.

Ensure the complete gas system was (or is regularily) checked for leaks before use. Do not smoke while handling product.

Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.

Avoid suck back of water, acid and alkalis.



ARCAL N2-2

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 300-15-027ALBNL-ARC

Safe handling of the gas receptacle	<ul> <li>Refer to supplier's container handling instructions.</li> <li>Do not allow backfeed into the container.</li> <li>Protect containers from physical damage; do not drag, roll, slide or drop.</li> <li>When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.</li> <li>Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.</li> <li>If user experiences any difficulty operating valve discontinue use and contact supplier.</li> <li>Never attempt to repair or modify container valves or safety relief devices.</li> <li>Damaged valves should be reported immediately to the supplier.</li> <li>Keep container valve outlets clean and free from contaminants particularly oil and water.</li> <li>Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.</li> <li>Close container valve after each use and when empty, even if still connected to equipment.</li> <li>Never attempt to transfer gases from one cylinder/container to another.</li> <li>Never use direct flame or electrical heating devices to raise the pressure of a container.</li> <li>Do not remove or deface labels provided by the supplier for the identification of the content of the container.</li> </ul>
	Open valve slowly to avoid pressure shock.
7.2. Conditions for safe storage, including any in	
	Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials.
7.3. Specific end use(s)	
	None.

None.

8.1. Control parameters	
	· Name and labor
OEL (Occupational Exposure Limits)	: None available.
DNEL (Derived-No Effect Level)	: None available.
PNEC (Predicted No-Effect Concentration)	: None available.
8.2. Exposure controls	
8.2.1. Appropriate engineering controls	
	Provide adequate general and local exhaust ventilation.
	Systems under pressure should be regularily checked for leakages.
	Oxygen detectors should be used when asphyxiating gases may be released.
	Consider the use of a work permit system e.g. for maintenance activities.
8.2.2. Individual protection measures, e.g. pe	rsonal protective equipment
	A risk assessment should be conducted and documented in each work area to assess the
	risks related to the use of the product and to select the PPE that matches the relevant risk
	The following recommendations should be considered:
	PPE compliant to the recommended EN/ISO standards should be selected.
Eye/face protection	: Wear safety glasses with side shields.
	Standard EN 166 - Personal eye-protection - specifications.
Skin protection	



## ARCAL N2-2

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 300-15-027ALBNL-ARC

- Hand protection	: Wear working gloves when handling gas containers.
	Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.
- Other	: Wear safety shoes while handling containers.
	Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
Respiratory protection	<ul> <li>Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.</li> </ul>
	When indicated by a risk assessment, Respiratory Protective Equipment must be used. The
	selection of the Respiratory Protective Device (RPD) must be based on known or
	anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD.
	Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres.
	Self contained breathing apparatus is recommended, where unknown exposure may be
	expected, e.g. during maintenance activities on installation systems.
Thermal hazards	: None in addition to the above sections.
8.2.3. Environmental exposure controls	
	None necessary

None necessary.

## **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

Appearance	
<ul> <li>Physical state at 20°C / 101.3kPa</li> </ul>	: Gas.
- Colour	: Colourless.
Odour	: Odourless.
	Odour threshold is subjective and inadequate to warn of overexposure.
Melting point / Freezing point	: Not applicable for gas mixtures.
Boiling point	: Not applicable for gas mixtures.
	It is technically not possible to determine the boiling point or range of this mixture.
	Component with lowest boiling point: Nitrogen -196 °C
Flammability	: Non flammable.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Flash point	: Not applicable for gases and gas mixtures.
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
рН	: Not applicable for gases and gas mixtures.
Viscosity, kinematic	: No reliable data available.
Water solubility [20°C]	: Mixture is partially soluble in water
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for gas mixtures.
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Density and/or relative density	: Not applicable.
Relative vapour density (air=1)	: Heavier than air.
Particle characteristics	: Not applicable for gases and gas mixtures.

### 9.2. Other information

9.2.1. Information with regard to physical hazard o	lasses
Explosive properties	: Not applicable.
Explosion limits	: Non flammable.
Oxidising properties	: Not applicable.
9.2.2. Other safety characteristics	
Molar mass	: Not applicable for gas mixtures.
Evaporation rate	: Not applicable for gases and gas mixtures.
Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.



ARCAL N2-2

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 300-15-027ALBNL-ARC

SECTION 10: Stability and reactivity	
10.1. Reactivity	
	No reactivity hazard other than the effects described in sub-sections below. Data for mixtures are not available. None.
10.2. Chemical stability	
	Stable under normal conditions.
10.3. Possibility of hazardous reactions	
	None.
10.4. Conditions to avoid	
	None under recommended storage and handling conditions (see section 7). Avoid moisture in installation systems.
10.5. Incompatible materials	
	None. For additional information on compatibility refer to ISO 11114.
10.6. Hazardous decomposition products	
	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information	
11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008	
Acute toxicity	: No toxicological effects from this product.

Acute toxicity	
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.
11.2. Information on other hazards	
Other information	: The substance/mixture has no endocrine disrupting properties.

SECTION 12: Ecological information	
12.1. Toxicity	
Assessment	: No ecological damage caused by this product.
EC50 48h - Daphnia magna [mg/l]	: No data available.
EC50 72h - Algae [mg/l]	: No data available.
LC50 96 h - Fish [mg/l]	: No data available.
Argon (7440-37-1)	
EC50 48h - Daphnia magna [mg/l]	No data available.



ARCAL N2-2

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 300-15-027ALBNL-ARC

Argon (7440-37-1)	
EC50 72h - Algae [mg/l]	No data available.
LC50 96 h - Fish [mg/l]	No data available.
Nitrogen (7727-37-9)	
EC50 48h - Daphnia magna [mg/l]	No data available.
EC50 72h - Algae [mg/l]	No data available.
LC50 96 h - Fish [mg/l]	No data available.
12.2. Persistence and degradability	
Assessment	: No ecological damage caused by this product.
12.3. Bioaccumulative potential	
Assessment	: No data available.
<u>12.4. Mobility in soil</u>	
Assessment	: Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.
12.5. Results of PBT and vPvB assessment	
Assessment	: Not classified as PBT or vPvB.
12.6. Endocrine disrupting properties	
Assessment	: The substance/mixture has no endocrine disrupting properties.
12.7. Other adverse effects	
Other adverse effects	: No known effects from this product.
Effect on the ozone layer Effect on global warming	<ul><li>None.</li><li>No known effects from this product.</li></ul>

SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)	<ul> <li>May be vented to atmosphere in a well ventilated place.</li> <li>Do not discharge into any place where its accumulation could be dangerous.</li> <li>Return unused product in original container to supplier.</li> <li>16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.</li> </ul>
13.2. Additional information	External treatment and disposal of waste should comply with applicable local and/or

External treatment and disposal of waste should comply with applicable local and/or national regulations.

## **SECTION 14: Transport information**

### 14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN UN-No. : 1956



## ARCAL N2-2

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 300-15-027ALBNL-ARC

### 14.2. UN proper shipping name

Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Transport by sea (IMDG)

- : COMPRESSED GAS, N.O.S. (Argon, Nitrogen)
- : Compressed gas, n.o.s. (Argon, Nitrogen)
- : COMPRESSED GAS, N.O.S. (Argon, Nitrogen)

### 14.3. Transport hazard class(es)

Labelling

Transport by	road/rail	(ADR/RID)
Class		

Classification code Hazard identification number Tunnel Restriction

### Transport by air (ICAO-TI / IATA-DGR) Class / Div. (Sub. risk(s))

#### Transport by sea (IMDG)

Class / Div. (Sub. risk(s))
Emergency Schedule (EmS) - Fire
Emergency Schedule (EmS) - Spillage

### 14.4. Packing group

Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Transport by sea (IMDG)

#### 14.5. Environmental hazards

Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Transport by sea (IMDG)

#### 14.6. Special precautions for user

#### Packing Instruction(s)

Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Passenger and Cargo Aircraft Cargo Aircraft only Transport by sea (IMDG)

Special transport precautions

- 2.2 : Non-flammable, non-toxic gases. : 2 : 1A : 20 : E - Passage forbidden through tunnels of category E : 2.2 : 2.2 · F-C : S-V : Not applicable. : Not applicable. : Not applicable. : None. : None. : None. : P200. : 200. : 200. : P200. : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured.
  - Ensure valve is closed and not leaking.
  - Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
  - Ensure valve protection device (where provided) is correctly fitted.

#### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable.



ARCAL N2-2

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 300-15-027ALBNL-ARC

## **SECTION 15: Regulatory information**

## 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations	
Restrictions on use	: None. Contains no substance(s) listed on the REACH Candidate List.
Other information, restriction and prohibition regulations	<ul> <li>Ensure all national/local regulations are observed.</li> <li>Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals).</li> <li>Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants).</li> </ul>
Seveso Directive : 2012/18/EU (Seveso III)	: Not covered.
National regulations	
Regulatory reference	: Ensure all national/local regulations are observed.
15.2. Chemical safety assessment	
	A CSA does not need to be carried out for this product.

Indication of changes	: Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.
Abbreviations and acronyms	: ATE - Acute Toxicity Estimate.
	CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008. REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
	EINECS - European Inventory of Existing Commercial Chemical Substances.
	CAS# - Chemical Abstract Service number.
	PPE - Personal Protection Equipment.
	LC50 - Lethal Concentration to 50 % of a test population.
	RMM - Risk Management Measures.
	PBT - Persistent, Bioaccumulative and Toxic.
	vPvB - Very Persistent and Very Bioaccumulative.
	STOT- SE : Specific Target Organ Toxicity - Single Exposure.
	CSA - Chemical Safety Assessment.
	EN - European Standard.
	UN - United Nations.
	ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road.
	IATA - International Air Transport Association.
	IMDG code - International Maritime Dangerous Goods.
	RID - Regulations concerning the International Carriage of Dangerous Goods by Rail. WGK - Water Hazard Class.
	STOT - RE : Specific Target Organ Toxicity - Repeated Exposure. UFI : Unique Formula Identifier.
Training advice	The hazard of asphyxiation is often overlooked and must be stressed during operator training.
	For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at http://www.eiga.eu
Further information	<ul> <li>Classification using data from databases maintained by the European Industrial Gases Association (EIGA). Data is maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at : http://www.eiga.eu.</li> </ul>
	Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).



ARCAL N2-2

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878 Reference number: 300-15-027ALBNL-ARC

Full text of H- and EUH-statements	
H280	Contains gas under pressure; may explode if heated.
Press. Gas (Comp.)	Gases under pressure : Compressed gas
DISCLAIMER OF LIABILITY	: Before using this product in any new process or experiment, a thorough material

 Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
 Details given in this document are believed to be correct at the time of going to press.
 Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

### End of document