

### Danger



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name	: Anhydrous ammonia
SDS no	: EIGA002-ALBNL
Other means of identification	: Anhydrous ammonia
	CAS-No. : 7664-41-7
	EC-No. : 231-635-3
	EC Index-No. : 007-001-00-5
REACH registration No	: 01-2119488876-14
Chemical formula	: NH <sub>3</sub>

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	: See the list of identified uses and exposure scenarios in the annex of the safety data sheet. Perform risk assessment prior to use.
Uses advised against	: Consumer use. Uses other than those listed above are not supported, contact your supplier for more information on other uses.

### 1.3. Details of the supplier of the safety data sheet

#### THE NETHERLANDS:

AIR LIQUIDE BV  
De Witbogt 1  
5652 AG Eindhoven  
the Netherlands-Nederland

#### BELGIUM:

L'AIR LIQUIDE BELGE S.A./N.V.  
Avenue de Bourget / Bourgetlaan 44  
1130 Bruxelles-Brussel  
Belgium-Belgique-België

#### LUXEMBURG:

L'AIR LIQUIDE LUXEMBOURG S.A.  
ZONE P.E.D.-B.P.20  
L-4801 RODANGE Luxembourg

[infosafetydatasheet.albv@airliquide.com](mailto:infosafetydatasheet.albv@airliquide.com)

[www.airliquide-benelux.com](http://www.airliquide-benelux.com)

### 1.4. Emergency telephone number

Emergency telephone number : NL: +31 (0)40 250 35 03 / BE: +32 (0)2 431 72 00 / LUX: +352 50 62 63 1

Country	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 1120 Bruxelles/Brussel	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)
Luxembourg	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Central de la Base - Reine Astrid	Rue Bruyn 1 1120 Bruxelles/Brussel	+352 8002 5500	Free telephone number with a 24/7 access. Experts answer all urgency questions on dangerous products in French, or German
Netherlands	Nationaal Vergiftigingen Informatie Centrum	Huispostnummer B.00.118 Postbus 85500 3508 GA Utrecht	+31 88 755 80 00	Only for the purpose of informing medical personnel in cases of acute intoxications

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards	Flammable gases, Category 2	H221
	Gases under pressure : Liquefied gas	H280
Health hazards	Skin corrosion/irritation, Category 1, Sub-Category 1B	H314
	Serious eye damage/eye irritation, Category 1	H318
	Acute toxicity (inhalation:gas) Category 3	H331
Environmental hazards	Hazardous to the aquatic environment – Acute Hazard, Category 1	H400
	Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS04

GHS05

GHS06

GHS09

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H314 - Causes severe skin burns and eye damage.  
H221 - Flammable gas.  
H280 - Contains gas under pressure; may explode if heated.  
H331 - Toxic if inhaled.  
H410 - Very toxic to aquatic life with long lasting effects.  
EUH071 - Corrosive to the respiratory tract.

### Precautionary statements (CLP)

- Prevention : P280 - Wear eye protection, face protection, protective clothing, protective gloves.  
P273 - Avoid release to the environment.  
P260 - Do not breathe gas, vapours.  
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.  
No smoking.
- Response : P303+P361+P353+P315 - IF ON SKIN : (or hair) Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Get immediate medical advice / attention.  
P304+P340+P315 - IF INHALED : Remove victim to fresh air and keep at rest in a position comfortable for breathing. Get immediate medical advice / attention.  
P305+P351+P338+P315 - IF IN EYES : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical advice / attention.  
P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
P381 - In case of leakage, eliminate all ignition sources.
- Storage : P405 - Store locked up.  
P403 - Store in a well-ventilated place.

### 2.3. Other hazards

Not classified as PBT or vPvB.

The substance/mixture has no endocrine disrupting properties.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Anhydrous ammonia	CAS-No.: 7664-41-7 EC-No.: 231-635-3 EC Index-No.: 007-001-00-5 REACH registration No: 01-2119488876-14	100	Flam. Gas 2, H221 Press. Gas (Liq.), H280 Skin Corr. 1B, H314 Eye Dam. 1, H318 Acute Tox. 3 (Inhalation:gas), H331 Aquatic Acute 1, H400 Aquatic Chronic 2, H411

Contains no other components or impurities which will influence the classification of the product.

### 3.2. Mixtures

Not established.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : Remove contaminated clothing. Drench affected area with water for at least 15 minutes. In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

### **4.2. Most important symptoms and effects, both acute and delayed**

Prolonged exposure to small concentrations may result in pulmonary oedema.  
May cause severe chemical burns to skin and cornea. Suitable first-aid treatment should be immediately available. Seek medical advice before using product.  
Material is destructive to tissue of the mucuous membranes and upper respiratory tract.  
Cough, shortness of breath, headache, nausea.  
See section 11.

### **4.3. Indication of any immediate medical attention and special treatment needed**

Obtain medical assistance.  
Treat with corticosteroid spray as soon as possible after inhalation.

## **SECTION 5: Firefighting measures**

### **5.1. Extinguishing media**

- Suitable extinguishing media : Water spray or fog.  
Foam.  
Shutting off the source of the gas is the preferred method of control.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

### **5.2. Special hazards arising from the substance or mixture**

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : Nitric oxide/nitrogen dioxide.

### **5.3. Advice for firefighters**

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.  
If possible, stop flow of product.  
Use water spray or fog to knock down fire fumes if possible.  
Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.  
Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus.  
Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Gas-tight chemical protective suits for emergency teams.  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

- For non-emergency personnel : Act in accordance with local emergency plan.  
Try to stop release.  
Evacuate area.  
Ensure adequate air ventilation.  
Eliminate ignition sources.  
Stay upwind.  
See section 8 of the SDS for more information on personal protective equipment
- For emergency responders : Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.  
Use chemically protective clothing.  
Monitor concentration of released product.  
Consider the risk of potentially explosive atmospheres.  
See section 5.3 of the SDS for more information.

### 6.2. Environmental precautions

Reduce vapour with fog or fine water spray.  
Try to stop release.

### 6.3. Methods and material for containment and cleaning up

Hose down area with water.  
Ventilate area.  
Wash contaminated equipment or sites of leaks with copious quantities of water.

### 6.4. Reference to other sections

See also sections 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Safe use of the product

: Do not breathe gas.  
Avoid release of product into work area.  
Use only lubricants and sealings approved for the specific gas service.  
The product must be handled in accordance with good industrial hygiene and safety procedures.  
Only experienced and properly instructed persons should handle gases under pressure.  
Consider pressure relief device(s) in gas installations.  
Ensure the complete gas system was (or is regularly) checked for leaks before use.  
Do not smoke while handling product.  
Avoid exposure, obtain special instructions before use.  
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.  
Installation of a cross purge assembly between the container and the regulator is recommended.  
Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service.  
Avoid suck back of water, acid and alkalis.  
Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment.  
Purge air from system before introducing gas.  
Take precautionary measures against static discharge.  
Keep away from ignition sources (including static discharges).  
Consider the use of only non-sparking tools.  
Ensure equipment is adequately earthed.

Safe handling of the gas receptacle

: Refer to supplier's container handling instructions.  
Do not allow backfeed into the container.  
Protect containers from physical damage; do not drag, roll, slide or drop.  
When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.  
Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.  
If user experiences any difficulty operating valve discontinue use and contact supplier.  
Never attempt to repair or modify container valves or safety relief devices.  
Damaged valves should be reported immediately to the supplier.  
Keep container valve outlets clean and free from contaminants particularly oil and water.  
Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.  
Close container valve after each use and when empty, even if still connected to equipment.  
Never attempt to transfer gases from one cylinder/container to another.  
Never use direct flame or electrical heating devices to raise the pressure of a container.  
Do not remove or deface labels provided by the supplier for the identification of the content of the container.  
Suck back of water into the container must be prevented.  
Open valve slowly to avoid pressure shock.

### 7.2. Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers.  
Containers should not be stored in conditions likely to encourage corrosion.  
Container valve guards or caps should be in place.  
Containers should be stored in the vertical position and properly secured to prevent them from falling over.  
Stored containers should be periodically checked for general condition and leakage.  
Keep container below 50°C in a well ventilated place.  
Store containers in location free from fire risk and away from sources of heat and ignition.  
Keep away from combustible materials.  
Segregate from oxidant gases and other oxidants in store.  
All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere.

### 7.3. Specific end use(s)

None.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Anhydrous ammonia (7664-41-7)	
DNEL: Derived no effect level (Workers)	
Acute - local effects, inhalation	36 mg/m <sup>3</sup>
Acute - systemic effects, inhalation	47,6 mg/m <sup>3</sup>
Long-term - local effects, inhalation	14 mg/m <sup>3</sup>
Long-term - systemic effects, inhalation	47,6 mg/m <sup>3</sup>
Acute - systemic effects, dermal	6,8 mg/kg bw/day
Long-term - systemic effects, dermal	6,8 mg/kg bw/day

Anhydrous ammonia (7664-41-7)	
PNEC: Predicted no effect concentration	
Aqua (freshwater)	0,0011 mg/l
Aqua (marine water)	0,0011 mg/l

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation.  
Product to be handled in a closed system.  
Systems under pressure should be regularly checked for leakages.  
Ensure exposure is below occupational exposure limits (where available).  
Gas detectors should be used when toxic gases may be released.  
Consider the use of a work permit system e.g. for maintenance activities.

#### 8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.  
The following recommendations should be considered:  
PPE compliant to the recommended EN/ISO standards should be selected.

#### • Eye/face protection

: Wear goggles and a face shield when transfilling or breaking transfer connections.  
Standard EN 166 - Personal eye-protection - specifications.  
Provide readily accessible eye wash stations and safety showers.

- Skin protection
  - Hand protection : Wear working gloves when handling gas containers.  
Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.  
Standard EN 511 - Cold insulating gloves.  
Wear chemically resistant protective gloves.  
Standard EN 374 - Protective gloves against chemicals.  
Permeation time: minimum >30min short term exposure: material / thickness [mm]  
Chloroprene rubber (CR) 0,5.  
Permeation time: minimum >480min long term exposure: material / thickness [mm] Butyl rubber (IIR) 0,7.  
Consult glove manufacturer's product information on material suitability and material thickness.  
The breakthrough time of the selected gloves must be greater than the intended use period.
  - Other : Keep suitable chemically resistant protective clothing readily available for emergency use.  
Standard EN943-1 - Full protective suits against liquid, solid and gaseous chemicals.  
Wear safety shoes while handling containers.  
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
- Respiratory protection : Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known.  
Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers.  
Recommended: Filter K (green).  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.  
Gas filters do not protect against oxygen deficiency.  
Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks .  
Keep self contained breathing apparatus readily available for emergency use.  
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
- Thermal hazards : None in addition to the above sections.

### 8.2.3. Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	
- Physical state at 20°C / 101.3kPa	: Gas
- Colour	: Colourless.
Odour	: Ammoniacal. Odour threshold is subjective and inadequate to warn of overexposure.
pH	: If dissolved in water pH-value will be affected.
Melting point / Freezing point	: -77,7 °C
Boiling point	: -33 °C
Flash point	: Not applicable for gases and gas mixtures.
Flammability	: Flammable gas.
Explosive limits	: 15,4 – 33,6 vol %
Lower explosive limit (LEL)	: Not available
Upper explosive limit (UEL)	: Not available
Vapour pressure [20°C]	: 8,6 bar(a)
Vapour pressure [50°C]	: 20 bar(a)
Density	: Not applicable
Vapour density	: Not applicable.
Relative density, liquid (water=1)	: 0,7
Relative density, gas (air=1)	: 0,6
Water solubility	: 517 g/l
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for inorganic products.

Auto-ignition temperature	: 630 °C
Decomposition temperature	: Not applicable.
Viscosity, kinematic	: No reliable data available.
Particle characteristics	: Not applicable

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

Oxidising properties	: No oxidising properties.
Critical temperature [°C]	: 132 °C

#### 9.2.2. Other safety characteristics

Molar mass	: 17 g/mol
------------	------------

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

### 10.2. Chemical stability

Stable under normal conditions.

### 10.3. Possibility of hazardous reactions

Can form explosive mixture with air.  
May react violently with oxidants.

### 10.4. Conditions to avoid

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
Avoid moisture in installation systems.

### 10.5. Incompatible materials

Reacts with water to form corrosive alkalis.  
May react violently with acids.  
Air, Oxidisers.  
For additional information on compatibility refer to ISO 11114.

### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

## SECTION 11: Toxicological information

### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity** : Toxic if inhaled.

LC50 Inhalation - Rat [ppm]	2000 ppm/4h
-----------------------------	-------------

**Skin corrosion/irritation** : Causes severe skin burns and eye damage.

**Serious eye damage/irritation** : Causes serious eye damage.

**Respiratory or skin sensitisation** : No known effects from this product.

**Germ cell mutagenicity** : No known effects from this product.

**Carcinogenicity** : No known effects from this product.

**Toxic for reproduction : Fertility** : No known effects from this product.

**Toxic for reproduction : unborn child** : No known effects from this product.

**STOT-single exposure** : May cause inflammation of the respiratory system.  
Severe corrosion to the respiratory tract at high concentrations.

**Target organ(s)** : Respiratory tract.



<b>STOT-repeated exposure</b>	: No known effects from this product.
<b>Aspiration hazard</b>	: Not applicable for gases and gas mixtures.
<b>11.2. Information on other hazards</b>	
Other information	: Inhalation of large amounts leads to bronchospasm, laryngeal oedema and pseudomembrane formation. The substance/mixture has no endocrine disrupting properties.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Assessment	: Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.
EC50 48h - Daphnia magna [mg/l]	: 101 mg/l
EC50 72h - Algae [mg/l]	: No data available.
LC50 96 h - Fish [mg/l]	: 0,89 mg/l

#### 12.2. Persistence and degradability

Assessment	: The substance is readily biodegradable. Unlikely to persist.
------------	--

#### 12.3. Bioaccumulative potential

Assessment	: No data available.
------------	----------------------

#### 12.4. Mobility in soil

Assessment	: Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.
------------	---

#### 12.5. Results of PBT and vPvB assessment

Assessment	: Not classified as PBT or vPvB.
------------	----------------------------------

#### 12.6. Endocrine disrupting properties

No additional information available

#### 12.7. Other adverse effects

Other adverse effects	: May cause pH changes in aqueous ecological systems.
Effect on the ozone layer	: No effect on the ozone layer.
Effect on global warming	: No known effects from this product.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

	Contact supplier if guidance is required. Must not be discharged to atmosphere. Toxic and corrosive gases formed during combustion should be scrubbed before discharge to atmosphere. Gas may be scrubbed in sulphuric acid solution. Gas may be scrubbed in water. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <a href="http://www.eiga.org">http://www.eiga.org</a> for more guidance on suitable disposal methods. Return unused product in original container to supplier.
List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)	: 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.

#### 13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

### SECTION 14: Transport information

#### 14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN

UN-No. : 1005

#### 14.2. UN proper shipping name


Transport by road/rail (ADR/RID) : AMMONIA, ANHYDROUS

Transport by air (ICAO-TI / IATA-DGR) : Ammonia, anhydrous

Transport by sea (IMDG) : AMMONIA, ANHYDROUS

#### 14.3. Transport hazard class(es)

Labelling



2.3 : Toxic gases.

8 : Corrosive substances.

Environmentally hazardous substances

#### Transport by road/rail (ADR/RID)

Class : 2

Classification code : 2TC

Hazard identification number : 268

Tunnel Restriction : C/D - Tank carriage : Passage forbidden through tunnels of category C, D and E. Other carriage : Passage forbidden through tunnels of category D and E

#### Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.3 (8)

Emergency Schedule (EmS) - Fire : F-C

Emergency Schedule (EmS) - Spillage : S-U

#### 14.4. Packing group

Transport by road/rail (ADR/RID) : Not established.

Transport by air (ICAO-TI / IATA-DGR) : Not established.

Transport by sea (IMDG) : Not established.

#### 14.5. Environmental hazards

Transport by road/rail (ADR/RID) : Environmentally hazardous substance / mixture.

Transport by air (ICAO-TI / IATA-DGR) : Environmentally hazardous substance / mixture.

Transport by sea (IMDG) : Marine pollutant

#### 14.6. Special precautions for user

##### Packing Instruction(s)

Transport by road/rail (ADR/RID) : P200

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : Forbidden.

Cargo Aircraft only : Forbidden.

Transport by sea (IMDG) : P200

Special transport precautions

: Avoid transport on vehicles where the load space is not separated from the driver's compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers:

- Ensure there is adequate ventilation.

- Ensure that containers are firmly secured.

- Ensure valve is closed and not leaking.

- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.

- Ensure valve protection device (where provided) is correctly fitted.

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU-Regulations

Restrictions on use : None.  
Seveso Directive : 2012/18/EU (Seveso III) : Listed.

#### National regulations

Regulatory reference : Ensure all national/local regulations are observed.

### 15.2. Chemical safety assessment

A CSA has been carried out.

## SECTION 16: Other information

Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.

Section	Changed item	Change	Comments
	Reference number	Modified	
	Supersedes	Modified	
	Revision date	Modified	
	Most important symptoms and effects, both acute and delayed	Modified	
	Safe use of the product	Modified	
2.3	Other hazards which do not result in classification	Modified	
9.1	Oxidising properties	Modified	
9.1	Flash point	Removed	
11.1	ATE CLP (gases)	Modified	
11.1	Other information	Modified	

Abbreviations and acronyms	<ul style="list-style-type: none"> <li>: ATE - Acute Toxicity Estimate</li> <li>CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008</li> <li>REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006</li> <li>EINECS - European Inventory of Existing Commercial Chemical Substances</li> <li>CAS# - Chemical Abstract Service number</li> <li>PPE - Personal Protection Equipment</li> <li>LC50 - Lethal Concentration to 50 % of a test population</li> <li>RMM - Risk Management Measures</li> <li>PBT - Persistent, Bioaccumulative and Toxic</li> <li>vPvB - Very Persistent and Very Bioaccumulative</li> <li>STOT- SE : Specific Target Organ Toxicity - Single Exposure</li> <li>CSA - Chemical Safety Assessment</li> <li>EN - European Standard</li> <li>UN - United Nations</li> <li>ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road</li> <li>IATA - International Air Transport Association</li> <li>IMDG code - International Maritime Dangerous Goods</li> <li>RID - Regulations concerning the International Carriage of Dangerous Goods by Rail</li> <li>WGK - Water Hazard Class</li> <li>STOT - RE : Specific Target Organ Toxicity - Repeated Exposure</li> <li>UFI : Unique Formula Identifier</li> </ul>
Training advice	<ul style="list-style-type: none"> <li>: Users of breathing apparatus must be trained.</li> <li>Ensure operators understand the flammability hazard.</li> <li>Ensure operators understand the toxicity hazard.</li> </ul>
Further information	<ul style="list-style-type: none"> <li>: Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).</li> <li>Key literature references and sources of data are maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at <a href="http://www.Eiga.eu">http://www.Eiga.eu</a> .</li> </ul>

Full text of H- and EUH-statements	
Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
EUH071	Corrosive to the respiratory tract.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Gas 2	Flammable gases, Category 2
H221	Flammable gas.
H280	Contains gas under pressure; may explode if heated.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B

# Safety Data Sheet

## Anhydrous ammonia

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878  
Reference number: EIGA002-ALBNL

---

### DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.  
Details given in this document are believed to be correct at the time of going to press.  
Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

### Annex to the safety data sheet

This Annex documents the Exposure Scenarios (ESs) related to the identified uses of the registered substance. The ESs detail protective measures for workers and the environment in addition to those described in sections 7, 8, 11, 12 and 13 of the SDS that are required to ensure that the potential exposure to workers and the environment remains within acceptable levels for each of the identified uses.

#### Table of contents of the Annex

Identified Uses	Es N°	Short title	Page
Water treatment	EIGA002-1	Industrial uses, closed contained conditions	15
Formulation of mixtures in pressure receptacles	EIGA002-1	Industrial uses, closed contained conditions	15
Transfilling in pressure receptacles	EIGA002-1	Industrial uses, closed contained conditions	15
Metal treatment	EIGA002-1	Industrial uses, closed contained conditions	15
Electronic component manufacture	EIGA002-1	Industrial uses, closed contained conditions	15
Manufacture of pharmaceutical products	EIGA002-1	Industrial uses, closed contained conditions	15
Calibration of analysis equipment	EIGA002-1	Industrial uses, closed contained conditions	15
Feedstock in chemical processes	EIGA002-1	Industrial uses, closed contained conditions	15
Precursor for fertiliser/explosive manufacture	EIGA002-1	Industrial uses, closed contained conditions	15
Exhaust gas DeNOx applications	EIGA002-1	Industrial uses, closed contained conditions	15
Treatment of plastics	EIGA002-1	Industrial uses, closed contained conditions	15
Aluminium casting	EIGA002-1	Industrial uses, closed contained conditions	15
Treatment of textiles	EIGA002-1	Industrial uses, closed contained conditions	15
Waste recycling	EIGA002-1	Industrial uses, closed contained conditions	15
Refilling of refrigeration equipment	EIGA002-2	Professional uses	26
In photocopying machines	EIGA002-2	Professional uses	26
Reaction gas in mass spectrometry	EIGA002-2	Professional uses	26
Microfiche developing and duplication	EIGA002-2	Professional uses	26

### 1. EIGA002-1 - Industrial uses, closed contained conditions

#### 1.1. Title section

##### Industrial uses, closed contained conditions

ES Ref.: EIGA002-1  
ES Type: Worker - EIGA  
Revision date: 25-4-2017

Processes, tasks, activities covered	Industrial uses, including product transfers and associated laboratory activities within different closed or contained systems
Assessment method	ECETOC TRA 2.0 EUSES

#### 1.2. Conditions of use affecting exposure

##### 1.2.1. Control of environmental exposure: Manufacture of the substance (ERC1)

ERC1	Manufacture of the substance
Assessment method	EUSES

#### Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

#### Amount used, frequency and duration of use (or from service life)

Annual site tonnage:	950000 t/yr
Regional use tonnage:	6500000 t/yr
Emission Days (days/year)	330

#### Technical and organisational conditions and measures

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.	
Soil emission controls are not applicable as there is no direct release to soil	
Ensure operatives are trained to minimise releases	

#### Conditions and measures related to sewage treatment plant

Direct emissions to the municipal STP should not be made.	
---	--

#### Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS	
---------------------------	--

#### Other conditions affecting environmental exposure

Flow rate of receiving water at least:	18000 m <sup>3</sup> /d
--	-------------------------

# Exposure scenario

## Anhydrous ammonia

Annex to the safety data sheet  
 Reference number: EIGA002-ALBNL  
 CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

### Other conditions affecting environmental exposure

Dilution of STP emissions at least:	10
Closed systems are used in order to prevent unintended emissions	

#### 1.2.2. Control of environmental exposure: Formulation into mixture (ERC2)

ERC2	Formulation into mixture
Assessment method	EUSES

### Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

### Amount used, frequency and duration of use (or from service life)

Annual site tonnage:	1000000 t/yr
Regional use tonnage:	3800000 t/yr
Emission Days (days/year)	330

### Technical and organisational conditions and measures

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.	
Soil emission controls are not applicable as there is no direct release to soil	
Ensure operatives are trained to minimise releases	

### Conditions and measures related to sewage treatment plant

Direct emissions to the municipal STP should not be made.	
---	--

### Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS	
---------------------------	--

### Other conditions affecting environmental exposure

Flow rate of receiving water at least:	18000 m <sup>3</sup> /d
Dilution of STP emissions at least:	10
Closed systems are used in order to prevent unintended emissions	

#### 1.2.3. Control of environmental exposure: Use of non-reactive processing aid at industrial site (no inclusion into or onto article) (ERC4)

ERC4	Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
------	---

### Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %



# Exposure scenario

## Anhydrous ammonia

Annex to the safety data sheet

Reference number: EIGA002-ALBNL

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

### Amount used, frequency and duration of use (or from service life)

Annual site tonnage:	25000 t/yr
Regional use tonnage:	354000 t/yr
Emission Days (days/year)	330

### Technical and organisational conditions and measures

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.	
Soil emission controls are not applicable as there is no direct release to soil	
Ensure operatives are trained to minimise releases	

### Conditions and measures related to sewage treatment plant

Direct emissions to the municipal STP should not be made.	
---	--

### Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS	
---------------------------	--

### Other conditions affecting environmental exposure

Flow rate of receiving water at least:	18000 m <sup>3</sup> /d
Dilution of STP emissions at least:	10
Closed systems are used in order to prevent unintended emissions	

#### 1.2.4. Control of environmental exposure: Use of intermediate (ERC6a)

ERC6a	Use of intermediate
Assessment method	EUSES

### Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

### Amount used, frequency and duration of use (or from service life)

Annual site tonnage:	800000 t/yr
Regional use tonnage:	3800000 t/yr
Emission Days (days/year)	330

### Technical and organisational conditions and measures

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.	
Soil emission controls are not applicable as there is no direct release to soil	
Ensure operatives are trained to minimise releases	

# Exposure scenario

## Anhydrous ammonia

Annex to the safety data sheet  
 Reference number: EIGA002-ALBNL  
 CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

### Conditions and measures related to sewage treatment plant

Direct emissions to the municipal STP should not be made.

### Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS

### Other conditions affecting environmental exposure

Flow rate of receiving water at least: 18000 m<sup>3</sup>/d

Dilution of STP emissions at least: 10

Closed systems are used in order to prevent unintended emissions

### 1.2.5. Control of environmental exposure: Use of reactive processing aid at industrial site (no inclusion into or onto article) (ERC6b)

ERC6b Use of reactive processing aid at industrial site (no inclusion into or onto article)

### Product (article) characteristics

Physical form of product See section 9 of the SDS, No additional information

Concentration of substance in product ≤ 100 %

### Amount used, frequency and duration of use (or from service life)

Annual site tonnage: 25000 t/yr

Regional use tonnage: 354000 t/yr

Emission Days (days/year) 330

### Technical and organisational conditions and measures

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.

Soil emission controls are not applicable as there is no direct release to soil

Ensure operatives are trained to minimise releases

### Conditions and measures related to sewage treatment plant

Direct emissions to the municipal STP should not be made.

### Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS

### Other conditions affecting environmental exposure

Flow rate of receiving water at least: 18000 m<sup>3</sup>/d

Dilution of STP emissions at least: 10

Closed systems are used in order to prevent unintended emissions

### 1.2.6. Control of environmental exposure: Use of functional fluid at industrial site (ERC7)

ERC7	Use of functional fluid at industrial site
------	--

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used, frequency and duration of use (or from service life)	
Annual site tonnage:	25000 t/yr
Regional use tonnage:	354000 t/yr
Emission Days (days/year)	330

Technical and organisational conditions and measures	
Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.	
Soil emission controls are not applicable as there is no direct release to soil	
Ensure operatives are trained to minimise releases	

Conditions and measures related to sewage treatment plant	
Direct emissions to the municipal STP should not be made.	

Conditions and measures related to treatment of waste (including article waste)	
See section 13 of the SDS	

Other conditions affecting environmental exposure	
Flow rate of receiving water at least:	18000 m <sup>3</sup> /d
Dilution of STP emissions at least:	10
Closed systems are used in order to prevent unintended emissions	

### 1.2.7. Control of worker exposure: Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions (PROC1)

PROC1	Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions
-------	--

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

# Exposure scenario

## Anhydrous ammonia

Annex to the safety data sheet

Reference number: EIGA002-ALBNL

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

### Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

### Technical and organisational conditions and measures

Handle product within a closed system	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

### Conditions and measures related to personal protection, hygiene and health evaluation

See section 8 of the SDS.	
---------------------------	--

### Other conditions affecting workers exposure

Indoor or outdoor use	
-----------------------	--

### 1.2.8. Control of worker exposure: Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions (PROC2)

PROC2	Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions
-------	--

### Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

### Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

### Technical and organisational conditions and measures

Handle product within a closed system	
---------------------------------------	--

### Technical and organisational conditions and measures

During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Ensure samples are obtained under containment or extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

### Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin	Personal protection measures have to be applied in case of potential exposure only.
Wear gloves providing a minimum efficiency of (%):	90
Wear a respirator providing a minimum efficiency of (%):	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

### Other conditions affecting workers exposure

Indoor or outdoor use	
-----------------------	--

### 1.2.9. Control of worker exposure: Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition (PROC3)

PROC3	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
-------	--

### Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

### Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

### Technical and organisational conditions and measures

Handle product within a closed system	
---------------------------------------	--

### Technical and organisational conditions and measures

During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Ensure samples are obtained under containment or extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

### Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin	Personal protection measures have to be applied in case of potential exposure only.
Wear gloves providing a minimum efficiency of (%):	90
Wear a respirator providing a minimum efficiency of (%):	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

### Other conditions affecting workers exposure

Indoor or outdoor use	
-----------------------	--

#### 1.2.10. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

PROC4	Chemical production where opportunity for exposure arises
-------	---

### Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

### Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

### Technical and organisational conditions and measures

Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Ensure samples are obtained under containment or extract ventilation.	

### Technical and organisational conditions and measures

Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

### Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin	Personal protection measures have to be applied in case of potential exposure only.
Wear gloves providing a minimum efficiency of (%):	90
Wear a respirator providing a minimum efficiency of (%):	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

### Other conditions affecting workers exposure

Indoor or outdoor use	
-----------------------	--

#### 1.2.11. Control of worker exposure: Transfer of substance or mixture (charging and discharging) at dedicated facilities (PROC8b)

PROC8b	Transfer of substance or mixture (charging and discharging) at dedicated facilities
--------	---

### Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

### Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

### Technical and organisational conditions and measures

Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Fill containers at dedicated fill points supplied with local extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	

# Exposure scenario

## Anhydrous ammonia

Annex to the safety data sheet  
 Reference number: EIGA002-ALBNL  
 CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

### Technical and organisational conditions and measures

Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

### Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin	Personal protection measures have to be applied in case of potential exposure only.
Wear gloves providing a minimum efficiency of (%):	90
Wear a respirator providing a minimum efficiency of (%):	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

### Other conditions affecting workers exposure

Indoor or outdoor use	
-----------------------	--

### 1.2.12. Control of worker exposure: Transfer of substance or mixture into small containers (dedicated filling line, including weighing) (PROC9)

PROC9	Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
-------	---

### Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

### Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

### Technical and organisational conditions and measures

Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Fill containers at dedicated fill points supplied with local extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	



### Technical and organisational conditions and measures

Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

### Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin	Personal protection measures have to be applied in case of potential exposure only.
Wear gloves providing a minimum efficiency of (%):	90
Wear a respirator providing a minimum efficiency of (%):	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

### Other conditions affecting workers exposure

Indoor or outdoor use

### 1.3. Exposure estimation and reference to its source

No data available

### 1.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

#### 1.4.1. Environment

Guidance - Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : . <a href="https://ec.europa.eu/jrc/en/scientific-tool/european-union-system-evaluation-substances">https://ec.europa.eu/jrc/en/scientific-tool/european-union-system-evaluation-substances</a>
------------------------	--

#### 1.4.2. Health

Guidance - Health	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : . <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>
-------------------	--

# Exposure scenario

## Anhydrous ammonia

Annex to the safety data sheet  
 Reference number: EIGA002-ALBNL  
 CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

### 2. EIGA002-2 - Professional uses

#### 2.1. Title section

##### Professional uses

ES Ref.: EIGA002-2  
 ES Type: Worker - EIGA  
 Revision date: 25-4-2017

Processes, tasks, activities covered	Professional uses, including transfer of product in non-industrial settings
Assessment method	ECETOC TRA 2.0

#### 2.2. Conditions of use affecting exposure

##### 2.2.1. Control of environmental exposure: Widespread use of functional fluid (indoor), Widespread use of functional fluid (outdoor) (ERC9a, ERC9b)

ERC9a	Widespread use of functional fluid (indoor)
ERC9b	Widespread use of functional fluid (outdoor)

##### Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

##### Amount used, frequency and duration of use (or from service life)

No additional information	
---------------------------	--

##### Technical and organisational conditions and measures

Ensure operatives are trained to minimise exposure	
--	--

##### Conditions and measures related to sewage treatment plant

No additional information	
---------------------------	--

##### Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS	
---------------------------	--

##### Other conditions affecting environmental exposure

Closed systems are used in order to prevent unintended emissions		
--	--	--

##### 2.2.2. Control of worker exposure: Chemical production where opportunity for exposure arises (PROC4)

PROC4	Chemical production where opportunity for exposure arises
-------	---

##### Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

# Exposure scenario

## Anhydrous ammonia

Annex to the safety data sheet

Reference number: EIGA002-ALBNL

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

### Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

### Technical and organisational conditions and measures

Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

### Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin	Personal protection measures have to be applied in case of potential exposure only.
Wear gloves providing a minimum efficiency of (%):	90
Wear a respirator providing a minimum efficiency of	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

### Other conditions affecting workers exposure

Indoor or outdoor use	
-----------------------	--

### 2.2.3. Control of worker exposure: Transfer of substance or mixture (charging and discharging) at non-dedicated facilities (PROC8a)

PROC8a	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
--------	---

### Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

# Exposure scenario

## Anhydrous ammonia

Annex to the safety data sheet

Reference number: EIGA002-ALBNL

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

### Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

### Technical and organisational conditions and measures

Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

### Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin	Personal protection measures have to be applied in case of potential exposure only.
Wear gloves providing a minimum efficiency of (%):	90
Wear a respirator providing a minimum efficiency of	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

### Other conditions affecting workers exposure

Indoor or outdoor use	
-----------------------	--

### 2.3. Exposure estimation and reference to its source

No data available

### 2.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

#### 2.4.1. Environment

Guidance - Environment	Check that RMMs and OCs are as described above or of equivalent efficiency
------------------------	--

#### 2.4.2. Health

Guidance - Health	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : . <a href="http://www.ecetoc.org/tra">http://www.ecetoc.org/tra</a>
-------------------	--

**End of document**