

Warning



SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name	: PHARGALIS 2
SDS no	: EIGA018A-PHA
Other means of identification	: Carbon dioxide
	CAS-No. : 124-38-9
	EC-No. : 204-696-9
	EC Index-No. : ---
REACH registration No	: Listed in Annex IV / V REACH, exempted from registration.
Chemical formula	: CO ₂

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	: Extinguishing agent. Industrial and professional uses. Perform risk assessment prior to use. Test gas/Calibration gas. Purge gas, diluting gas, inerting gas. Shield gas for welding processes. Use for manufacture of electronic/photovoltaic components. Consumer use. Treatment of water intended for human consumption. It is the responsibility of the end user to ensure that the product as supplied is suitable for its intended use.
Uses advised against	: None.

1.3. Details of the supplier of the safety data sheet

THE NETHERLANDS:

AIR LIQUIDE BV
De Witbogt 1
5652 AG Eindhoven
the Netherlands-Nederland
Tel: +31 (0)40 250 35 03

BELGIUM:

L'AIR LIQUIDE BELGE S.A./N.V.
Hermeslaan 11
1932 Zaventem
Belgium-Belgique-België
Tel: +32 (0)2 540 86 60

LUXEMBURG:

L'AIR LIQUIDE LUXEMBOURG S.A.
ZONE P.E.D.-B.P.20
L-4801 RODANGE Luxembourg
Tel: +352 26 30 29 03

2.3. Other hazards

Contact with liquid may cause cold burns/frostbite.
In high concentrations CO₂ causes rapid circulatory insufficiency even at normal levels of oxygen concentration. Symptoms are headache, nausea and vomiting, which may lead to unconsciousness and death.
Not classified as PBT or vPvB.
The substance/mixture has no endocrine disrupting properties.
Not classified as PMT or vPvM.

SECTION 3: Composition/information on ingredients

3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP] ATE, EUH-statements, M-Factors
Carbon dioxide	CAS-No.: 124-38-9 EC-No.: 204-696-9 EC Index-No.: --- REACH registration No: *1	100	Press. Gas (Liq.), H280

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*3: Registration not required: Substance manufactured or imported < 1t/y.

3.2. Mixtures

Not applicable

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation.
Low concentrations of CO₂ cause increased respiration and headache.
See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.
Product does not burn, use fire control measures appropriate for the surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

Specific hazards : Exposure to fire may cause containers to rupture/explode.
Hazardous combustion products : None.

5.3. Advice for firefighters

Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
If possible, stop flow of product.
Use water spray or fog to knock down fire fumes if possible.
Move containers away from the fire area if this can be done without risk.

Special protective equipment for fire fighters : In confined space use self-contained breathing apparatus.
Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters. EN 15090 Footwear for firefighters. EN 443 Helmets for fire fighting in buildings and other structures.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Act in accordance with local emergency plan.
Try to stop release.
Evacuate area.
Ensure adequate air ventilation.
Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
Stay upwind.
See section 8 of the SDS for more information on personal protective equipment.

For emergency responders : Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
Oxygen detectors should be used when asphyxiating gases may be released.
See section 5.3 of the SDS for more information.

6.2. Environmental precautions

Try to stop release.

6.3. Methods and material for containment and cleaning up

Ventilate area.

6.4. Reference to other sections

See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe use of the product

: Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Potential production of solid CO₂ particles must be ruled out. In order to rule out potential electrostatic discharge production, the system must be adequately grounded.

Do not breathe gas.

Avoid release of product into atmosphere.

The product must be handled in accordance with good industrial hygiene and safety procedures.

Only experienced and properly instructed persons should handle gases under pressure.

Consider pressure relief device(s) in gas installations.

Ensure the complete gas system was (or is regularly) checked for leaks before use.

Do not smoke while handling product.

Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.

Avoid suck back of water, acid and alkalis.

Be aware of the risk of formation of static electricity with the use of CO₂ extinguishers. Do not use them in places where a flammable atmosphere may be present.

Safe handling of the gas receptacle

: Do not allow backfeed into the container.

Protect containers from physical damage; do not drag, roll, slide or drop.

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.

Leave valve protection caps, when provided, in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating valve discontinue use and contact supplier.

Never attempt to repair or modify container valves or safety relief devices.

Damaged valves should be reported immediately to the supplier.

Keep container valve outlets clean and free from contaminants particularly oil and water.

Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container.

Do not remove or deface labels provided by the supplier for the identification of the content of the container.

Suck back of water into the container must be prevented.

Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion.

Container valve guards or caps, when provided, should be in place.

Containers should be stored in the vertical position and properly secured to prevent them from falling over.

Stored containers should be periodically checked for general condition and leakage.

Keep container below 50°C in a well ventilated place.

Store containers in location free from fire risk and away from sources of heat and ignition.

Keep away from combustible materials.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

PHARGALIS 2 (124-38-9)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Carbon dioxide
IOEL TWA	9000 mg/m ³
	5000 ppm
Regulatory reference	COMMISSION DIRECTIVE 2006/15/EC
Belgium - Occupational Exposure Limits	
Local name	Carbone (dioxyde de) # Koolstofdioxide
OEL TWA	9131 mg/m ³
	5000 ppm
OEL STEL	54784 mg/m ³
	30000 ppm
Remark	A: la mention "A" signifie que l'agent libère un gaz ou une vapeur qui n'ont en eux-mêmes aucun effet physiologique mais peuvent diminuer le taux d'oxygène dans l'air. Lorsque le taux d'oxygène descend en dessous de 17-18 % (vol/vol) le manque d'oxygène provoque des suffocations qu'aucun symptôme préalable n'annonce. # A: de vermelding "A" betekent dat dit agens gas of damp vrijgeeft dat of die op zich geen fysiologische werking heeft, maar het zuurstofgehalte in de lucht verlaagt. Wanneer het zuurstofgehalte daalt onder de 17-18 % (vol/vol), veroorzaakt het zuurstoftekort verstikking, die zich manifesteert zonder dat er een waarschuwing aan voorafgaat.
Regulatory reference	Koninklijk besluit/Arrêté royal 16/11/2023
Luxembourg - Occupational Exposure Limits	
Local name	Dioxyde de carbone
OEL TWA	9000 mg/m ³
	5000 ppm
Regulatory reference	Mémorial A N° 226 de 2021 concernant la protection de la sécurité et de la santé des salariés contre les risques liés à des agents chimiques sur le lieu de travail
Netherlands - Occupational Exposure Limits	
Local name	Kooldioxide
TGG-8u (OEL TWA)	9000 mg/m ³
	5000 ppm
Regulatory reference	Arbeidsomstandighedenregeling 2024

DNEL (Derived-No Effect Level) : None available.

PNEC (Predicted No-Effect Concentration) : None available.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation.
Systems under pressure should be regularly checked for leakages.
Ensure exposure is below occupational exposure limits (where available).
Oxygen detectors should be used when asphyxiating gases may be released.
Consider the use of a work permit system e.g. for maintenance activities.
CO2 detectors should be used when CO2 may be released.

8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.

The following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

- Eye/face protection : Wear goggles when transfilling or breaking transfer connections.
Standard EN 166 - Personal eye-protection - specifications.
- Skin protection : Wear working gloves when handling gas containers.
Standard EN 388 - Protective gloves against mechanical risks, performance level 1 or higher. Recommended types include wrist gloves from leather or synthetic material with equivalent performance, fabric gloves, fabric gloves with leather palms.
Wear cold insulating gloves when transfilling or breaking transfer connections.
Standard EN 511 - Cold insulating gloves, performance level 1 or higher. Recommended types include insulated gauntlets or gloves specifically selected to prevent liquid penetration and ingress of cryogenic liquids and to provide mechanical resistance.
- Hand protection : Wear safety shoes while handling containers.
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
- Other : Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Consult respiratory device supplier's product information for the selection of the appropriate device.
Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres.
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
- Respiratory protection : None in addition to the above sections.
- Thermal hazards

8.2.3. Environmental exposure controls

None necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
- Physical state at 20°C / 101.3kPa	: Gas.
- Colour	: Colourless.
Odour	: Odourless.
Melting point / Freezing point	: -78,5 °C Melting point at normal conditions does not exist. At atmospheric pressure solid carbon dioxide sublimates into gaseous carbon dioxide at -78.5°C
Boiling point	: -56,6 °C
Flammability	: Non flammable.
Lower explosion limit	: Not applicable.
Upper explosion limit	: Not applicable.
Flash point	: Not applicable for gases and gas mixtures.
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
pH	: Not applicable for gases and gas mixtures.
Viscosity, kinematic	: Not applicable for gases and gas mixtures.
Water solubility [20°C]	: 2000 mg/l

Partition coefficient n-octanol/water (Log Kow)	: 0,83
Vapour pressure [20°C]	: 57,3 bar(a)
Vapour pressure [50°C]	: No reliable data available.
Density and/or relative density	: Not applicable for gases and gas mixtures.
Relative vapour density (air=1)	: 1,52
Particle characteristics	: Not applicable for gases and gas mixtures. Nanoforms are not relevant for gases and gas mixtures.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Oxidising properties	: No oxidising properties.
Critical temperature [°C]	: 31 °C

9.2.2. Other safety characteristics

Molar mass	: 44 g/mol
Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Avoid moisture in installation systems.

10.5. Incompatible materials

For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity	: Toxicological effects not expected by inhalation from this product if occupational exposure limit values are not exceeded.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.

Aspiration hazard : Not applicable for gases and gas mixtures.

11.2. Information on other hazards

Other information : Unlike simple asphyxiants, carbon dioxide has the ability to cause death even when normal oxygen levels (20-21%) are maintained. 5% CO₂ has been found to act synergistically to increase the toxicity of certain other gases (CO, NO₂). CO₂ has been shown to enhance the production of carboxy- or met-hemoglobin by these gases possibly due to carbon dioxide's stimulatory effects on the respiratory and circulatory systems.
For more information, see 'EIGA Safety Info 24: Carbon Dioxide, Physiological Hazards' at www.eiga.eu.
The substance/mixture has no endocrine disrupting properties.

SECTION 12: Ecological information

12.1. Toxicity

Assessment : No ecological damage caused by this product.
EC50 48h - Daphnia magna [mg/l] : No data available.
EC50 72h - Algae [mg/l] : No data available.
LC50 96 h - Fish [mg/l] : No data available.

12.2. Persistence and degradability

Assessment : No ecological damage caused by this product.

12.3. Bioaccumulative potential

Assessment : No ecological damage caused by this product.
Not expected to bioaccumulate due to the low log Kow (log Kow < 4).
See section 9.

12.4. Mobility in soil

Assessment : No ecological damage caused by this product.

12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.

12.6. Endocrine disrupting properties

Assessment : The substance/mixture has no endocrine disrupting properties.

12.7. Other adverse effects

Other adverse effects : Not classified as PMT or vPvM.
Effect on the ozone layer : No effect on the ozone layer.
Global warming potential [CO₂=1] : 1
Effect on global warming : When discharged in large quantities may contribute to the greenhouse effect.
Contains greenhouse gas(es).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Discharge to atmosphere in large quantities should be avoided.
Do not discharge into any place where its accumulation could be dangerous.
Return unused product in original container to supplier.

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended) : 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.

13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN

UN-No. : 1013

14.2. UN proper shipping name

Transport by road/rail/inland waterways (ADR/RID/ADN) : CARBON DIOXIDE

Transport by air (ICAO-TI / IATA-DGR) : Carbon dioxide

Transport by sea (IMDG) : CARBON DIOXIDE

14.3. Transport hazard class(es)

Labelling :



2.2 : Non-flammable, non-toxic gases.

Transport by road/rail/inland waterways (ADR/RID/ADN)

Class : 2

Classification code : 2A

Hazard identification number : 20

Tunnel Restriction : C/E - Tank carriage: Passage forbidden through tunnels of category C, D and E. Other carriage: Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.2

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2

Emergency Schedule (EmS) - Fire : F-C

Emergency Schedule (EmS) - Spillage : S-V

14.4. Packing group

Transport by road/rail/inland waterways (ADR/RID/ADN) : Not applicable.

Transport by air (ICAO-TI / IATA-DGR) : Not applicable.

Transport by sea (IMDG) : Not applicable.

14.5. Environmental hazards

Transport by road/rail/inland waterways (ADR/RID/ADN) : None.

Transport by air (ICAO-TI / IATA-DGR) : None.

Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail/inland waterways (ADR/RID/ADN) : P200.

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : 200.

Cargo Aircraft only : 200.

Transport by sea (IMDG) : P200.

- Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment.
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
Before transporting product containers:
- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

- Restrictions on use : None.
Other information, restriction and prohibition regulations : Not listed on the PIC list (Regulation EU 649/2012).
Not listed on the POP list (Regulation EU 2019/1021).
Seveso Directive : 2012/18/EU (Seveso III) : Covered.

National regulations

- Regulatory reference : Ensure all national/local regulations are observed.

15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.

SECTION 16: Other information

- Indication of changes : Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.

Section	Changed item	Comments
	Supersedes version of	Modified
	Revision date	Modified
	Endocrine disrupting properties	Added
1	Relevant identified uses	Modified
2	Supplemental information	Added
2.3	Other hazards which do not result in classification	Modified
7	Safe handling of the gas receptacle	Modified
8	Regulatory reference	Added
8	Regulatory reference	Added
8	TGG-8u (OEL TWA) [ppm]	Added
8	Regulatory reference	Added
8	Local name	Added
8	Local name	Added
8	Local name	Added

8	OEL TWA	Added
8	OEL TWA	Added
8	TGG-8u (OEL TWA)	Added
8	OEL STEL	Added
8	OEL STEL	Added
8	OEL TWA	Added
8	OEL TWA	Added
8	Remark	Added
8	Regulatory reference	Added
8	Local name	Added
8	IOEL TWA [ppm]	Added
8	IOEL TWA	Added
8.2	Appropriate engineering controls	Modified
8.2	Respiratory protection	Modified
9	Particle characteristics	Added
9	Partition coefficient n-octanol/water (Log Pow)	Modified
9	Density	Added
9	Partition coefficient n-octanol/water (Log Kow)	Added
9	Lower explosive limit (LEL)	Added
9	Upper explosive limit (UEL)	Added
9	Melting point	Modified
9	Odour	Modified
9	Vapour pressure at 50°C	Modified
9	Viscosity, kinematic	Modified
9.1	Explosive limits (vol %)	Removed
9.1	Critical temperature	Modified
9.1	Decomposition temperature	Modified
12.7	Other adverse effects	Modified
13.1	Waste treatment methods	Modified
14	Number of blue cones/lights (ADN)	Added
14	Classification code (ADN)	Added
14	Equipment required (ADN)	Added
14	Excepted quantities (ADN)	Added
14	Danger labels (ADN)	Added
14	Limited quantities (ADN)	Added
14	Classification code (RID)	Added
14	Colis express (express parcels) (RID)	Added
14	Excepted quantities (RID)	Added
14	Hazard identification number (RID)	Added

14	Limited quantities (RID)	Added
14	Mixed packing provisions (RID)	Added
14	Packing instructions (RID)	Added
14	Special provisions for carriage - Loading, unloading and handling (RID)	Added
14	Proper Shipping Name (RID)	Added
14	Portable tank and bulk container instructions (RID)	Added
14	Special provisions (RID)	Added
14	Tank codes for RID tanks (RID)	Added
14	Special provisions for RID tanks (RID)	Added
14	Transport category (RID)	Added
14	UN-No. (RID)	Modified
14.1	UN-No. (ADN)	Added
14.2	Proper Shipping Name (ADN)	Added
14.3	Danger labels (RID)	Added
14.6	Special provisions (ADN)	Added
14.6	Special provisions (ADR)	Modified
15	Seveso Directive : 2012/18/EU (Seveso III)	Modified
16	Abbreviations and acronyms	Modified

Abbreviations and acronyms

- : ATE - Acute Toxicity Estimate.
- CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008.
- REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.
- EINECS - European Inventory of Existing Commercial Chemical Substances.
- CAS# - Chemical Abstract Service number.
- PPE - Personal Protection Equipment.
- LC50 - Lethal Concentration to 50 % of a test population.
- RMM - Risk Management Measures.
- PBT - Persistent, Bioaccumulative and Toxic.
- vPvB - Very Persistent and Very Bioaccumulative.
- STOT- SE : Specific Target Organ Toxicity - Single Exposure.
- CSA - Chemical Safety Assessment.
- EN - European Standard.
- UN - United Nations.
- ADR - Agreement concerning the International Carriage of Dangerous Goods by Road.
- IATA - International Air Transport Association.
- IMDG code - International Maritime Dangerous Goods.
- RID - Regulations concerning the International Carriage of Dangerous Goods by Rail.
- WGK - Water Hazard Class.
- STOT - RE : Specific Target Organ Toxicity - Repeated Exposure.
- UFI : Unique Formula Identifier.
- ADN -International Carriage of Dangerous Goods by Inland Waterways.
- PROC -Process category
- .
- ERC – Environmental release category.
- PMT - Persistent, Mobile and Toxic.
- vPvM – very Persistent and very Mobile.

- Training advice : The hazard of asphyxiation is often overlooked and must be stressed during operator training.
For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at <http://www.eiga.eu>.
- Further information : Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).
Key literature references and sources of data are maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at <http://www.Eiga.eu>.

Full text of H- and EUH-statements	
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
H280	Contains gas under pressure; may explode if heated.

- DISCLAIMER OF LIABILITY : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
Details given in this document are believed to be correct at the time of going to press.
Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document