

### Warning



## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name	:	Xenon
SDS no	:	EIGA127-ALBNL
Other means of identification	:	Xenon
	CAS-No.	: 7440-63-3
	EC-No.	: 231-172-7
	EC Index-No.	: ---
REACH registration No	:	Listed in Annex IV / V REACH, exempted from registration.
Chemical formula	:	Xe

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	:	Insulation material in glazing. Lighting. Industrial and professional uses. Perform risk assessment prior to use. Test gas/Calibration gas. Laboratory and Process control. Laser gas.
Uses advised against	:	Consumer use. Uses other than those listed above are not supported, contact your supplier for more information on other uses.

### 1.3. Details of the supplier of the safety data sheet

#### THE NETHERLANDS:

AIR LIQUIDE BV  
De Witbogt 1  
5652 AG Eindhoven  
the Netherlands-Nederland  
Tel: +31 (0)40 250 35 03

#### BELGIUM:

L'AIR LIQUIDE BELGE S.A./N.V.  
Hermeslaan 11  
1932 Zaventem  
Belgium-Belgique-België  
Tel: +32 (0)2 540 86 60

#### LUXEMBURG:

L'AIR LIQUIDE LUXEMBOURG S.A.  
ZONE P.E.D.-B.P.20  
L-4801 RODANGE Luxemburg  
Tel: +352 26 30 29 03

[infosafetydatasheet.albv@airliquide.com](mailto:infosafetydatasheet.albv@airliquide.com)  
[www.airliquide-benelux.com](http://www.airliquide-benelux.com)

### 1.4. Emergency telephone number

Country/Area	Organisation/Company	Address	Emergency number	Comment
Belgium	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Bruxelles/Brussel	+32 70 245 245	Please dial: 070 245 245 for any urgent questions about intoxication (free of charge 24/7), if not accessible, dial: 02 264 96 30 (standard fee)
Luxembourg	Centre Anti-Poisons/Antigifcentrum c/o Hôpital Militaire Reine Astrid	Rue Bruyn 1 1120 Bruxelles/Brussel	+352 8002 5500	Free telephone number with a 24/7 access. Experts answer all urgency questions on dangerous products in French, Dutch and English
Netherlands	Nationaal Vergiftigingen Informatie Centrum	Huispostnummer Q03.2.315 Postbus 85500 3508 GA Utrecht	+31 88 755 80 00	Only for the purpose of informing medical personnel in cases of acute intoxications (24 hours a day, 7 days a week)

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards      Gases under pressure : Liquefied gas      H280

### 2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS04

Signal word (CLP) : Warning  
 Hazard statements (CLP) : H280 - Contains gas under pressure; may explode if heated.  
 Precautionary statements (CLP)  
 - Storage : P403 - Store in a well-ventilated place.  
 Supplemental information : Asphyxiant in high concentrations.

### 2.3. Other hazards

Contact with liquid may cause cold burns/frostbite.  
 Not classified as PBT or vPvB.  
 The substance/mixture has no endocrine disrupting properties.  
 Not classified as PMT or vPvM.

### SECTION 3: Composition/information on ingredients

#### 3.1. Substances

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP] ATE, EUH-statements, M-Factors
Xenon	CAS-No.: 7440-63-3 EC-No.: 231-172-7 EC Index-No.: --- REACH registration No: *1	100	Press. Gas (Liq.), H280

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

\*1: Listed in Annex IV / V REACH, exempted from registration.

\*3: Registration not required: Substance manufactured or imported < 1t/y.

#### 3.2. Mixtures

Not applicable

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

#### 4.2. Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation.  
See section 11.

#### 4.3. Indication of any immediate medical attention and special treatment needed

None.

### SECTION 5: Firefighting measures

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.  
Product does not burn, use fire control measures appropriate for the surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : None.

### **5.3. Advice for firefighters**

Specific methods	: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Move containers away from the fire area if this can be done without risk.
Special protective equipment for fire fighters	: In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters. EN 15090 Footwear for firefighters. EN 443 Helmets for fire fighting in buildings and other structures.

## **SECTION 6: Accidental release measures**

### **6.1. Personal precautions, protective equipment and emergency procedures**

For non-emergency personnel	: Act in accordance with local emergency plan. Try to stop release. Evacuate area. Ensure adequate air ventilation. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Stay upwind. See section 8 of the SDS for more information on personal protective equipment.
For emergency responders	: Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Oxygen detectors should be used when asphyxiating gases may be released. See section 5.3 of the SDS for more information.

### **6.2. Environmental precautions**

Try to stop release.

### **6.3. Methods and material for containment and cleaning up**

Ventilate area.

### **6.4. Reference to other sections**

See also sections 8 and 13.

## **SECTION 7: Handling and storage**

### **7.1. Precautions for safe handling**

Safe use of the product	: Do not breathe gas. Avoid release of product into atmosphere. The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularly) checked for leaks before use. Do not smoke while handling product. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Avoid suck back of water, acid and alkalis.
-------------------------	---

### Safe handling of the gas receptacle

- : Do not allow backfeed into the container.
- Protect containers from physical damage; do not drag, roll, slide or drop.
- When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
- Leave valve protection caps, when provided, in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
- If user experiences any difficulty operating valve discontinue use and contact supplier.
- Never attempt to repair or modify container valves or safety relief devices.
- Damaged valves should be reported immediately to the supplier.
- Keep container valve outlets clean and free from contaminants particularly oil and water.
- Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
- Close container valve after each use and when empty, even if still connected to equipment.
- Never attempt to transfer gases from one cylinder/container to another.
- Never use direct flame or electrical heating devices to raise the pressure of a container.
- Do not remove or deface labels provided by the supplier for the identification of the content of the container.
- Suck back of water into the container must be prevented.
- Open valve slowly to avoid pressure shock.

### 7.2. Conditions for safe storage, including any incompatibilities

- Observe all regulations and local requirements regarding storage of containers.
- Containers should not be stored in conditions likely to encourage corrosion.
- Container valve guards or caps, when provided, should be in place.
- Containers should be stored in the vertical position and properly secured to prevent them from falling over.
- Stored containers should be periodically checked for general condition and leakage.
- Keep container below 50°C in a well ventilated place.
- Store containers in location free from fire risk and away from sources of heat and ignition.
- Keep away from combustible materials.

### 7.3. Specific end use(s)

None.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

- OEL (Occupational Exposure Limits) : None available.
- DNEL (Derived-No Effect Level) : None available.
- PNEC (Predicted No-Effect Concentration) : None available.

### 8.2. Exposure controls

#### **8.2.1. Appropriate engineering controls**

- Provide adequate general and local exhaust ventilation.
- Systems under pressure should be regularly checked for leakages.
- Oxygen detectors should be used when asphyxiating gases may be released.
- Consider the use of a work permit system e.g. for maintenance activities.

#### **8.2.2. Individual protection measures, e.g. personal protective equipment**

- A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.
- The following recommendations should be considered:
  - PPE compliant to the recommended EN/ISO standards should be selected.

- Eye/face protection : Wear goggles when transfilling or breaking transfer connections.

- Skin protection

- Standard EN 166 - Personal eye-protection - specifications.

- Hand protection : Wear working gloves when handling gas containers.  
Standard EN 388 - Protective gloves against mechanical risks, performance level 1 or higher. Recommended types include wrist gloves from leather or synthetic material with equivalent performance, fabric gloves, fabric gloves with leather palms.  
Wear cold insulating gloves when transfilling or breaking transfer connections.  
Standard EN 511 - Cold insulating gloves, performance level 1 or higher. Recommended types include insulated gauntlets or gloves specifically selected to prevent liquid penetration and ingress of cryogenic liquids and to provide mechanical resistance.
- Other : Wear safety shoes while handling containers.  
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
- Respiratory protection : Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.  
Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres.  
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
- Thermal hazards : None in addition to the above sections.

### 8.2.3. Environmental exposure controls

None necessary.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	
- Physical state at 20°C / 101.3kPa	: Gas.
- Colour	: Colourless.
Odour	: Odourless.
Melting point / Freezing point	: -112 °C
Boiling point	: -108 °C
Flammability	: Non flammable.
Lower explosion limit	: Not applicable.
Upper explosion limit	: Not applicable.
Flash point	: Not applicable for gases and gas mixtures.
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
pH	: Not applicable for gases and gas mixtures.
Viscosity, kinematic	: No reliable data available.
Water solubility [20°C]	: 644 mg/l
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for inorganic products.
Vapour pressure [20°C]	: No reliable data available.
Vapour pressure [50°C]	: Not applicable.
Density and/or relative density	: Not applicable for gases and gas mixtures.
Relative vapour density (air=1)	: 4,5
Particle characteristics	: Not applicable for gases and gas mixtures. Nanofoms are not relevant for gases and gas mixtures.

### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

Oxidising properties	: No oxidising properties.
Critical temperature [°C]	: 16,6 °C

#### 9.2.2. Other safety characteristics

Molar mass	: 131 g/mol
Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

None.

#### 10.4. Conditions to avoid

Avoid moisture in installation systems.

#### 10.5. Incompatible materials

For additional information on compatibility refer to ISO 11114.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity	: No known toxicological effects by inhalation from this product.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.

#### 11.2. Information on other hazards

Other information : The substance/mixture has no endocrine disrupting properties.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Assessment	: No ecological damage caused by this product.
EC50 48h - Daphnia magna [mg/l]	: No data available.
EC50 72h - Algae [mg/l]	: No data available.
LC50 96 h - Fish [mg/l]	: No data available.

#### 12.2. Persistence and degradability

Assessment : No ecological damage caused by this product.

#### 12.3. Bioaccumulative potential

Assessment : No ecological damage caused by this product.

#### 12.4. Mobility in soil

Assessment : No ecological damage caused by this product.

### 12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.

### 12.6. Endocrine disrupting properties

Assessment : The substance/mixture has no endocrine disrupting properties.

### 12.7. Other adverse effects

Other adverse effects : Not classified as PMT or vPvM.

Effect on the ozone layer : No effect on the ozone layer.

Effect on global warming : None.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

May be vented to atmosphere in a well ventilated place.  
Do not discharge into any place where its accumulation could be dangerous.  
Return unused product in original container to supplier.

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended) : 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.

### 13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

## SECTION 14: Transport information

### 14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN  
UN-No. : 2036

### 14.2. UN proper shipping name

Transport by road/rail/inland waterways (ADR/RID/ADN) : XENON

Transport by air (ICAO-TI / IATA-DGR) : Xenon

Transport by sea (IMDG) : XENON

### 14.3. Transport hazard class(es)

Labelling :



2.2 : Non-flammable, non-toxic gases.

Transport by road/rail/inland waterways (ADR/RID/ADN)

Class : 2

Classification code : 2A

Hazard identification number : 20

Tunnel Restriction : C/E - Tank carriage: Passage forbidden through tunnels of category C, D and E. Other carriage: Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.2

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2

Emergency Schedule (EmS) - Fire : F-C

Emergency Schedule (EmS) - Spillage : S-V

### 14.4. Packing group

Transport by road/rail/inland waterways (ADR/RID/ADN)	: Not applicable.
Transport by air (ICAO-TI / IATA-DGR)	: Not applicable.
Transport by sea (IMDG)	: Not applicable.

### 14.5. Environmental hazards

Transport by road/rail/inland waterways (ADR/RID/ADN)	: None.
Transport by air (ICAO-TI / IATA-DGR)	: None.
Transport by sea (IMDG)	: None.

### 14.6. Special precautions for user

#### **Packing Instruction(s)**

Transport by road/rail/inland waterways (ADR/RID/ADN)	: P200.
Transport by air (ICAO-TI / IATA-DGR)	
Passenger and Cargo Aircraft	: 200.
Cargo Aircraft only	: 200.
Transport by sea (IMDG)	: P200.

Special transport precautions	: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: <ul style="list-style-type: none"><li>- Ensure there is adequate ventilation.</li><li>- Ensure that containers are firmly secured.</li><li>- Ensure valve is closed and not leaking.</li><li>- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.</li><li>- Ensure valve protection device (where provided) is correctly fitted.</li></ul>
-------------------------------	--

### 14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

## **SECTION 15: Regulatory information**

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU-Regulations**

Restrictions on use	: None.
Other information, restriction and prohibition regulations	: Not listed on the PIC list (Regulation EU 649/2012). Not listed on the POP list (Regulation EU 2019/1021).
Seveso Directive : 2012/18/EU (Seveso III)	: Covered.

#### **National regulations**

Regulatory reference	: Ensure all national/local regulations are observed.
----------------------	---

### 15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.

## **SECTION 16: Other information**

Indication of changes	: Revised safety data sheet in accordance with commission regulation (EU) No 453/2010.
-----------------------	--

Section	Changed item	Comments
	Endocrine disrupting properties	<b>Added</b>
	Supersedes version of	<b>Modified</b>
	Revision date	<b>Modified</b>
1.1	EC Index-No.	<b>Removed</b>
2	Supplemental information	<b>Added</b>
2.3	Other hazards which do not result in classification	<b>Modified</b>
7	Safe handling of the gas receptacle	<b>Modified</b>
9	Particle characteristics	<b>Added</b>
9	Vapour pressure	<b>Modified</b>
9	Partition coefficient n-octanol/water (Log Pow)	<b>Added</b>
9	Upper explosive limit (UEL)	<b>Added</b>
9	Lower explosive limit (LEL)	<b>Added</b>
9	Density	<b>Added</b>
9	Partition coefficient n-octanol/water (Log Kow)	<b>Added</b>
9.1	Decomposition temperature	<b>Modified</b>
11	Acute toxicity - comment	<b>Modified</b>
12.7	Other adverse effects	<b>Modified</b>
14	Number of blue cones/lights (ADN)	<b>Added</b>
14	Classification code (ADN)	<b>Added</b>
14	Equipment required (ADN)	<b>Added</b>
14	Excepted quantities (ADN)	<b>Added</b>
14	Danger labels (ADN)	<b>Added</b>
14	Limited quantities (ADN)	<b>Added</b>
14	Classification code (RID)	<b>Added</b>
14	Colis express (express parcels) (RID)	<b>Added</b>
14	Excepted quantities (RID)	<b>Added</b>
14	Hazard identification number (RID)	<b>Added</b>
14	Limited quantities (RID)	<b>Added</b>
14	Mixed packing provisions (RID)	<b>Added</b>
14	Packing instructions (RID)	<b>Added</b>
14	Special provisions for carriage - Loading, unloading and handling (RID)	<b>Added</b>
14	Proper Shipping Name (RID)	<b>Added</b>
14	Portable tank and bulk container instructions (RID)	<b>Added</b>
14	Special provisions (RID)	<b>Added</b>
14	Tank codes for RID tanks (RID)	<b>Added</b>
14	Special provisions for RID tanks (RID)	<b>Added</b>

14	Transport category (RID)	<b>Added</b>
14	UN-No. (RID)	<b>Modified</b>
14.1	UN-No. (ADN)	<b>Added</b>
14.2	Proper Shipping Name (ADN)	<b>Added</b>
14.3	Danger labels (RID)	<b>Added</b>
14.6	Special provisions (ADN)	<b>Added</b>
14.6	Special provisions (ADR)	<b>Modified</b>
15	Seveso Directive : 2012/18/EU (Seveso III)	<b>Modified</b>
16	Abbreviations and acronyms	<b>Modified</b>

### Abbreviations and acronyms

: ATE - Acute Toxicity Estimate.  
 CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008.  
 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006.  
 EINECS - European Inventory of Existing Commercial Chemical Substances.  
 CAS# - Chemical Abstract Service number.  
 PPE - Personal Protection Equipment.  
 LC50 - Lethal Concentration to 50 % of a test population.  
 RMM - Risk Management Measures.  
 PBT - Persistent, Bioaccumulative and Toxic.  
 vPvB - Very Persistent and Very Bioaccumulative.  
 STOT- SE : Specific Target Organ Toxicity - Single Exposure.  
 CSA - Chemical Safety Assessment.  
 EN - European Standard.  
 UN - United Nations.  
 ADR - Agreement concerning the International Carriage of Dangerous Goods by Road.  
 IATA - International Air Transport Association.  
 IMDG code - International Maritime Dangerous Goods.  
 RID - Regulations concerning the International Carriage of Dangerous Goods by Rail.  
 WGK - Water Hazard Class.  
 STOT - RE : Specific Target Organ Toxicity - Repeated Exposure.  
 UFI : Unique Formula Identifier.  
 ADN -International Carriage of Dangerous Goods by Inland Waterways.  
 PROC -Process category

### Training advice

: The hazard of asphyxiation is often overlooked and must be stressed during operator training.  
 For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at <http://www.eiga.eu>.

### Further information

: Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).  
 Key literature references and sources of data are maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at <http://www.Eiga.eu>.

Full text of H- and EUH-statements	
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
H280	Contains gas under pressure; may explode if heated.

### DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.  
Details given in this document are believed to be correct at the time of going to press.  
Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

**End of document**