

Arsine**NOAL_0005**

Country : DK / Language : EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Trade name : Arsine, Arsine N56
SDS no : NOAL_0005
Other means of identification : Arsine
CAS-No. : 7784-42-1
EC-No. : 232-066-3
EC Index-No. : 033-006-00-7
REACH registration No : 01-2120048082-66
Chemical formula : AsH₃

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use.
Test gas/Calibration gas.
Laboratory use.
Contact supplier for more information on uses.
Uses advised against : Consumer use.
Uses other than those listed above are not supported, contact your supplier for more information on other uses.

1.3. Details of the supplier of the safety data sheet**Company identification****Supplier**

AIR LIQUIDE Denmark A/S
Høje Taastrupvej 42
2630 Taastrup - DENMARK
T +45 76 25 25 25
info.denmark@airliquide.com


E-Mail address (competent person) : eunordic-sds@airliquide.com

1.4. Emergency telephone number

Emergency telephone number : 112
(24 / 7)
Availability

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Physical hazards	Flammable gases, Category 1A	H220
	Gases under pressure : Liquefied gas	H280
Health hazards	Acute toxicity (inhalation:gas) Category 1	H330
	Specific target organ toxicity – Repeated exposure, Category 2	H373
Environmental hazards	Hazardous to the aquatic environment – Acute Hazard, Category 1	H400
	Hazardous to the aquatic environment – Chronic Hazard, Category 1	H410

	SAFETY DATA SHEET	Page : 2/18
		Revised edition no : 4.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
Arsine		NOAL_0005
		Country : DK / Language : EN

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazard statements (CLP) :

H220 - Extremely flammable gas.
 H280 - Contains gas under pressure; may explode if heated.
 H330 - Fatal if inhaled.
 H373 - May cause damage to organs through prolonged or repeated exposure.
 H410 - Very toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

- Prevention

: P271 - Use only outdoors or in a well-ventilated area.
 P273 - Avoid release to the environment.
 P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
 P284 - Wear respiratory protection.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- Response

: P314 - Get medical advice/attention if you feel unwell.
 P391 - Collect spillage.
 P320 - Specific treatment is urgent (see supplemental first aid instruction on this label).
 P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P310 - Immediately call a POISON CENTER or doctor.
 P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
 P381 - In case of leakage, eliminate all ignition sources.
 P381 - In case of leakage, eliminate all ignition sources.

- Storage

: P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
 P405 - Store locked up.
 P403 - Store in a well-ventilated place.
 P410+P403 - Protect from sunlight. Store in a well-ventilated place.

- Disposal considerations

: P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.


2.3. Other hazards

Contact with liquid may cause cold burns/frostbite.
 Not classified as PBT or vPvB.
 The substance/mixture has no endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.1. Substances

Name	Product identifier	Composition [V-%]:	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Arsine	CAS-No.: 7784-42-1 EC-No.: 232-066-3 EC Index-No.: 033-006-00-7 REACH registration No: 01-2120048082-66	100	Flam. Gas 1A, H220 Press. Gas (Liq.), H280 Acute Tox. 1 (Inhalation:gas), H330 STOT RE 2, H373 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

	SAFETY DATA SHEET	Page : 3/18
		Revised edition no : 4.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
Arsine		NOAL_0005
		Country : DK / Language : EN

Contains no other components or impurities which will influence the classification of the product.

3.2. Mixtures

Not established.

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

SECTION 5: Firefighting measures

5.1. Extinguishing media


- Suitable extinguishing media : Shutting off the source of the gas is the preferred method of control.
- Unsuitable extinguishing media : Do not use water jet to extinguish.
Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : Arsenic and its oxides.

5.3. Advice for firefighters

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
If possible, stop flow of product.
Use water spray or fog to knock down fire fumes if possible.
Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.
Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus.
Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Gas-tight chemical protective suits for emergency teams.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

	SAFETY DATA SHEET	Page : 4/18
		Revised edition no : 4.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
Arsine		NOAL_0005
		Country : DK / Language : EN

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel :
- : Act in accordance with local emergency plan.
 - Try to stop release.
 - Evacuate area.
 - Eliminate ignition sources.
 - Ensure adequate air ventilation.
 - Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
 - Stay upwind.
 - See section 8 of the SDS for more information on personal protective equipment
- For emergency responders :
- : Monitor concentration of released product.
 - Consider the risk of potentially explosive atmospheres.
 - Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
 - See section 5.3 of the SDS for more information.

6.2. Environmental precautions

- Try to stop release.

6.3. Methods and material for containment and cleaning up

- Ventilate area.


6.4. Reference to other sections

- See also sections 8 and 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

- Safe use of the product :
- : Do not breathe gas.
 - Avoid release of product into atmosphere.
 - The product must be handled in accordance with good industrial hygiene and safety procedures.
 - Only experienced and properly instructed persons should handle gases under pressure.
 - Consider pressure relief device(s) in gas installations.
 - Ensure the complete gas system was (or is regularly) checked for leaks before use.
 - Do not smoke while handling product.
 - Avoid exposure, obtain special instructions before use.
 - Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
 - Installation of a cross purge assembly between the container and the regulator is recommended.
 - Avoid suck back of water, acid and alkalis.
 - Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment.
 - Purge air from system before introducing gas.
 - Take precautionary measures against static discharge.
 - Keep away from ignition sources (including static discharges).
 - Consider the use of only non-sparking tools.
 - Ensure equipment is adequately earthed.

	SAFETY DATA SHEET	Page : 5/18
		Revised edition no : 4.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
Arsine		NOAL_0005
		Country : DK / Language : EN

Safe handling of the gas receptacle

: Refer to supplier's container handling instructions.
 Do not allow backfeed into the container.
 Protect containers from physical damage; do not drag, roll, slide or drop.
 When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
 Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
 If user experiences any difficulty operating valve discontinue use and contact supplier.
 Never attempt to repair or modify container valves or safety relief devices.
 Damaged valves should be reported immediately to the supplier.
 Keep container valve outlets clean and free from contaminants particularly oil and water.
 Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
 Close container valve after each use and when empty, even if still connected to equipment.
 Never attempt to transfer gases from one cylinder/container to another.
 Never use direct flame or electrical heating devices to raise the pressure of a container.
 Do not remove or deface labels provided by the supplier for the identification of the content of the container.
 Suck back of water into the container must be prevented.
 Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers.
 Containers should not be stored in conditions likely to encourage corrosion.
 Container valve guards or caps should be in place.
 Containers should be stored in the vertical position and properly secured to prevent them from falling over.
 Stored containers should be periodically checked for general condition and leakage.
 Keep container below 50°C in a well ventilated place.
 Store containers in location free from fire risk and away from sources of heat and ignition.
 Keep away from combustible materials.
 Segregate from oxidant gases and other oxidants in store.
 All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Arsine (7784-42-1)	
Austria - Occupational Exposure Limits	
Local name	Arsenwasserstoff
MAK (mg/m³)	0.2 mg/m³
MAK (OEL TWA) [ppm]	0.05 ppm
MAK (OEL STEL)	1 mg/m³
MAK (OEL STEL) [ppm]	0.25 ppm
Belgium - Occupational Exposure Limits	
Local name	Arsine # Arsine
OEL TWA	0.16 mg/m³

Arsine

NOAL_0005

Country : DK / Language : EN


OEL TWA [ppm]	0.05 ppm
Bulgaria - Occupational Exposure Limits	
Local name	Арсеноводород (арсин)
OEL TWA	0.05 mg/m ³
Croatia - Occupational Exposure Limits	
Local name	Arsin
GVI (OEL TWA) [1]	0.16 mg/m ³
GVI (OEL TWA) [2]	0.05 ppm
Remark	F+, T+, N
Czech Republic - Occupational Exposure Limits	
Local name	Arsenovodík
PEL (OEL TWA)	0.1 mg/m ³
PEL (OEL TWA) [ppm]	0.031 ppm
NPK-P (OEL C)	0.2 mg/m ³
NPK-P (OEL C) [ppm]	0.063 ppm
Denmark - Occupational Exposure Limits	
Local name	Arsin (Arsenbrinte)
OEL TWA [1]	0.03 mg/m ³
OEL TWA [2]	0.01 ppm
Estonia - Occupational Exposure Limits	
Local name	Arseenhüdriid
OEL TWA	0.05 mg/m ³
OEL TWA [ppm]	0.02 ppm
Finland - Occupational Exposure Limits	
Local name	Arseenivety
HTP (OEL TWA) [1]	0.01 mg/m ³
France - Occupational Exposure Limits	
Local name	Hydrogène arsénié (Arsine)
VME (OEL TWA)	0.2 mg/m ³
VME (OEL TWA) [ppm]	0.05 ppm
VLE (OEL C/STEL)	0.8 mg/m ³
VLE (OEL C/STEL) [ppm]	0.2 ppm
Remark	Valeurs recommandées/admises
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Arsin

Arsine

NOAL_0005

Country : DK / Language : EN

AGW (OEL TWA) [1]	0.016 mg/m ³
AGW (OEL TWA) [2]	0.005 ppm
Remark	AGS
Greece - Occupational Exposure Limits	
OEL TWA	0.2 mg/m ³
OEL TWA [ppm]	0.05 ppm
Hungary - Occupational Exposure Limits	
Local name	ARZIN
AK (OEL TWA)	0.2 mg/m ³
CK (OEL STEL)	0.8 mg/m ³
Ireland - Occupational Exposure Limits	
Local name	Arsine
OEL TWA [1]	0.02 mg/m ³
OEL TWA [2]	0.005 ppm
Lithuania - Occupational Exposure Limits	
Local name	Arsanas (arseno hidridas, arsinas)
IPRV (OEL TWA)	0.05 mg/m ³
IPRV (OEL TWA) [ppm]	0.02 ppm
Poland - Occupational Exposure Limits	
Local name	Arsan
NDS (OEL TWA)	0.02 mg/m ³
Portugal - Occupational Exposure Limits	
Local name	Arsina
OEL TWA [ppm]	0.05 ppm
Romania - Occupational Exposure Limits	
Local name	Hidrogen arseniat
OEL TWA	0.1 mg/m ³
OEL TWA [ppm]	0.03 ppm
OEL STEL	0.3 mg/m ³
OEL STEL [ppm]	0.09 ppm
Slovenia - Occupational Exposure Limits	
Local name	arzin
OEL TWA	0.2 mg/m ³
OEL TWA [ppm]	0.05 ppm
OEL STEL	0.8 mg/m ³

	SAFETY DATA SHEET	Page : 8/18
		Revised edition no : 4.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
Arsine		NOAL_0005
		Country : DK / Language : EN

OEL STEL [ppm]	0.2 ppm
Spain - Occupational Exposure Limits	
Local name	Hidruro de arsénico (Arsenamina)
VLA-ED (OEL TWA) [1]	0.16 mg/m ³
VLA-ED (OEL TWA) [2]	0.05 ppm
Remark	r (Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el "Reglamento (CE) n° 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos" (REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido).
Sweden - Occupational Exposure Limits	
Local name	Arseniktrihydrid
NGV (OEL TWA)	0.05 mg/m ³
NGV (OEL TWA) [ppm]	0.02 ppm
United Kingdom - Occupational Exposure Limits	
Local name	Arsine
WEL TWA (OEL TWA) [1]	0.16 mg/m ³
WEL TWA (OEL TWA) [2]	0.05 ppm
Norway - Occupational Exposure Limits	
Local name	Arsenhydrid
Grenseverdi (OEL TWA) [1]	0.01 mg/m ³
Grenseverdi (OEL TWA) [2]	0.003 ppm
Switzerland - Occupational Exposure Limits	
Local name	Arsenwasserstoff
MAK (OEL TWA) [1]	0.16 mg/m ³
MAK (OEL TWA) [2]	0.05 ppm
Remark	HSE, NIOSH
USA - ACGIH - Occupational Exposure Limits	
Local name	Arsine
ACGIH OEL TWA [ppm]	0.01 ppm
Remark (ACGIH)	PNS & vascular system impair

Arsine (7784-42-1)	
Austria - Occupational Exposure Limits	
Local name	Arsenwasserstoff

Arsine

NOAL_0005

Country : DK / Language : EN


MAK (mg/m ³)	0.2 mg/m ³
MAK (OEL TWA) [ppm]	0.05 ppm
MAK (OEL STEL)	1 mg/m ³
MAK (OEL STEL) [ppm]	0.25 ppm
Belgium - Occupational Exposure Limits	
Local name	Arsine # Arsine
OEL TWA	0.16 mg/m ³
OEL TWA [ppm]	0.05 ppm
Bulgaria - Occupational Exposure Limits	
Local name	Арсеноводород (арсин)
OEL TWA	0.05 mg/m ³
Croatia - Occupational Exposure Limits	
Local name	Arsin
GVI (OEL TWA) [1]	0.16 mg/m ³
GVI (OEL TWA) [2]	0.05 ppm
Remark	F+, T+, N
Czech Republic - Occupational Exposure Limits	
Local name	Arsenovodík
PEL (OEL TWA)	0.1 mg/m ³
PEL (OEL TWA) [ppm]	0.031 ppm
NPK-P (OEL C)	0.2 mg/m ³
NPK-P (OEL C) [ppm]	0.063 ppm
Denmark - Occupational Exposure Limits	
Local name	Arsin (Arsenbrinte)
OEL TWA [1]	0.03 mg/m ³
OEL TWA [2]	0.01 ppm
Estonia - Occupational Exposure Limits	
Local name	Arseenhüdiid
OEL TWA	0.05 mg/m ³
OEL TWA [ppm]	0.02 ppm
Finland - Occupational Exposure Limits	
Local name	Arseenivety
HTP (OEL TWA) [1]	0.01 mg/m ³
France - Occupational Exposure Limits	
Local name	Hydrogène arsénié (Arsine)


Arsine

NOAL_0005

Country : DK / Language : EN

VME (OEL TWA)	0.2 mg/m ³
VME (OEL TWA) [ppm]	0.05 ppm
VLE (OEL C/STEL)	0.8 mg/m ³
VLE (OEL C/STEL) [ppm]	0.2 ppm
Remark	Valeurs recommandées/admises
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Arsin
AGW (OEL TWA) [1]	0.016 mg/m ³
AGW (OEL TWA) [2]	0.005 ppm
Remark	AGS
Greece - Occupational Exposure Limits	
OEL TWA	0.2 mg/m ³
OEL TWA [ppm]	0.05 ppm
Hungary - Occupational Exposure Limits	
Local name	ARZIN
AK (OEL TWA)	0.2 mg/m ³
CK (OEL STEL)	0.8 mg/m ³
Ireland - Occupational Exposure Limits	
Local name	Arsine
OEL TWA [1]	0.02 mg/m ³
OEL TWA [2]	0.005 ppm
Lithuania - Occupational Exposure Limits	
Local name	Arsanas (arseno hidridas, arsinas)
IPRV (OEL TWA)	0.05 mg/m ³
IPRV (OEL TWA) [ppm]	0.02 ppm
Poland - Occupational Exposure Limits	
Local name	Arsan
NDS (OEL TWA)	0.02 mg/m ³
Portugal - Occupational Exposure Limits	
Local name	Arsina
OEL TWA [ppm]	0.05 ppm
Romania - Occupational Exposure Limits	
Local name	Hidrogen arseniat
OEL TWA	0.1 mg/m ³
OEL TWA [ppm]	0.03 ppm

	SAFETY DATA SHEET		Page : 11/18
			Revised edition no : 4.0
			Revision date : 2023-01-19
			Supersedes version of : 2021-06-16
Arsine		NOAL_0005	
		Country : DK / Language : EN	
OEL STEL	0.3 mg/m ³		
OEL STEL [ppm]	0.09 ppm		
Slovenia - Occupational Exposure Limits			
Local name	arzin		
OEL TWA	0.2 mg/m ³		
OEL TWA [ppm]	0.05 ppm		
OEL STEL	0.8 mg/m ³		
OEL STEL [ppm]	0.2 ppm		
Spain - Occupational Exposure Limits			
Local name	Hidruro de arsénico (Arsenamína)		
VLA-ED (OEL TWA) [1]	0.16 mg/m ³		
VLA-ED (OEL TWA) [2]	0.05 ppm		
Remark	<p>r (Esta sustancia tiene establecidas restricciones a la fabricación, la comercialización o el uso en los términos especificados en el "Reglamento (CE) n° 1907/2006 sobre Registro, Evaluación, Autorización y Restricción de sustancias y preparados químicos" (REACH) de 18 de diciembre de 2006 (DOUE L 369 de 30 de diciembre de 2006). Las restricciones de una sustancia pueden aplicarse a todos los usos o sólo a usos concretos. El anexo XVII del Reglamento REACH contiene la lista de todas las sustancias restringidas y especifica los usos que se han restringido).</p>		
Sweden - Occupational Exposure Limits			
Local name	Arseniktrihydrid		
NGV (OEL TWA)	0.05 mg/m ³		
NGV (OEL TWA) [ppm]	0.02 ppm		
United Kingdom - Occupational Exposure Limits			
Local name	Arsine		
WEL TWA (OEL TWA) [1]	0.16 mg/m ³		
WEL TWA (OEL TWA) [2]	0.05 ppm		
Norway - Occupational Exposure Limits			
Local name	Arsenhydrid		
Grenseverdi (OEL TWA) [1]	0.01 mg/m ³		
Grenseverdi (OEL TWA) [2]	0.003 ppm		
Switzerland - Occupational Exposure Limits			
Local name	Arsenwasserstoff		
MAK (OEL TWA) [1]	0.16 mg/m ³		
MAK (OEL TWA) [2]	0.05 ppm		
Remark	HSE, NIOSH		

	SAFETY DATA SHEET	Page : 12/18
		Revised edition no : 4.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
Arsine		NOAL_0005 Country : DK / Language : EN

USA - ACGIH - Occupational Exposure Limits

Local name	Arsine
ACGIH OEL TWA [ppm]	0.01 ppm
Remark (ACGIH)	PNS & vascular system impair

DNEL (Derived-No Effect Level) : None established.

PNEC (Predicted No-Effect Concentration) : None established.

8.2. Exposure controls
8.2.1. Appropriate engineering controls

Product to be handled in a closed system and under strictly controlled conditions.
Provide adequate general and local exhaust ventilation.
Preferably use permanent leak-tight installations (e.g. welded pipes).
Systems under pressure should be regularly checked for leakages.
Ensure exposure is below occupational exposure limits (where available).
Gas detectors should be used when toxic gases may be released.
Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.
The following recommendations should be considered:

- Eye/face protection : Wear goggles when transfilling or breaking transfer connections.
Standard EN 166 - Personal eye-protection - specifications.
- Skin protection
 - Hand protection : Wear working gloves when handling gas containers.
Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.
Wear cold insulating gloves when transfilling or breaking transfer connections.
Standard EN 511 - Cold insulating gloves.
 - Other : Consider the use of flame resistant anti-static safety clothing.
Standard EN ISO 14116 - Limited flame spread materials.
Standard EN 1149-5 - Protective clothing: Electrostatic properties.
Wear safety shoes while handling containers.
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
- Respiratory protection : Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Consult respiratory device supplier's product information for the selection of the appropriate device.
Keep self contained breathing apparatus readily available for emergency use.
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
- Thermal hazards : None in addition to the above sections.

8.2.3. Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties
9.1. Information on basic physical and chemical properties

Appearance

- Physical state at 20°C / 101.3kPa : Gas
- Colour : Colourless.

Arsine**NOAL_0005**

Country : DK / Language : EN

Odour	: Odourless. Odour threshold is subjective and inadequate to warn of overexposure.
pH	: Not applicable for gases and gas mixtures.
Melting point / Freezing point	: -117 °C -117 °C
Boiling point	: -62.5 °C
Flash point	: Not applicable for gases and gas mixtures.
Flammability	: Extremely flammable gas
Explosive limits	: 3.9 – 77.8 vol %
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Vapour pressure [20°C]	: 15 bar(a)
Vapour pressure [50°C]	: 27.5 bar(a)
Density	: Not applicable
Vapour density	: Not applicable for gases and gas mixtures.
Relative density, liquid (water=1)	: 1.6
Relative density, gas (air=1)	: 2.7
Water solubility	: 778 mg/l
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for inorganic products.
Auto-ignition temperature	: 285 °C
Decomposition temperature	: Not applicable.
Viscosity, kinematic	: Not applicable for gases and gas mixtures.
Particle characteristics	: Not applicable for gases and gas mixtures.

9.2. Other information**9.2.1. Information with regard to physical hazard classes**

Oxidising properties	: No oxidising properties.
Tci	: 3.9 %
Critical temperature [°C]	: 100 °C

9.2.2. Other safety characteristics

Molar mass	: 78 g/mol
Gas group	: Press. Gas (Liq.)
Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.


10.3. Possibility of hazardous reactions

None.

Reactivity	: This mixture contains components with the following reactivity : Can form explosive mixture with air. May react violently with oxidants.
------------	--

10.4. Conditions to avoidNone under recommended storage and handling conditions (see section 7).
Avoid moisture in installation systems.**10.5. Incompatible materials**

For additional information on compatibility refer to ISO 11114.

	SAFETY DATA SHEET	Page : 14/18
		Revised edition no : 4.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
Arsine		NOAL_0005
		Country : DK / Language : EN

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Fatal if inhaled.

LC50 Inhalation - Rat [ppm]	10 ppm/4h
-----------------------------	-----------

Arsine (7784-42-1)

LC50 Inhalation - Rat [ppm]	10 ppm/4h
-----------------------------	-----------

Skin corrosion/irritation : No known effects from this product.
Serious eye damage/irritation : No known effects from this product.
Respiratory or skin sensitisation : No known effects from this product.
Germ cell mutagenicity : No known effects from this product.
Carcinogenicity : No known effects from this product.
Toxic for reproduction : Fertility : No known effects from this product.
Toxic for reproduction : unborn child : No known effects from this product.
STOT-single exposure : No known effects from this product.
STOT-repeated exposure : May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard : Not applicable for gases and gas mixtures.

11.2. Information on other hazards

Other information : The substance/mixture has no endocrine disrupting properties.

SECTION 12: Ecological information

12.1. Toxicity

Assessment : Very toxic to aquatic life.
Very toxic to aquatic life with long lasting effects.
EC50 48h - Daphnia magna [mg/l] : No data available.
EC50 72h - Algae [mg/l] : No data available.
LC50 96 h - Fish [mg/l] : No data available.

12.2. Persistence and degradability

Assessment : No data available.

12.3. Bioaccumulative potential

Assessment : No data available.

12.4. Mobility in soil


Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.
Partition into soil is unlikely.

12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.

12.6. Endocrine disrupting properties

The substance/mixture has no endocrine disrupting properties.

	SAFETY DATA SHEET	Page : 15/18
		Revised edition no : 4.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
Arsine		NOAL_0005
		Country : DK / Language : EN

12.7. Other adverse effects

Other adverse effects : No known effects from this product.
Effect on the ozone layer : No effect on the ozone layer.
Effect on global warming : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Contact supplier if guidance is required.
Do not discharge into areas where there is a risk of forming an explosive mixture with air.
Waste gas should be flared through a suitable burner with flash back arrestor.
Must not be discharged to atmosphere.
Ensure that the emission levels from local regulations or operating permits are not exceeded.
Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods.
Return unused product in original container to supplier.

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended) : 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.

13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN
UN-No. : 2188

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) : ARSINE
Transport by air (ICAO-TI / IATA-DGR) : Arsine
Transport by sea (IMDG) : ARSINE

14.3. Transport hazard class(es)

Labelling



2.3 : Toxic gases.
2.1 : Flammable gases.

Transport by road/rail (ADR/RID)


Class : 2
Classification code : 2TF
Tunnel Restriction : D - Passage forbidden through tunnels of category D and E

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.3 (2.1)
Emergency Schedule (EmS) - Fire : F-D
Emergency Schedule (EmS) - Spillage : S-U

14.4. Packing group

Transport by road/rail (ADR/RID) : Not established.
Transport by air (ICAO-TI / IATA-DGR) : Not established.

	SAFETY DATA SHEET	Page : 16/18
		Revised edition no : 4.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
Arsine		NOAL_0005
		Country : DK / Language : EN

Transport by sea (IMDG) : Not established.

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : Environmentally hazardous substance / mixture.
 Transport by air (ICAO-TI / IATA-DGR) : Environmentally hazardous substance / mixture.
 Transport by sea (IMDG) : Marine pollutant

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P200
 Transport by air (ICAO-TI / IATA-DGR)
 Passenger and Cargo Aircraft : Forbidden.
 Cargo Aircraft only : Forbidden.
 Transport by sea (IMDG) : P200

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment.
 Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
 Before transporting product containers:
 - Ensure there is adequate ventilation.
 - Ensure that containers are firmly secured.
 - Ensure valve is closed and not leaking.
 - Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
 - Ensure valve protection device (where provided) is correctly fitted.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Restrictions on use : None.
 Seveso Directive : 2012/18/EU (Seveso III) : Covered.

National regulations

Ensure all national/local regulations are observed.


France	
Occupational diseases	
Code	Description
RG 21	Professional poisoning by arsenic hydrogen

Germany

Water hazard class (WGK) : WGK 3, Highly hazardous to water (Classification according to AwSV)
 National Rules and Recommendations : [German regulations] BetriebssicherheitsV mit TRBSen insbesondere TRBS 3145 / TRGS 725 Ortsbewegliche Druckgasbehälter", TRBS 2141, BGR Regel 500 Teil 2.33: "Umgang mit Gasen", GefahrstoffV mit Technischen Regeln Gefährliche Stoffe TRGS insbesondere TRGS 407 "Tätigkeiten mit Gasen - Gefährdungsbeurteilung", TRGS 400, 500, 510, 900." BGR 104, TRBS 2152.

Netherlands

SZW-lijst van kankerverwekkende stoffen : The substance is not listed
 SZW-lijst van mutagene stoffen : The substance is not listed
 SZW-lijst van reprotoxische stoffen – Borstvoeding : The substance is not listed

	SAFETY DATA SHEET	Page : 17/18
		Revised edition no : 4.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
Arsine		NOAL_0005
		Country : DK / Language : EN

SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : The substance is not listed

SZW-lijst van reprotoxische stoffen – Ontwikkeling : The substance is not listed

Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product
Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

Storage class (LK) : LK 2 - Liquefied or pressurized gases

15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.

SECTION 16: Other information


Indication of changes : Safety data sheet in accordance with commission regulation (EU) No 2020/878.

Abbreviations and acronyms : ATE - Acute Toxicity Estimate
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
EINECS - European Inventory of Existing Commercial Chemical Substances
CAS# - Chemical Abstract Service number
PPE - Personal Protection Equipment
LC50 - Lethal Concentration to 50 % of a test population
RMM - Risk Management Measures
PBT - Persistent, Bioaccumulative and Toxic
vPvB - Very Persistent and Very Bioaccumulative
STOT- SE : Specific Target Organ Toxicity - Single Exposure
CSA - Chemical Safety Assessment
EN - European Standard
UN - United Nations
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA - International Air Transport Association
IMDG code - International Maritime Dangerous Goods
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
WGK - Water Hazard Class
STOT - RE : Specific Target Organ Toxicity - Repeated Exposure
UFI : Unique Formula Identifier

Training advice : Ensure operators understand the flammability hazard.
Users of breathing apparatus must be trained.
Ensure operators understand the toxicity hazard.

Further information : Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).
Key literature references and sources of data are maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at <http://www.Eiga.eu> .

Full text of H- and EUH-statements	
Acute Tox. 1 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 1
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Flam. Gas 1A	Flammable gases, Category 1A
H220	Extremely flammable gas.

	SAFETY DATA SHEET	Page : 18/18
		Revised edition no : 4.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
Arsine		NOAL_0005
		Country : DK / Language : EN
H280	Contains gas under pressure; may explode if heated.	
H330	Fatal if inhaled.	
H373	May cause damage to organs through prolonged or repeated exposure.	
H400	Very toxic to aquatic life.	
H410	Very toxic to aquatic life with long lasting effects.	
Press. Gas (Liq.)	Gases under pressure : Liquefied gas	
STOT RE 2	Specific target organ toxicity – Repeated exposure, Category 2	

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
 Details given in this document are believed to be correct at the time of going to press.
 Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document