

Page : 1/10 Revised edition no : 6.0

Revision date : 2023-01-19 Supersedes version of : 2021-06-16

Hydrogen

NOAL_0067A Country : DK / Language : EN

1.1. Product identifier			
Trade name	: Hydrogen, Alphagaz 1 Hydrogen, Alphagaz 2 Hydrogen, Hydrogen N50, Hydrogen N56, Hydrogen N35, Hydrogen N25 Tubetrailer		
SDS no	: NOAL_0067A		
Other means of identification	: Hydrogen		
	CAS-No. : 1333-74-0		
	EC-No. : 215-605-7		
	EC Index-No. : 001-001-00-9		
REACH registration No	: Listed in Annex IV / V REACH, exempted from registration.		
Chemical formula	: H2		
1.2. Relevant identified uses of the subst	ance or mixture and uses advised against		
Relevant identified uses	: Industrial and professional uses. Perform risk assessment prior to use.		
	Test gas/Calibration gas.		
	Laboratory use.		
	Chemical reaction / Synthesis. Use as a fuel.		
	Shield gas for welding processes.		
	Use for manufacture of electronic/photovoltaic components.		
	Laser gas.		
	Contact supplier for more information on uses.		
Uses advised against	: Do not inflate in party balloons because of the risk of explosion.		
	Consumer use.		
	Uses other than those listed above are not supported, contact your supplier for more information on other uses.		
1.3. Details of the supplier of the safety of	lata sheet		
Company identification			
Supplier			
AIR LIQUIDE Denmark A/S			
Høje Taastrupvej 42 2630 Taastrup - DENMARK			
T +45 76 25 25 25			
info.denmark@airliquide.com			
E-Mail address (competent person)	: eunordic-sds@airliquide.com		
1.4. Emergency telephone number			
Emergency telephone number	: 112		
	(24 / 7)		
	Availability		

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards	Flammable gases, Category 1A	H220
	Gases under pressure : Compressed gas	H280



Page : 2/10 Revised edition no : 6.0 Revision date : 2023-01-19

Supersedes version of : 2021-06-16 **NOAL 0067A**

Country : DK / Language : EN

Hydrogen

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)	
	GHS02 GHS04
Signal word (CLP)	: Danger
Hazard statements (CLP)	: H220 - Extremely flammable gas.
	H280 - Contains gas under pressure; may explode if heated.
Precautionary statements (CLP)	
- Prevention	 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
- Response	 P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely. P381 - In case of leakage, eliminate all ignition sources. P381 - In case of leakage, eliminate all ignition sources.
- Storage	: P403 - Store in a well-ventilated place. P410+P403 - Protect from sunlight. Store in a well-ventilated place.
2.3. Other hazards	
	None.
	Not classified as PBT or vPvB.
	The substance/mixture has no endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.1. Substances

Name	Product identifier	Composition [V- %]:	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrogen	CAS-No.: 1333-74-0 EC-No.: 215-605-7 EC Index-No.: 001-001-00-9 REACH registration No: *1	100	Flam. Gas 1A, H220 Press. Gas (Comp.), H280

Contains no other components or impurities which will influence the classification of the product. *1: Listed in Annex IV / V REACH, exempted from registration.

*3: Registration not required: Substance manufactured or imported < 1t/y.

3.2. Mixtures Not established.

SECTION 4: First aid measures	
4.1. Description of first aid measure	25
- Inhalation	 Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact	: Adverse effects not expected from this product.
- Eye contact	: Adverse effects not expected from this product.

⁻ Ingestion : Ingestion is not considered a potential route of exposure.



Page : 3/10

Revised edition no : 6.0

Revision date : 2023-01-19 Supersedes version of : 2021-06-16

Hydrogen

NOAL_0067A Country : DK / Language : EN

4.2. Most important symptoms and effects, both acute and delayed

See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures	
5.1. Extinguishing media	
- Suitable extinguishing media	: Water spray or fog.
the solution of the solution of the term of the	Dry powder.
- Unsuitable extinguishing media	: Carbon dioxide. Do not use water jet to extinguish.
5.2. Special hazards arising from the substan	ice or mixture
Specific hazards	: Exposure to fire may cause containers to rupture/explode.
Hazardous combustion products	: None.
5.3. Advice for firefighters	
Specific methods	 Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire. Move containers away from the fire area if this can be done without risk. In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

SECTION 6: Accidental release measures	
--	--

6.1. Personal precautions, protective equipment and emergency procedures		
For non-emergency personnel	 Act in accordance with local emergency plan. Stay upwind. See section 8 of the SDS for more information on personal protective equipment 	
For emergency responders	: See section 5.3 of the SDS for more information.	
6.2. Environmental precautions		
	Try to stop release.	
6.3. Methods and material for containment and cleaning up		
	Ventilate area.	
6.4. Reference to other sections		
	See also sections 8 and 13.	



Page : 4/10

Revised edition no : 6.0

Revision date : 2023-01-19 Supersedes version of : 2021-06-16

Hydrogen

NOAL_0067A Country : DK / Language : EN

SECTION 7: Handling and storage

7.1. Precautions for safe handling	
<u>7.1. Precautions for safe handling</u> Safe use of the product	 Do not breathe gas. Avoid release of product into atmosphere. The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularily) checked for leaks before use. Do not smoke while handling product. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Avoid suck back of water, acid and alkalis. Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment. Purge air from system before introducing gas. Take precautionary measures against static discharge. Keep away from ignition sources (including static discharges).
Safe handling of the gas receptacle	Consider the use of only non-sparking tools. Ensure equipment is adequately earthed. Refer to supplier's container handling instructions.
	 Do not allow backfeed into the container. Protect containers from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the content of the container. Suck back of water into the container must be prevented. Open valve slowly to avoid pressure shock.
7.2. Conditions for safe storage, including	any incompatibilities
	Observe all regulations and local requirements regarding storage of containers. Containers should not be stored in conditions likely to encourage corrosion. Container valve guards or caps should be in place. Containers should be stored in the vertical position and properly secured to prevent them from falling over. Stored containers should be periodically checked for general condition and leakage. Keep container below 50°C in a well ventilated place. Store containers in location free from fire risk and away from sources of heat and ignition. Keep away from combustible materials. Segregate from oxidant gases and other oxidants in store. All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere.
7.3. Specific end use(s)	None.

	SAFETY DATA SHEET	Page : 5/10
O Air Liquide		Revised edition no : 6.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-1
	Hydrogen	NOAL_0067A
	, ,	Country : DK / Language : EN
SECTION 8: Exposure control	s/personal protection	
8.1. Control parameters		
OEL (Occupational Exposure Limits)	: None available.	
DNEL (Derived-No Effect Level)	: None available.	
PNEC (Predicted No-Effect Concentratio	on) : None available.	
8.2. Exposure controls		
8.2.1. Appropriate engineering control	ls	
	Provide adequate general and local exhaust vent	lation.
	Product to be handled in a closed system.	
	Systems under pressure should be regularily che	-
	Gas detectors should be used when flammable g	· · · · · · · · · · · · · · · · · · ·
	Consider the use of a work permit system e.g. for	maintenance activities.
8.2.2. Individual protection measures,	, e.g. personal protective equipment	
	A rick apparement should be conducted and dear	
		imented in each work area to assess the
	risks related to the use of the product and to select	ct the PPE that matches the relevant risk.
	risks related to the use of the product and to select The following recommendations should be consid	ct the PPE that matches the relevant risk. lered:
- Fuelface protection	risks related to the use of the product and to selec The following recommendations should be consid PPE compliant to the recommended EN/ISO stan	ct the PPE that matches the relevant risk. lered:
• Eye/face protection	risks related to the use of the product and to selec The following recommendations should be consid PPE compliant to the recommended EN/ISO stan : Wear safety glasses with side shields.	ct the PPE that matches the relevant risk. lered: dards should be selected.
	risks related to the use of the product and to selec The following recommendations should be consid PPE compliant to the recommended EN/ISO stan	ct the PPE that matches the relevant risk. lered: dards should be selected.
 Eye/face protection Skin protection Hand protection 	risks related to the use of the product and to selec The following recommendations should be consid PPE compliant to the recommended EN/ISO stan : Wear safety glasses with side shields.	ct the PPE that matches the relevant risk. lered: dards should be selected. cifications.
Skin protection	risks related to the use of the product and to select The following recommendations should be conside PPE compliant to the recommended EN/ISO stan Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - spec	ot the PPE that matches the relevant risk. lered: dards should be selected. cifications.
Skin protection	risks related to the use of the product and to select The following recommendations should be conside PPE compliant to the recommended EN/ISO stan Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - spect	et the PPE that matches the relevant risk. lered: dards should be selected. cifications. ers. hanical risk, performance level 1 or higher.
Skin protection - Hand protection	 risks related to the use of the product and to select The following recommendations should be considered PPE compliant to the recommended EN/ISO stants: Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specence Wear working gloves when handling gas contained Standard EN 388 - Protective gloves against meet Standard EN ISO 14116 - Limited flame spread meta Standard EN ISO 14116 - Lim	et the PPE that matches the relevant risk. lered: dards should be selected. cifications. ers. hanical risk, performance level 1 or higher. ety clothing. haterials.
Skin protection - Hand protection	 risks related to the use of the product and to select The following recommendations should be considered PPE compliant to the recommended EN/ISO stants: Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specence Standard EN 388 - Protective gloves against meters. Consider the use of flame resistant anti-static safet Standard EN ISO 14116 - Limited flame spread m Standard EN 1149-5 - Protective clothing: Electron 	et the PPE that matches the relevant risk. lered: dards should be selected. cifications. ers. hanical risk, performance level 1 or higher. ety clothing. haterials.
Skin protection - Hand protection	 risks related to the use of the product and to select The following recommendations should be considered PPE compliant to the recommended EN/ISO stants: Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specence Standard EN 388 - Protective gloves against meters. Consider the use of flame resistant anti-static safet Standard EN ISO 14116 - Limited flame spread m Standard EN 1149-5 - Protective clothing: Electron Wear safety shoes while handling containers. 	et the PPE that matches the relevant risk. lered: dards should be selected. cifications. ers. hanical risk, performance level 1 or higher. ety clothing. haterials. static properties.
 Skin protection Hand protection Other 	 risks related to the use of the product and to select The following recommendations should be considered PPE compliant to the recommended EN/ISO stants: Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specence Standard EN 388 - Protective gloves against meters. Consider the use of flame resistant anti-static safets Standard EN ISO 14116 - Limited flame spread m Standard EN 1149-5 - Protective clothing: Electron Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipation of the specific equi	et the PPE that matches the relevant risk. lered: dards should be selected. cifications. ers. hanical risk, performance level 1 or higher. ety clothing. naterials. static properties.
Skin protection - Hand protection	 risks related to the use of the product and to select The following recommendations should be considered PPE compliant to the recommended EN/ISO stands: Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - spece Wear working gloves when handling gas contained Standard EN 388 - Protective gloves against meters and the use of flame resistant anti-static safet Standard EN ISO 14116 - Limited flame spread m Standard EN 1149-5 - Protective clothing: Electrow Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equip Self contained breathing apparatus is recommented for the specific term of the set of the set	ct the PPE that matches the relevant risk. lered: dards should be selected. cifications. ers. hanical risk, performance level 1 or higher. ety clothing. haterials. static properties. uipment - Safety footwear. ded, where unknown exposure may be
 Skin protection Hand protection Other 	 risks related to the use of the product and to select The following recommendations should be considered PPE compliant to the recommended EN/ISO stands: Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - spectrum standard EN 388 - Protective gloves against meters Standard EN 388 - Protective gloves against meters Standard EN ISO 14116 - Limited flame spread meters Standard EN 1149-5 - Protective clothing: Electrod Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment of the set of th	ct the PPE that matches the relevant risk. lered: dards should be selected. cifications. ers. hanical risk, performance level 1 or higher. ety clothing. haterials. static properties. uipment - Safety footwear. ded, where unknown exposure may be
 Skin protection Hand protection Other 	 risks related to the use of the product and to select The following recommendations should be considered PPE compliant to the recommended EN/ISO stands: Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - spece Wear working gloves when handling gas contained Standard EN 388 - Protective gloves against meters and the use of flame resistant anti-static safet Standard EN ISO 14116 - Limited flame spread m Standard EN 1149-5 - Protective clothing: Electrow Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equip Self contained breathing apparatus is recommented for the specific term of the set of the set	ct the PPE that matches the relevant risk. lered: dards should be selected. cifications. ers. hanical risk, performance level 1 or higher. ety clothing. haterials. static properties. uipment - Safety footwear. ded, where unknown exposure may be
 Skin protection Hand protection Other Respiratory protection 	 risks related to the use of the product and to select The following recommendations should be conside PPE compliant to the recommended EN/ISO stant Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - spece Wear working gloves when handling gas contained Standard EN 388 - Protective gloves against meet Consider the use of flame resistant anti-static safed Standard EN ISO 14116 - Limited flame spread m Standard EN 1149-5 - Protective clothing: Electron Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equitational protective equitations. Standard EN ISO 20345 - Personal protective equitations in the spreader of the spected, e.g. during maintenance activities on in None necessary. None in addition to the above sections. 	ct the PPE that matches the relevant risk. lered: dards should be selected. cifications. ers. hanical risk, performance level 1 or higher. ety clothing. haterials. static properties. uipment - Safety footwear. ded, where unknown exposure may be
 Skin protection Hand protection Other Respiratory protection Thermal hazards 	 risks related to the use of the product and to select The following recommendations should be conside PPE compliant to the recommended EN/ISO stant Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - spece Wear working gloves when handling gas contained Standard EN 388 - Protective gloves against meet Consider the use of flame resistant anti-static safed Standard EN ISO 14116 - Limited flame spread m Standard EN 1149-5 - Protective clothing: Electron Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equitational protective equitations. Standard EN ISO 20345 - Personal protective equitations in the spreader of the spected, e.g. during maintenance activities on in None necessary. None in addition to the above sections. 	ct the PPE that matches the relevant risk. lered: dards should be selected. cifications. ers. hanical risk, performance level 1 or higher. ety clothing. haterials. static properties. uipment - Safety footwear. ded, where unknown exposure may be istallation systems.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
	Gas
	Colourless.
Odour	Odourless.
	Odour threshold is subjective and inadequate to warn of overexposure.
рН	Not applicable for gases and gas mixtures.
Melting point / Freezing point	-259 °C
	-259 °C
Boiling point	-253 °C
Flash point	Not applicable for gases and gas mixtures.
Flammability	Extremely flammable gas
Explosive limits	: 4 – 77 vol %
Lower explosion limit	Not available

Air Liquide

SAFETY DATA SHEET

Page : 6/10

Revised edition no : 6.0

Revision date : 2023-01-19 Supersedes version of : 2021-06-16

NOAL_0067A Country : DK / Language : EN

Hydrogen

Upper explosion limit	: Not available
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Density	: Not applicable
Vapour density	: Not applicable for gases and gas mixtures.
Relative density, liquid (water=1)	: 0.07
Relative density, gas (air=1)	: 0.07
Water solubility	: 1.6 mg/l
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for inorganic products.
Auto-ignition temperature	: 560 °C
Decomposition temperature	: Not applicable.
Viscosity, kinematic	No reliable data available.
Particle characteristics	: Not applicable for gases and gas mixtures.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.
Tci	: 5.5 %
Critical temperature [°C]	: -240 °C
9.2.2. Other safety characteristics	
Molar mass	: 2 g/mol
Evaporation rate	: Not applicable for gases and gas mixtures.
Gas group	: Compressed gas
Other data	: Burns with an invisible flame.

SECTION 10: Stability and reactivity 10.1. Reactivity No reactivity hazard other than the effects described in sub-sections below. 10.2. Chemical stability Stable under normal conditions. 10.3. Possibility of hazardous reactions None. Can form explosive mixture with air. May react violently with oxidants. Reactivity : This mixture contains components with the following reactivity : Can form explosive mixture with air. May react violently with oxidants. 10.4. Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Avoid moisture in installation systems. 10.5. Incompatible materials Air, Oxidisers. For additional information on compatibility refer to ISO 11114. 10.6. Hazardous decomposition products Under normal conditions of storage and use, hazardous decomposition products should not be produced.



Page : 7/10

Revised edition no : 6.0

Revision date : 2023-01-19 Supersedes version of : 2021-06-16

Hydrogen

NOAL_0067A Country : DK / Language : EN

SECTION 11: Toxicological information

Acute toxicity	: No known toxicological effects from this product.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Foxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.
11.2. Information on other hazards	
Other information	: The substance/mixture has no endocrine disrupting properties.

SECTION 12: Ecological information

12.1. Toxicity

Assessment	: No ecological damage caused by this product.
EC50 48h - Daphnia magna [mg/l]	: No data available.
EC50 72h - Algae [mg/l]	: No data available.
LC50 96 h - Fish [mg/l]	: No data available.
12.2. Persistence and degradability	
Assessment	: No ecological damage caused by this product.
12.3. Bioaccumulative potential	
Assessment	: No data available.
<u>12.4. Mobility in soil</u>	
Assessment	: Because of its high volatility, the product is unlikely to cause ground or water pollution.
	Partition into soil is unlikely.
12.5. Results of PBT and vPvB assessment	
Assessment	: No data available.
	Not classified as PBT or vPvB.
12.6. Endocrine disrupting properties	
	The substance/mixture has no endocrine disrupting properties.
12.7. Other adverse effects	
Other adverse effects	: No known effects from this product.
Effect on the ozone layer	: None.
Global warming potential [CO2=1]	: 6
Effect on global warming	: Contains greenhouse gas(es).
	When discharged in large quantities may contribute to the greenhouse effect.

Air Liquide

SAFETY DATA SHEET

Page : 8/10

Revised edition no : 6.0

Revision date : 2023-01-19 Supersedes version of : 2021-06-16

Hydrogen

NOAL 0067A Country : DK / Language : EN

SECTION 13: Disposal considerations

13.1. Waste treatment methods	
Decision 2000/532/EC as amended)	 Contact supplier if guidance is required. Do not discharge into areas where there is a risk of forming an explosive mixture with air. Waste gas should be flared through a suitable burner with flash back arrestor. Do not discharge into any place where its accumulation could be dangerous. Ensure that the emission levels from local regulations or operating permits are not exceeded. Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at http://www.eiga.org for more guidance on suitable disposal methods. Return unused product in original container to supplier. 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.
13.2. Additional information	
	External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number or ID number	
In accordance with ADR / RID / IMDG / IATA / ADN	
UN-No.	: 1049
14.2. UN proper shipping name	
Transport by road/rail (ADR/RID)	: HYDROGEN, COMPRESSED
Transport by air (ICAO-TI / IATA-DGR)	: Hydrogen, compressed
Transport by sea (IMDG)	: HYDROGEN, COMPRESSED
14.3. Transport hazard class(es)	
Labelling	
	2.1 : Flammable gases.
Transport by road/rail (ADR/RID) Class	: 2
Classification code	. z : 1F
Hazard identification number	23
Tunnel Restriction	 B/D - Tank carriage : Passage forbidden through tunnels of category B, C, D and E. Other carriage : Passage forbidden through tunnels of category D and E
Transport by air (ICAO-TI / IATA-DGR)	
Class / Div. (Sub. risk(s))	: 2.1
Transport by sea (IMDG)	
Class / Div. (Sub. risk(s))	: 2.1
Emergency Schedule (EmS) - Fire	: F-D
Emergency Schedule (EmS) - Spillage	: S-U
14.4. Packing group	
Transport by road/rail (ADR/RID)	: Not established.
Transport by air (ICAO-TI / IATA-DGR)	: Not established.
Transport by sea (IMDG)	: Not established.

	SAFETY DATA SHEET	Page : 9/10
O Air Liquide		Revised edition no : 6.0
Hirtiquide		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
	Hydrogen	NOAL_0067A
	<i>,</i>	Country : DK / Language : EN
14.5. Environmental hazards		· ·
Transport by road/rail (ADR/RID)	: None.	
Transport by air (ICAO-TI / IATA-DGR)	: None.	
Transport by sea (IMDG)	: None.	
14.6. Special precautions for user		
Packing Instruction(s)		
Transport by road/rail (ADR/RID)	: P200	
Transport by air (ICAO-TI / IATA-DGR)		
Passenger and Cargo Aircraft	: Forbidden.	
Cargo Aircraft only	: 200.	
Transport by sea (IMDG)	: P200	
Special transport precautions	: Avoid transport on vehicles where the load space	e is not separated from the driver's
	compartment.	
	Ensure vehicle driver is aware of the potential ha	izards of the load and knows what to do in
	the event of an accident or an emergency. Before transporting product containers:	
	- Ensure there is adequate ventilation.	
	- Ensure that containers are firmly secured.	
	- Ensure valve is closed and not leaking.	
	- Ensure valve outlet cap nut or plug (where prov	rided) is correctly fitted.
	- Ensure valve protection device (where provided	· ·

14.7. Maritime transport in bulk according to IMO instruments

I

Not applicable.

<u>15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture</u> EU-Regulations	
National legislation	: Ensure all national/local regulations are observed.
Seveso Directive : 2012/18/EU (Seveso III)	: Listed. Covered.
National regulations	
Ensure all national/local regulations are observed.	
Germany	
Water hazard class (WGK)	: WGK nwg, Non-hazardous to water (Classification according to AwSV)
National Rules and Recommendations	 [German regulations] BetriebssicherheitsV mit TRBSen insbesondere TRBS 3145 / TRGS 725 Ortsbewegliche Druckgasbehälter", TRBS 2141, BGRegel 500 Teil 2.33: "Umgang mi Gasen", GefahrstoffV mit Technischen Regeln Gefährliche Stoffe TRGS insbesondere TRGS 407 "Tätigkeiten mit Gasen - Gefährdungsbeurteilung", TRGS 400, 500, 510, 900." BGR 104, TRBS 2152.
Netherlands	
SZW-lijst van kankerverwekkende stoffen	: The substance is not listed
SZW-lijst van mutagene stoffen	: The substance is not listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: The substance is not listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: The substance is not listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: The substance is not listed
Denmark	
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product
Switzerland	
Storage class (LK)	: LK 2 - Liquefied or pressurized gases

O Air Liquide

SAFETY DATA SHEET

Page : 10/10

Revised edition no : 6.0 Revision date : 2023-01-19

Supersedes version of : 2021-06-16

Hydrogen

NOAL_0067A Country : DK / Language : EN

15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.

SECTION 16: Other information	
Indication of changes	: Safety data sheet in accordance with commission regulation (EU) No 2020/878.
Abbreviations and acronyms	: ATE - Acute Toxicity Estimate CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
	REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
	EINECS - European Inventory of Existing Commercial Chemical Substances
	CAS# - Chemical Abstract Service number
	PPE - Personal Protection Equipment
	LC50 - Lethal Concentration to 50 % of a test population
	RMM - Risk Management Measures
	PBT - Persistent, Bioaccumulative and Toxic
	vPvB - Very Persistent and Very Bioaccumulative
	STOT- SE : Specific Target Organ Toxicity - Single Exposure
	CSA - Chemical Safety Assessment
	EN - European Standard
	UN - United Nations
	ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
	IATA - International Air Transport Association
	IMDG code - International Maritime Dangerous Goods
	RID - Regulations concerning the International Carriage of Dangerous Goods by Rail WGK - Water Hazard Class
	STOT - RE : Specific Target Organ Toxicity - Repeated Exposure UFI : Unique Formula Identifier
Training advice	Ensure operators understand the flammability hazard.
Further information	: Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).
	Key literature references and sources of data are maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at http://www.Eiga.eu .

Full text of H- and EUH-statements	
Flam. Gas 1A	Flammable gases, Category 1A
H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
Press. Gas (Comp.)	Gases under pressure : Compressed gas

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Details given in this document are believed to be correct at the time of going to press.

Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document