

**Hydrogen sulphide****NOAL\_0073**

Country : DK / Language : EN

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Trade name : Hydrogen sulphide  
SDS no : NOAL\_0073  
Other means of identification : Hydrogen sulphide  
CAS-No. : 7783-06-4  
EC-No. : 231-977-3  
EC Index-No. : 016-001-00-4  
REACH registration No : 01-2119445737-29  
Chemical formula : H<sub>2</sub>S

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use.  
Test gas/Calibration gas.  
Laboratory use.  
Use for manufacture of electronic/photovoltaic components.  
Contact supplier for more information on uses.

Uses advised against : Consumer use.  
Uses other than those listed above are not supported, contact your supplier for more information on other uses.

**1.3. Details of the supplier of the safety data sheet****Company identification****Supplier**

AIR LIQUIDE Denmark A/S  
Høje Taastrupvej 42  
2630 Taastrup - DENMARK  
T +45 76 25 25 25  
[info.denmark@airliquide.com](mailto:info.denmark@airliquide.com)

E-Mail address (competent person) : eunordic-sds@airliquide.com

**1.4. Emergency telephone number**

Emergency telephone number : 112  
(24 / 7)  
Availability

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Physical hazards	Flammable gases, Category 1A	H220
	Gases under pressure : Liquefied gas	H280
Health hazards	Acute toxicity (inhalation:gas) Category 2	H330
	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation	H335
Environmental hazards	Hazardous to the aquatic environment – Acute Hazard, Category 1	H400

## Hydrogen sulphide


### NOAL\_0073

Country : DK / Language : EN

### 2.2. Label elements

#### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS04

GHS06

GHS09

Signal word (CLP) :

Danger

Hazard statements (CLP) :

H220 - Extremely flammable gas.  
 H280 - Contains gas under pressure; may explode if heated.  
 H330 - Fatal if inhaled.  
 H335 - May cause respiratory irritation.  
 H400 - Very toxic to aquatic life.

Precautionary statements (CLP) :

- Prevention

P271 - Use only outdoors or in a well-ventilated area.  
 P273 - Avoid release to the environment.  
 P260 - Do not breathe dust/fume/gas/mist/vapours/spray.  
 P284 - Wear respiratory protection.  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- Response

P391 - Collect spillage.  
 P320 - Specific treatment is urgent (see supplemental first aid instruction on this label).  
 P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
 P310 - Immediately call a POISON CENTER or doctor.  
 P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
 P381 - In case of leakage, eliminate all ignition sources.  
 P381 - In case of leakage, eliminate all ignition sources.  
 P312 - Call a POISON CENTRE or doctor if you feel unwell.

- Storage

P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
 P405 - Store locked up.  
 P403 - Store in a well-ventilated place.  
 P410+P403 - Protect from sunlight. Store in a well-ventilated place.

- Disposal considerations

P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.


### 2.3. Other hazards

Contact with liquid may cause cold burns/frostbite.  
 Not classified as PBT or vPvB.  
 The substance/mixture has no endocrine disrupting properties.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Name	Product identifier	Composition [V-%]:	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Hydrogen sulphide	CAS-No.: 7783-06-4 EC-No.: 231-977-3 EC Index-No.: 016-001-00-4 REACH registration No: 01-2119445737-29	100	Flam. Gas 1A, H220 Press. Gas (Liq.), H280 Acute Tox. 2 (Inhalation:gas), H330 STOT SE 3, H335 Aquatic Acute 1, H400

	<b>SAFETY DATA SHEET</b>	Page : 3/21
		Revised edition no : 5.0
		Revision date : 2023-01-20
		Supersedes version of : 2021-06-24
<b>Hydrogen sulphide</b>		<b>NOAL_0073</b>
		Country : DK / Language : EN

Contains no other components or impurities which will influence the classification of the product.

**3.2. Mixtures**

Not established.

**SECTION 4: First aid measures**

**4.1. Description of first aid measures**

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

**4.2. Most important symptoms and effects, both acute and delayed**

May cause irritation to the respiratory tract, sneezing, coughing, burning sensation of throat with constricting sensation of the larynx and difficulty in breathing.  
 May cause damaging effects to central nervous system, metabolism and gastrointestinal tract.  
 Prolonged exposure to small concentrations may result in pulmonary oedema.  
 See section 11.

**4.3. Indication of any immediate medical attention and special treatment needed**

Obtain medical assistance.

**SECTION 5: Firefighting measures**

**5.1. Extinguishing media**

- Suitable extinguishing media : Water spray or fog.  
Dry powder.
- Unsuitable extinguishing media : Carbon dioxide.  
Do not use water jet to extinguish.

**5.2. Special hazards arising from the substance or mixture**

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : Sulphur dioxide.

**5.3. Advice for firefighters**

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.  
If possible, stop flow of product.  
Use water spray or fog to knock down fire fumes if possible.  
Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.  
Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus.  
Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Gas-tight chemical protective suits for emergency teams.  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

**Hydrogen sulphide****NOAL\_0073**

Country : DK / Language : EN

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

- For non-emergency personnel : Act in accordance with local emergency plan.  
Try to stop release.  
Evacuate area.  
Ensure adequate air ventilation.  
Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.  
Stay upwind.  
See section 8 of the SDS for more information on personal protective equipment
- For emergency responders : Monitor concentration of released product.  
Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.  
See section 5.3 of the SDS for more information.

**6.2. Environmental precautions**

Try to stop release.

**6.3. Methods and material for containment and cleaning up**


Keep area evacuated and free from ignition sources until any spilled liquid has evaporated (ground free from frost).

**6.4. Reference to other sections**

See also sections 8 and 13.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling**

- Safe use of the product : Do not breathe gas.  
Avoid release of product into atmosphere.  
The product must be handled in accordance with good industrial hygiene and safety procedures.  
Only experienced and properly instructed persons should handle gases under pressure.  
Consider pressure relief device(s) in gas installations.  
Ensure the complete gas system was (or is regularly) checked for leaks before use.  
Do not smoke while handling product.  
Avoid exposure, obtain special instructions before use.  
Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.  
Installation of a cross purge assembly between the container and the regulator is recommended.  
Avoid suck back of water, acid and alkalis.  
Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment.  
Purge air from system before introducing gas.  
Take precautionary measures against static discharge.  
Keep away from ignition sources (including static discharges).  
Consider the use of only non-sparking tools.  
Ensure equipment is adequately earthed.

	<b>SAFETY DATA SHEET</b>	Page : 5/21
		Revised edition no : 5.0
		Revision date : 2023-01-20
		Supersedes version of : 2021-06-24
<b>Hydrogen sulphide</b>		<b>NOAL_0073</b>
		Country : DK / Language : EN

Safe handling of the gas receptacle : Refer to supplier's container handling instructions.

- Do not allow backfeed into the container.
- Protect containers from physical damage; do not drag, roll, slide or drop.
- When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
- Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
- If user experiences any difficulty operating valve discontinue use and contact supplier.
- Never attempt to repair or modify container valves or safety relief devices.
- Damaged valves should be reported immediately to the supplier.
- Keep container valve outlets clean and free from contaminants particularly oil and water.
- Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
- Close container valve after each use and when empty, even if still connected to equipment.
- Never attempt to transfer gases from one cylinder/container to another.
- Never use direct flame or electrical heating devices to raise the pressure of a container.
- Do not remove or deface labels provided by the supplier for the identification of the content of the container.
- Suck back of water into the container must be prevented.
- Open valve slowly to avoid pressure shock.

**7.2. Conditions for safe storage, including any incompatibilities**

- Observe all regulations and local requirements regarding storage of containers.
- Containers should not be stored in conditions likely to encourage corrosion.
- Container valve guards or caps should be in place.
- Containers should be stored in the vertical position and properly secured to prevent them from falling over.
- Stored containers should be periodically checked for general condition and leakage.
- Keep container below 50°C in a well ventilated place.
- Store containers in location free from fire risk and away from sources of heat and ignition.
- Keep away from combustible materials.
- Segregate from oxidant gases and other oxidants in store.
- All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere.

**7.3. Specific end use(s)**

None.

**SECTION 8: Exposure controls/personal protection**

**8.1. Control parameters**

<b>Hydrogen sulphide (7783-06-4)</b>	
<b>EU - Indicative Occupational Exposure Limit (IOEL)</b>	
Local name	Hydrogen sulphide
IOEL TWA	7 mg/m <sup>3</sup>
IOEL TWA [ppm]	5 ppm
IOEL STEL	14 mg/m <sup>3</sup>
IOEL STEL [ppm]	10 ppm
<b>Austria - Occupational Exposure Limits</b>	
Local name	Schwefelwasserstoff
MAK (mg/m <sup>3</sup> )	7 mg/m <sup>3</sup>

## Hydrogen sulphide

### NOAL\_0073

Country : DK / Language : EN

MAK (OEL TWA) [ppm]	5 ppm
MAK (OEL STEL)	7 mg/m <sup>3</sup>
MAK (OEL STEL) [ppm]	5 ppm
<b>Belgium - Occupational Exposure Limits</b>	
Local name	Hydrogène (sulfure d')
OEL TWA	7 mg/m <sup>3</sup>
OEL TWA [ppm]	5 ppm
OEL STEL	14 mg/m <sup>3</sup>
OEL STEL [ppm]	10 ppm
<b>Bulgaria - Occupational Exposure Limits</b>	
Local name	Сероводород
OEL TWA	7 mg/m <sup>3</sup>
OEL TWA [ppm]	5 ppm
OEL STEL	14 mg/m <sup>3</sup>
OEL STEL [ppm]	10 ppm
Remark	• (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
<b>Czech Republic - Occupational Exposure Limits</b>	
Local name	Sirovodík
PEL (OEL TWA)	10 mg/m <sup>3</sup>
PEL (OEL TWA) [ppm]	7.2 ppm
NPK-P (OEL C)	20 mg/m <sup>3</sup>
NPK-P (OEL C) [ppm]	14.4 ppm
<b>Denmark - Occupational Exposure Limits</b>	
Local name	Hydrogensulfid (Svovlbrinte)
OEL TWA [1]	15 mg/m <sup>3</sup>
OEL TWA [2]	10 ppm
<b>Estonia - Occupational Exposure Limits</b>	
Local name	Vesiniksulfid
OEL TWA	7 mg/m <sup>3</sup>
OEL TWA [ppm]	5 ppm
OEL STEL	14 mg/m <sup>3</sup>
OEL STEL [ppm]	10 ppm
<b>Finland - Occupational Exposure Limits</b>	
Local name	Rikkivety
HTP (OEL TWA) [1]	7 mg/m <sup>3</sup>

## Hydrogen sulphide

### NOAL\_0073

Country : DK / Language : EN

HTP (OEL TWA) [2]	5 ppm
HTP (OEL STEL)	14 mg/m <sup>3</sup>
HTP (OEL STEL) [ppm]	10 ppm
<b>France - Occupational Exposure Limits</b>	
Local name	Hydrogène sulfuré
VME (OEL TWA)	7 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	5 ppm
VLE (OEL C/STEL)	14 mg/m <sup>3</sup>
VLE (OEL C/STEL) [ppm]	10 ppm
Remark	Valeurs réglementaires contraignantes
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
Local name	Hydrogensulfid
AGW (OEL TWA) [1]	7.1 mg/m <sup>3</sup>
AGW (OEL TWA) [2]	5 ppm
Remark	EU,DFG,AGS,Y
<b>Greece - Occupational Exposure Limits</b>	
OEL TWA	15 mg/m <sup>3</sup>
OEL TWA [ppm]	10 ppm
OEL STEL	21 mg/m <sup>3</sup>
OEL STEL [ppm]	15 ppm
<b>Hungary - Occupational Exposure Limits</b>	
Local name	KÉN-HIDROGÉN
AK (OEL TWA)	7 mg/m <sup>3</sup>
CK (OEL STEL)	14 mg/m <sup>3</sup>
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Hydrogen sulphide
OEL TWA [1]	7 mg/m <sup>3</sup>
OEL TWA [2]	5 ppm
OEL STEL	14 mg/m <sup>3</sup>
OEL STEL [ppm]	10 ppm
<b>Italy - Occupational Exposure Limits</b>	
Local name	Acido solfidrico
OEL TWA	7 mg/m <sup>3</sup>
OEL TWA [ppm]	5 ppm
OEL STEL	14 mg/m <sup>3</sup>
OEL STEL [ppm]	10 ppm

## Hydrogen sulphide

### NOAL\_0073

Country : DK / Language : EN

**Latvia - Occupational Exposure Limits**

Local name	Serudenradis
OEL TWA	7 mg/m <sup>3</sup>
OEL TWA [ppm]	5 ppm
OEL STEL	14 mg/m <sup>3</sup>
OEL STEL [ppm]	10 ppm

**Lithuania - Occupational Exposure Limits**

Local name	Vandenilio sulfidas
IPRV (OEL TWA)	7 mg/m <sup>3</sup>
IPRV (OEL TWA) [ppm]	5 ppm
TPRV (OEL STEL)	14 mg/m <sup>3</sup>
TPRV (OEL STEL) [ppm]	10 ppm
NRV (OEL C)	20 mg/m <sup>3</sup>
NRV (OEL C) [ppm]	15 ppm

**Netherlands - Occupational Exposure Limits**

Local name	Zwavelwaterstof
TGG-8u (OEL TWA)	2.3 mg/m <sup>3</sup>

**Poland - Occupational Exposure Limits**

Local name	Siarkowodór
NDS (OEL TWA)	7 mg/m <sup>3</sup>
NDSch (OEL STEL)	14 mg/m <sup>3</sup>

**Portugal - Occupational Exposure Limits**

Local name	Ácido sulfídrico
OEL TWA [ppm]	10 ppm
OEL STEL [ppm]	15 ppm

**Romania - Occupational Exposure Limits**

Local name	Hidrogen sulfurat
OEL TWA	10 mg/m <sup>3</sup>
OEL TWA [ppm]	7.2 ppm
OEL STEL	15 mg/m <sup>3</sup>
OEL STEL [ppm]	10.8 ppm

**Slovakia - Occupational Exposure Limits**

NPHV (OEL TWA) [1]	14 mg/m <sup>3</sup>
NPHV (OEL TWA) [2]	10 ppm
NPHV (OEL STEL)	28 mg/m <sup>3</sup>



**Hydrogen sulphide****NOAL\_0073**

Country : DK / Language : EN

**Slovenia - Occupational Exposure Limits**

Local name	vodikov sulfid
OEL TWA	7 mg/m <sup>3</sup>
OEL TWA [ppm]	5 ppm
OEL STEL	14 mg/m <sup>3</sup>
OEL STEL [ppm]	10 ppm

**Spain - Occupational Exposure Limits**

Local name	Sulfuro de hidrógeno
VLA-ED (OEL TWA) [1]	7 mg/m <sup>3</sup>
VLA-ED (OEL TWA) [2]	5 ppm
VLA-EC (OEL STEL)	14 mg/m <sup>3</sup>
VLA-EC (OEL STEL) [ppm]	10 ppm
Remark	VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país).

**Sweden - Occupational Exposure Limits**

Local name	Svavelväte
NGV (OEL TWA)	7 mg/m <sup>3</sup>
NGV (OEL TWA) [ppm]	5 ppm
KTV (OEL STEL)	14 mg/m <sup>3</sup>
KTV (OEL STEL) [ppm]	10 ppm

**United Kingdom - Occupational Exposure Limits**

Local name	Hydrogen sulphide
WEL TWA (OEL TWA) [1]	7 mg/m <sup>3</sup>
WEL TWA (OEL TWA) [2]	5 ppm
WEL STEL (OEL STEL)	14 mg/m <sup>3</sup>
WEL STEL (OEL STEL) [ppm]	10 ppm

**Iceland - Occupational Exposure Limits**

Local name	Vetnissúlfíð (brennisteinsvetni)
OEL TWA	14 mg/m <sup>3</sup>
OEL TWA [ppm]	10 ppm
OEL STEL	20 mg/m <sup>3</sup>
OEL STEL [ppm]	15 ppm

## Hydrogen sulphide

### NOAL\_0073

Country : DK / Language : EN

#### Switzerland - Occupational Exposure Limits

Local name	Schwefelwasserstoff
MAK (OEL TWA) [1]	7.1 mg/m <sup>3</sup>
MAK (OEL TWA) [2]	5 ppm
KZGW (OEL STEL)	14.2 mg/m <sup>3</sup>
KZGW (OEL STEL) [ppm]	10 ppm
Remark	SS <sub>C</sub> - OAW, Geruch, NS - NIOSH, OSHA

#### USA - ACGIH - Occupational Exposure Limits

Local name	Hydrogen sulfide
ACGIH OEL TWA [ppm]	1 ppm
ACGIH OEL STEL [ppm]	5 ppm
Remark (ACGIH)	URT irr; CNS impair

#### Hydrogen sulphide (7783-06-4)

#### EU - Indicative Occupational Exposure Limit (IOEL)

Local name	Hydrogen sulphide
IOEL TWA	7 mg/m <sup>3</sup>
IOEL TWA [ppm]	5 ppm
IOEL STEL	14 mg/m <sup>3</sup>
IOEL STEL [ppm]	10 ppm

#### Austria - Occupational Exposure Limits

Local name	Schwefelwasserstoff
MAK (mg/m <sup>3</sup> )	7 mg/m <sup>3</sup>
MAK (OEL TWA) [ppm]	5 ppm
MAK (OEL STEL)	7 mg/m <sup>3</sup>
MAK (OEL STEL) [ppm]	5 ppm

#### Belgium - Occupational Exposure Limits

Local name	Hydrogène (sulfure d')
OEL TWA	7 mg/m <sup>3</sup>
OEL TWA [ppm]	5 ppm
OEL STEL	14 mg/m <sup>3</sup>
OEL STEL [ppm]	10 ppm

#### Bulgaria - Occupational Exposure Limits

Local name	Сероводород
OEL TWA	7 mg/m <sup>3</sup>
OEL TWA [ppm]	5 ppm

**Hydrogen sulphide****NOAL\_0073**

Country : DK / Language : EN

OEL STEL	14 mg/m <sup>3</sup>
OEL STEL [ppm]	10 ppm
Remark	• (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
<b>Czech Republic - Occupational Exposure Limits</b>	
Local name	Sirovodík
PEL (OEL TWA)	10 mg/m <sup>3</sup>
PEL (OEL TWA) [ppm]	7.2 ppm
NPK-P (OEL C)	20 mg/m <sup>3</sup>
NPK-P (OEL C) [ppm]	14.4 ppm
<b>Denmark - Occupational Exposure Limits</b>	
Local name	Hydrogensulfid (Svovlbrinte)
OEL TWA [1]	15 mg/m <sup>3</sup>
OEL TWA [2]	10 ppm
<b>Estonia - Occupational Exposure Limits</b>	
Local name	Vesiniksulfiid
OEL TWA	7 mg/m <sup>3</sup>
OEL TWA [ppm]	5 ppm
OEL STEL	14 mg/m <sup>3</sup>
OEL STEL [ppm]	10 ppm
<b>Finland - Occupational Exposure Limits</b>	
Local name	Rikkivety
HTP (OEL TWA) [1]	7 mg/m <sup>3</sup>
HTP (OEL TWA) [2]	5 ppm
HTP (OEL STEL)	14 mg/m <sup>3</sup>
HTP (OEL STEL) [ppm]	10 ppm
<b>France - Occupational Exposure Limits</b>	
Local name	Hydrogène sulfuré
VME (OEL TWA)	7 mg/m <sup>3</sup>
VME (OEL TWA) [ppm]	5 ppm
VLE (OEL C/STEL)	14 mg/m <sup>3</sup>
VLE (OEL C/STEL) [ppm]	10 ppm
Remark	Valeurs réglementaires contraignantes
<b>Germany - Occupational Exposure Limits (TRGS 900)</b>	
Local name	Hydrogensulfid
AGW (OEL TWA) [1]	7.1 mg/m <sup>3</sup>

## Hydrogen sulphide

### NOAL\_0073

Country : DK / Language : EN


AGW (OEL TWA) [2]	5 ppm
Remark	EU,DFG,AGS,Y
<b>Greece - Occupational Exposure Limits</b>	
OEL TWA	15 mg/m <sup>3</sup>
OEL TWA [ppm]	10 ppm
OEL STEL	21 mg/m <sup>3</sup>
OEL STEL [ppm]	15 ppm
<b>Hungary - Occupational Exposure Limits</b>	
Local name	KÉN-HIDROGÉN
AK (OEL TWA)	7 mg/m <sup>3</sup>
CK (OEL STEL)	14 mg/m <sup>3</sup>
<b>Ireland - Occupational Exposure Limits</b>	
Local name	Hydrogen sulphide
OEL TWA [1]	7 mg/m <sup>3</sup>
OEL TWA [2]	5 ppm
OEL STEL	14 mg/m <sup>3</sup>
OEL STEL [ppm]	10 ppm
<b>Italy - Occupational Exposure Limits</b>	
Local name	Acido solfidrico
OEL TWA	7 mg/m <sup>3</sup>
OEL TWA [ppm]	5 ppm
OEL STEL	14 mg/m <sup>3</sup>
OEL STEL [ppm]	10 ppm
<b>Latvia - Occupational Exposure Limits</b>	
Local name	Serudenradis
OEL TWA	7 mg/m <sup>3</sup>
OEL TWA [ppm]	5 ppm
OEL STEL	14 mg/m <sup>3</sup>
OEL STEL [ppm]	10 ppm
<b>Lithuania - Occupational Exposure Limits</b>	
Local name	Vandenilio sulfidas
IPRV (OEL TWA)	7 mg/m <sup>3</sup>
IPRV (OEL TWA) [ppm]	5 ppm
TPRV (OEL STEL)	14 mg/m <sup>3</sup>
TPRV (OEL STEL) [ppm]	10 ppm
NRV (OEL C)	20 mg/m <sup>3</sup>

## Hydrogen sulphide

### NOAL\_0073


Country : DK / Language : EN

NRV (OEL C) [ppm]	15 ppm
<b>Netherlands - Occupational Exposure Limits</b>	
Local name	Zwavelwaterstof
TGG-8u (OEL TWA)	2.3 mg/m <sup>3</sup>
<b>Poland - Occupational Exposure Limits</b>	
Local name	Siarkowodór
NDS (OEL TWA)	7 mg/m <sup>3</sup>
NDSch (OEL STEL)	14 mg/m <sup>3</sup>
<b>Portugal - Occupational Exposure Limits</b>	
Local name	Ácido sulfídrico
OEL TWA [ppm]	10 ppm
OEL STEL [ppm]	15 ppm
<b>Romania - Occupational Exposure Limits</b>	
Local name	Hidrogen sulfurat
OEL TWA	10 mg/m <sup>3</sup>
OEL TWA [ppm]	7.2 ppm
OEL STEL	15 mg/m <sup>3</sup>
OEL STEL [ppm]	10.8 ppm
<b>Slovakia - Occupational Exposure Limits</b>	
NPHV (OEL TWA) [1]	14 mg/m <sup>3</sup>
NPHV (OEL TWA) [2]	10 ppm
NPHV (OEL STEL)	28 mg/m <sup>3</sup>
<b>Slovenia - Occupational Exposure Limits</b>	
Local name	vodikov sulfid
OEL TWA	7 mg/m <sup>3</sup>
OEL TWA [ppm]	5 ppm
OEL STEL	14 mg/m <sup>3</sup>
OEL STEL [ppm]	10 ppm
<b>Spain - Occupational Exposure Limits</b>	
Local name	Sulfuro de hidrógeno
VLA-ED (OEL TWA) [1]	7 mg/m <sup>3</sup>
VLA-ED (OEL TWA) [2]	5 ppm
VLA-EC (OEL STEL)	14 mg/m <sup>3</sup>
VLA-EC (OEL STEL) [ppm]	10 ppm

	<b>SAFETY DATA SHEET</b>	Page : 14/21
		Revised edition no : 5.0
		Revision date : 2023-01-20
		Supersedes version of : 2021-06-24
<b>Hydrogen sulphide</b>		<b>NOAL_0073</b>
		Country : DK / Language : EN
Remark	VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país).	
<b>Sweden - Occupational Exposure Limits</b>		
Local name	Svavelväte	
NGV (OEL TWA)	7 mg/m <sup>3</sup>	
NGV (OEL TWA) [ppm]	5 ppm	
KTV (OEL STEL)	14 mg/m <sup>3</sup>	
KTV (OEL STEL) [ppm]	10 ppm	
<b>United Kingdom - Occupational Exposure Limits</b>		
Local name	Hydrogen sulphide	
WEL TWA (OEL TWA) [1]	7 mg/m <sup>3</sup>	
WEL TWA (OEL TWA) [2]	5 ppm	
WEL STEL (OEL STEL)	14 mg/m <sup>3</sup>	
WEL STEL (OEL STEL) [ppm]	10 ppm	
<b>Iceland - Occupational Exposure Limits</b>		
Local name	Vetnissúlfíð (brennisteinsvetni)	
OEL TWA	14 mg/m <sup>3</sup>	
OEL TWA [ppm]	10 ppm	
OEL STEL	20 mg/m <sup>3</sup>	
OEL STEL [ppm]	15 ppm	
<b>Switzerland - Occupational Exposure Limits</b>		
Local name	Schwefelwasserstoff	
MAK (OEL TWA) [1]	7.1 mg/m <sup>3</sup>	
MAK (OEL TWA) [2]	5 ppm	
KZGW (OEL STEL)	14.2 mg/m <sup>3</sup>	
KZGW (OEL STEL) [ppm]	10 ppm	
Remark	SS <sub>C</sub> - OAW, Geruch, NS - NIOSH, OSHA	
<b>USA - ACGIH - Occupational Exposure Limits</b>		
Local name	Hydrogen sulfide	
ACGIH OEL TWA [ppm]	1 ppm	
ACGIH OEL STEL [ppm]	5 ppm	
Remark (ACGIH)	URT irr; CNS impair	

DNEL (Derived-No Effect Level)

: None established.

	<b>SAFETY DATA SHEET</b>	Page : 15/21
		Revised edition no : 5.0
		Revision date : 2023-01-20
		Supersedes version of : 2021-06-24
<b>Hydrogen sulphide</b>		<b>NOAL_0073</b>
		Country : DK / Language : EN

PNEC (Predicted No-Effect Concentration) : None established.

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

Product to be handled in a closed system and under strictly controlled conditions.  
 Provide adequate general and local exhaust ventilation.  
 Preferably use permanent leak-tight installations (e.g. welded pipes).  
 Systems under pressure should be regularly checked for leakages.  
 Ensure exposure is below occupational exposure limits (where available).  
 Gas detectors should be used when toxic gases may be released.  
 Consider the use of a work permit system e.g. for maintenance activities.

### 8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.  
 The following recommendations should be considered:

- Eye/face protection : Wear goggles when transfilling or breaking transfer connections.  
Standard EN 166 - Personal eye-protection - specifications.
- Skin protection
  - Hand protection : Wear working gloves when handling gas containers.  
Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.  
Wear cold insulating gloves when transfilling or breaking transfer connections.  
Standard EN 511 - Cold insulating gloves.  
Permeation time: minimum >480min long term exposure : material / thickness Nitrile rubber (NBR) / 0.7 [mm].
  - Other : Consider the use of flame resistant anti-static safety clothing.  
Standard EN ISO 14116 - Limited flame spread materials.  
Standard EN 1149-5 - Protective clothing: Electrostatic properties.  
Wear safety shoes while handling containers.  
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
- Respiratory protection : Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known.  
Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers.  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.  
Recommended: Filter B (grey).  
Gas filters do not protect against oxygen deficiency.  
Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks .  
Keep self contained breathing apparatus readily available for emergency use.  
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
- Thermal hazards : None in addition to the above sections.

### 8.2.3. Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

- Appearance
- Physical state at 20°C / 101.3kPa : Gas
  - Colour : Colourless.
- Odour : Odour can persist. Rotten eggs. Poor warning properties at low concentrations.  
Odour threshold is subjective and inadequate to warn of overexposure.
- pH : Not applicable for gases and gas mixtures.

**Hydrogen sulphide****NOAL\_0073**

Country : DK / Language : EN

Melting point / Freezing point	: -86 °C
	-86 °C
Boiling point	: -60.2 °C
Flash point	: Not applicable for gases and gas mixtures.
Flammability	: Extremely flammable gas
Explosive limits	: 3.9 – 45.5 vol %
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Vapour pressure [20°C]	: 18.8 bar(a)
Vapour pressure [50°C]	: 36.4 bar(a)
Density	: Not applicable
Vapour density	: Not applicable for gases and gas mixtures.
Relative density, liquid (water=1)	: 0.92
Relative density, gas (air=1)	: 1.2
Water solubility	: 3980 mg/l
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for inorganic products.
Auto-ignition temperature	: 270 °C
Decomposition temperature	: Not applicable.
Viscosity, kinematic	: No reliable data available.
Particle characteristics	: Not applicable for gases and gas mixtures.

**9.2. Other information****9.2.1. Information with regard to physical hazard classes**

Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.
Tci	: 8.9 %
Critical temperature [°C]	: 100 °C

**9.2.2. Other safety characteristics**

Molar mass	: 34 g/mol
Evaporation rate	: Not applicable for gases and gas mixtures.
Gas group	: Press. Gas (Liq.)
Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

**SECTION 10: Stability and reactivity****10.1. Reactivity**

No reactivity hazard other than the effects described in sub-sections below.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**

None.

Reactivity : This mixture contains components with the following reactivity : Can form explosive mixture with air. May react violently with oxidants.

**10.4. Conditions to avoid**None under recommended storage and handling conditions (see section 7).  
Avoid moisture in installation systems.**10.5. Incompatible materials**

For additional information on compatibility refer to ISO 11114.



**Hydrogen sulphide****NOAL\_0073**

Country : DK / Language : EN

**10.6. Hazardous decomposition products**

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**

**Acute toxicity** : Fatal if inhaled.

LC50 Inhalation - Rat [ppm]	356 ppm/4h
-----------------------------	------------

**Hydrogen sulphide (7783-06-4)**

LC50 Inhalation - Rat [ppm]	356 ppm/4h
-----------------------------	------------

**Skin corrosion/irritation** : No known effects from this product.

**Serious eye damage/irritation** : No known effects from this product.

**Respiratory or skin sensitisation** : No known effects from this product.

**Germ cell mutagenicity** : No known effects from this product.

**Carcinogenicity** : No known effects from this product.

**Toxic for reproduction : Fertility** : No known effects from this product.

**Toxic for reproduction : unborn child** : No known effects from this product.

**STOT-single exposure** : May cause respiratory irritation.  
Irritation to the respiratory tract.

**STOT-repeated exposure** : Damage to central nervous system.

**Aspiration hazard** : Not applicable for gases and gas mixtures.

**11.2. Information on other hazards**

Other information : The substance/mixture has no endocrine disrupting properties.

**SECTION 12: Ecological information****12.1. Toxicity**

Assessment : Very toxic to aquatic life.

EC50 48h - Daphnia magna [mg/l] : 0.12 mg/l

EC50 72h - Algae [mg/l] : 1.87 mg/l

LC50 96 h - Fish [mg/l] : 0.007 - 0.019

**Hydrogen sulphide (7783-06-4)**

EC50 48h - Daphnia magna [mg/l]	0.12 mg/l
EC50 72h - Algae [mg/l]	1.87 mg/l
LC50 96 h - Fish [mg/l]	0.007 - 0.019

**12.2. Persistence and degradability**


Assessment : Not applicable for inorganic products.

**12.3. Bioaccumulative potential**

Assessment : No data available.

**12.4. Mobility in soil**

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.  
Partition into soil is unlikely.

	<b>SAFETY DATA SHEET</b>	Page : 18/21
		Revised edition no : 5.0
		Revision date : 2023-01-20
		Supersedes version of : 2021-06-24
<b>Hydrogen sulphide</b>		<b>NOAL_0073</b>
		Country : DK / Language : EN

#### 12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.

#### 12.6. Endocrine disrupting properties

The substance/mixture has no endocrine disrupting properties.

#### 12.7. Other adverse effects

Other adverse effects : No known effects from this product.  
Effect on the ozone layer : None.  
Effect on global warming : No known effects from this product.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Contact supplier if guidance is required.  
Do not discharge into areas where there is a risk of forming an explosive mixture with air.  
Waste gas should be flared through a suitable burner with flash back arrestor.  
Must not be discharged to atmosphere.  
Toxic and corrosive gases formed during combustion should be scrubbed before discharge to atmosphere.  
Gas may be scrubbed in alkaline solution under controlled conditions to avoid violent reaction.  
Ensure that the emission levels from local regulations or operating permits are not exceeded.  
Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods.  
Return unused product in original container to supplier.

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended) : 16 05 04 \*: Gases in pressure containers (including halons) containing hazardous substances.

#### 13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

### SECTION 14: Transport information

#### 14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN  
UN-No. : 1053

#### 14.2. UN proper shipping name

Transport by road/rail (ADR/RID) : HYDROGEN SULPHIDE  
Transport by air (ICAO-TI / IATA-DGR) : Hydrogen sulphide  
Transport by sea (IMDG) : HYDROGEN SULPHIDE

#### 14.3. Transport hazard class(es)


Labelling :



2.3 : Toxic gases.  
2.1 : Flammable gases.

#### Transport by road/rail (ADR/RID)

Class : 2  
Classification code : 2TF

	<b>SAFETY DATA SHEET</b>	Page : 19/21
		Revised edition no : 5.0
		Revision date : 2023-01-20
		Supersedes version of : 2021-06-24
<b>Hydrogen sulphide</b>		<b>NOAL_0073</b>
		Country : DK / Language : EN

Hazard identification number : 263  
Tunnel Restriction : B/D - Tank carriage : Passage forbidden through tunnels of category B, C, D and E. Other carriage : Passage forbidden through tunnels of category D and E

**Transport by sea (IMDG)**

Class / Div. (Sub. risk(s)) : 2.3 (2.1)  
Emergency Schedule (EmS) - Fire : F-D  
Emergency Schedule (EmS) - Spillage : S-U

**14.4. Packing group**

Transport by road/rail (ADR/RID) : Not established.  
Transport by air (ICAO-TI / IATA-DGR) : Not established.  
Transport by sea (IMDG) : Not established.

**14.5. Environmental hazards**

Transport by road/rail (ADR/RID) : Environmentally hazardous substance / mixture.  
Transport by air (ICAO-TI / IATA-DGR) : Environmentally hazardous substance / mixture.  
Transport by sea (IMDG) : Marine pollutant

**14.6. Special precautions for user**

**Packing Instruction(s)**

Transport by road/rail (ADR/RID) : P200  
Transport by air (ICAO-TI / IATA-DGR)  
Passenger and Cargo Aircraft : Forbidden.  
Cargo Aircraft only : Forbidden.  
Transport by sea (IMDG) : P200

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment.  
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.  
Before transporting product containers:  
- Ensure there is adequate ventilation.  
- Ensure that containers are firmly secured.  
- Ensure valve is closed and not leaking.  
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.  
- Ensure valve protection device (where provided) is correctly fitted.

**14.7. Maritime transport in bulk according to IMO instruments**

Not applicable.

**SECTION 15: Regulatory information**

**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU-Regulations**


Restrictions on use : None.  
National legislation : Ensure all national/local regulations are observed.  
Seveso Directive : 2012/18/EU (Seveso III) : Listed.  
Covered.

**National regulations**

Ensure all national/local regulations are observed.

**Germany**

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV)

	<b>SAFETY DATA SHEET</b>	Page : 20/21
		Revised edition no : 5.0
		Revision date : 2023-01-20
		Supersedes version of : 2021-06-24
<b>Hydrogen sulphide</b>		<b>NOAL_0073</b>
		Country : DK / Language : EN

National Rules and Recommendations : [German regulations] BetriebssicherheitsV mit TRBSen insbesondere TRBS 3145 / TRGS 725 Ortsbewegliche Druckgasbehälter", TRBS 2141, BGR Regel 500 Teil 2.33: "Umgang mit Gasen", GefahrstoffV mit Technischen Regeln Gefährliche Stoffe TRGS insbesondere TRGS 407 "Tätigkeiten mit Gasen - Gefährdungsbeurteilung", TRGS 400, 500, 510, 900." BGR 104, TRBS 2152.

#### Netherlands

SZW-lijst van kankerverwekkende stoffen : The substance is not listed  
SZW-lijst van mutagene stoffen : The substance is not listed  
SZW-lijst van reprotoxische stoffen – Borstvoeding : The substance is not listed  
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : The substance is not listed  
SZW-lijst van reprotoxische stoffen – Ontwikkeling : The substance is not listed

#### Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

#### Switzerland

Storage class (LK) : LK 2 - Liquefied or pressurized gases

#### 15.2. Chemical safety assessment

A CSA has been carried out.

### SECTION 16: Other information

Indication of changes : Safety data sheet in accordance with commission regulation (EU) No 2020/878.

#### Abbreviations and acronyms

: ATE - Acute Toxicity Estimate  
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008  
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006  
EINECS - European Inventory of Existing Commercial Chemical Substances  
CAS# - Chemical Abstract Service number  
PPE - Personal Protection Equipment  
LC50 - Lethal Concentration to 50 % of a test population  
RMM - Risk Management Measures  
PBT - Persistent, Bioaccumulative and Toxic  
vPvB - Very Persistent and Very Bioaccumulative  
STOT- SE : Specific Target Organ Toxicity - Single Exposure  
CSA - Chemical Safety Assessment  
EN - European Standard  
UN - United Nations  
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road  
IATA - International Air Transport Association  
IMDG code - International Maritime Dangerous Goods  
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail  
WGK - Water Hazard Class  
STOT - RE : Specific Target Organ Toxicity - Repeated Exposure  
UFI : Unique Formula Identifier

#### Training advice

: Ensure operators understand the flammability hazard.  
Users of breathing apparatus must be trained.  
Ensure operators understand the toxicity hazard.

#### Further information

: Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).  
Key literature references and sources of data are maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at <http://www.Eiga.eu> .

**Hydrogen sulphide****NOAL\_0073**

Country : DK / Language : EN

**Full text of H- and EUH-statements**

Acute Tox. 2 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 2
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Flam. Gas 1A	Flammable gases, Category 1A
H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
H330	Fatal if inhaled.
H335	May cause respiratory irritation.
H400	Very toxic to aquatic life.
Press. Gas (Liq.)	Gases under pressure : Liquefied gas
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Respiratory tract irritation

**DISCLAIMER OF LIABILITY**

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.  
Details given in this document are believed to be correct at the time of going to press.  
Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

**End of document**