

**Helium****NOAL\_0061A**

Country : NO / Language : EN

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Trade name : Helium, Medical helium, Helium N25, Helium N45, Helium N50, Helium N55, Lasal 4, Lasal 2004, Alphagaz 1 Helium, Alphagaz 2 Helium, Helium HG, Helium Ballon, Albee Fly He, Helium flotation

SDS no : NOAL\_0061A

Other means of identification : Helium  
CAS-No. : 7440-59-7  
EC-No. : 231-168-5  
EC Index-No. : ---

REACH registration No : Listed in Annex IV / V REACH, exempted from registration.

Chemical formula : He

**1.2. Relevant identified uses of the substance or mixture and uses advised against**

Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use.  
Test gas/Calibration gas.  
Laboratory use.  
Purge gas, diluting gas, inerting gas.  
Purging.  
Use for manufacture of electronic/photovoltaic components.  
Shield gas for welding processes.  
Contact supplier for more information on uses.

Uses advised against : Do not inhale product on purpose because of the risk of asphyxiation.  
Uses other than those listed above are not supported, contact your supplier for more information on other uses.

**1.3. Details of the supplier of the safety data sheet****Company identification****Supplier**

AIR LIQUIDE NORWAY AS  
Drammensveien 64 B  
3050 Mjøndalen - NORWAY  
T + 47 32 27 41 40  
[info.norway@airliquide.com](mailto:info.norway@airliquide.com)

E-Mail address (competent person) : eunordic-sds@airliquide.com


**1.4. Emergency telephone number**

Emergency telephone number : 112 / Giftinformasjon: + 47 22 59 13 00  
Availability  
(24 / 7)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Physical hazards Gases under pressure : Compressed gas

H280

	<b>SAFETY DATA SHEET</b>	Page : 2/10
		Revised edition no : 5.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
<b>Helium</b>		<b>NOAL_0061A</b>
		Country : NO / Language : EN

## 2.2. Label elements

### Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS04

Signal word (CLP) :

Warning

Hazard statements (CLP) :

H280 - Contains gas under pressure; may explode if heated.

Precautionary statements (CLP)

- Storage

: P410+P403 - Protect from sunlight. Store in a well-ventilated place.

## 2.3. Other hazards

Asphyxiant in high concentrations.

Not classified as PBT or vPvB.

The substance/mixture has no endocrine disrupting properties.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

Name	Product identifier	Composition [V-%]:	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Helium	CAS-No.: 7440-59-7 EC-No.: 231-168-5 EC Index-No.: --- REACH registration No: *1	100	Press. Gas (Comp.), H280

Contains no other components or impurities which will influence the classification of the product.

\*1: Listed in Annex IV / V REACH, exempted from registration.

\*3: Registration not required: Substance manufactured or imported < 1t/y.

### 3.2. Mixtures

Not established.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : Adverse effects not expected from this product.
- Eye contact : Adverse effects not expected from this product.
- Ingestion : Ingestion is not considered a potential route of exposure.


### 4.2. Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation.

See section 11.

### 4.3. Indication of any immediate medical attention and special treatment needed

None.

	<b>SAFETY DATA SHEET</b>	Page : 3/10
		Revised edition no : 5.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
<b>Helium</b>		<b>NOAL_0061A</b>
		Country : NO / Language : EN

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.  
Product does not burn, use fire control measures appropriate for the surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

### 5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : None.

### 5.3. Advice for firefighters

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.  
If possible, stop flow of product.  
Use water spray or fog to knock down fire fumes if possible.  
Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters : In confined space use self-contained breathing apparatus.  
Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.  
Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel : Act in accordance with local emergency plan.  
Try to stop release.  
Evacuate area.  
Ensure adequate air ventilation.  
Stay upwind.  
See section 8 of the SDS for more information on personal protective equipment
- For emergency responders : Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.  
Oxygen detectors should be used when asphyxiating gases may be released.  
See section 5.3 of the SDS for more information.

### 6.2. Environmental precautions

Try to stop release.

### 6.3. Methods and material for containment and cleaning up

Ventilate area.

### 6.4. Reference to other sections

See also sections 8 and 13.

	<b>SAFETY DATA SHEET</b>	Page : 4/10
		Revised edition no : 5.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
<b>Helium</b>		<b>NOAL_0061A</b> Country : NO / Language : EN

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Safe use of the product	<ul style="list-style-type: none"> <li>: Do not breathe gas.</li> <li>Avoid release of product into atmosphere.</li> <li>The product must be handled in accordance with good industrial hygiene and safety procedures.</li> <li>Only experienced and properly instructed persons should handle gases under pressure.</li> <li>Consider pressure relief device(s) in gas installations.</li> <li>Ensure the complete gas system was (or is regularly) checked for leaks before use.</li> <li>Do not smoke while handling product.</li> <li>Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.</li> <li>Avoid suck back of water, acid and alkalis.</li> </ul>
Safe handling of the gas receptacle	<ul style="list-style-type: none"> <li>: Refer to supplier's container handling instructions.</li> <li>Do not allow backfeed into the container.</li> <li>Protect containers from physical damage; do not drag, roll, slide or drop.</li> <li>When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.</li> <li>Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.</li> <li>If user experiences any difficulty operating valve discontinue use and contact supplier.</li> <li>Never attempt to repair or modify container valves or safety relief devices.</li> <li>Damaged valves should be reported immediately to the supplier.</li> <li>Keep container valve outlets clean and free from contaminants particularly oil and water.</li> <li>Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.</li> <li>Close container valve after each use and when empty, even if still connected to equipment.</li> <li>Never attempt to transfer gases from one cylinder/container to another.</li> <li>Never use direct flame or electrical heating devices to raise the pressure of a container.</li> <li>Do not remove or deface labels provided by the supplier for the identification of the content of the container.</li> <li>Suck back of water into the container must be prevented.</li> <li>Open valve slowly to avoid pressure shock.</li> </ul>

### 7.2. Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers.  
Containers should not be stored in conditions likely to encourage corrosion.  
Container valve guards or caps should be in place.  
Containers should be stored in the vertical position and properly secured to prevent them from falling over.  
Stored containers should be periodically checked for general condition and leakage.  
Keep container below 50°C in a well ventilated place.  
Store containers in location free from fire risk and away from sources of heat and ignition.  
Keep away from combustible materials.


### 7.3. Specific end use(s)

None.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

OEL (Occupational Exposure Limits)	: None available.
DNEL (Derived-No Effect Level)	: None available.
PNEC (Predicted No-Effect Concentration)	: None available.

	<b>SAFETY DATA SHEET</b>	Page : 5/10
		Revised edition no : 5.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
<b>Helium</b>		<b>NOAL_0061A</b>
		Country : NO / Language : EN

## 8.2. Exposure controls

### 8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation.  
Systems under pressure should be regularly checked for leakages.  
Oxygen detectors should be used when asphyxiating gases may be released.  
Consider the use of a work permit system e.g. for maintenance activities.

### 8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.

The following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

- Eye/face protection : Wear safety glasses with side shields.  
Standard EN 166 - Personal eye-protection - specifications.
- Skin protection :
  - Hand protection : Wear working gloves when handling gas containers.  
Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.
  - Other : Wear safety shoes while handling containers.  
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
- Respiratory protection : Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.  
Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres.  
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
- Thermal hazards : None in addition to the above sections.

### 8.2.3. Environmental exposure controls

None necessary.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance	
- Physical state at 20°C / 101.3kPa	: Gas
- Colour	: Colourless.
Odour	: No odour warning properties. Odour threshold is subjective and inadequate to warn of overexposure.
pH	: Not applicable for gases and gas mixtures.
Melting point / Freezing point	: -272 °C
Boiling point	: -269 °C
Flash point	: Not applicable for gases and gas mixtures.
Flammability	: Non flammable.
Explosive limits	: Non flammable.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Density	: Not applicable
Vapour density	: Not applicable for gases and gas mixtures.
Relative density, liquid (water=1)	: Not applicable.
Relative density, gas (air=1)	: 0.14
Water solubility	: 1.5 mg/l
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for inorganic products.
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
Viscosity, kinematic	: No reliable data available.

**Helium****NOAL\_0061A**

Country : NO / Language : EN

Particle characteristics : Not applicable for gases and gas mixtures.

**9.2. Other information****9.2.1. Information with regard to physical hazard classes**Explosive properties : Not applicable.  
Oxidising properties : Not applicable.  
Critical temperature [°C] : -268 °C**9.2.2. Other safety characteristics**Molar mass : 4 g/mol  
Evaporation rate : Not applicable for gases and gas mixtures.  
Gas group : Compressed gas**SECTION 10: Stability and reactivity****10.1. Reactivity**

No reactivity hazard other than the effects described in sub-sections below.

**10.2. Chemical stability**

Stable under normal conditions.

**10.3. Possibility of hazardous reactions**None.  
None under normal use.

Reactivity : None.

**10.4. Conditions to avoid**

Avoid moisture in installation systems.

**10.5. Incompatible materials**


For additional information on compatibility refer to ISO 11114.

**10.6. Hazardous decomposition products**

None.

**SECTION 11: Toxicological information****11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008**Acute toxicity : No toxicological effects from this product.  
Skin corrosion/irritation : No known effects from this product.  
Serious eye damage/irritation : No known effects from this product.  
Respiratory or skin sensitisation : No known effects from this product.  
Germ cell mutagenicity : No known effects from this product.  
Carcinogenicity : No known effects from this product.  
Toxic for reproduction : Fertility : No known effects from this product.  
Toxic for reproduction : unborn child : No known effects from this product.  
STOT-single exposure : No known effects from this product.  
STOT-repeated exposure : No known effects from this product.  
Aspiration hazard : Not applicable for gases and gas mixtures.**11.2. Information on other hazards**

Other information : The substance/mixture has no endocrine disrupting properties.

	<b>SAFETY DATA SHEET</b>	Page : 7/10
		Revised edition no : 5.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
<b>Helium</b>		<b>NOAL_0061A</b>
		Country : NO / Language : EN

## SECTION 12: Ecological information

### 12.1. Toxicity

Assessment : No ecological damage caused by this product.

EC50 48h - Daphnia magna [mg/l] : No data available.

EC50 72h - Algae [mg/l] : No data available.

LC50 96 h - Fish [mg/l] : No data available.

### 12.2. Persistence and degradability

Assessment : No ecological damage caused by this product.

### 12.3. Bioaccumulative potential

Assessment : No data available.

### 12.4. Mobility in soil

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.

### 12.5. Results of PBT and vPvB assessment

Assessment : No data available.  
Not classified as PBT or vPvB.

### 12.6. Endocrine disrupting properties

The substance/mixture has no endocrine disrupting properties.

### 12.7. Other adverse effects

Other adverse effects : No known effects from this product.

Effect on the ozone layer : None.

Effect on global warming : None.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

May be vented to atmosphere in a well ventilated place.  
Do not discharge into any place where its accumulation could be dangerous.  
Return unused product in original container to supplier.

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended) : 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.


### 13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

## SECTION 14: Transport information

### 14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN  
UN-No. : 1046

	<b>SAFETY DATA SHEET</b>	Page : 8/10
		Revised edition no : 5.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
<b>Helium</b>		<b>NOAL_0061A</b>
		Country : NO / Language : EN

**14.2. UN proper shipping name**

**Transport by road/rail (ADR/RID)** : HELIUM, COMPRESSED  
**Transport by air (ICAO-TI / IATA-DGR)** : Helium, compressed  
**Transport by sea (IMDG)** : HELIUM, COMPRESSED

**14.3. Transport hazard class(es)**

**Labelling**



2.2 : Non-flammable, non-toxic gases.

**Transport by road/rail (ADR/RID)**

Class : 2  
 Classification code : 1A  
 Hazard identification number : 20  
 Tunnel Restriction : E - Passage forbidden through tunnels of category E

**Transport by air (ICAO-TI / IATA-DGR)**

Class / Div. (Sub. risk(s)) : 2.2

**Transport by sea (IMDG)**

Class / Div. (Sub. risk(s)) : 2.2  
 Emergency Schedule (EmS) - Fire : F-C  
 Emergency Schedule (EmS) - Spillage : S-V

**14.4. Packing group**

**Transport by road/rail (ADR/RID)** : Not established.  
**Transport by air (ICAO-TI / IATA-DGR)** : Not established.  
**Transport by sea (IMDG)** : Not established.

**14.5. Environmental hazards**

**Transport by road/rail (ADR/RID)** : None.  
**Transport by air (ICAO-TI / IATA-DGR)** : None.  
**Transport by sea (IMDG)** : None.

**14.6. Special precautions for user**

**Packing Instruction(s)**

**Transport by road/rail (ADR/RID)** : P200  
**Transport by air (ICAO-TI / IATA-DGR)**  
     Passenger and Cargo Aircraft : 200.  
     Cargo Aircraft only : 200.  
**Transport by sea (IMDG)** : P200


**Special transport precautions**

: Avoid transport on vehicles where the load space is not separated from the driver's compartment.  
 Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.  
 Before transporting product containers:  
 - Ensure there is adequate ventilation.  
 - Ensure that containers are firmly secured.  
 - Ensure valve is closed and not leaking.  
 - Ensure valve outlet cap nut or plug (where provided) is correctly fitted.  
 - Ensure valve protection device (where provided) is correctly fitted.

**14.7. Maritime transport in bulk according to IMO instruments**

Not applicable.



	<b>SAFETY DATA SHEET</b>	Page : 9/10
		Revised edition no : 5.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
<b>Helium</b>		<b>NOAL_0061A</b>
		Country : NO / Language : EN

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU-Regulations

Restrictions on use	: None.
National legislation	: Ensure all national/local regulations are observed.
Seveso Directive : 2012/18/EU (Seveso III)	: Not covered.

#### National regulations

Ensure all national/local regulations are observed.

#### Germany

Water hazard class (WGK)	: WGK nwg, Non-hazardous to water
National Rules and Recommendations	: [German regulations] BetriebssicherheitsV mit TRBSen insbesondere TRBS 3145 / TRGS 725 Ortsbewegliche Druckgasbehälter", TRBS 2141, BGR Regel 500 Teil 2.33: "Umgang mit Gasen", GefahrstoffV mit Technischen Regeln Gefährliche Stoffe TRGS insbesondere TRGS 407 "Tätigkeiten mit Gasen - Gefährdungsbeurteilung", TRGS 400, 500, 510, 900."

#### Netherlands

SZW-lijst van kankerverwekkende stoffen	: The substance is not listed
SZW-lijst van mutagene stoffen	: The substance is not listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: The substance is not listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: The substance is not listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: The substance is not listed

#### Switzerland


Storage class (LK)	: LK 2 - Liquefied or pressurized gases
--------------------	---

### 15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.

## SECTION 16: Other information

Indication of changes	: Safety data sheet in accordance with commission regulation (EU) No 2020/878.
Abbreviations and acronyms	: <ul style="list-style-type: none"> <li>ATE - Acute Toxicity Estimate</li> <li>CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008</li> <li>REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006</li> <li>EINECS - European Inventory of Existing Commercial Chemical Substances</li> <li>CAS# - Chemical Abstract Service number</li> <li>PPE - Personal Protection Equipment</li> <li>LC50 - Lethal Concentration to 50 % of a test population</li> <li>RMM - Risk Management Measures</li> <li>PBT - Persistent, Bioaccumulative and Toxic</li> <li>vPvB - Very Persistent and Very Bioaccumulative</li> <li>STOT- SE : Specific Target Organ Toxicity - Single Exposure</li> <li>CSA - Chemical Safety Assessment</li> <li>EN - European Standard</li> <li>UN - United Nations</li> <li>ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road</li> <li>IATA - International Air Transport Association</li> <li>IMDG code - International Maritime Dangerous Goods</li> <li>RID - Regulations concerning the International Carriage of Dangerous Goods by Rail</li> <li>WGK - Water Hazard Class</li> <li>STOT - RE : Specific Target Organ Toxicity - Repeated Exposure</li> <li>UFI : Unique Formula Identifier</li> </ul>

	<b>SAFETY DATA SHEET</b>	Page : 10/10
		Revised edition no : 5.0
		Revision date : 2023-01-19
		Supersedes version of : 2021-06-16
<b>Helium</b>		<b>NOAL_0061A</b>
		Country : NO / Language : EN

Training advice : The hazard of asphyxiation is often overlooked and must be stressed during operator training.  
For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at <http://www.eiga.eu>.

Further information : Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).  
Key literature references and sources of data are maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at <http://www.Eiga.eu> .

Full text of H- and EUH-statements	
H280	Contains gas under pressure; may explode if heated.
Press. Gas (Comp.)	Gases under pressure : Compressed gas

DISCLAIMER OF LIABILITY : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.  
Details given in this document are believed to be correct at the time of going to press.  
Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

**End of document**