



SAFETY DATA SHEET

Page : 1/46

Revised edition no : 6.0

Revision date : 2024-02-02

Supersedes version of : 2023-01-19

Ammonia, anhydrous**NOAL_0002**

Country : SE / Language : EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : Ammonia, anhydrous, Ammonia, Ammonia N38, Ammonia HG, Ammonia LGC
SDS no : NOAL_0002
Other means of identification : Ammonia, anhydrous
CAS-No. : 7664-41-7
EC-No. : 231-635-3
EC Index-No. : 007-001-00-5
REACH registration No : 01-2119488876-14
Chemical formula : NH₃

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use.
Test gas/Calibration gas.
Laboratory use.
Contact supplier for more information on uses.
Uses advised against : Consumer use.
Uses other than those listed above are not supported, contact your supplier for more information on other uses.

1.3. Details of the supplier of the safety data sheet

Company identification

Supplier

AIR LIQUIDE GAS AB
Pulpetgatan 20
215 37 Malmö - SWEDEN
T +46 40 38 10 00
info.sweden@airliquide.com

E-Mail address (competent person) : eunordic-sds@airliquide.com

1.4. Emergency telephone number

Emergency telephone number : 112
Availability
(24 / 7)


Country	Organisation/Company	Address	Emergency number	Comment
Germany	Giftnotruf Erfurt Gemeinsames Giftinformationszentrum der Länder Mecklenburg-Vorpommern, Sachsen, Sachsen-Anhalt und Thüringen, c/o HELIOS Klinikum Erfurt	Nordhäuser Straße 74 99089 Erfurt	+49 (0) 361 730 730	

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards Flammable gases, Category 2 H221
Gases under pressure : Liquefied gas H280


	SAFETY DATA SHEET	Page : 2/46
		Revised edition no : 6.0
		Revision date : 2024-02-02
		Supersedes version of : 2023-01-19
Ammonia, anhydrous		NOAL_0002
		Country : SE / Language : EN

Health hazards	Acute toxicity (inhalation:gas) Category 3	H331
	Skin corrosion/irritation, Category 1, Sub-Category 1B	H314
	Serious eye damage/eye irritation, Category 1	H318
Environmental hazards	Hazardous to the aquatic environment – Acute Hazard, Category 1	H400
	Hazardous to the aquatic environment – Chronic Hazard, Category 2	H411

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



Signal word (CLP)

: Danger

Hazard statements (CLP)

: H314 - Causes severe skin burns and eye damage.
H221 - Flammable gas.
H280 - Contains gas under pressure; may explode if heated.
H331 - Toxic if inhaled.
H410 - Very toxic to aquatic life with long lasting effects.
EUH071 - Corrosive to the respiratory tract.

Precautionary statements (CLP)

- Prevention

: P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
P271 - Use only outdoors or in a well-ventilated area.
P273 - Avoid release to the environment.
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
P264 - Wash hands, forearms and face thoroughly after handling.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- Response

: P391 - Collect spillage.
P321 - Specific treatment (see supplemental first aid instruction on this label).
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P310 - Immediately call a POISON CENTER or doctor.
P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
P381 - In case of leakage, eliminate all ignition sources.
P381 - In case of leakage, eliminate all ignition sources.
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

- Storage


: P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
P405 - Store locked up.
P403 - Store in a well-ventilated place.
P410+P403 - Protect from sunlight. Store in a well-ventilated place.

- Disposal considerations

: P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

None.
Not classified as PBT or vPvB.
The substance/mixture has no endocrine disrupting properties.

	SAFETY DATA SHEET	Page : 3/46
		Revised edition no : 6.0
		Revision date : 2024-02-02
		Supersedes version of : 2023-01-19
Ammonia, anhydrous	NOAL_0002	
		Country : SE / Language : EN

SECTION 3: Composition/information on ingredients

3.1. Substances

Name	Product identifier	Composition [V-%]:	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Ammonia, anhydrous	CAS-No.: 7664-41-7 EC-No.: 231-635-3 EC Index-No.: 007-001-00-5 REACH registration No: 01-2119488876-14	100	Flam. Gas 2, H221 Press. Gas (Liq.), H280 Acute Tox. 3 (Inhalation:gas), H331 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400 Aquatic Chronic 2, H411

Contains no other components or impurities which will influence the classification of the product.

3.2. Mixtures

Not established.

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : Remove contaminated clothing. Drench affected area with water for at least 15 minutes. In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

May cause severe chemical burns to skin and cornea. Suitable first-aid treatment should be immediately available. Seek medical advice before using product.
Material is destructive to tissue of the mucuous membranes and upper respiratory tract.
Cough, shortness of breath, headache, nausea.
See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.
Treat with corticosteroid spray as soon as possible after inhalation.


SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Shutting off the source of the gas is the preferred method of control.
- Unsuitable extinguishing media : Do not use water jet to extinguish.
Carbon dioxide.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : Nitric oxide/nitrogen dioxide.

	SAFETY DATA SHEET	Page : 4/46
		Revised edition no : 6.0
		Revision date : 2024-02-02
		Supersedes version of : 2023-01-19
Ammonia, anhydrous	NOAL_0002	Country : SE / Language : EN

5.3. Advice for firefighters

Specific methods

: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
If possible, stop flow of product.
Use water spray or fog to knock down fire fumes if possible.
Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.
Move containers away from the fire area if this can be done without risk.

Special protective equipment for fire fighters

: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus.
Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Gas-tight chemical protective suits for emergency teams.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

: Act in accordance with local emergency plan.
Try to stop release.
Evacuate area.
Ensure adequate air ventilation.
Eliminate ignition sources.
Stay upwind.

For emergency responders

See section 8 of the SDS for more information on personal protective equipment
: Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
Use chemically protective clothing.
Monitor concentration of released product.
Consider the risk of potentially explosive atmospheres.
See section 5.3 of the SDS for more information.

6.2. Environmental precautions


Reduce vapour with fog or fine water spray.
Try to stop release.

6.3. Methods and material for containment and cleaning up

Hose down area with water.
Wash contaminated equipment or sites of leaks with copious quantities of water.

6.4. Reference to other sections


See also sections 8 and 13.

	SAFETY DATA SHEET	Page : 5/46
		Revised edition no : 6.0
		Revision date : 2024-02-02
		Supersedes version of : 2023-01-19
Ammonia, anhydrous		NOAL_0002
		Country : SE / Language : EN

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe use of the product	: Do not breathe gas. Avoid release of product into atmosphere. The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularly) checked for leaks before use. Do not smoke while handling product. Avoid exposure, obtain special instructions before use. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Installation of a cross purge assembly between the container and the regulator is recommended. Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service. Avoid suck back of water, acid and alkalis. Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment. Purge air from system before introducing gas. Take precautionary measures against static discharge. Keep away from ignition sources (including static discharges). Consider the use of only non-sparking tools. Ensure equipment is adequately earthed.
Safe handling of the gas receptacle	: Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect containers from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the content of the container. Suck back of water into the container must be prevented. Open valve slowly to avoid pressure shock.

	SAFETY DATA SHEET	Page : 6/46
		Revised edition no : 6.0
		Revision date : 2024-02-02
		Supersedes version of : 2023-01-19
Ammonia, anhydrous		NOAL_0002
		Country : SE / Language : EN

7.2. Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers.
Containers should not be stored in conditions likely to encourage corrosion.
Container valve guards or caps should be in place.
Containers should be stored in the vertical position and properly secured to prevent them from falling over.
Stored containers should be periodically checked for general condition and leakage.
Keep container below 50°C in a well ventilated place.
Store containers in location free from fire risk and away from sources of heat and ignition.
Keep away from combustible materials.
Segregate from oxidant gases and other oxidants in store.
All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere.


7.3. Specific end use(s)


None.


SECTION 8: Exposure controls/personal protection


8.1. Control parameters


Ammonia, anhydrous (7664-41-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ammonia, anhydrous
IOEL TWA	14 mg/m³
IOEL TWA [ppm]	20 ppm
IOEL STEL	36 mg/m³
IOEL STEL [ppm]	50 ppm
Austria - Occupational Exposure Limits	
Local name	Ammoniak
MAK (mg/m³)	14 mg/m³
MAK (OEL TWA) [ppm]	20 ppm
MAK (OEL STEL)	36 mg/m³
MAK (OEL STEL) [ppm]	50 ppm
Belgium - Occupational Exposure Limits	
Local name	Ammoniac # Ammoniak
OEL TWA	14 mg/m³
OEL TWA [ppm]	20 ppm
OEL STEL	36 mg/m³
OEL STEL [ppm]	50 ppm
Bulgaria - Occupational Exposure Limits	
Local name	Амоняк
OEL TWA	14 mg/m³

	SAFETY DATA SHEET		Page : 7/46
			Revised edition no : 6.0
			Revision date : 2024-02-02
			Supersedes version of : 2023-01-19
Ammonia, anhydrous			NOAL_0002
			Country : SE / Language : EN
OEL TWA [ppm]		20 ppm	
OEL STEL		36 mg/m³	
OEL STEL [ppm]		50 ppm	
Remark		• (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)	
Croatia - Occupational Exposure Limits			
Local name		Amonijak, bezvodni	
GVI (OEL TWA) [1]		14 mg/m³	
GVI (OEL TWA) [2]		20 ppm	
KGVI (OEL STEL)		36 mg/m³	
KGVI (OEL STEL) [ppm]		50 ppm	
Remark		K, T, N, EU*	
Czech Republic - Occupational Exposure Limits			
Local name		Amoniak	
PEL (OEL TWA)		14 mg/m³	
PEL (OEL TWA) [ppm]		20.13 ppm	
NPK-P (OEL C)		36 mg/m³	
NPK-P (OEL C) [ppm]		51.77 ppm	
Denmark - Occupational Exposure Limits			
Local name		Ammoniak	
OEL TWA [1]		14 mg/m³	
OEL TWA [2]		20 ppm	
Estonia - Occupational Exposure Limits			
Local name		Ammoniaak	
OEL TWA		14 mg/m³	
OEL TWA [ppm]		20 ppm	
OEL STEL		36 mg/m³	
OEL STEL [ppm]		50 ppm	
Finland - Occupational Exposure Limits			
Local name		Vedetön ammoniakki	
HTP (OEL TWA) [1]		14 mg/m³	
HTP (OEL TWA) [2]		20 ppm	
HTP (OEL STEL)		36 mg/m³	
HTP (OEL STEL) [ppm]		50 ppm	
France - Occupational Exposure Limits			
Local name		Ammoniac anhydre	

	SAFETY DATA SHEET		Page : 8/46
			Revised edition no : 6.0
			Revision date : 2024-02-02
			Supersedes version of : 2023-01-19
Ammonia, anhydrous			NOAL_0002
			Country : SE / Language : EN
VME (OEL TWA)		7 mg/m³	
VME (OEL TWA) [ppm]		10 ppm	
VLE (OEL C/STEL)		14 mg/m³	
VLE (OEL C/STEL) [ppm]		20 ppm	
Remark		Valeurs réglementaires contraignantes	
Germany - Occupational Exposure Limits (TRGS 900)			
Local name		Ammoniak	
AGW (OEL TWA) [1]		14 mg/m³	
AGW (OEL TWA) [2]		20 ppm	
Remark		DFG,EU,Y	
Greece - Occupational Exposure Limits			
OEL TWA		35 mg/m³	
OEL TWA [ppm]		50 ppm	
OEL STEL		35 mg/m³	
OEL STEL [ppm]		50 ppm	
Hungary - Occupational Exposure Limits			
Local name		AMMÓNIA	
AK (OEL TWA)		14 mg/m³	
CK (OEL STEL)		36 mg/m³	
Ireland - Occupational Exposure Limits			
Local name		Ammonia, anhydrous	
OEL TWA [1]		14 mg/m³	
OEL TWA [2]		20 ppm	
OEL STEL		36 mg/m³	
OEL STEL [ppm]		50 ppm	
Italy - Occupational Exposure Limits			
Local name		Ammoniaca anidra	
OEL TWA		14 mg/m³	
OEL TWA [ppm]		20 ppm	
OEL STEL		36 mg/m³	
OEL STEL [ppm]		50 ppm	
Latvia - Occupational Exposure Limits			
Local name		Amonjaks	
OEL TWA		14 mg/m³	
OEL TWA [ppm]		20 ppm	
OEL STEL		36 mg/m³	

	SAFETY DATA SHEET		Page : 9/46
			Revised edition no : 6.0
			Revision date : 2024-02-02
			Supersedes version of : 2023-01-19
Ammonia, anhydrous			NOAL_0002
			Country : SE / Language : EN
OEL STEL [ppm]		50 ppm	
Lithuania - Occupational Exposure Limits			
Local name		Amoniakas (bevandenis)	
IPRV (OEL TWA)		14 mg/m³	
IPRV (OEL TWA) [ppm]		20 ppm	
TPRV (OEL STEL)		36 mg/m³	
TPRV (OEL STEL) [ppm]		50 ppm	
Luxembourg - Occupational Exposure Limits			
Local name		Ammoniac anhydre	
OEL TWA		14 mg/m³	
OEL TWA [ppm]		20 ppm	
OEL STEL		36 mg/m³	
OEL STEL [ppm]		50 ppm	
Malta - Occupational Exposure Limits			
Local name		Ammonia, anhydrous	
OEL TWA		14 mg/m³	
OEL TWA [ppm]		20 ppm	
OEL STEL		36 mg/m³	
OEL STEL [ppm]		50 ppm	
Netherlands - Occupational Exposure Limits			
Local name		Ammoniak	
TGG-8u (OEL TWA)		14 mg/m³	
TGG-15min (OEL STEL)		36 mg/m³	
Poland - Occupational Exposure Limits			
Local name		Amoniak	
NDS (OEL TWA)		14 mg/m³	
NDSch (OEL STEL)		28 mg/m³	
Portugal - Occupational Exposure Limits			
Local name		Amoníaco	
OEL TWA [ppm]		25 ppm	
OEL STEL [ppm]		35 ppm	
Romania - Occupational Exposure Limits			
Local name		Amoniac	
OEL TWA		14 mg/m³	
OEL TWA [ppm]		20 ppm	
OEL STEL		36 mg/m³	

	SAFETY DATA SHEET		Page : 10/46
			Revised edition no : 6.0
			Revision date : 2024-02-02
			Supersedes version of : 2023-01-19
Ammonia, anhydrous			NOAL_0002
			Country : SE / Language : EN
OEL STEL [ppm]		50 ppm	
Slovakia - Occupational Exposure Limits			
NPHV (OEL TWA) [1]		14 mg/m³	
NPHV (OEL TWA) [2]		20 ppm	
NPHV (OEL STEL)		36 mg/m³	
Slovenia - Occupational Exposure Limits			
Local name		amonijak, brezvodni	
OEL TWA		14 mg/m³	
OEL TWA [ppm]		20 ppm	
OEL STEL		35 mg/m³	
OEL STEL [ppm]		50 ppm	
Spain - Occupational Exposure Limits			
Local name		Amoníaco	
VLA-ED (OEL TWA) [1]		14 mg/m³	
VLA-ED (OEL TWA) [2]		20 ppm	
VLA-EC (OEL STEL)		36 mg/m³	
VLA-EC (OEL STEL) [ppm]		50 ppm	
Remark		VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país).	
Sweden - Occupational Exposure Limits			
Local name		Ammoniak	
NGV (OEL TWA)		14 mg/m³	
NGV (OEL TWA) [ppm]		20 ppm	
KTV (OEL STEL)		36 mg/m³	
KTV (OEL STEL) [ppm]		50 ppm	
United Kingdom - Occupational Exposure Limits			
Local name		Ammonia, anhydrous	
WEL TWA (OEL TWA) [1]		18 mg/m³	
WEL TWA (OEL TWA) [2]		25 ppm	
WEL STEL (OEL STEL)		25 mg/m³	
WEL STEL (OEL STEL) [ppm]		35 ppm	
Iceland - Occupational Exposure Limits			
Local name		Ammóníak	

	SAFETY DATA SHEET	Page : 11/46
		Revised edition no : 6.0
		Revision date : 2024-02-02
		Supersedes version of : 2023-01-19
Ammonia, anhydrous		NOAL_0002
		Country : SE / Language : EN


OEL TWA	14 mg/m³
OEL TWA [ppm]	20 ppm
OEL STEL	36 mg/m³
OEL STEL [ppm]	50 ppm
Remark	H


Norway - Occupational Exposure Limits	
Local name	Ammoniakk
Grenseverdi (OEL TWA) [1]	18 mg/m³
Grenseverdi (OEL TWA) [2]	25 ppm


Switzerland - Occupational Exposure Limits	
Local name	Ammoniak
MAK (OEL TWA) [1]	14 mg/m³
MAK (OEL TWA) [2]	20 ppm
KZGW (OEL STEL)	28 mg/m³
KZGW (OEL STEL) [ppm]	40 ppm
Remark	SS _C - Auge ^{KT HU} & OAW ^{KT HU} - NIOSH, OSHA


USA - ACGIH - Occupational Exposure Limits	
Local name	Ammonia
ACGIH OEL TWA [ppm]	25 ppm
ACGIH OEL STEL [ppm]	35 ppm
Remark (ACGIH)	Eye dam; URT irr


Ammonia, anhydrous (7664-41-7)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Ammonia, anhydrous
IOEL TWA	14 mg/m³
IOEL TWA [ppm]	20 ppm
IOEL STEL	36 mg/m³
IOEL STEL [ppm]	50 ppm
Austria - Occupational Exposure Limits	
Local name	Ammoniak
MAK (mg/m³)	14 mg/m³
MAK (OEL TWA) [ppm]	20 ppm
MAK (OEL STEL)	36 mg/m³
MAK (OEL STEL) [ppm]	50 ppm


	SAFETY DATA SHEET		Page : 12/46
			Revised edition no : 6.0
			Revision date : 2024-02-02
			Supersedes version of : 2023-01-19
Ammonia, anhydrous			NOAL_0002
			Country : SE / Language : EN
Belgium - Occupational Exposure Limits			
Local name		Ammoniac # Ammoniak	
OEL TWA		14 mg/m³	
OEL TWA [ppm]		20 ppm	
OEL STEL		36 mg/m³	
OEL STEL [ppm]		50 ppm	
Bulgaria - Occupational Exposure Limits			
Local name		Амоняк	
OEL TWA		14 mg/m³	
OEL TWA [ppm]		20 ppm	
OEL STEL		36 mg/m³	
OEL STEL [ppm]		50 ppm	
Remark		• (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)	
Croatia - Occupational Exposure Limits			
Local name		Amonijak, bezvodni	
GVI (OEL TWA) [1]		14 mg/m³	
GVI (OEL TWA) [2]		20 ppm	
KGVI (OEL STEL)		36 mg/m³	
KGVI (OEL STEL) [ppm]		50 ppm	
Remark		K, T, N, EU*	
Czech Republic - Occupational Exposure Limits			
Local name		Amoniak	
PEL (OEL TWA)		14 mg/m³	
PEL (OEL TWA) [ppm]		20.13 ppm	
NPK-P (OEL C)		36 mg/m³	
NPK-P (OEL C) [ppm]		51.77 ppm	
Denmark - Occupational Exposure Limits			
Local name		Ammoniak	
OEL TWA [1]		14 mg/m³	
OEL TWA [2]		20 ppm	
Estonia - Occupational Exposure Limits			
Local name		Ammoniaak	
OEL TWA		14 mg/m³	
OEL TWA [ppm]		20 ppm	
OEL STEL		36 mg/m³	

	SAFETY DATA SHEET		Page : 13/46
			Revised edition no : 6.0
			Revision date : 2024-02-02
			Supersedes version of : 2023-01-19
Ammonia, anhydrous			NOAL_0002
			Country : SE / Language : EN
OEL STEL [ppm]		50 ppm	
Finland - Occupational Exposure Limits			
Local name		Vedetön ammoniakki	
HTP (OEL TWA) [1]		14 mg/m³	
HTP (OEL TWA) [2]		20 ppm	
HTP (OEL STEL)		36 mg/m³	
HTP (OEL STEL) [ppm]		50 ppm	
France - Occupational Exposure Limits			
Local name		Ammoniac anhydre	
VME (OEL TWA)		7 mg/m³	
VME (OEL TWA) [ppm]		10 ppm	
VLE (OEL C/STEL)		14 mg/m³	
VLE (OEL C/STEL) [ppm]		20 ppm	
Remark		Valeurs réglementaires contraignantes	
Germany - Occupational Exposure Limits (TRGS 900)			
Local name		Ammoniak	
AGW (OEL TWA) [1]		14 mg/m³	
AGW (OEL TWA) [2]		20 ppm	
Remark		DFG,EU,Y	
Greece - Occupational Exposure Limits			
OEL TWA		35 mg/m³	
OEL TWA [ppm]		50 ppm	
OEL STEL		35 mg/m³	
OEL STEL [ppm]		50 ppm	
Hungary - Occupational Exposure Limits			
Local name		AMMÓNIA	
AK (OEL TWA)		14 mg/m³	
CK (OEL STEL)		36 mg/m³	
Ireland - Occupational Exposure Limits			
Local name		Ammonia, anhydrous	
OEL TWA [1]		14 mg/m³	
OEL TWA [2]		20 ppm	
OEL STEL		36 mg/m³	
OEL STEL [ppm]		50 ppm	
Italy - Occupational Exposure Limits			
Local name		Ammoniaca anidra	

	SAFETY DATA SHEET		Page : 14/46
			Revised edition no : 6.0
			Revision date : 2024-02-02
			Supersedes version of : 2023-01-19
Ammonia, anhydrous			NOAL_0002
			Country : SE / Language : EN
OEL TWA		14 mg/m³	
OEL TWA [ppm]		20 ppm	
OEL STEL		36 mg/m³	
OEL STEL [ppm]		50 ppm	
Latvia - Occupational Exposure Limits			
Local name		Amonjaks	
OEL TWA		14 mg/m³	
OEL TWA [ppm]		20 ppm	
OEL STEL		36 mg/m³	
OEL STEL [ppm]		50 ppm	
Lithuania - Occupational Exposure Limits			
Local name		Amoniakas (bevandenis)	
IPRV (OEL TWA)		14 mg/m³	
IPRV (OEL TWA) [ppm]		20 ppm	
TPRV (OEL STEL)		36 mg/m³	
TPRV (OEL STEL) [ppm]		50 ppm	
Luxembourg - Occupational Exposure Limits			
Local name		Ammoniac anhydre	
OEL TWA		14 mg/m³	
OEL TWA [ppm]		20 ppm	
OEL STEL		36 mg/m³	
OEL STEL [ppm]		50 ppm	
Malta - Occupational Exposure Limits			
Local name		Ammonia, anhydrous	
OEL TWA		14 mg/m³	
OEL TWA [ppm]		20 ppm	
OEL STEL		36 mg/m³	
OEL STEL [ppm]		50 ppm	
Netherlands - Occupational Exposure Limits			
Local name		Ammoniak	
TGG-8u (OEL TWA)		14 mg/m³	
TGG-15min (OEL STEL)		36 mg/m³	
Poland - Occupational Exposure Limits			
Local name		Amoniak	
NDS (OEL TWA)		14 mg/m³	
NDSCh (OEL STEL)		28 mg/m³	

	SAFETY DATA SHEET		Page : 15/46
			Revised edition no : 6.0
			Revision date : 2024-02-02
			Supersedes version of : 2023-01-19
Ammonia, anhydrous			NOAL_0002
			Country : SE / Language : EN
Portugal - Occupational Exposure Limits			
Local name		Amoníaco	
OEL TWA [ppm]		25 ppm	
OEL STEL [ppm]		35 ppm	
Romania - Occupational Exposure Limits			
Local name		Amoniac	
OEL TWA		14 mg/m³	
OEL TWA [ppm]		20 ppm	
OEL STEL		36 mg/m³	
OEL STEL [ppm]		50 ppm	
Slovakia - Occupational Exposure Limits			
NPHV (OEL TWA) [1]		14 mg/m³	
NPHV (OEL TWA) [2]		20 ppm	
NPHV (OEL STEL)		36 mg/m³	
Slovenia - Occupational Exposure Limits			
Local name		amonijak, brezvodni	
OEL TWA		14 mg/m³	
OEL TWA [ppm]		20 ppm	
OEL STEL		35 mg/m³	
OEL STEL [ppm]		50 ppm	
Spain - Occupational Exposure Limits			
Local name		Amoníaco	
VLA-ED (OEL TWA) [1]		14 mg/m³	
VLA-ED (OEL TWA) [2]		20 ppm	
VLA-EC (OEL STEL)		36 mg/m³	
VLA-EC (OEL STEL) [ppm]		50 ppm	
Remark		VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país).	
Sweden - Occupational Exposure Limits			
Local name		Ammoniak	
NGV (OEL TWA)		14 mg/m³	
NGV (OEL TWA) [ppm]		20 ppm	
KTV (OEL STEL)		36 mg/m³	

	SAFETY DATA SHEET		Page : 16/46
			Revised edition no : 6.0
			Revision date : 2024-02-02
			Supersedes version of : 2023-01-19
Ammonia, anhydrous			NOAL_0002
			Country : SE / Language : EN
KTV (OEL STEL) [ppm]		50 ppm	
United Kingdom - Occupational Exposure Limits			
Local name		Ammonia, anhydrous	
WEL TWA (OEL TWA) [1]		18 mg/m³	
WEL TWA (OEL TWA) [2]		25 ppm	
WEL STEL (OEL STEL)		25 mg/m³	
WEL STEL (OEL STEL) [ppm]		35 ppm	
Iceland - Occupational Exposure Limits			
Local name		Ammóníak	
OEL TWA		14 mg/m³	
OEL TWA [ppm]		20 ppm	
OEL STEL		36 mg/m³	
OEL STEL [ppm]		50 ppm	
Remark		H	
Norway - Occupational Exposure Limits			
Local name		Ammoniakk	
Grenseverdi (OEL TWA) [1]		18 mg/m³	
Grenseverdi (OEL TWA) [2]		25 ppm	
Switzerland - Occupational Exposure Limits			
Local name		Ammoniak	
MAK (OEL TWA) [1]		14 mg/m³	
MAK (OEL TWA) [2]		20 ppm	
KZGW (OEL STEL)		28 mg/m³	
KZGW (OEL STEL) [ppm]		40 ppm	
Remark		SS _C - Auge ^{KT HU} & OAW ^{KT HU} - NIOSH, OSHA	
USA - ACGIH - Occupational Exposure Limits			
Local name		Ammonia	
ACGIH OEL TWA [ppm]		25 ppm	
ACGIH OEL STEL [ppm]		35 ppm	
Remark (ACGIH)		Eye dam; URT irr	
Ammonia, anhydrous (7664-41-7)			
DNEL: Derived no effect level (Workers)			
Acute - local effects, inhalation		36 mg/m³	
Acute - systemic effects, inhalation		47.6 mg/m³	
Long-term - local effects, inhalation		14 mg/m³	

	SAFETY DATA SHEET	Page : 17/46
		Revised edition no : 6.0
		Revision date : 2024-02-02
		Supersedes version of : 2023-01-19
Ammonia, anhydrous		NOAL_0002
		Country : SE / Language : EN

Long-term - systemic effects, inhalation	47.6 mg/m³
Acute - systemic effects, dermal	6.8 mg/kg bw/day
Long-term - systemic effects, dermal	6.8 mg/kg bw/day

Ammonia, anhydrous (7664-41-7)	
DNEL: Derived no effect level (Workers)	
Acute - local effects, inhalation	36 mg/m³
Acute - systemic effects, inhalation	47.6 mg/m³
Long-term - local effects, inhalation	14 mg/m³
Long-term - systemic effects, inhalation	47.6 mg/m³
Acute - systemic effects, dermal	6.8 mg/kg bw/day
Long-term - systemic effects, dermal	6.8 mg/kg bw/day

Ammonia, anhydrous (7664-41-7)	
PNEC: Predicted no effect concentration	
Aqua (freshwater)	0.0011 mg/l
Aqua (marine water)	0.0011 mg/l

Ammonia, anhydrous (7664-41-7)	
PNEC: Predicted no effect concentration	
Aqua (freshwater)	0.0011 mg/l
Aqua (marine water)	0.0011 mg/l

8.2. Exposure controls


8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation.
 Product to be handled in a closed system.
 Systems under pressure should be regularly checked for leakages.
 Ensure exposure is below occupational exposure limits (where available).
 Gas detectors should be used when toxic gases may be released.
 Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.
 The following recommendations should be considered:
 PPE compliant to the recommended EN/ISO standards should be selected.
 : Wear goggles and a face shield when transfilling or breaking transfer connections.
 Standard EN 166 - Personal eye-protection - specifications.
 Provide readily accessible eye wash stations and safety showers.

- Eye/face protection
- Skin protection

	SAFETY DATA SHEET	Page : 18/46
		Revised edition no : 6.0
		Revision date : 2024-02-02
		Supersedes version of : 2023-01-19
Ammonia, anhydrous	NOAL_0002	Country : SE / Language : EN

- Hand protection	: Wear chemically resistant protective gloves. Wear working gloves when handling gas containers. Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher. Standard EN 511 - Cold insulating gloves. Standard EN 374 - Protective gloves against chemicals. Permeation time: minimum >30min short term exposure: material / thickness Chloroprene rubber (Neoprene®) (CR) / 0,5 [mm]. Permeation time: minimum >480min long term exposure : material / thickness Butyl rubber (IIR) / 0,7 [mm]. Consult glove manufacturer's product information on material suitability and material thickness. The breakthrough time of the selected gloves must be greater than the intended use period.
- Other	: Keep suitable chemically resistant protective clothing readily available for emergency use. Standard EN943-1 - Full protective suits against liquid, solid and gaseous chemicals. Wear safety shoes while handling containers. Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
• Respiratory protection	: Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask. Consult respiratory device supplier's product information for the selection of the appropriate device. Keep self contained breathing apparatus readily available for emergency use. Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
• Thermal hazards	: None in addition to the above sections.


8.2.3. Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
- Physical state at 20°C / 101.3kPa	: Gas
- Colour	: Colourless.
Odour	: Odourless. Odour threshold is subjective and inadequate to warn of overexposure.
pH	: Not applicable for gases and gas mixtures.
Melting point / Freezing point	: -77.7 °C -77.7 °C
Boiling point	: -33 °C
Flash point	: Not applicable for gases and gas mixtures.
Flammability	: Flammable gas.
Explosive limits	: 15.4 – 33.6 vol %
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Vapour pressure [20°C]	: 8.6 bar(a)
Vapour pressure [50°C]	: 20 bar(a)
Density	: Not applicable
Vapour density	: Not applicable for gases and gas mixtures.
Relative density, liquid (water=1)	: 0.7
Relative density, gas (air=1)	: 0.6
Water solubility	: 517 g/l
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for inorganic products.
Auto-ignition temperature	: 630 °C
Decomposition temperature	: Not applicable.
Viscosity, kinematic	: Not applicable for gases and gas mixtures.
Particle characteristics	: Not applicable for gases and gas mixtures.

	SAFETY DATA SHEET	Page : 19/46
		Revised edition no : 6.0
		Revision date : 2024-02-02
		Supersedes version of : 2023-01-19
Ammonia, anhydrous	NOAL_0002	
		Country : SE / Language : EN

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Explosive properties

: Not applicable.

Oxidising properties

: Not applicable.

Tci

: 40.1 %

Critical temperature [°C]

: 132 °C

9.2.2. Other safety characteristics

Molar mass

: 17 g/mol

Gas group

: Press. Gas (Liq.)

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactivity

None.

Can form explosive mixture with air.

May react violently with oxidants.

: This mixture contains components with the following reactivity : Can form explosive mixture with air. May react violently with oxidants.

10.4. Conditions to avoid

Avoid moisture in installation systems.

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

10.5. Incompatible materials

With water causes rapid corrosion of some metals.

Reacts with water to form corrosive acids.

May react violently with alkalis.

Air, Oxidisers.

For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008


Acute toxicity : Toxic if inhaled.

LC50 Inhalation - Rat [ppm]	2000 ppm/4h
-----------------------------	-------------

Ammonia, anhydrous (7664-41-7)	
LC50 Inhalation - Rat [ppm]	2000 ppm/4h

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

	SAFETY DATA SHEET	Page : 20/46
		Revised edition no : 6.0
		Revision date : 2024-02-02
		Supersedes version of : 2023-01-19
Ammonia, anhydrous	NOAL_0002	Country : SE / Language : EN

Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: Severe corrosion to the respiratory tract at high concentrations.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.

11.2. Information on other hazards

Other information	: The substance/mixture has no endocrine disrupting properties.
-------------------	---

SECTION 12: Ecological information

12.1. Toxicity

Assessment	: Very toxic to aquatic life. Toxic to aquatic life with long lasting effects.
EC50 48h - Daphnia magna [mg/l]	: 101 mg/l
EC50 72h - Algae [mg/l]	: No data available.
LC50 96 h - Fish [mg/l]	: 0.89 mg/l

Ammonia, anhydrous (7664-41-7)	
EC50 48h - Daphnia magna [mg/l]	101 mg/l
EC50 72h - Algae [mg/l]	No data available.
LC50 96 h - Fish [mg/l]	0.89 mg/l

12.2. Persistence and degradability

Assessment	: No data available.
------------	----------------------

12.3. Bioaccumulative potential

Assessment	: No data available.
------------	----------------------

12.4. Mobility in soil

Assessment	: Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.
------------	---

12.5. Results of PBT and vPvB assessment


Assessment	: Not classified as PBT or vPvB.
------------	----------------------------------

12.6. Endocrine disrupting properties

The substance/mixture has no endocrine disrupting properties.

12.7. Other adverse effects

Other adverse effects	: May cause pH changes in aqueous ecological systems.
Effect on the ozone layer	: None.
Effect on global warming	: No known effects from this product.

	SAFETY DATA SHEET	Page : 21/46
		Revised edition no : 6.0
		Revision date : 2024-02-02
		Supersedes version of : 2023-01-19
Ammonia, anhydrous		NOAL_0002
		Country : SE / Language : EN

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Contact supplier if guidance is required.
Must not be discharged to atmosphere.
Ensure that the emission levels from local regulations or operating permits are not exceeded.
Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods.
Return unused product in original container to supplier.

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)

: 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.

13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN

UN-No. : 1005

14.2. UN proper shipping name

Transport by road/rail (ADR/RID)

: AMMONIA, ANHYDROUS

Transport by air (ICAO-TI / IATA-DGR)


: Ammonia, anhydrous

Transport by sea (IMDG)

: AMMONIA, ANHYDROUS

14.3. Transport hazard class(es)

Labelling



2.3 : Toxic gases.
8 : Corrosive substances.
Environmentally hazardous substances

Transport by road/rail (ADR/RID)

Class : 2
Classification code : 2TC
Hazard identification number : 268
Tunnel Restriction : C/D - Tank carriage: Passage forbidden through tunnels of category C, D and E. Other carriage: Passage forbidden through tunnels of category D and E

Transport by sea (IMDG)


Class / Div. (Sub. risk(s)) : 2.3 (8)
Emergency Schedule (EmS) - Fire : F-C
Emergency Schedule (EmS) - Spillage : S-U

14.4. Packing group

Transport by road/rail (ADR/RID) : Not established.
Transport by air (ICAO-TI / IATA-DGR) : Not established.
Transport by sea (IMDG) : Not established.

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : Environmentally hazardous substance / mixture.
Transport by air (ICAO-TI / IATA-DGR) : Environmentally hazardous substance / mixture.
Transport by sea (IMDG) : Marine pollutant

	SAFETY DATA SHEET	Page : 22/46
		Revised edition no : 6.0
		Revision date : 2024-02-02
		Supersedes version of : 2023-01-19
Ammonia, anhydrous		NOAL_0002
		Country : SE / Language : EN

14.6. Special precautions for user

Packing Instruction(s)	
Transport by road/rail (ADR/RID)	: P200
Transport by air (ICAO-TI / IATA-DGR)	
Passenger and Cargo Aircraft	: Forbidden.
Cargo Aircraft only	: Forbidden.
Transport by sea (IMDG)	: P200
Special transport precautions	: Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers: - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture


EU-Regulations	
Restrictions on use	: None.
National legislation	: Ensure all national/local regulations are observed.
Seveso Directive : 2012/18/EU (Seveso III)	: Covered.
National regulations	
Ensure all national/local regulations are observed.	
Germany	
Water hazard class (WGK)	: WGK 2, Significantly hazardous to water (Classification according to AwSV)
National Rules and Recommendations	: [German regulations] BetriebssicherheitsV mit TRBSen insbesondere TRBS 3145 / TRGS 725 Ortsbewegliche Druckgasbehälter", TRBS 2141, BGR Regel 500 Teil 2.33: "Umgang mit Gasen", GefahrstoffV mit Technischen Regeln Gefährliche Stoffe TRGS insbesondere TRGS 407 "Tätigkeiten mit Gasen - Gefährdungsbeurteilung", TRGS 400, 500, 510, 900." BGR 104, TRBS 2152.
Netherlands	
SZW-lijst van kankerverwekkende stoffen	: The substance is not listed
SZW-lijst van mutagene stoffen	: The substance is not listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: The substance is not listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: The substance is not listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: The substance is not listed
Denmark	
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product

15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.

SECTION 16: Other information


Indication of changes	: Safety data sheet in accordance with commission regulation (EU) No 2020/878.
-----------------------	--

	SAFETY DATA SHEET	Page : 23/46
		Revised edition no : 6.0
		Revision date : 2024-02-02
		Supersedes version of : 2023-01-19
Ammonia, anhydrous		NOAL_0002
		Country : SE / Language : EN

Section	Changed item	Change	Comments
1.3	Company	Modified	Version 6.0. New address in Sweden. (This change only applies to the Swedish (SE) version of this SDS)

Abbreviations and acronyms	: ATE - Acute Toxicity Estimate CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006 EINECS - European Inventory of Existing Commercial Chemical Substances CAS# - Chemical Abstract Service number PPE - Personal Protection Equipment LC50 - Lethal Concentration to 50 % of a test population RMM - Risk Management Measures PBT - Persistent, Bioaccumulative and Toxic vPvB - Very Persistent and Very Bioaccumulative STOT- SE : Specific Target Organ Toxicity - Single Exposure CSA - Chemical Safety Assessment EN - European Standard UN - United Nations ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road IATA - International Air Transport Association IMDG code - International Maritime Dangerous Goods RID - Regulations concerning the International Carriage of Dangerous Goods by Rail WGK - Water Hazard Class STOT - RE : Specific Target Organ Toxicity - Repeated Exposure UFI : Unique Formula Identifier
Training advice	: Users of breathing apparatus must be trained. Ensure operators understand the flammability hazard. Ensure operators understand the toxicity hazard.
Further information	: Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP). Key literature references and sources of data are maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at http://www.Eiga.eu .

Full text of H- and EUH-statements	
Acute Tox. 3 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 3
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2
EUH071	Corrosive to the respiratory tract.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Gas 2	Flammable gases, Category 2
H221	Flammable gas.
H280	Contains gas under pressure; may explode if heated.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H331	Toxic if inhaled.
H400	Very toxic to aquatic life.
H411	Toxic to aquatic life with long lasting effects.


	SAFETY DATA SHEET	Page : 24/46
		Revised edition no : 6.0
		Revision date : 2024-02-02
		Supersedes version of : 2023-01-19
Ammonia, anhydrous		NOAL_0002
		Country : SE / Language : EN
Press. Gas (Liq.)	Gases under pressure : Liquefied gas	
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B	

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press.

Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

	SAFETY DATA SHEET	Page : 25/46
		Revised edition no : 6.0
		Revision date : 2024-02-02
		Supersedes version of : 2023-01-19
Ammonia, anhydrous		NOAL_0002
		Country : SE / Language : EN

Annex to the safety data sheet

This Annex documents the Exposure Scenarios (ESs) related to the identified uses of the registered substance. The ESs detail protective measures for workers and the environment in addition to those described in sections 7, 8, 11, 12 and 13 of the SDS that are required to ensure that the potential exposure to workers and the environment remains within acceptable levels for each of the identified uses.

Table of contents of the Annex

Identified Uses	Es N°	Short title	Page
Water treatment	EIGA002-1	Industrial uses, closed contained conditions	26
Formulation of mixtures in pressure receptacles	EIGA002-1	Industrial uses, closed contained conditions	26
Transfilling in pressure receptacles	EIGA002-1	Industrial uses, closed contained conditions	26
Metal treatment	EIGA002-1	Industrial uses, closed contained conditions	26
Electronic component manufacture	EIGA002-1	Industrial uses, closed contained conditions	26
Manufacture of pharmaceutical products	EIGA002-1	Industrial uses, closed contained conditions	26
Calibration of analysis equipment	EIGA002-1	Industrial uses, closed contained conditions	26
Feedstock in chemical processes	EIGA002-1	Industrial uses, closed contained conditions	26
Precursor for fertiliser/explosive manufacture	EIGA002-1	Industrial uses, closed contained conditions	26
Exhaust gas DeNOx applications	EIGA002-1	Industrial uses, closed contained conditions	26
Treatment of plastics	EIGA002-1	Industrial uses, closed contained conditions	26
Aluminium casting	EIGA002-1	Industrial uses, closed contained conditions	26
Treatment of textiles	EIGA002-1	Industrial uses, closed contained conditions	26
Waste recycling	EIGA002-1	Industrial uses, closed contained conditions	26
Refilling of refrigeration equipment	EIGA002-2	Professional uses	42
In photocopying machines	EIGA002-2	Professional uses	42
Reaction gas in mass spectrometry	EIGA002-2	Professional uses	42
Microfiche developing and duplication	EIGA002-2	Professional uses	42

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet

Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

1. EIGA002-1: Industrial uses, closed contained conditions

1.1. Title section

Industrial uses, closed contained conditions

ES Ref.: EIGA002-1

Revision date: 7/1/2016

Processes, tasks, activities covered

Industrial uses, including product transfers and associated laboratory activities within different closed or contained systems

Environment	Use descriptors
CS1	ERC1
CS2	ERC2
CS3	ERC4
CS4	ERC6a
CS5	ERC6b
CS6	ERC7

Worker	Use descriptors
CS7	PROC1
CS8	PROC2
CS9	PROC3
CS10	PROC4
CS11	PROC8b
CS12	PROC9

Assessment method

ECETOC TRA 2.0
EUSES

1.2. Conditions of use affecting exposure

1.2.1. Control of environmental exposure: ERC1

ERC1 Manufacture of the substance

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet
Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

Amount used, frequency and duration of use (or from service life)

Annual site tonnage:	950000 t/yr
Regional use tonnage:	6500000 t/yr
Emission Days (days/year)	330

Technical and organisational conditions and measures

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.	
Soil emission controls are not applicable as there is no direct release to soil	
Ensure operatives are trained to minimise releases	

Conditions and measures related to sewage treatment plant

Direct emissions to the municipal STP should not be made.	
---	--

Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS	
---------------------------	--

Other conditions affecting environmental exposure

Closed systems are used in order to prevent unintended emissions	
Flow rate of receiving water at least:	18000 m³/d
Dilution of STP emissions at least:	10

1.2.2. Control of environmental exposure: ERC2

ERC2	Formulation into mixture
------	--------------------------

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used, frequency and duration of use (or from service life)

Annual site tonnage:	1000000 t/yr
Regional use tonnage:	3800000 t/yr
Emission Days (days/year)	330

Technical and organisational conditions and measures

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.	
Soil emission controls are not applicable as there is no direct release to soil	

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet

Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

Ensure operatives are trained to minimise releases	
--	--

Conditions and measures related to sewage treatment plant

Direct emissions to the municipal STP should not be made.	
---	--

Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS	
---------------------------	--

Other conditions affecting environmental exposure

Closed systems are used in order to prevent unintended emissions	
Flow rate of receiving water at least:	18000 m ³ /d
Dilution of STP emissions at least:	10

1.2.3. Control of environmental exposure: ERC4

ERC4	Use of non-reactive processing aid at industrial site (no inclusion into or onto article)
------	---

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used, frequency and duration of use (or from service life)

Annual site tonnage:	25000 t/yr
Regional use tonnage:	354000 t/yr
Emission Days (days/year)	330

Technical and organisational conditions and measures

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.	
Soil emission controls are not applicable as there is no direct release to soil	
Ensure operatives are trained to minimise releases	

Conditions and measures related to sewage treatment plant

Direct emissions to the municipal STP should not be made.	
---	--

Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS	
---------------------------	--

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet

Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

Other conditions affecting environmental exposure

Closed systems are used in order to prevent unintended emissions	
Flow rate of receiving water at least:	18000 m³/d
Dilution of STP emissions at least:	10

1.2.4. Control of environmental exposure: ERC6a

ERC6a	Use of intermediate
-------	---------------------

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used, frequency and duration of use (or from service life)

Annual site tonnage:	800000 t/yr
Regional use tonnage:	3800000 t/yr
Emission Days (days/year)	330

Technical and organisational conditions and measures

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.	
Soil emission controls are not applicable as there is no direct release to soil	
Ensure operatives are trained to minimise releases	

Conditions and measures related to sewage treatment plant

Direct emissions to the municipal STP should not be made.	
---	--

Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS	
---------------------------	--

Other conditions affecting environmental exposure

Closed systems are used in order to prevent unintended emissions	
Flow rate of receiving water at least:	18000 m³/d
Dilution of STP emissions at least:	10

1.2.5. Control of environmental exposure: ERC6b

ERC6b	Use of reactive processing aid at industrial site (no inclusion into or onto article)
-------	---

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet
Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used, frequency and duration of use (or from service life)	
Annual site tonnage:	25000 t/yr
Regional use tonnage:	354000 t/yr
Emission Days (days/year)	330

Technical and organisational conditions and measures	
Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.	
Soil emission controls are not applicable as there is no direct release to soil	
Ensure operatives are trained to minimise releases	

Conditions and measures related to sewage treatment plant	
Direct emissions to the municipal STP should not be made.	

Conditions and measures related to treatment of waste (including article waste)	
See section 13 of the SDS	

Other conditions affecting environmental exposure	
Closed systems are used in order to prevent unintended emissions	
Flow rate of receiving water at least:	18000 m³/d
Dilution of STP emissions at least:	10

1.2.6. Control of environmental exposure: ERC7

ERC7	Use of functional fluid at industrial site
------	--

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used, frequency and duration of use (or from service life)	
Annual site tonnage:	25000 t/yr
Regional use tonnage:	354000 t/yr
Emission Days (days/year)	330

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet

Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

Technical and organisational conditions and measures

Use appropriate abatement systems to ensure that the emission levels defined by local regulations are not exceeded.

Soil emission controls are not applicable as there is no direct release to soil

Ensure operatives are trained to minimise releases

Conditions and measures related to sewage treatment plant

Direct emissions to the municipal STP should not be made.

Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS

Other conditions affecting environmental exposure

Closed systems are used in order to prevent unintended emissions

Flow rate of receiving water at least: 18000 m³/d

Dilution of STP emissions at least: 10

1.2.7. Control of worker exposure: PROC1

PROC1

Chemical production or refinery in closed process without likelihood of exposure or processes with equivalent containment conditions

Product (article) characteristics

Physical form of product See section 9 of the SDS, No additional information

Concentration of substance in product ≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.

Exposure duration ≤ 8 h/day

Covers frequency up to: 5 days/week

Technical and organisational conditions and measures

Handle product within a closed system

Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

Ensure operatives are trained to minimise exposure

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet

Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

See section 8 of the SDS.

Other conditions affecting workers exposure

Indoor or outdoor use

1.2.8. Control of worker exposure: PROC2

PROC2

Chemical production or refinery in closed continuous process with occasional controlled exposure or processes with equivalent containment conditions

Product (article) characteristics

Physical form of product

See section 9 of the SDS, No additional information

Concentration of substance in product

≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.

Exposure duration

≤ 8 h/day

Covers frequency up to:

5 days/week

Technical and organisational conditions and measures

Handle product within a closed system

During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.

Ensure samples are obtained under containment or extract ventilation.

Drain down and flush system prior to equipment break-in or maintenance.

Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

Ensure operatives are trained to minimise exposure

Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin

Personal protection measures have to be applied in case of potential exposure only.

Wear gloves providing a minimum efficiency of (%):

90

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet
Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

Wear a respirator providing a minimum efficiency of (%):	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

Other conditions affecting workers exposure

Indoor or outdoor use	
-----------------------	--

1.2.9. Control of worker exposure: PROC3

PROC3	Manufacture or formulation in the chemical industry in closed batch processes with occasional controlled exposure or processes with equivalent containment condition
-------	--

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures

Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Ensure samples are obtained under containment or extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin	Personal protection measures have to be applied in case of potential exposure only.
Wear gloves providing a minimum efficiency of (%):	90

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet
Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

Wear a respirator providing a minimum efficiency of (%):	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

Other conditions affecting workers exposure	
Indoor or outdoor use	

1.2.10. Control of worker exposure: PROC4

PROC4	Chemical production where opportunity for exposure arises
-------	---

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure	
The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures	
Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Ensure samples are obtained under containment or extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation	
Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin	Personal protection measures have to be applied in case of potential exposure only.
Wear gloves providing a minimum efficiency of (%):	90

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet

Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

Wear a respirator providing a minimum efficiency of (%):	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

Other conditions affecting workers exposure	
Indoor or outdoor use	

1.2.11. Control of worker exposure: PROC8b

PROC8b	Transfer of substance or mixture (charging and discharging) at dedicated facilities
--------	---

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure	
The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures	
Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Fill containers at dedicated fill points supplied with local extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation	
Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin	Personal protection measures have to be applied in case of potential exposure only.
Wear gloves providing a minimum efficiency of (%):	90

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet
Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

Wear a respirator providing a minimum efficiency of (%):	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

Other conditions affecting workers exposure

Indoor or outdoor use	
-----------------------	--

1.2.12. Control of worker exposure: PROC9

PROC9	Transfer of substance or preparation into small containers (dedicated filling line, including weighing)
-------	---

Product (article) characteristics

Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures

Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Fill containers at dedicated fill points supplied with local extract ventilation.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin	Personal protection measures have to be applied in case of potential exposure only.
Wear gloves providing a minimum efficiency of (%):	90

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet

Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

Wear a respirator providing a minimum efficiency of (%):	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

Other conditions affecting workers exposure	
Indoor or outdoor use	

1.3. Exposure estimation and reference to its source

1.3.1. Environmental release and exposure: ERC1

Assessment method	EUSES
-------------------	-------

Protection target	Unit	Exposure estimation	PNEC	RCR	Assessment conditions
Freshwater	mg/l	0.000133	0.0011	0.121	
Marine water	mg/l	0.0000315	0.0011	0.029	

1.3.2. Environmental release and exposure: ERC2

Assessment method	EUSES
-------------------	-------

Protection target	Unit	Exposure estimation	PNEC	RCR	Assessment conditions
Freshwater	mg/l	0.0000497	0.0011	0.045	
Marine water	mg/l	0.000012	0.0011	0.011	

1.3.3. Environmental release and exposure: ERC4

Protection target	Unit	Exposure estimation	PNEC	RCR	Assessment conditions
Freshwater	mg/l	0.0000108	0.0011	0.01	
Marine water	mg/l	0.0000231	0.0011	0.021	

1.3.4. Environmental release and exposure: ERC6a

Assessment method	EUSES
-------------------	-------

Protection target	Unit	Exposure estimation	PNEC	RCR	Assessment conditions
Freshwater	mg/l	0.0000837	0.0011	0.076	
Marine water	mg/l	0.0000205	0.0011	0.019	

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet
Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

1.3.5. Environmental release and exposure: ERC6b

Protection target	Unit	Exposure estimation	PNEC	RCR	Assessment conditions
Freshwater	mg/l	0.00000173	0.0011	0.002	
Marine water	mg/l	0.00000019	0.0011	≈ 0.00018	

1.3.6. Environmental release and exposure: ERC7

Protection target	Unit	Exposure estimation	PNEC	RCR	Assessment conditions
Freshwater	mg/l	0.00000558	0.0011	0.005	
Marine water	mg/l	0.00000121	0.0011	0.001	

1.3.7. Worker exposure: PROC1

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects	0.34 mg/kg bodyweight/day	Outdoor use, Indoor use, Without LEV, No gloves worn	0.05
Inhalation - Long-term - systemic effects	0 mg/m ³	Outdoor use, Indoor use, Without LEV	< 0.01
Dermal - Acute - systemic effects	0.34 mg/kg bodyweight/day	Outdoor use, Indoor use, Without LEV, No gloves worn	0.05
Inhalation - Acute - systemic effects	0 mg/m ³	Outdoor use, Indoor use, Without LEV	< 0.01
Acute - Local - Inhalation	0 mg/m ³	Outdoor use, Indoor use, Without LEV	< 0.01
Long term - Local - Inhalation	0 mg/m ³	Outdoor use, Indoor use, Without LEV	< 0.01

1.3.8. Worker exposure: PROC2

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects	1.37 mg/kg bodyweight/day	Outdoor use, Indoor use, Without LEV, No gloves worn	0.201
	0.14 mg/kg bodyweight/day	Indoor use, With LEV, No gloves worn	0.021
Inhalation - Long-term - systemic effects	1.24 mg/m ³	Outdoor use, With RPE95%	0.026
	3.54 mg/m ³	Indoor use, With LEV, No RPE	0.074
Dermal - Acute - systemic effects	1.37 mg/kg bodyweight/day	Outdoor use, Indoor use, Without LEV, No gloves worn	0.201
	0.14 mg/kg bodyweight/day	Indoor use, With LEV, No gloves worn	0.021
Inhalation - Acute - systemic effects	1.24 mg/m ³	Outdoor use, With RPE95%	0.026
	3.54 mg/m ³	Indoor use, With LEV, No RPE	0.074
Acute - Local - Inhalation	1.24 mg/m ³	Outdoor use, With RPE95%	0.034

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet

Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

	3.54 mg/m ³	Indoor use, With LEV, No RPE	0.098
Long term - Local - Inhalation	1.24 mg/m ³	Outdoor use, With RPE95%	0.089
	3.54 mg/m ³	Indoor use, With LEV, No RPE	0.253

1.3.9. Worker exposure: PROC3

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects	0.34 mg/kg bodyweight/day	Outdoor use, Indoor use, Without LEV, No gloves worn	0.05
	0.03 mg/kg bodyweight/day	Indoor use, With LEV, No gloves worn	0.004
Inhalation - Long-term - systemic effects	2.48 mg/m ³	Outdoor use, With RPE95%	0.052
	7.08 mg/m ³	Indoor use, With LEV, No RPE	0.149
Dermal - Acute - systemic effects	0.34 mg/kg bodyweight/day	Outdoor use, Indoor use, Without LEV, No gloves worn	0.05
	0.03 mg/kg bodyweight/day	Indoor use, With LEV, No gloves worn	0.004
Inhalation - Acute - systemic effects	2.48 mg/m ³	Outdoor use, With RPE95%	0.052
	7.08 mg/m ³	Indoor use, With LEV, No RPE	0.149
Acute - Local - Inhalation	2.48 mg/m ³	Outdoor use, With RPE95%	0.069
	7.08 mg/m ³	Indoor use, With LEV, No RPE	0.197
Long term - Local - Inhalation	2.48 mg/m ³	Outdoor use, With RPE95%	0.177
	7.08 mg/m ³	Indoor use, With LEV, No RPE	0.506

1.3.10. Worker exposure: PROC4

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects	0.69 mg/kg bodyweight/day	Outdoor use, Indoor use, Without LEV, Gloves worn (90% Reduction)	0.101
	0.69 mg/kg bodyweight/day	Indoor use, With LEV, No gloves worn	0.101
Inhalation - Long-term - systemic effects	2.48 mg/m ³	Outdoor use, With RPE95%	0.052
	7.08 mg/m ³	Indoor use, With LEV, No RPE	0.149
Dermal - Acute - systemic effects	0.69 mg/kg bodyweight/day	Outdoor use, Indoor use, Without LEV, Gloves worn (90% Reduction)	0.101
	0.69 mg/kg bodyweight/day	Indoor use, With LEV, No gloves worn	0.101
Inhalation - Acute - systemic effects	2.48 mg/m ³	Outdoor use, With RPE95%	0.052
	7.08 mg/m ³	Indoor use, With LEV, No RPE	0.149
Acute - Local - Inhalation	2.48 mg/m ³	Outdoor use, With RPE95%	0.069
	7.08 mg/m ³	Indoor use, With LEV, No RPE	0.197

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet

Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

Long term - Local - Inhalation	2.48 mg/m ³	Outdoor use, With RPE95%	0.177
	7.08 mg/m ³	Indoor use, With LEV, No RPE	0.506

1.3.11. Worker exposure: PROC8b

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects	0.69 mg/kg bodyweight/day	Outdoor use, Indoor use, Without LEV, Gloves worn (90% Reduction)	0.101
	0.69 mg/kg bodyweight/day	Indoor use, With LEV, No gloves worn	0.101
Inhalation - Long-term - systemic effects	3.72 mg/m ³	Outdoor use, With RPE95%	0.078
	3.19 mg/m ³	Indoor use, With LEV, No RPE	0.067
Dermal - Acute - systemic effects	0.69 mg/kg bodyweight/day	Outdoor use, Indoor use, Without LEV, Gloves worn (90% Reduction)	0.101
	0.69 mg/kg bodyweight/day	Indoor use, With LEV, No gloves worn	0.101
Inhalation - Acute - systemic effects	3.72 mg/m ³	Outdoor use, With RPE95%	0.078
	3.19 mg/m ³	Indoor use, With LEV, No RPE	0.067
Acute - Local - Inhalation	3.72 mg/m ³	Outdoor use, With RPE95%	0.103
	3.19 mg/m ³	Indoor use, With LEV, No RPE	0.089
Long term - Local - Inhalation	3.72 mg/m ³	Outdoor use, With RPE95%	0.266
	3.19 mg/m ³	Indoor use, With LEV, No RPE	0.228

1.3.12. Worker exposure: PROC9

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects	0.69 mg/kg bodyweight/day	Outdoor use, Indoor use, Without LEV, Gloves worn (90% Reduction)	0.101
	0.69 mg/kg bodyweight/day	Indoor use, With LEV, No RPE	0.101
Inhalation - Long-term - systemic effects	4.96 mg/m ³	Outdoor use, With RPE95%	0.104
	0.71 mg/m ³	Indoor use, With LEV, With RPE	0.015
Dermal - Acute - systemic effects	0.69 mg/kg bodyweight/day	Outdoor use, Indoor use, Without LEV, Gloves worn (90% Reduction)	0.101
	0.69 mg/kg bodyweight/day	Indoor use, With LEV, No RPE	0.101
Inhalation - Acute - systemic effects	4.96 mg/m ³	Outdoor use, With RPE95%	0.104
	0.71 mg/m ³	Indoor use, With LEV, With RPE	0.015
Acute - Local - Inhalation	4.96 mg/m ³	Outdoor use, With RPE95%	0.138
	0.71 mg/m ³	Indoor use, With LEV, With RPE	0.02
Long term - Local - Inhalation	4.96 mg/m ³	Outdoor use, With RPE95%	0.354

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet

Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

	0.71 mg/m ³	Indoor use, With LEV, With RPE	0.051
--	------------------------	--------------------------------	-------

1.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

1.4.1. Environment

Guidance - Environment	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see :
------------------------	--

1.4.2. Health

Guidance - Health	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see :
-------------------	--

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet

Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

2. EIGA002-2: Professional uses

2.1. Title section

Professional uses

ES Ref.: EIGA002-2

Revision date: 7/1/2016

Processes, tasks, activities covered

Professional uses, including transfer of product in non-industrial settings

Environment

Use descriptors

CS1

ERC9a, ERC9b

Worker

Use descriptors

CS2

PROC4

CS3

PROC8a

Assessment method

ECETOC TRA 2.0

2.2. Conditions of use affecting exposure

2.2.1. Control of environmental exposure: ERC9a, ERC9b

ERC9a

Widespread use of functional fluid (indoor)

ERC9b

Widespread use of functional fluid (outdoor)

Product (article) characteristics

Physical form of product

See section 9 of the SDS, No additional information

Concentration of substance in product

≤ 100 %

Amount used, frequency and duration of use (or from service life)

No additional information

Technical and organisational conditions and measures

Ensure operatives are trained to minimise exposure

Conditions and measures related to sewage treatment plant

No additional information

Conditions and measures related to treatment of waste (including article waste)

See section 13 of the SDS

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet

Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

Other conditions affecting environmental exposure

Closed systems are used in order to prevent unintended emissions

2.2.2. Control of worker exposure: PROC4

PROC4

Chemical production where opportunity for exposure arises

Product (article) characteristics

Physical form of product

See section 9 of the SDS, No additional information

Concentration of substance in product

≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure

The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.

Exposure duration

≤ 8 h/day

Covers frequency up to:

5 days/week

Technical and organisational conditions and measures

Handle product within a closed system

During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.

Drain down and flush system prior to equipment break-in or maintenance.

Apply a good standard of general or controlled ventilation when maintenance activities are carried out.

Ensure operatives are trained to minimise exposure

Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed

Conditions and measures related to personal protection, hygiene and health evaluation

Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin

Personal protection measures have to be applied in case of potential exposure only.

Wear gloves providing a minimum efficiency of (%):

90

Wear a respirator providing a minimum efficiency of

95

Mandatory if activities take place outdoors or indoors with no local exhaust ventilation

See section 8 of the SDS.

Other conditions affecting workers exposure

Indoor or outdoor use

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet

Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

2.2.3. Control of worker exposure: PROC8a

PROC8a	Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
--------	---

Product (article) characteristics	
Physical form of product	See section 9 of the SDS, No additional information
Concentration of substance in product	≤ 100 %

Amount used (or contained in articles), frequency and duration of use/exposure	
The actual tonnage handled per shift is not considered to influence the exposure as such for this scenario. Instead, the combination of the scale of operation and level of containment/automation (as reflected in the technical conditions) is the main determinant of the process-intrinsic emission potential.	
Exposure duration	≤ 8 h/day
Covers frequency up to:	5 days/week

Technical and organisational conditions and measures	
Handle product within a closed system	
During indoor processes or in cases where natural ventilation is not sufficient, LEV should be in place at points where emissions could occur. Outdoor, LEV is not generally required.	
Drain down and flush system prior to equipment break-in or maintenance.	
Apply a good standard of general or controlled ventilation when maintenance activities are carried out.	
Ensure operatives are trained to minimise exposure	
Ensure supervision is in place to check that the RMMs are in place and are being used correctly and that the OCs are being followed	

Conditions and measures related to personal protection, hygiene and health evaluation	
Use suitable eye protection. Wear suitable face shield. Wear suitable coveralls to prevent exposure to the skin	Personal protection measures have to be applied in case of potential exposure only.
Wear gloves providing a minimum efficiency of (%):	90
Wear a respirator providing a minimum efficiency of	95 Mandatory if activities take place outdoors or indoors with no local exhaust ventilation
See section 8 of the SDS.	

Other conditions affecting workers exposure	
Indoor or outdoor use	

2.3. Exposure estimation and reference to its source

2.3.1. Environmental release and exposure: ERC9a, ERC9b

Qualitative approach used to conclude safe use, The exposure of aquatic, terrestrial, sediment and sewage treatment microorganisms is considered to be negligible because the substance partitions primarily to air when released to the environment, The resulting environmental exposure is not expected to add significantly to already present background levels of the gas in the environment, An additional assessment for environmental exposure for wide dispersive uses has therefore not been presented in section 3.

2.3.2. Worker exposure: PROC4

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects	0.69 mg/kg bodyweight/day	Indoor use, With LEV, No gloves worn	0.101
	0.69 mg/kg bodyweight/day	Outdoor use, Indoor use, Without LEV, Gloves worn (90% Reduction)	0.101
Inhalation - Long-term - systemic effects	2.48 mg/m ³	Outdoor use, With RPE95%	0.052
	7.08 mg/m ³	Indoor use, With LEV, No RPE	0.149
Dermal - Acute - systemic effects	0.69 mg/kg bodyweight/day	Indoor use, With LEV, No gloves worn	0.101
	0.69 mg/kg bodyweight/day	Outdoor use, Indoor use, Without LEV, Gloves worn (90% Reduction)	0.101
Inhalation - Acute - systemic effects	2.48 mg/m ³	Outdoor use, With RPE95%	0.052
	7.08 mg/m ³	Indoor use, With LEV, No RPE	0.149
Acute - Local - Inhalation	2.48 mg/m ³	Outdoor use, With RPE95%	0.069
	7.08 mg/m ³	Indoor use, With LEV, No RPE	0.197
Long term - Local - Inhalation	2.48 mg/m ³	Outdoor use, With RPE95%	0.177
	7.08 mg/m ³	Indoor use, With LEV, No RPE	0.506

2.3.3. Worker exposure: PROC8a

Route of exposure and type of effects	Exposure estimate	Assessment conditions	RCR
Dermal - Long-term - systemic effects	0.14 mg/kg bodyweight/day	Indoor use, With LEV, No gloves worn	0.021
	1.37 mg/kg bodyweight/day	Outdoor use, Indoor use, Without LEV, Gloves worn (90% Reduction)	0.201
Inhalation - Long-term - systemic effects	6.2 mg/m ³	Outdoor use, With RPE95%	0.13
	0.89 mg/m ³	Indoor use, With LEV, No RPE	0.019
Dermal - Acute - systemic effects	0.14 mg/kg bodyweight/day	Indoor use, With LEV, No gloves worn	0.021
	1.37 mg/kg bodyweight/day	Outdoor use, Indoor use, Without LEV, Gloves worn (90% Reduction)	0.201

Exposure scenario

Ammonia, anhydrous

Annex to the safety data sheet

Reference number: NOAL_0002

CAS-No.: 7664-41-7 Product form: Substance Physical state: Gas

Inhalation - Acute - systemic effects	6.2 mg/m ³	Outdoor use, With RPE95%	0.13
	0.89 mg/m ³	Indoor use, With LEV, No RPE	0.019
Acute - Local - Inhalation	6.2 mg/m ³	Outdoor use, With RPE95%	0.172
	0.89 mg/m ³	Indoor use, With LEV, No RPE	0.025
Long term - Local - Inhalation	6.2 mg/m ³	Outdoor use, With RPE95%	0.443
	0.89 mg/m ³	Indoor use, With LEV, No RPE	0.064

2.4. Guidance to Downstream User to evaluate whether he works inside the boundaries set by the ES

2.4.1. Environment

Guidance - Environment	Check that RMMs and OCs are as described above or of equivalent efficiency
------------------------	--

2.4.2. Health

Guidance - Health	Guidance is based on assumed operating conditions which may not be applicable to all sites; thus, scaling may be necessary to define appropriate site-specific risk management measures. For scaling see : http://www.ecetoc.org/tra
-------------------	--

End of document