



SAFETY DATA SHEET

Page : 1/20

Revised edition no : 6.0

Revision date : 2024-02-02

Supersedes version of : 2023-01-19

Carbon dioxide (refrigerated)

NOAL_0018B

Country : SE / Language : EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name : Carbon dioxide (refrigerated), Aligal 2 liquide, Aligal 2 LGC, Aligal Drink 2 liquide, Aligal freeze 2 liquide, Phargalis 2 liquide

SDS no : NOAL_0018B

Other means of identification : Carbon dioxide (refrigerated)

CAS-No. : 124-38-9

EC-No. : 204-696-9

EC Index-No. : ---

REACH registration No : Listed in Annex IV / V REACH, exempted from registration.

Chemical formula : CO₂

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use.

Test gas/Calibration gas.

Laboratory use.

Purge gas, diluting gas, inerting gas.

Purging.

Use for manufacture of electronic/photovoltaic components.

Shield gas for welding processes.

Food applications.

Contact supplier for more information on uses.

Uses advised against : Consumer use.

Uses other than those listed above are not supported, contact your supplier for more information on other uses.

1.3. Details of the supplier of the safety data sheet

Company identification

Supplier

AIR LIQUIDE GAS AB
Pulpetgatan 20
215 37 Malmö - SWEDEN
T +46 40 38 10 00
info.sweden@airliquide.com


E-Mail address (competent person) : eunordic-sds@airliquide.com

1.4. Emergency telephone number

Emergency telephone number : 112

Availability
(24 / 7)

| Country | Organisation/Company | Address | Emergency number | Comment |
|---------|--|--------------------------------------|---------------------|---------|
| Germany | Giftnotruf Erfurt Gemeinsames Giftinformationszentrum der Länder Mecklenburg-Vorpommern, Sachsen, Sachsen-Anhalt und Thüringen, c/o HELIOS Klinikum Erfurt | Nordhäuser Straße 74 99089 Erfurt | +49 (0) 361 730 730 | |

| | | |
|---|-------------------|------------------------------------|
|  | SAFETY DATA SHEET | Page : 2/20 |
| | | Revised edition no : 6.0 |
| | | Revision date : 2024-02-02 |
| | | Supersedes version of : 2023-01-19 |
| Carbon dioxide (refrigerated) | | NOAL_0018B |
| | | Country : SE / Language : EN |

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards Gases under pressure : Refrigerated liquefied gas H281

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS04

Signal word (CLP) :

Warning

Hazard statements (CLP) :

H281 - Contains refrigerated gas; may cause cryogenic burns or injury.

Precautionary statements (CLP)

- Prevention

: P282 - Wear cold insulating gloves and either face shield or eye protection. cold insulating gloves, face shield, eye protection.

P282 - Wear cold insulating gloves and either face shield or eye protection.

- Response

: P336+P315 - Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice.

P336+P315 - Thaw frosted parts with lukewarm water. Do not rub affected area. Get immediate medical advice/attention.

- Storage

: P403 - Store in a well-ventilated place.

2.3. Other hazards

Asphyxiant in high concentrations.

In high concentrations CO₂ causes rapid circulatory insufficiency even at normal levels of oxygen concentration. Symptoms are headache, nausea and vomiting, which may lead to unconsciousness and death.

Not classified as PBT or vPvB.

The substance/mixture has no endocrine disrupting properties.

SECTION 3: Composition/information on ingredients


3.1. Substances

| Name | Product identifier | Composition [V-%]: | Classification according to Regulation (EC) No. 1272/2008 [CLP] |
|-------------------------------|--|--------------------|---|
| Carbon dioxide (refrigerated) | CAS-No.: 124-38-9 EC-No.: 204-696-9 EC Index-No.: --- REACH registration No: *1 | 100 | Press. Gas (Ref. Liq.), H281 |

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*3: Registration not required: Substance manufactured or imported < 1t/y.

| | | |
|---|-------------------|------------------------------------|
|  | SAFETY DATA SHEET | Page : 3/20 |
| | | Revised edition no : 6.0 |
| | | Revision date : 2024-02-02 |
| | | Supersedes version of : 2023-01-19 |
| Carbon dioxide (refrigerated) | | NOAL_0018B |
| | | Country : SE / Language : EN |

3.2. Mixtures Not established.

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation.
Low concentrations of CO2 cause increased respiration and headache.
See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

None.

SECTION 5: Firefighting measures

5.1. Extinguishing media


- Suitable extinguishing media : Water spray or fog.
Product does not burn, use fire control measures appropriate for the surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : None.

5.3. Advice for firefighters

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
If possible, stop flow of product.
Use water spray or fog to knock down fire fumes if possible.
If leaking do not spray water onto container. Water surrounding area (from protected position) to contain fire.
Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters : In confined space use self-contained breathing apparatus.
Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Standard EN 469 - Protective clothing for firefighters. Standard - EN 659: Protective gloves for firefighters.


| | | |
|---|--------------------------|------------------------------------|
|  | SAFETY DATA SHEET | Page : 4/20 |
| | | Revised edition no : 6.0 |
| | | Revision date : 2024-02-02 |
| | | Supersedes version of : 2023-01-19 |
| Carbon dioxide (refrigerated) | NOAL_0018B | |
| | | Country : SE / Language : EN |

SECTION 6: Accidental release measures

| | | |
|---|---|--|
| 6.1. Personal precautions, protective equipment and emergency procedures | | |
| For non-emergency personnel | : | Act in accordance with local emergency plan. Try to stop release. Evacuate area. Ensure adequate air ventilation. Use protective clothing. Stay upwind. See section 8 of the SDS for more information on personal protective equipment |
| For emergency responders | : | Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe. Oxygen detectors should be used when asphyxiating gases may be released. See section 5.3 of the SDS for more information. |
| 6.2. Environmental precautions | | |
| | | Try to stop release. Liquid spillages can cause embrittlement of structural materials. |
| 6.3. Methods and material for containment and cleaning up | | |
| | | Ventilate area. |
| 6.4. Reference to other sections | | |
| | | See also sections 8 and 13. |

SECTION 7: Handling and storage

| | | |
|---|---|---|
| 7.1. Precautions for safe handling | | |
| Safe use of the product | : | Do not breathe gas. Avoid release of product into atmosphere. Containers, which contain or have contained flammable or explosive substances, must not be inerted with liquid carbon dioxide. Potential production of solid CO2 particles must be ruled out. In order to rule out potential electrostatic discharge production, the system must be adequately grounded. The product must be handled in accordance with good industrial hygiene and safety procedures. Only experienced and properly instructed persons should handle gases under pressure. Consider pressure relief device(s) in gas installations. Ensure the complete gas system was (or is regularly) checked for leaks before use. Do not smoke while handling product. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt. Avoid suck back of water, acid and alkalis. |

| | | |
|---|-------------------|------------------------------------|
|  | SAFETY DATA SHEET | Page : 5/20 |
| | | Revised edition no : 6.0 |
| | | Revision date : 2024-02-02 |
| | | Supersedes version of : 2023-01-19 |
| Carbon dioxide (refrigerated) | | NOAL_0018B |
| | | Country : SE / Language : EN |

| | |
|-------------------------------------|--|
| Safe handling of the gas receptacle | : Refer to supplier's container handling instructions. Do not allow backfeed into the container. Protect containers from physical damage; do not drag, roll, slide or drop. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use. If user experiences any difficulty operating valve discontinue use and contact supplier. Never attempt to repair or modify container valves or safety relief devices. Damaged valves should be reported immediately to the supplier. Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment. Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another. Never use direct flame or electrical heating devices to raise the pressure of a container. Do not remove or deface labels provided by the supplier for the identification of the content of the container. Suck back of water into the container must be prevented. Open valve slowly to avoid pressure shock. |
|-------------------------------------|--|

7.2. Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers.
Containers should not be stored in conditions likely to encourage corrosion.
Container valve guards or caps should be in place.
Containers should be stored in the vertical position and properly secured to prevent them from falling over.
Stored containers should be periodically checked for general condition and leakage.
Keep container below 50°C in a well ventilated place.
Store containers in location free from fire risk and away from sources of heat and ignition.
Keep away from combustible materials.


7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

| | |
|---|-------------------|
| Carbon dioxide (refrigerated) (124-38-9) | |
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| Local name | Carbon dioxide |
| IOEL TWA | 9000 mg/m³ |
| IOEL TWA [ppm] | 5000 ppm |
| Austria - Occupational Exposure Limits | |
| Local name | Kohlenstoffdioxid |
| MAK (mg/m³) | 9000 mg/m³ |
| MAK (OEL TWA) [ppm] | 5000 ppm |
| MAK (OEL STEL) | 18000 mg/m³ |
| MAK (OEL STEL) [ppm] | 10000 ppm |

| | | |
|---|------------------------------|------------------------------------|
|  | SAFETY DATA SHEET | Page : 6/20 |
| | | Revised edition no : 6.0 |
| | | Revision date : 2024-02-02 |
| | | Supersedes version of : 2023-01-19 |
| Carbon dioxide (refrigerated) | NOAL_0018B | |
| | Country : SE / Language : EN | |

Belgium - Occupational Exposure Limits

| | |
|----------------|--|
| Local name | Carbone (dioxyde de) # Koolstofdioxide |
| OEL TWA | 9131 mg/m³ |
| OEL TWA [ppm] | 5000 ppm |
| OEL STEL | 54784 mg/m³ |
| OEL STEL [ppm] | 30000 ppm |
| Remark | A: La mention A signifie que l'agent libère un gaz ou une vapeur qui n'ont en eux-mêmes aucun effet physiologique mais peuvent diminuer le taux d'oxygène dans l'air. Lorsque le taux d'oxygène descend en dessous de 17-18 % (vol/vol) le manque d'oxygène provoque des suffocations qu'aucun symptôme préalable n'annonce. # De vermelding A betekent dat dit agens gas of damp vrijgeeft dat of die op zich geen fysiologische werking heeft, maar het zuurstofgehalte in de lucht verlaagt. Wanneer het zuurstofgehalte daalt onder de 17-18 % (vol/vol), veroorzaakt het zuurstoftekort verstikking, die zich manifesteert zonder dat er een waarschuwing aan voorafgaat. |

Bulgaria - Occupational Exposure Limits

| | |
|---------------|--|
| Local name | Въглероден диоксид |
| OEL TWA | 9000 mg/m³ |
| OEL TWA [ppm] | 5000 ppm |
| Remark | • (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност) |

Croatia - Occupational Exposure Limits

| | |
|-------------------|------------------|
| Local name | Ugljikov dioksid |
| GVI (OEL TWA) [1] | 9000 mg/m³ |
| GVI (OEL TWA) [2] | 5000 ppm |
| Remark | EU** |

Czech Republic - Occupational Exposure Limits


| | |
|---------------------|---------------|
| Local name | Oxid uhli itý |
| PEL (OEL TWA) | 9000 mg/m³ |
| PEL (OEL TWA) [ppm] | 5000 ppm |
| NPK-P (OEL C) | 45000 mg/m³ |
| NPK-P (OEL C) [ppm] | 25020 ppm |


Denmark - Occupational Exposure Limits


| | |
|-------------|-----------------------------------|
| Local name | Carbondioxid (Kuldioxid; Kulsyre) |
| OEL TWA [1] | 9000 mg/m³ |
| OEL TWA [2] | 5000 ppm |


Estonia - Occupational Exposure Limits

| | |
|------------|-----------------|
| Local name | Süsinikdioksiid |
| OEL TWA | 9000 mg/m³ |

| | | | |
|---|--------------------------|------------------------------------|------------------------------------|
|  | SAFETY DATA SHEET | | Page : 7/20 |
| | | | Revised edition no : 6.0 |
| | | | Revision date : 2024-02-02 |
| | | | Supersedes version of : 2023-01-19 |
| Carbon dioxide (refrigerated) | | | NOAL_0018B |
| | | | Country : SE / Language : EN |
| OEL TWA [ppm] | | 5000 ppm | |
| Finland - Occupational Exposure Limits | | | |
| Local name | | Hiilidioksidi | |
| HTP (OEL TWA) [1] | | 9100 mg/m³ | |
| HTP (OEL TWA) [2] | | 5000 ppm | |
| France - Occupational Exposure Limits | | | |
| Local name | | Dioxyde de carbone | |
| VME (OEL TWA) | | 9000 mg/m³ | |
| VME (OEL TWA) [ppm] | | 5000 ppm | |
| Remark | | Valeurs réglementaires indicatives | |
| Germany - Occupational Exposure Limits (TRGS 900) | | | |
| Local name | | Kohlenstoffdioxid | |
| AGW (OEL TWA) [1] | | 9100 mg/m³ | |
| AGW (OEL TWA) [2] | | 5000 ppm | |
| Remark | | DFG,EU | |
| Greece - Occupational Exposure Limits | | | |
| OEL TWA | | 9000 mg/m³ | |
| OEL TWA [ppm] | | 5000 ppm | |
| OEL STEL | | 54000 mg/m³ | |
| Hungary - Occupational Exposure Limits | | | |
| Local name | | SZÉN-DIOXID | |
| AK (OEL TWA) | | 9000 mg/m³ | |
| Ireland - Occupational Exposure Limits | | | |
| Local name | | Carbon dioxide | |
| OEL TWA [1] | | 9000 mg/m³ | |
| OEL TWA [2] | | 5000 ppm | |
| OEL STEL | | 27000 mg/m³ | |
| OEL STEL [ppm] | | 15000 ppm | |
| Italy - Occupational Exposure Limits | | | |
| Local name | | Anidride carbonica | |
| OEL TWA | | 9000 mg/m³ | |
| OEL TWA [ppm] | | 5000 ppm | |
| Latvia - Occupational Exposure Limits | | | |
| Local name | | Oglekļadioksīds | |
| OEL TWA | | 9000 mg/m³ | |


| | | | |
|---|-------------------|--------------------|------------------------------------|
|  | SAFETY DATA SHEET | | Page : 8/20 |
| | | | Revised edition no : 6.0 |
| | | | Revision date : 2024-02-02 |
| | | | Supersedes version of : 2023-01-19 |
| Carbon dioxide (refrigerated) | | | NOAL_0018B |
| | | | Country : SE / Language : EN |
| OEL TWA [ppm] | | 5000 ppm | |
| Lithuania - Occupational Exposure Limits | | | |
| Local name | | Anglies dioksidas | |
| IPRV (OEL TWA) | | 9000 mg/m³ | |
| IPRV (OEL TWA) [ppm] | | 5000 ppm | |
| Luxembourg - Occupational Exposure Limits | | | |
| Local name | | Dioxyde de carbone | |
| OEL TWA | | 9000 mg/m³ | |
| OEL TWA [ppm] | | 5000 ppm | |
| Malta - Occupational Exposure Limits | | | |
| Local name | | Carbondioxide | |
| OEL TWA | | 9000 mg/m³ | |
| OEL TWA [ppm] | | 5000 ppm | |
| Netherlands - Occupational Exposure Limits | | | |
| Local name | | Kooldioxide | |
| TGG-8u (OEL TWA) | | 9000 mg/m³ | |
| Poland - Occupational Exposure Limits | | | |
| Local name | | Ditlenek węgla 7 | |
| NDS (OEL TWA) | | 9000 mg/m³ | |
| NDSch (OEL STEL) | | 27000 mg/m³ | |
| Portugal - Occupational Exposure Limits | | | |
| Local name | | Dióxido de carbono | |
| OEL TWA [ppm] | | 5000 ppm | |
| OEL STEL [ppm] | | 30000 ppm | |
| Romania - Occupational Exposure Limits | | | |
| Local name | | Bioxid de carbon | |
| OEL TWA | | 9000 mg/m³ | |
| OEL TWA [ppm] | | 5000 ppm | |
| Slovenia - Occupational Exposure Limits | | | |
| Local name | | ogljikov dioksid | |
| OEL TWA | | 9000 mg/m³ | |
| OEL TWA [ppm] | | 5000 ppm | |
| Spain - Occupational Exposure Limits | | | |
| Local name | | Dióxido de carbono | |
| VLA-ED (OEL TWA) [1] | | 9150 mg/m³ | |


| | | | |
|---|---|--|------------------------------------|
|  | SAFETY DATA SHEET | | Page : 9/20 |
| | | | Revised edition no : 6.0 |
| | | | Revision date : 2024-02-02 |
| | | | Supersedes version of : 2023-01-19 |
| Carbon dioxide (refrigerated) | | | NOAL_0018B |
| | | | Country : SE / Language : EN |
| VLA-ED (OEL TWA) [2] | 5000 ppm | | |
| Remark | VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país). | | |
| Sweden - Occupational Exposure Limits | | | |
| Local name | Koldioxid | | |
| NGV (OEL TWA) | 9000 mg/m³ | | |
| NGV (OEL TWA) [ppm] | 5000 ppm | | |
| KTV (OEL STEL) | 18000 mg/m³ | | |
| KTV (OEL STEL) [ppm] | 10000 ppm | | |
| United Kingdom - Occupational Exposure Limits | | | |
| Local name | Carbon dioxide | | |
| WEL TWA (OEL TWA) [1] | 9150 mg/m³ | | |
| WEL TWA (OEL TWA) [2] | 5000 ppm | | |
| WEL STEL (OEL STEL) | 27400 mg/m³ | | |
| WEL STEL (OEL STEL) [ppm] | 15000 ppm | | |
| Iceland - Occupational Exposure Limits | | | |
| Local name | Koldíoxíð (koltvísýringur, kolsýra) | | |
| OEL TWA | 9000 mg/m³ | | |
| OEL TWA [ppm] | 5000 ppm | | |
| Norway - Occupational Exposure Limits | | | |
| Local name | Karbondioksid | | |
| Grenseverdi (OEL TWA) [1] | 9000 mg/m³ | | |
| Grenseverdi (OEL TWA) [2] | 5000 ppm | | |
| Switzerland - Occupational Exposure Limits | | | |
| Local name | Kohlendioxid | | |
| MAK (OEL TWA) [1] | 9000 mg/m³ | | |
| MAK (OEL TWA) [2] | 5000 ppm | | |
| Remark | Asphyxie - NIOSH | | |
| USA - ACGIH - Occupational Exposure Limits | | | |
| Local name | Carbon dioxide | | |
| ACGIH OEL TWA [ppm] | 5000 ppm | | |
| ACGIH OEL STEL [ppm] | 30000 ppm | | |
| Remark (ACGIH) | Asphyxia | | |


| | | |
|---|--------------------------|------------------------------------|
|  | SAFETY DATA SHEET | Page : 10/20 |
| | | Revised edition no : 6.0 |
| | | Revision date : 2024-02-02 |
| | | Supersedes version of : 2023-01-19 |
| Carbon dioxide (refrigerated) | | NOAL_0018B |
| | | Country : SE / Language : EN |

| Carbon dioxide (refrigerated) (124-38-9) | |
|--|--|
| EU - Indicative Occupational Exposure Limit (IOEL) | |
| Local name | Carbon dioxide |
| IOEL TWA | 9000 mg/m ³ |
| IOEL TWA [ppm] | 5000 ppm |
| Austria - Occupational Exposure Limits | |
| Local name | Kohlenstoffdioxid |
| MAK (mg/m ³) | 9000 mg/m ³ |
| MAK (OEL TWA) [ppm] | 5000 ppm |
| MAK (OEL STEL) | 18000 mg/m ³ |
| MAK (OEL STEL) [ppm] | 10000 ppm |
| Belgium - Occupational Exposure Limits | |
| Local name | Carbone (dioxyde de) # Koolstofdioxide |
| OEL TWA | 9131 mg/m ³ |
| OEL TWA [ppm] | 5000 ppm |
| OEL STEL | 54784 mg/m ³ |
| OEL STEL [ppm] | 30000 ppm |
| Remark | A: La mention A signifie que l'agent libère un gaz ou une vapeur qui n'ont en eux-mêmes aucun effet physiologique mais peuvent diminuer le taux d'oxygène dans l'air. Lorsque le taux d'oxygène descend en dessous de 17-18 % (vol/vol) le manque d'oxygène provoque des suffocations qu'aucun symptôme préalable n'annonce. # De vermelding A betekent dat dit agens gas of damp vrijgeeft dat of die op zich geen fysiologische werking heeft, maar het zuurstofgehalte in de lucht verlaagt. Wanneer het zuurstofgehalte daalt onder de 17-18 % (vol/vol), veroorzaakt het zuurstoftekort verstikking, die zich manifesteert zonder dat er een waarschuwing aan voorafgaat. |
| Bulgaria - Occupational Exposure Limits | |
| Local name | Въглероден диоксид |
| OEL TWA | 9000 mg/m ³ |
| OEL TWA [ppm] | 5000 ppm |
| Remark | • (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност) |
| Croatia - Occupational Exposure Limits | |
| Local name | Ugljikov dioksid |
| GVI (OEL TWA) [1] | 9000 mg/m ³ |
| GVI (OEL TWA) [2] | 5000 ppm |
| Remark | EU** |
| Czech Republic - Occupational Exposure Limits | |
| Local name | Oxid uhli ítý |

| | | | |
|---|-------------------|------------------------------------|------------------------------------|
|  | SAFETY DATA SHEET | | Page : 11/20 |
| | | | Revised edition no : 6.0 |
| | | | Revision date : 2024-02-02 |
| | | | Supersedes version of : 2023-01-19 |
| Carbon dioxide (refrigerated) | | | NOAL_0018B |
| | | | Country : SE / Language : EN |
| PEL (OEL TWA) | | 9000 mg/m³ | |
| PEL (OEL TWA) [ppm] | | 5000 ppm | |
| NPK-P (OEL C) | | 45000 mg/m³ | |
| NPK-P (OEL C) [ppm] | | 25020 ppm | |
| Denmark - Occupational Exposure Limits | | | |
| Local name | | Carbondioxid (Kuldioxid; Kulsyre) | |
| OEL TWA [1] | | 9000 mg/m³ | |
| OEL TWA [2] | | 5000 ppm | |
| Estonia - Occupational Exposure Limits | | | |
| Local name | | Süsinikdioksiid | |
| OEL TWA | | 9000 mg/m³ | |
| OEL TWA [ppm] | | 5000 ppm | |
| Finland - Occupational Exposure Limits | | | |
| Local name | | Hiilidioksidi | |
| HTP (OEL TWA) [1] | | 9100 mg/m³ | |
| HTP (OEL TWA) [2] | | 5000 ppm | |
| France - Occupational Exposure Limits | | | |
| Local name | | Dioxyde de carbone | |
| VME (OEL TWA) | | 9000 mg/m³ | |
| VME (OEL TWA) [ppm] | | 5000 ppm | |
| Remark | | Valeurs règlementaires indicatives | |
| Germany - Occupational Exposure Limits (TRGS 900) | | | |
| Local name | | Kohlenstoffdioxid | |
| AGW (OEL TWA) [1] | | 9100 mg/m³ | |
| AGW (OEL TWA) [2] | | 5000 ppm | |
| Remark | | DFG,EU | |
| Greece - Occupational Exposure Limits | | | |
| OEL TWA | | 9000 mg/m³ | |
| OEL TWA [ppm] | | 5000 ppm | |
| OEL STEL | | 54000 mg/m³ | |
| Hungary - Occupational Exposure Limits | | | |
| Local name | | SZÉN-DIOXID | |
| AK (OEL TWA) | | 9000 mg/m³ | |
| Ireland - Occupational Exposure Limits | | | |
| Local name | | Carbon dioxide | |

| | | | |
|---|--------------------------|--------------------|------------------------------------|
|  | SAFETY DATA SHEET | | Page : 12/20 |
| | | | Revised edition no : 6.0 |
| | | | Revision date : 2024-02-02 |
| | | | Supersedes version of : 2023-01-19 |
| Carbon dioxide (refrigerated) | | | NOAL_0018B |
| | | | Country : SE / Language : EN |
| OEL TWA [1]9000 mg/m³ | | | |
| OEL TWA [2]5000 ppm | | | |
| OEL STEL27000 mg/m³ | | | |
| OEL STEL [ppm]15000 ppm | | | |
| Italy - Occupational Exposure Limits | | | |
| Local name | | Anidride carbonica | |
| OEL TWA | | 9000 mg/m³ | |
| OEL TWA [ppm] | | 5000 ppm | |
| Latvia - Occupational Exposure Limits | | | |
| Local name | | Oglekļadioksīds | |
| OEL TWA | | 9000 mg/m³ | |
| OEL TWA [ppm] | | 5000 ppm | |
| Lithuania - Occupational Exposure Limits | | | |
| Local name | | Anglies dioksidas | |
| IPRV (OEL TWA) | | 9000 mg/m³ | |
| IPRV (OEL TWA) [ppm] | | 5000 ppm | |
| Luxembourg - Occupational Exposure Limits | | | |
| Local name | | Dioxyde de carbone | |
| OEL TWA | | 9000 mg/m³ | |
| OEL TWA [ppm] | | 5000 ppm | |
| Malta - Occupational Exposure Limits | | | |
| Local name | | Carbondioxide | |
| OEL TWA | | 9000 mg/m³ | |
| OEL TWA [ppm] | | 5000 ppm | |
| Netherlands - Occupational Exposure Limits | | | |
| Local name | | Kooldioxide | |
| TGG-8u (OEL TWA) | | 9000 mg/m³ | |
| Poland - Occupational Exposure Limits | | | |
| Local name | | Ditlenek węgla 7 | |
| NDS (OEL TWA) | | 9000 mg/m³ | |
| NDSch (OEL STEL) | | 27000 mg/m³ | |
| Portugal - Occupational Exposure Limits | | | |
| Local name | | Dióxido de carbono | |
| OEL TWA [ppm] | | 5000 ppm | |
| OEL STEL [ppm] | | 30000 ppm | |

| | | | |
|---|--------------------------|---|------------------------------------|
|  | SAFETY DATA SHEET | | Page : 13/20 |
| | | | Revised edition no : 6.0 |
| | | | Revision date : 2024-02-02 |
| | | | Supersedes version of : 2023-01-19 |
| Carbon dioxide (refrigerated) | | | NOAL_0018B |
| | | | Country : SE / Language : EN |
| Romania - Occupational Exposure Limits | | | |
| Local name | | Bioxid de carbon | |
| OEL TWA | | 9000 mg/m³ | |
| OEL TWA [ppm] | | 5000 ppm | |
| Slovenia - Occupational Exposure Limits | | | |
| Local name | | ogljikov dioksid | |
| OEL TWA | | 9000 mg/m³ | |
| OEL TWA [ppm] | | 5000 ppm | |
| Spain - Occupational Exposure Limits | | | |
| Local name | | Dióxido de carbono | |
| VLA-ED (OEL TWA) [1] | | 9150 mg/m³ | |
| VLA-ED (OEL TWA) [2] | | 5000 ppm | |
| Remark | | VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país). | |
| Sweden - Occupational Exposure Limits | | | |
| Local name | | Koldioxid | |
| NGV (OEL TWA) | | 9000 mg/m³ | |
| NGV (OEL TWA) [ppm] | | 5000 ppm | |
| KTV (OEL STEL) | | 18000 mg/m³ | |
| KTV (OEL STEL) [ppm] | | 10000 ppm | |
| United Kingdom - Occupational Exposure Limits | | | |
| Local name | | Carbon dioxide | |
| WEL TWA (OEL TWA) [1] | | 9150 mg/m³ | |
| WEL TWA (OEL TWA) [2] | | 5000 ppm | |
| WEL STEL (OEL STEL) | | 27400 mg/m³ | |
| WEL STEL (OEL STEL) [ppm] | | 15000 ppm | |
| Iceland - Occupational Exposure Limits | | | |
| Local name | | Koldíoxíð (koltvísýringur, kolsýra) | |
| OEL TWA | | 9000 mg/m³ | |
| OEL TWA [ppm] | | 5000 ppm | |
| Norway - Occupational Exposure Limits | | | |
| Local name | | Karbondioksid | |
| Grenseverdi (OEL TWA) [1] | | 9000 mg/m³ | |

| | | |
|---|-------------------|------------------------------------|
|  | SAFETY DATA SHEET | Page : 14/20 |
| | | Revised edition no : 6.0 |
| | | Revision date : 2024-02-02 |
| | | Supersedes version of : 2023-01-19 |
| Carbon dioxide (refrigerated) | | NOAL_0018B |
| | | Country : SE / Language : EN |

| | |
|---|------------------|
| Grenseverdi (OEL TWA) [2] | 5000 ppm |
| Switzerland - Occupational Exposure Limits | |
| Local name | Kohlendioxid |
| MAK (OEL TWA) [1] | 9000 mg/m³ |
| MAK (OEL TWA) [2] | 5000 ppm |
| Remark | Asphyxie - NIOSH |
| USA - ACGIH - Occupational Exposure Limits | |
| Local name | Carbon dioxide |
| ACGIH OEL TWA [ppm] | 5000 ppm |
| ACGIH OEL STEL [ppm] | 30000 ppm |
| Remark (ACGIH) | Asphyxia |

DNEL (Derived-No Effect Level) : None available.

PNEC (Predicted No-Effect Concentration) : None available.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation.
Systems under pressure should be regularly checked for leakages.
Ensure exposure is below occupational exposure limits (where available).
Oxygen detectors should be used when asphyxiating gases may be released.
Consider the use of a work permit system e.g. for maintenance activities.
CO2 detectors should be used when CO2 may be released.

8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.
The following recommendations should be considered:
PPE compliant to the recommended EN/ISO standards should be selected.
: Wear goggles and a face shield when transfilling or breaking transfer connections.
Standard EN 166 - Personal eye-protection - specifications.

• Eye/face protection

• Skin protection

- Hand protection

: Wear working gloves when handling gas containers.
Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.
Wear cold insulating gloves when transfilling or breaking transfer connections.
Standard EN 511 - Cold insulating gloves.


- Other

: Wear safety shoes while handling containers.
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
: Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known.
Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Gas filters do not protect against oxygen deficiency.
Self contained breathing apparatus (SCBA) or positive pressure airline with mask are to be used in oxygen-deficient atmospheres.
Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks .
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.

• Respiratory protection

• Thermal hazards

: None in addition to the above sections.

| | | |
|---|--------------------------|------------------------------------|
|  | SAFETY DATA SHEET | Page : 15/20 |
| | | Revised edition no : 6.0 |
| | | Revision date : 2024-02-02 |
| | | Supersedes version of : 2023-01-19 |
| Carbon dioxide (refrigerated) | | NOAL_0018B |
| | | Country : SE / Language : EN |

8.2.3. Environmental exposure controls

None necessary.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

- Physical state at 20°C / 101.3kPa
- Colour

Odour

pH

Melting point / Freezing point

Boiling point

Flash point

Flammability

Explosive limits

Lower explosion limit

Upper explosion limit

Vapour pressure [20°C]

Vapour pressure [50°C]

Density

Vapour density

Relative density, liquid (water=1)

Relative density, gas (air=1)

Water solubility

Partition coefficient n-octanol/water (Log Kow)

Auto-ignition temperature

Decomposition temperature

Viscosity, kinematic

Particle characteristics

- : Gas
- : Colourless.
- : No odour warning properties.
- Odour threshold is subjective and inadequate to warn of overexposure.
- : Not applicable for gases and gas mixtures.
- : 78.5 °C At atmospheric pressure dry ice sublimates into gaseous carbon dioxide.
- : -56.6 °C
- : Not applicable for gases and gas mixtures.
- : Non flammable.
- : Non flammable.
- : Not available
- : Not available
- : 57.3 bar(a)
- : Not applicable.
- : Not applicable
- : Not applicable for gases and gas mixtures.
- : 0.82
- : 1.52
- : 2000 mg/l Completely soluble.
- : 0.83
- : Non flammable.
- : Not applicable.
- : No reliable data available.
- : Not applicable for gases and gas mixtures.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

- Explosive properties : Not applicable.
- Oxidising properties : Not applicable.
- Critical temperature [°C] : 30 °C

9.2.2. Other safety characteristics

- Molar mass : 44 g/mol
- Evaporation rate : Not applicable for gases and gas mixtures.
- Gas group : Press. Gas (Ref. Liq.)
- Other data : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity


No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None.

| | | |
|---|--------------------------|------------------------------------|
|  | SAFETY DATA SHEET | Page : 16/20 |
| | | Revised edition no : 6.0 |
| | | Revision date : 2024-02-02 |
| | | Supersedes version of : 2023-01-19 |
| Carbon dioxide (refrigerated) | | NOAL_0018B |
| | | Country : SE / Language : EN |

Reactivity : None.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).
Avoid moisture in installation systems.

10.5. Incompatible materials

For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

None.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

| | |
|---------------------------------------|---|
| Acute toxicity | : Unlike simple asphyxiants, carbon dioxide has the ability to cause death even when normal oxygen levels (20-21%) are maintained. 5% CO2 has been found to act synergistically to increase the toxicity of certain other gases (CO, NO2). CO2 has been shown to enhance the production of carboxy- or met-hemoglobin by these gases possibly due to carbon dioxide's stimulatory effects on the respiratory and circulatory systems. For more information, see 'EIGA Safety Info 24: Carbon Dioxide, Physiological Hazards' at www.eiga.eu . |
| Skin corrosion/irritation | : No known effects from this product. |
| Serious eye damage/irritation | : No known effects from this product. |
| Respiratory or skin sensitisation | : No known effects from this product. |
| Germ cell mutagenicity | : No known effects from this product. |
| Carcinogenicity | : No known effects from this product. |
| Toxic for reproduction : Fertility | : No known effects from this product. |
| Toxic for reproduction : unborn child | : No known effects from this product. |
| STOT-single exposure | : No known effects from this product. |
| STOT-repeated exposure | : No known effects from this product. |
| Aspiration hazard | : Not applicable for gases and gas mixtures. |

11.2. Information on other hazards

| | |
|-------------------|--|
| Other information | : For more information, see 'EIGA Safety Info 24: Carbon Dioxide, Physiological Hazards' at www.eiga.eu . Unlike simple asphyxiants, carbon dioxide has the ability to cause death even when normal oxygen levels (20-21%) are maintained. 5% CO2 has been found to act synergistically to increase the toxicity of certain other gases (CO, NO2). CO2 has been shown to enhance the production of carboxy- or met-hemoglobin by these gases possibly due to carbon dioxide's stimulatory effects on the respiratory and circulatory systems. The substance/mixture has no endocrine disrupting properties. |
|-------------------|--|


SECTION 12: Ecological information

12.1. Toxicity

| | |
|---------------------------------|--|
| Assessment | : No ecological damage caused by this product. |
| EC50 48h - Daphnia magna [mg/l] | : No data available. |
| EC50 72h - Algae [mg/l] | : No data available. |
| LC50 96 h - Fish [mg/l] | : No data available. |

12.2. Persistence and degradability

| | |
|------------|--|
| Assessment | : No ecological damage caused by this product. |
|------------|--|

| | | |
|---|----------------------------|------------------------------------|
|  | <h1>SAFETY DATA SHEET</h1> | Page : 17/20 |
| | | Revised edition no : 6.0 |
| | | Revision date : 2024-02-02 |
| | | Supersedes version of : 2023-01-19 |
| <h2>Carbon dioxide (refrigerated)</h2> | | NOAL_0018B |
| | | Country : SE / Language : EN |

12.3. Bioaccumulative potential

Assessment : No ecological damage caused by this product.
Not expected to bioaccumulate due to the low log Kow (log Kow < 4).
See section 9.

12.4. Mobility in soil

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.
Partition into soil is unlikely.

12.5. Results of PBT and vPvB assessment

Assessment : No data available.
Not classified as PBT or vPvB.

12.6. Endocrine disrupting properties

The substance/mixture has no endocrine disrupting properties.

12.7. Other adverse effects

Other adverse effects : Can cause frost damage to vegetation.
Effect on the ozone layer : None.
Global warming potential [CO₂=1] : 1
Effect on global warming : Contains greenhouse gas(es).
When discharged in large quantities may contribute to the greenhouse effect.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

May be vented to atmosphere in a well ventilated place.
Discharge to atmosphere in large quantities should be avoided.
Do not discharge into any place where its accumulation could be dangerous.
Return unused product in original container to supplier.
List of hazardous waste codes (from Commission Decision 2000/532/EC as amended) : 16 05 05 : Gases in pressure containers other than those mentioned in 16 05 04.

13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN
UN-No. : 2187

14.2. UN proper shipping name


Transport by road/rail (ADR/RID) : CARBON DIOXIDE, REFRIGERATED LIQUID
Transport by air (ICAO-TI / IATA-DGR) : Carbon dioxide, refrigerated liquid
Transport by sea (IMDG) : CARBON DIOXIDE, REFRIGERATED LIQUID

14.3. Transport hazard class(es)

Labelling :



2.2 : Non-flammable, non-toxic gases.

| | | |
|---|--------------------------|------------------------------------|
|  | SAFETY DATA SHEET | Page : 18/20 |
| | | Revised edition no : 6.0 |
| | | Revision date : 2024-02-02 |
| | | Supersedes version of : 2023-01-19 |
| Carbon dioxide (refrigerated) | | NOAL_0018B |
| | | Country : SE / Language : EN |

Transport by road/rail (ADR/RID)

Class : 2
 Classification code : 3A
 Hazard identification number : 22
 Tunnel Restriction : C/E - Tank carriage: Passage forbidden through tunnels of category C, D and E. Other carriage: Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.2

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2
 Emergency Schedule (EmS) - Fire : F-C
 Emergency Schedule (EmS) - Spillage : S-V

14.4. Packing group

Transport by road/rail (ADR/RID) : Not established.
 Transport by air (ICAO-TI / IATA-DGR) : Not established.
 Transport by sea (IMDG) : Not established.

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.
 Transport by air (ICAO-TI / IATA-DGR) : None.
 Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P203
 Transport by air (ICAO-TI / IATA-DGR)
 Passenger and Cargo Aircraft : 202.
 Cargo Aircraft only : 202.
 Transport by sea (IMDG) : P203

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment.
 Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
 Before transporting product containers:
 - Ensure there is adequate ventilation.
 - Ensure that containers are firmly secured.
 - Ensure valve is closed and not leaking.
 - Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
 - Ensure valve protection device (where provided) is correctly fitted.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information


15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Restrictions on use : None.
 National legislation : Ensure all national/local regulations are observed.
 Seveso Directive : 2012/18/EU (Seveso III) : Not covered.

National regulations

Ensure all national/local regulations are observed.

| | | |
|---|-------------------|------------------------------------|
|  | SAFETY DATA SHEET | Page : 19/20 |
| | | Revised edition no : 6.0 |
| | | Revision date : 2024-02-02 |
| | | Supersedes version of : 2023-01-19 |
| Carbon dioxide (refrigerated) | | NOAL_0018B |
| | | Country : SE / Language : EN |

| | |
|------------------------------|----------------------------------|
| France | |
| Occupational diseases | |
| Code | Description |
| RG 66 | Occupational rhinitis and asthma |

| | |
|--|--|
| Germany | |
| Water hazard class (WGK) | : WGK nwg, Non-hazardous to water (Classification according to AwSV) |
| National Rules and Recommendations | : [German regulations] BetriebssicherheitsV mit TRBSen insbesondere TRBS 3145 / TRGS 725 Ortsbewegliche Druckgasbehälter", TRBS 2141, BGR Regel 500 Teil 2.33: "Umgang mit Gasen", GefahrstoffV mit Technischen Regeln Gefährliche Stoffe TRGS insbesondere TRGS 407 "Tätigkeiten mit Gasen - Gefährdungsbeurteilung", TRGS 400, 500, 510, 900." |
| Netherlands | |
| SZW-lijst van kankerverwekkende stoffen | : The substance is not listed |
| SZW-lijst van mutagene stoffen | : The substance is not listed |
| SZW-lijst van reprotoxische stoffen – Borstvoeding | : The substance is not listed |
| SZW-lijst van reprotoxische stoffen – Vruchtbaarheid | : The substance is not listed |
| SZW-lijst van reprotoxische stoffen – Ontwikkeling | : The substance is not listed |

15.2. Chemical safety assessment


A CSA does not need to be carried out for this product.

SECTION 16: Other information

Indication of changes : Safety data sheet in accordance with commission regulation (EU) No 2020/878.

| Section | Changed item | Change | Comments |
|---------|--------------|----------|--|
| 1.3 | Company | Modified | Version 6.0. New address in Sweden. (This change only applies to the Swedish (SE) version of this SDS) |

| | |
|----------------------------|---|
| Abbreviations and acronyms | : ATE - Acute Toxicity Estimate |
| | CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 |
| | REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006 |
| | EINECS - European Inventory of Existing Commercial Chemical Substances |
| | CAS# - Chemical Abstract Service number |
| | PPE - Personal Protection Equipment |
| | LC50 - Lethal Concentration to 50 % of a test population |
| | RMM - Risk Management Measures |
| | PBT - Persistent, Bioaccumulative and Toxic |
| | vPvB - Very Persistent and Very Bioaccumulative |
| | STOT- SE : Specific Target Organ Toxicity - Single Exposure |
| | CSA - Chemical Safety Assessment |
| | EN - European Standard |
| | UN - United Nations |
| | ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road |
| | IATA - International Air Transport Association |
| | IMDG code - International Maritime Dangerous Goods |
| | RID - Regulations concerning the International Carriage of Dangerous Goods by Rail |
| | WGK - Water Hazard Class |
| | STOT - RE : Specific Target Organ Toxicity - Repeated Exposure |
| | UFI : Unique Formula Identifier |

| | | |
|---|--------------------------|------------------------------------|
|  | SAFETY DATA SHEET | Page : 20/20 |
| | | Revised edition no : 6.0 |
| | | Revision date : 2024-02-02 |
| | | Supersedes version of : 2023-01-19 |
| Carbon dioxide (refrigerated) | | NOAL_0018B |
| | | Country : SE / Language : EN |

| | |
|---------------------|--|
| Training advice | : The hazard of asphyxiation is often overlooked and must be stressed during operator training. For more guidance, refer to EIGA SL 01 "Dangers of Asphyxiation", downloadable at http://www.eiga.eu . |
| Further information | : Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP). Key literature references and sources of data are maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at http://www.Eiga.eu . |

| Full text of H- and EUH-statements | |
|------------------------------------|---|
| H281 | Contains refrigerated gas; may cause cryogenic burns or injury. |
| Press. Gas (Ref. Liq.) | Gases under pressure : Refrigerated liquefied gas |

| | |
|----------------------------|---|
| DISCLAIMER OF LIABILITY | : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out. Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. |
| <div>End of document</div> | |