

Kalinox**NOAL_1027**

Country : SE / Language : EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Trade name : Kalinox
SDS no : NOAL_1027

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use.
Industrial and professional use for chemical analysis, calibration, (routine) quality control, laboratory use, under controlled conditions.
Contact supplier for more information on uses.

Uses advised against : Consumer use.
Uses other than those listed above are not supported, contact your supplier for more information on other uses.

1.3. Details of the supplier of the safety data sheet**Company identification****Supplier**

AIR LIQUIDE GAS AB
Lundavägen 151
212 09 Malmö - SWEDEN
T +46 40 38 10 00
info.sweden@airliquide.com

E-Mail address (competent person) : eunordic-sds@airliquide.com

1.4. Emergency telephone number

Emergency telephone number : 112
Availability
(24 / 7)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**

Physical hazards	Oxidising Gases, Category 1	H270
	Gases under pressure : Liquefied gas	H280
Health hazards	Specific target organ toxicity – Single exposure, Category 3, Narcosis	H336

2.2. Label elements**Labelling according to Regulation (EC) No. 1272/2008 [CLP]**

Hazard pictograms (CLP) :



GHS03

GHS04

GHS07

Signal word (CLP) :


: Danger

Hazard statements (CLP) :

: H270 - May cause or intensify fire; oxidiser.

H280 - Contains gas under pressure; may explode if heated.

H336 - May cause drowsiness or dizziness.

	SAFETY DATA SHEET	Page : 2/14
		Revised edition no : 3.0
		Revision date : 2023-01-23
		Supersedes version of : 2020-07-14
Kalinox		NOAL_1027
		Country : SE / Language : EN

Precautionary statements (CLP)

- Prevention : P220 - Keep away from clothing and other combustible materials.
P244 - Keep valves and fittings free from oil and grease.
- Response : P304+P340+P315 - IF INHALED : Remove person to fresh air and keep comfortable for breathing. Get immediate medical advice.
P370+P376 - In case of fire: Stop leak if safe to do so.
- Storage : P403 - Store in a well-ventilated place.

2.3. Other hazards

Contact with liquid may cause cold burns/frostbite.
Not classified as PBT or vPvB.
The substance/mixture has no endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.1. Substances Not established.

3.2. Mixtures

Name	Product identifier	Composition [V-%]:	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Oxygen	CAS-No.: 7782-44-7 EC-No.: 231-956-9 EC Index-No.: 008-001-00-8 REACH-no: *1	50	Ox. Gas 1, H270 Press. Gas (Comp.), H280
Nitrous oxide	CAS-No.: 10024-97-2 EC-No.: 233-032-0 EC Index-No.: --- REACH-no: 01-2119970538-25	50	Ox. Gas 1, H270 Press. Gas (Liq.), H280 STOT SE 3, H336

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*3: Registration not required: Substance manufactured or imported < 1t/y.

SECTION 4: First aid measures

4.1. Description of first aid measures


- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

In low concentrations may cause narcotic effects. Symptoms may include dizziness, headache, nausea and loss of co-ordination.
See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

	SAFETY DATA SHEET	Page : 3/14
		Revised edition no : 3.0
		Revision date : 2023-01-23
		Supersedes version of : 2020-07-14
Kalinox		NOAL_1027
		Country : SE / Language : EN

SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.
Product does not burn, use fire control measures appropriate for the surrounding fire.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Supports combustion.
Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : Nitric oxide/nitrogen dioxide.

5.3. Advice for firefighters

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
If possible, stop flow of product.
Use water spray or fog to knock down fire fumes if possible.
Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus.
Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Gas-tight chemical protective suits for emergency teams.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

- For non-emergency personnel : Act in accordance with local emergency plan.
Try to stop release.
Evacuate area.
Ensure adequate air ventilation.
Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.
Stay upwind.
See section 8 of the SDS for more information on personal protective equipment
- For emergency responders : Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.
See section 5.3 of the SDS for more information.

6.2. Environmental precautions


Try to stop release.

6.3. Methods and material for containment and cleaning up

Ventilate area.

6.4. Reference to other sections

See also sections 8 and 13.

	SAFETY DATA SHEET	Page : 4/14
		Revised edition no : 3.0
		Revision date : 2023-01-23
		Supersedes version of : 2020-07-14
Kalinox		NOAL_1027
		Country : SE / Language : EN

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe use of the product

- : Do not breathe gas.
- Avoid release of product into atmosphere.
- The product must be handled in accordance with good industrial hygiene and safety procedures.
- Only experienced and properly instructed persons should handle gases under pressure.
- Consider pressure relief device(s) in gas installations.
- Ensure the complete gas system was (or is regularly) checked for leaks before use.
- Do not smoke while handling product.
- Keep equipment free from oil and grease. For more guidance, refer to the EIGA Doc. 33 - Cleaning of Equipment for Oxygen Service downloadable at <http://www.eiga.eu>.
- Use no oil or grease.
- Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
- Use only oxygen approved lubricants and oxygen approved sealings.
- Avoid suck back of water, acid and alkalis.

Safe handling of the gas receptacle

- : Refer to supplier's container handling instructions.
- Do not allow backfeed into the container.
- Protect containers from physical damage; do not drag, roll, slide or drop.
- When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
- Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
- If user experiences any difficulty operating valve discontinue use and contact supplier.
- Never attempt to repair or modify container valves or safety relief devices.
- Damaged valves should be reported immediately to the supplier.
- Keep container valve outlets clean and free from contaminants particularly oil and water.
- Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
- Close container valve after each use and when empty, even if still connected to equipment.
- Never attempt to transfer gases from one cylinder/container to another.
- Never use direct flame or electrical heating devices to raise the pressure of a container.
- Do not remove or deface labels provided by the supplier for the identification of the content of the container.
- Suck back of water into the container must be prevented.
- Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

- Observe all regulations and local requirements regarding storage of containers.
- Containers should not be stored in conditions likely to encourage corrosion.
- Container valve guards or caps should be in place.
- Containers should be stored in the vertical position and properly secured to prevent them from falling over.
- Stored containers should be periodically checked for general condition and leakage.
- Keep container below 50°C in a well ventilated place.
- Segregate from flammable gases and other flammable materials in store.
- Store containers in location free from fire risk and away from sources of heat and ignition.
- Keep away from combustible materials.

7.3. Specific end use(s)

None.

Kalinox

NOAL_1027

Country : SE / Language : EN

SECTION 8: Exposure controls/personal protection


8.1. Control parameters


Nitrous oxide (10024-97-2)	
Austria - Occupational Exposure Limits	
Local name	Distickstoffmonoxid
MAK (mg/m ³)	180 mg/m ³
MAK (OEL TWA) [ppm]	100 ppm
MAK (OEL STEL)	720 mg/m ³
MAK (OEL STEL) [ppm]	400 ppm
Belgium - Occupational Exposure Limits	
Local name	Diazote (oxyde de) # Diazote (oxyde de)
OEL TWA	91 mg/m ³
OEL TWA [ppm]	50 ppm
Croatia - Occupational Exposure Limits	
Local name	Didušikov oksid
GVI (OEL TWA) [1]	90 mg/m ³
GVI (OEL TWA) [2]	50 ppm
Czech Republic - Occupational Exposure Limits	
Local name	Oxid dusný
PEL (OEL TWA)	180 mg/m ³
PEL (OEL TWA) [ppm]	100 ppm
NPK-P (OEL C)	360 mg/m ³
NPK-P (OEL C) [ppm]	200 ppm
Denmark - Occupational Exposure Limits	
Local name	Dinitrogenoxid (Kvælstofforilte)
OEL TWA [1]	90 mg/m ³
OEL TWA [2]	50 ppm
Estonia - Occupational Exposure Limits	
Local name	Dilämmastikoksiid (naerugaas)
OEL TWA	180 mg/m ³
OEL TWA [ppm]	100 ppm
OEL STEL	900 mg/m ³
OEL STEL [ppm]	500 ppm
Finland - Occupational Exposure Limits	
Local name	Typpioksiduuli

Kalinox**NOAL_1027**

Country : SE / Language : EN

HTP (OEL TWA) [1]	180 mg/m ³
HTP (OEL TWA) [2]	100 ppm
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Distickstoffoxid
AGW (OEL TWA) [1]	180 mg/m ³
AGW (OEL TWA) [2]	100 ppm
Remark	DFG,Y
Hungary - Occupational Exposure Limits	
Local name	DINITROGÉN-OXID
AK (OEL TWA)	180 mg/m ³
CK (OEL STEL)	720 mg/m ³
Ireland - Occupational Exposure Limits	
Local name	Nitrous oxide
OEL TWA [1]	90 mg/m ³
OEL TWA [2]	50 ppm
Lithuania - Occupational Exposure Limits	
Local name	Diazoto oksidas (azoto suboksidas)
IPRV (OEL TWA)	180 mg/m ³
IPRV (OEL TWA) [ppm]	100 ppm
TPRV (OEL STEL)	900 mg/m ³
TPRV (OEL STEL) [ppm]	500 ppm
Poland - Occupational Exposure Limits	
Local name	Tlenek diazotu
NDS (OEL TWA)	90 mg/m ³
Portugal - Occupational Exposure Limits	
Local name	Óxido nitroso
OEL TWA [ppm]	50 ppm
Slovenia - Occupational Exposure Limits	
Local name	didušikov oksid
OEL TWA	180 mg/m ³
OEL TWA [ppm]	100 ppm
OEL STEL	720 mg/m ³
OEL STEL [ppm]	400 ppm
Spain - Occupational Exposure Limits	
Local name	Óxido de dinitrógeno (Protóxido de nitrógeno)

	SAFETY DATA SHEET		Page : 7/14
			Revised edition no : 3.0
			Revision date : 2023-01-23
			Supersedes version of : 2020-07-14
Kalinox		NOAL_1027	
		Country : SE / Language : EN	
VLA-ED (OEL TWA) [1]	92 mg/m ³		
VLA-ED (OEL TWA) [2]	50 ppm		
Sweden - Occupational Exposure Limits			
Local name	Dikväveoxid		
NGV (OEL TWA)	180 mg/m ³ 180 mg/m ³		
NGV (OEL TWA) [ppm]	100 ppm 100 ppm		
KTV (OEL STEL)	900 mg/m ³ 900 mg/m ³		
KTV (OEL STEL) [ppm]	500 ppm 500 ppm		
United Kingdom - Occupational Exposure Limits			
Local name	Nitrous oxide		
WEL TWA (OEL TWA) [1]	183 mg/m ³		
WEL TWA (OEL TWA) [2]	100 ppm		
Iceland - Occupational Exposure Limits			
Local name	Díköfnunarefnisoxíð (dínítrógenoxíð, glaðloft, hláturgas)		
OEL TWA	90 mg/m ³		
OEL TWA [ppm]	50 ppm		
Norway - Occupational Exposure Limits			
Local name	Dinitrogenoksid		
Grenseverdi (OEL TWA) [1]	90 mg/m ³		
Grenseverdi (OEL TWA) [2]	50 ppm		
Switzerland - Occupational Exposure Limits			
Local name	Distickstoffmonoxid		
MAK (OEL TWA) [1]	182 mg/m ³ 182 mg/m ³		
MAK (OEL TWA) [2]	100 ppm 100 ppm		
KZGW (OEL STEL)	364 mg/m ³ 364 mg/m ³		
KZGW (OEL STEL) [ppm]	200 ppm 200 ppm		
Remark	R2 _F R2 _D - ZNS, Blut, Leber ^{KT HU} - NIOSH		
USA - ACGIH - Occupational Exposure Limits			
Local name	Nitrous oxide		
ACGIH OEL TWA [ppm]	50 ppm		
Remark (ACGIH)	CNS impair; hematologic eff		

	SAFETY DATA SHEET	Page : 8/14
		Revised edition no : 3.0
		Revision date : 2023-01-23
		Supersedes version of : 2020-07-14
Kalinox		NOAL_1027 Country : SE / Language : EN

Nitrous oxide (10024-97-2)	
DNEL: Derived no effect level (Workers)	
Long-term - systemic effects, inhalation	183 mg/m ³

PNEC (Predicted No-Effect Concentration) : None established.

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation.
Product to be handled in a closed system.
Systems under pressure should be regularly checked for leakages.
Ensure exposure is below occupational exposure limits (where available).
Gas detectors should be used when oxidising gases may be released.
Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.

The following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

- Eye/face protection : Wear goggles when transfilling or breaking transfer connections.
Standard EN 166 - Personal eye-protection - specifications.
- Skin protection :
 - Hand protection : Wear working gloves when handling gas containers.
Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.
 - Other : Wear safety shoes while handling containers.
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
- Respiratory protection : Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known.
Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers.
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Consult respiratory device supplier's product information for the selection of the appropriate device.
When indicated by a risk assessment, Respiratory Protective Equipment must be used. The selection of the Respiratory Protective Device (RPD) must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected RPD.
Gas filters do not protect against oxygen deficiency.
Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks .
Keep self contained breathing apparatus readily available for emergency use.
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
- Thermal hazards : None in addition to the above sections.

8.2.3. Environmental exposure controls


Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

- Physical state at 20°C / 101.3kPa : Gas

	SAFETY DATA SHEET	Page : 9/14
		Revised edition no : 3.0
		Revision date : 2023-01-23
		Supersedes version of : 2020-07-14
Kalinox		NOAL_1027
		Country : SE / Language : EN

- Colour	: Colourless
Odour	: Odour threshold is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour: Sweetish. Odour threshold is subjective and inadequate to warn of overexposure.
pH	: Not applicable for gases and gas mixtures.
Melting point / Freezing point	: Not applicable for gas mixtures.
Boiling point	: Not applicable for gas mixtures.
Flash point	: Not applicable for gases and gas mixtures.
Flammability	: Non flammable.
Explosive limits	: Non flammable.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Vapour pressure [20°C]	: Not known.
Vapour pressure [50°C]	: Not available
Density	: Not applicable
Vapour density	: Not applicable for gases and gas mixtures.
Relative density, liquid (water=1)	: Not applicable
Relative density, gas (air=1)	: Heavier than air.
Water solubility	: Solubility in water of component(s) of the mixture : • Oxygen: 39 mg/l • Nitrous oxide: 1500 mg/l
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for gas mixtures.
Auto-ignition temperature	: Non flammable.
Decomposition temperature	: Not applicable.
Viscosity, kinematic	: No reliable data available.
Particle characteristics	: Not applicable for gases and gas mixtures.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

Explosive properties	: Not applicable.
Oxidising properties	: Oxidiser.

9.2.2. Other safety characteristics

Molar mass	: Not applicable for gas mixtures.
Evaporation rate	: Not applicable for gases and gas mixtures.
Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability


Stable under normal conditions.

10.3. Possibility of hazardous reactions

Reactivity	: Violently oxidises organic material. : This mixture contains components with the following reactivity : Violently oxidises organic material.
------------	---

10.4. Conditions to avoid

Avoid moisture in installation systems.
Water, humidity.

	SAFETY DATA SHEET	Page : 10/14
		Revised edition no : 3.0
		Revision date : 2023-01-23
		Supersedes version of : 2020-07-14
Kalinox		NOAL_1027
		Country : SE / Language : EN

10.5. Incompatible materials

May react violently with combustible materials.
 May react violently with reducing agents.
 Keep equipment free from oil and grease. For more guidance, refer to the EIGA Doc. 33 - Cleaning of Equipment for Oxygen Service downloadable at <http://www.eiga.eu>.
 Consider the potential toxicity hazard due to the presence of chlorinated or fluorinated polymers in high pressure (> 30 bar) oxygen lines in case of combustion.
 For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Classification criteria are not met.

Nitrous oxide (10024-97-2)

LC50 Inhalation - Rat [ppm]	500000 ppm/4h
-----------------------------	---------------

Skin corrosion/irritation : No known effects from this product.
Serious eye damage/irritation : No known effects from this product.
Respiratory or skin sensitisation : No known effects from this product.
Germ cell mutagenicity : No known effects from this product.
Carcinogenicity : No known effects from this product.
Toxic for reproduction : Fertility : No known effects from this product.
Toxic for reproduction : unborn child : No known effects from this product.
STOT-single exposure : May cause drowsiness or dizziness.
STOT-repeated exposure : No known effects from this product.
Aspiration hazard : Not applicable for gases and gas mixtures.

11.2. Information on other hazards

Other information : The substance/mixture has no endocrine disrupting properties.

SECTION 12: Ecological information

12.1. Toxicity


Assessment : No ecological damage caused by this product.
 EC50 48h - Daphnia magna [mg/l] : No data available.
 EC50 72h - Algae [mg/l] : No data available.
 LC50 96 h - Fish [mg/l] : No data available.

Nitrous oxide (10024-97-2)

EC50 48h - Daphnia magna [mg/l]	Study scientifically unjustified.
EC50 72h - Algae [mg/l]	Study scientifically unjustified.
LC50 96 h - Fish [mg/l]	Study scientifically unjustified.

12.2. Persistence and degradability

Assessment : No data available.

	SAFETY DATA SHEET	Page : 11/14
		Revised edition no : 3.0
		Revision date : 2023-01-23
		Supersedes version of : 2020-07-14
Kalinox		NOAL_1027
		Country : SE / Language : EN

12.3. Bioaccumulative potential

Assessment : No data available.

12.4. Mobility in soil

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution. Partition into soil is unlikely.

12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.

12.6. Endocrine disrupting properties

The substance/mixture has no endocrine disrupting properties.

12.7. Other adverse effects

Other adverse effects : No known effects from this product.
 Effect on the ozone layer : None.
 Effect on global warming : Contains greenhouse gas(es).

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Contact supplier if guidance is required.
 May be vented to atmosphere in a well ventilated place.
 Do not discharge into any place where its accumulation could be dangerous.
 Ensure that the emission levels from local regulations or operating permits are not exceeded.
 Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods.
 Return unused product in original container to supplier.

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended) : 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.

13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information

14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN
 UN-No. : 3156

14.2. UN proper shipping name


Transport by road/rail (ADR/RID) : COMPRESSED GAS, OXIDIZING, N.O.S. (Oxygen, Nitrous oxide)
 Transport by air (ICAO-TI / IATA-DGR) : Compressed gas, oxidizing, n.o.s. (Oxygen, Nitrous oxide)
 Transport by sea (IMDG) : COMPRESSED GAS, OXIDIZING, N.O.S. (Oxygen, Nitrous oxide)

14.3. Transport hazard class(es)

Labelling :



2.2 : Non-flammable, non-toxic gases.
 5.1 : Oxidizing substances.

	SAFETY DATA SHEET	Page : 12/14
		Revised edition no : 3.0
		Revision date : 2023-01-23
		Supersedes version of : 2020-07-14
Kalinox		NOAL_1027
		Country : SE / Language : EN

Transport by road/rail (ADR/RID)

Class : 2
 Classification code : 10
 Hazard identification number : 25
 Tunnel Restriction : E - Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 2.2 (5.1)

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.2 (5.1)
 Emergency Schedule (EmS) - Fire : F-C
 Emergency Schedule (EmS) - Spillage : S-W

14.4. Packing group

Transport by road/rail (ADR/RID) : Not established.
 Transport by air (ICAO-TI / IATA-DGR) : Not established.
 Transport by sea (IMDG) : Not established.

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : None.
 Transport by air (ICAO-TI / IATA-DGR) : None.
 Transport by sea (IMDG) : None.

14.6. Special precautions for user
Packing Instruction(s)

Transport by road/rail (ADR/RID) : P200
 Transport by air (ICAO-TI / IATA-DGR)
 Passenger and Cargo Aircraft : 200.
 Cargo Aircraft only : 200.
 Transport by sea (IMDG) : P200

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment.
 Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
 Before transporting product containers:
 - Ensure there is adequate ventilation.
 - Ensure that containers are firmly secured.
 - Ensure valve is closed and not leaking.
 - Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
 - Ensure valve protection device (where provided) is correctly fitted.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information
15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
EU-Regulations


Restrictions on use : None.
 Contains no substance(s) listed on the REACH Candidate List
 National legislation : Ensure all national/local regulations are observed.
 Seveso Directive : 2012/18/EU (Seveso III) : Covered.

National regulations

Ensure all national/local regulations are observed.

Germany

Water hazard class (WGK) : WGK 1, Slightly hazardous to water (Classification according to AwSV, Annex 1)

	SAFETY DATA SHEET	Page : 13/14
		Revised edition no : 3.0
		Revision date : 2023-01-23
		Supersedes version of : 2020-07-14
Kalinox		NOAL_1027
		Country : SE / Language : EN

National Rules and Recommendations : [German regulations] BetriebssicherheitsV mit TRBSen insbesondere TRBS 3145 / TRGS 725 Ortsbewegliche Druckgasbehälter", TRBS 2141, BGR Regel 500 Teil 2.33: "Umgang mit Gasen", GefahrstoffV mit Technischen Regeln Gefährliche Stoffe TRGS insbesondere TRGS 407 "Tätigkeiten mit Gasen - Gefährdungsbeurteilung", TRGS 400, 500, 510, 900."

Netherlands

SZW-lijst van kankerverwekkende stoffen : None of the components are listed
SZW-lijst van mutagene stoffen : None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding : None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling : None of the components are listed

Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Switzerland

Storage class (LK) : LK 2 - Liquefied or pressurized gases

15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.

SECTION 16: Other information

Indication of changes : Safety data sheet in accordance with commission regulation (EU) No 2020/878.

Abbreviations and acronyms

: ATE - Acute Toxicity Estimate
CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
EINECS - European Inventory of Existing Commercial Chemical Substances
CAS# - Chemical Abstract Service number
PPE - Personal Protection Equipment
LC50 - Lethal Concentration to 50 % of a test population
RMM - Risk Management Measures
PBT - Persistent, Bioaccumulative and Toxic
vPvB - Very Persistent and Very Bioaccumulative
STOT- SE : Specific Target Organ Toxicity - Single Exposure
CSA - Chemical Safety Assessment
EN - European Standard
UN - United Nations
ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road
IATA - International Air Transport Association
IMDG code - International Maritime Dangerous Goods
RID - Regulations concerning the International Carriage of Dangerous Goods by Rail
WGK - Water Hazard Class
STOT - RE : Specific Target Organ Toxicity - Repeated Exposure
UFI : Unique Formula Identifier


Training advice

: None.

Further information

: Classification using data from databases maintained by the European Industrial Gases Association (EIGA). Data is maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at : <http://www.eiga.eu>.
Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP).

Full text of H- and EUH-statements	
H270	May cause or intensify fire; oxidiser.
H280	Contains gas under pressure; may explode if heated.

	SAFETY DATA SHEET	Page : 14/14
		Revised edition no : 3.0
		Revision date : 2023-01-23
		Supersedes version of : 2020-07-14
Kalinox		NOAL_1027
		Country : SE / Language : EN
H336	May cause drowsiness or dizziness.	
Ox. Gas 1	Oxidising Gases, Category 1	
Press. Gas (Comp.)	Gases under pressure : Compressed gas	
Press. Gas (Liq.)	Gases under pressure : Liquefied gas	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
 Details given in this document are believed to be correct at the time of going to press.
 Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document