

Page : 1/11 Revised edition no: 6.0 Revision date: 2024-12-02

Supersedes version of : 2024-02-02

**NOAL 0687** 

Country: SE / Language: EN

# **Methanol**

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

#### 1.1. Product identifier

Trade name : Methanol SDS no : NOAL\_0687 Other means of identification : Methanol

CAS-No. : 67-56-1

EC-No. : 200-659;200-659-6 EC Index-No. : 603-001-00-X

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use.

Contact supplier for more information on uses.

Uses advised against Consumer use.

Uses other than those listed above are not supported, contact your supplier for more

information on other uses.

### 1.3. Details of the supplier of the safety data sheet

#### Company identification

Supplier

AIR LIQUIDE GAS AB Pulpetgatan 20 215 37 Malmö - SWEDEN T +46 40 38 10 00 info.sweden@airliquide.com

E-Mail address (competent person) : eunordic-sds@airliquide.com

### 1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Sweden	Giftinformationscentralen	Solna Strandväg 21 171 54 Solna	112 – begär Giftinformation	

# **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

# Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards	Flammable liquids, Category 2	H225
Health hazards	Acute toxicity (oral), Category 3	H301
	Acute toxicity (dermal), Category 3	H311
	Acute toxicity (inhal.), Category 3	H331
	Specific target organ toxicity – single exposure, Category 1	H370



Page : 2/11

Revised edition no : 6.0

Revision date : 2024-12-02

Supersedes version of : 2024-02-02

# Methanol NOAL\_0687 Country: SE / Language: EN

#### 2.2. Label elements

Signal word (CLP)

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)







GHS02

GHS08

: Danger

Hazard statements (CLP) : H225 - Highly flammable liquid and vapour.

H301 - Toxic if swallowed.

H311 - Toxic in contact with skin.

H331 - Toxic if inhaled.

H370 - Causes damage to organs.

Precautionary statements (CLP)

- Prevention : P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing

protection.

P271 - Use only outdoors or in a well-ventilated area.

P260 - Do not breathe dust/fume/gas/mist/vapours/spray.

P233 - Keep container tightly closed.

P264 - Wash hands, forearms and face thoroughly after handling.

P270 - Do not eat, drink or smoke when using this product.
P240 - Ground and bond container and receiving equipment.

P241 - Use explosion-proof electrical/ventilating/lighting equipment.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

- Response : P308+P311 - IF exposed or concerned: Call a POISON CENTER or doctor.

P311 - Call a POISON CENTER or doctor.

P321 - Specific treatment (see supplemental first aid instruction on this label).

P330 - Rinse mouth.

P361+P364 - Take off immediately all contaminated clothing and wash it before reuse.

P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P301+P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor.

P302+P352 - IF ON SKIN: Wash with plenty of water.

P370+P378 - In case of fire: Use media other than water to extinguish.

P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing.

Rinse skin with water .

- Storage : P403+P233 - Store in a well-ventilated place. Keep container tightly closed.

P403+P235 - Store in a well-ventilated place. Keep cool.

P405 - Store locked up.

- Disposal considerations : P501 - Dispose of contents/container to hazardous or special waste collection point, in

accordance with local, regional, national and/or international regulation.

2.3. Other hazards

None.

The substance/mixture has no endocrine disrupting properties.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances



Page: 3/11

Revised edition no: 6.0

Revision date: 2024-12-02

Supersedes version of: 2024-02-02

NOAL 0687

STOT SE 1, H370

Country : SE / Language : EN

Name	Product identifier	Composition [V-%]:	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Methanol	CAS-No.: 67-56-1 EC-No.: 200-659;200-659-6	100	Flam. Liq. 2, H225 Acute Tox. 3 (Oral), H301
	EC Index-No.: 603-001-00-X		Acute Tox. 3 (Dermal), H311 Acute Tox. 3 (Inhalation), H331

Contains no other components or impurities which will influence the classification of the product.

**Methanol** 

3.2. Mixtures Not established.

### **SECTION 4: First aid measures**

#### 4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep

victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing

stopped.

Skin contact
 Eye contact
 Adverse effects not expected from this product.
 Adverse effects not expected from this product.

- Ingestion : Ingestion is not considered a potential route of exposure.

# 4.2. Most important symptoms and effects, both acute and delayed

See section 11.

# 4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.

# **SECTION 5: Firefighting measures**

#### 5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.

Product does not burn, use fire control measures appropriate for the surrounding fire.

- Unsuitable extinguishing media : Do not use water jet to extinguish.

#### 5.2. Special hazards arising from the substance or mixture

Specific hazards : Exposure to fire may cause containers to rupture/explode.

#### 5.3. Advice for firefighters

Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat

radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering

sewers and drainage systems.

If possible, stop flow of product.

Use water spray or fog to knock down fire fumes if possible.

Move containers away from the fire area if this can be done without risk.

Special protective equipment for fire fighters : Wear gas tight chemically protective clothing in combination with self contained breathing

apparatus.

Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and

solid particles. Gas-tight chemical protective suits for emergency teams.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

face mask.



Page: 4/11
Revised edition no: 6.0

Revision date : 2024-12-02 Supersedes version of : 2024-02-02

# Methanol NOAL\_0687

Country : SE / Language : EN

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel : Act in accordance with local emergency plan.

Try to stop release. Evacuate area.

Ensure adequate air ventilation.

Stay upwind.

See section 8 of the SDS for more information on personal protective equipment

For emergency responders : Monitor concentration of released product.

Wear self-contained breathing apparatus when entering area unless atmosphere is proved

to be safe.

See section 5.3 of the SDS for more information.

6.2. Environmental precautions

Try to stop release.

#### 6.3. Methods and material for containment and cleaning up

Ventilate area.

6.4. Reference to other sections

See also sections 8 and 13.

## **SECTION 7: Handling and storage**

#### 7.1. Precautions for safe handling

Safe use of the product : Do not breathe gas.

Avoid release of product into atmosphere.

The product must be handled in accordance with good industrial hygiene and safety

procedures.

Only experienced and properly instructed persons should handle gases under pressure.

Consider pressure relief device(s) in gas installations.

Ensure the complete gas system was (or is regularily) checked for leaks before use.

Do not smoke while handling product.

Avoid exposure, obtain special instructions before use.

Use only properly specified equipment which is suitable for this product, its supply pressure

and temperature. Contact your gas supplier if in doubt.

Installation of a cross purge assembly between the container and the regulator is

recommended.

Avoid suck back of water, acid and alkalis.



Page : 5/11

Revised edition no : 6.0

Revision date : 2024-12-02

Revision date : 2024-12-02 Supersedes version of : 2024-02-02

Country: SE / Language: EN

# Methanol NOAL\_0687

Safe handling of the gas receptacle

: Refer to supplier's container handling instructions.

Do not allow backfeed into the container.

Protect containers from physical damage; do not drag, roll, slide or drop.

When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.

Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.

If user experiences any difficulty operating valve discontinue use and contact supplier.

Never attempt to repair or modify container valves or safety relief devices.

Damaged valves should be reported immediately to the supplier.

Keep container valve outlets clean and free from contaminants particularly oil and water. Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.

Close container valve after each use and when empty, even if still connected to equipment. Never attempt to transfer gases from one cylinder/container to another.

Never use direct flame or electrical heating devices to raise the pressure of a container.

Do not remove or deface labels provided by the supplier for the identification of the content of the container.

Suck back of water into the container must be prevented.

Open valve slowly to avoid pressure shock.

#### 7.2. Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers.

Containers should not be stored in conditions likely to encourage corrosion.

Container valve guards or caps should be in place.

Containers should be stored in the vertical position and properly secured to prevent them from falling over.

Stored containers should be periodically checked for general condition and leakage.

Keep container below 50°C in a well ventilated place.

Store containers in location free from fire risk and away from sources of heat and ignition.

Keep away from combustible materials.

#### 7.3. Specific end use(s)

None.

### SECTION 8: Exposure controls/personal protection

#### 8.1. Control parameters

Methanol (67-56-1)	
Sweden - Occupational Exposure Limits	
Local name	Metanol
NGV (OEL TWA)	250 mg/m³
	200 ppm
KGV (OEL STEL)	350 mg/m³
	250 ppm

DNEL (Derived-No Effect Level) : None available.

PNEC (Predicted No-Effect Concentration) : None available.



Page: 6/11 Revised edition no: 6.0 Revision date: 2024-12-02

Supersedes version of: 2024-02-02

# **Methanol**

**NOAL 0687** Country: SE / Language: EN

#### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation.

Product to be handled in a closed system.

Systems under pressure should be regularily checked for leakages. Ensure exposure is below occupational exposure limits (where available). Gas detectors should be used when toxic gases may be released. Consider the use of a work permit system e.g. for maintenance activities.

#### 8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.

The following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

· Eye/face protection Wear safety glasses with side shields.

Standard EN 166 - Personal eye-protection - specifications.

Skin protection

- Hand protection : Wear working gloves when handling gas containers.

> Standard EN 388 - Protective gloves against mechanical risks, performance level 1 or higher. Recommended types include wrist gloves from leather or synthetic material with

equivalent performance, fabric gloves, fabric gloves with leather palms.

- Other Wear safety shoes while handling containers.

Standard EN ISO 20345 - Personal protective equipment - Safety footwear.

· Respiratory protection Gas filters may be used if all surrounding conditions e.g. type and concentration of the

contaminant(s) and duration of use are known.

Use gas filters with full face mask, where exposure limits may be exceeded for a short-term

period, e.g. connecting or disconnecting containers.

Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full

face mask

Consult respiratory device supplier's product information for the selection of the appropriate

device

Gas filters do not protect against oxygen deficiency.

Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks .

Keep self contained breathing apparatus readily available for emergency use.

Self contained breathing apparatus is recommended, where unknown exposure may be

expected, e.g. during maintenance activities on installation systems.

 Thermal hazards None in addition to the above sections.

### 8.2.3. Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

### **SECTION 9: Physical and chemical properties**

#### 9.1. Information on basic physical and chemical properties

Appearance

- Physical state at 20°C / 101.3kPa : Liquid - Colour : Colourless. Odour Pungent.

Odour threshold is subjective and inadequate to warn of overexposure.

рΗ : Not applicable for gases and gas mixtures.

Melting point / Freezing point Not known. Boiling point Not known.

Flash point : Not applicable for gases and gas mixtures.

Flammability Flammable **Explosive limits** 6 - 36 vol % Lower explosion limit : Not available

AIR LIQUIDE GAS AB SE - en 6/11



Page : 7/11

Revised edition no : 6.0
Revision date : 2024-12-02
Supersedes version of : 2024-02-02

Country: SE / Language: EN

7/11

# Methanol NOAL\_0687

Upper explosion limit : Not available Vapour pressure [20°C] : Not available Vapour pressure [50°C] : Not available Density : Not available : Not available

Vapour density : Not applicable for gases and gas mixtures.

Relative density, liquid (water=1) : No reliable data available.
Relative density, gas (air=1) : Lighter or similar to air.
Water solubility : No reliable data available.
Partition coefficient n-octanol/water (Log Kow) : Not applicable for gas mixtures.

Auto-ignition temperature : 455 °C

Decomposition temperature : Not applicable.

Viscosity, kinematic : No reliable data available.

Particle characteristics : Not applicable for gases and gas mixtures.

#### 9.2. Other information

#### 9.2.1. Information with regard to physical hazard classes

Explosive properties : Not applicable.

Oxidising properties : Not applicable.

Critical temperature [°C] : 239,35 °C

9.2.2. Other safety characteristics

Molar mass : 32,04 g/mol

Evaporation rate : Not applicable for gases and gas mixtures.

### **SECTION 10: Stability and reactivity**

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

Avoid moisture in installation systems.

10.5. Incompatible materials

For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not

be produced.

### **SECTION 11: Toxicological information**

# 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Toxic if inhaled.

Toxic in contact with skin.

Skin corrosion/irritation: No known effects from this product.Serious eye damage/irritation: No known effects from this product.Respiratory or skin sensitisation: No known effects from this product.



Page: 8/11
Revised edition no: 6.0
evision date: 2024-12-02

Revision date : 2024-12-02 Supersedes version of : 2024-02-02

Methanol

NOAL\_0687

Country: SE / Language: EN

Germ cell mutagenicity : No known effects from this product.

Carcinogenicity : No known effects from this product.

Toxic for reproduction : Fertility : No known effects from this product.

Toxic for reproduction : unborn child : No known effects from this product.

STOT-single exposure : Causes damage to organs.

STOT-repeated exposure : No known effects from this product.

Aspiration hazard : Not applicable for gases and gas mixtures.

11.2. Information on other hazards

Other information : The substance/mixture has no endocrine disrupting properties.

### **SECTION 12: Ecological information**

### 12.1. Toxicity

EC50 48h - Daphnia magna [mg/l] : No data available. EC50 72h - Algae [mg/l] : No data available. LC50 96 h - Fish [mg/l] : No data available.

## 12.2. Persistence and degradability

No additional information available

### 12.3. Bioaccumulative potential

Assessment : No data available.

12.4. Mobility in soil

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.

Partition into soil is unlikely.

## 12.5. Results of PBT and vPvB assessment

Assessment : No data available.

12.6. Endocrine disrupting properties

The substance/mixture has no endocrine disrupting properties.

12.7. Other adverse effects

Other adverse effects : No known effects from this product.

Effect on the ozone layer : None.

Effect on global warming : No known effects from this product.

### **SECTION 13: Disposal considerations**

#### 13.1. Waste treatment methods

Contact supplier if guidance is required. Must not be discharged to atmosphere.

Ensure that the emission levels from local regulations or operating permits are not

exceeded.

Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at

http://www.eiga.org for more guidance on suitable disposal methods.

Return unused product in original container to supplier.

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)

16 05 04 \*: Gases in pressure containers (including halons) containing hazardous substances.

# 13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

AIR LIQUIDE GAS AB SE - en 8/11



Page : 9/11

Revised edition no : 6.0 Revision date : 2024-12-02

Supersedes version of : 2024-02-02

# NOAL\_0687

Country: SE / Language: EN

# **Methanol**

# **SECTION 14: Transport information**

#### 14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN

UN-No. : 1230

14.2. UN proper shipping name

Transport by road/rail/inland waterways

(ADR/RID/ADN)

: METHANOL

Transport by air (ICAO-TI / IATA-DGR) : Methanol
Transport by sea (IMDG) : METHANOL

14.3. Transport hazard class(es)

Labelling



3 : Flammable liquids.6.1 : Toxic substances.

Transport by road/rail/inland waterways (ADR/RID/ADN)

Class : 3 Classification code : FT1 Hazard identification number : 336

Tunnel Restriction : D/E - Bulk or Tank carriage: Passage forbidden through tunnels of category D and E. Other

carriage: Passage forbidden through tunnels of category E

Transport by air (ICAO-TI / IATA-DGR)

Class / Div. (Sub. risk(s)) : 3 (6.1)

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 3 (6.1)
Emergency Schedule (EmS) - Fire : F-E
Emergency Schedule (EmS) - Spillage : S-D

14.4. Packing group

Transport by road/rail/inland waterways : II - substances presenting medium danger.

(ADR/RID/ADN)

Transport by air (ICAO-TI / IATA-DGR) : II - Medium danger.

Transport by sea (IMDG) : II - substances presenting medium danger.

14.5. Environmental hazards

Transport by road/rail/inland waterways : None.

(ADR/RID/ADN)

Transport by air (ICAO-TI / IATA-DGR) : None.
Transport by sea (IMDG) : None.

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail/inland waterways : P001. (ADR/RID/ADN) IBC02

Transport by air (ICAO-TI / IATA-DGR)

Passenger and Cargo Aircraft : 352.
Cargo Aircraft only : 364.
Transport by sea (IMDG) : P001



Page: 10/11

Revised edition no: 6.0

Revision date: 2024-12-02

Supersedes version of: 2024-02-02

Methanol NOAL\_0687

Country : SE / Language : EN

Special transport precautions

 Avoid transport on vehicles where the load space is not separated from the driver's compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Before transporting product containers:

- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

#### 14.7. Maritime transport in bulk according to IMO instruments

No additional information available

# **SECTION 15: Regulatory information**

#### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### **EU-Regulations**

Restrictions on use : None.

National legislation : Ensure all national/local regulations are observed.

Seveso Directive: 2012/18/EU (Seveso III) : Not covered.

**National regulations** 

Ensure all national/local regulations are observed.

#### 15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.

### **SECTION 16: Other information**

Indication of changes

: Safety data sheet in accordance with commission regulation (EU) No 2020/878.

Section	Changed item	Change	Comments
1.3	Company		Version 5.0. Ny adresse i Sverige. (Denne ændring gælder kun for den svenske (SE) version af dette sikkerhedsdatablad)



Page : 11/11
Revised edition no : 6.0
Revision date : 2024-12-02

Revision date : 2024-12-02 Supersedes version of : 2024-02-02

NOAL\_0687

Country: SE / Language: EN

Methanol

Abbreviations and acronyms

: ATE - Acute Toxicity Estimate

CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation

(EC) No 1907/2006

EINECS - European Inventory of Existing Commercial Chemical Substances

CAS# - Chemical Abstract Service number

PPE - Personal Protection Equipment

LC50 - Lethal Concentration to 50 % of a test population

RMM - Risk Management Measures

PBT - Persistent, Bioaccumulative and Toxic

vPvB - Very Persistent and Very Bioaccumulative

STOT- SE: Specific Target Organ Toxicity - Single Exposure

CSA - Chemical Safety Assessment

EN - European Standard

UN - United Nations

ADR - Agreement concerning the International Carriage of Dangerous Goods by Road

IATA - International Air Transport Association

IMDG code - International Maritime Dangerous Goods

RID - Regulations concerning the International Carriage of Dangerous Goods by Rail

WGK - Water Hazard Class

STOT - RE : Specific Target Organ Toxicity - Repeated Exposure

UFI: Unique Formula Identifier

: Users of breathing apparatus must be trained.

Ensure operators understand the toxicity hazard.

: Classification in accordance with the procedures and calculation methods of Regulation

(EC) 1272/2008 (CLP).

Key literature references and sources of data are maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at http://www.Eiga.eu .

Full text of H- and EUH-statements		
Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3	
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3	
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3	
Flam. Liq. 2	Flammable liquids, Category 2	
H225	Highly flammable liquid and vapour.	
H301	Toxic if swallowed.	
H311	Toxic in contact with skin.	
H331	Toxic if inhaled.	
H370	Causes damage to organs.	
STOT SE 1	Specific target organ toxicity – single exposure, Category 1	

DISCLAIMER OF LIABILITY

Training advice

Further information

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

**End of document**