Air Liquide

SAFETY DATA SHEET

Page : 1/12

Revised edition no : 6.0 Revision date : 2024-02-02

Supersedes version of : 2023-01-23

ALPHAGAZ MIX CH4 10%/AR

NOAL_1005 UFI: T9S2-00K9-400E-E2EM

Country : SE / Language : EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name	:	ALPHAGAZ MIX CH4 10%/AR
SDS no	:	NOAL_1005
		UFI: T9S2-00K9-400E-E2EM

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	: Industrial and professional uses. Perform risk assessment prior to use.
	Industrial and professional use for chemical analysis, calibration, (routine) quality control,
	laboratory use, under controlled conditions.
	Contact supplier for more information on uses.
Uses advised against	: Consumer use.
	Uses other than those listed above are not supported, contact your supplier for more
	information on other uses.

1.3. Details of the supplier of the safety data sheet

Company identification Supplier AIR LIQUIDE GAS AB Pulpetgatan 20 215 37 Malmö - SWEDEN

T +46 40 38 10 00 info.sweden@airliquide.com

E-Mail address (competent person)

: eunordic-sds@airliquide.com

1.4. Emergency telephone number

Emergency telephone number

: 112 Availability (24 / 7)

Country	Organisation/Company	Address	Emergency number	Comment
Germany	Giftnotruf Erfurt Gemeinsames Giftinformationszentrum der Länder Mecklenburg-Vorpommern, Sachsen, Sachsen-Anhalt und Thüringen, c/o HELIOS Klinikum Erfurt	Nordhäuser Straße 74 99089 Erfurt	+49 (0) 361 730 730	

H221

H280

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Physical hazards	Flammable gases, Category 1B
	Gases under pressure : Compressed gas

	SAFETY DATA SHEET		
Air Liquide			
		Revision date : 2024-02-02	
		Supersedes version of : 2023-01-23	
ALPHA	GAZ MIX CH4 10%/AR	NOAL_1005	
<i>,</i> . _ , . <i>,</i> .		UFI: T9S2-00K9-400E-	
		E2EM	
		Country : SE / Language : EN	
2.2. Label elements		!	
Labelling according to Regulation (EC)	No. 1272/2008 [CLP]		
Hazard pictograms (CLP)			
	GHS02 GHS04		
Signal word (CLP)	: Danger		
Hazard statements (CLP)	: H221 - Flammable gas.		
	H280 - Contains gas under pressure; may explod	e if heated.	
Precautionary statements (CLP)			
- Prevention	: P210 - Keep away from heat, hot surfaces, sparks	s, open flames and other ignition sources.	
	No smoking.		
- Response	: P377 - Leaking gas fire: Do not extinguish, unless		
_	P381 - In case of leakage, eliminate all ignition so	urces.	
- Storage	: P403 - Store in a well-ventilated place.		
2.2 Other hererde			
2.3. Other hazards			
2.3. Other hazards	None.		
	None. Not classified as PBT or vPvB.		

SECTION 3: Composition/information on ingredients

3.1. Substances

Not established.

3.2. Mixtures

Name	Product identifier	Composition [V- %]:	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Argon	CAS-No.: 7440-37-1 EC-No.: 231-147-0 EC Index-No.: REACH-no: *1	90	Press. Gas (Comp.), H280
Methane	CAS-No.: 74-82-8 EC-No.: 200-812-7 EC Index-No.: 601-001-00-4 REACH-no: 01-2119474442-39	10	Flam. Gas 1A, H220 Press. Gas (Comp.), H280

Full text of H- and EUH-statements: see section 16

Contains no other components or impurities which will influence the classification of the product.

*1: Listed in Annex IV / V REACH, exempted from registration.

*3: Registration not required: Substance manufactured or imported < 1t/y.

	SAFETY DATA SHEET	Page : 3/12			
O Air Liquide		Revised edition no : 6.0			
G Hil Liquide		Revision date : 2024-02-02			
		Supersedes version of : 2023-01-2			
ALPHA	NOAL_1005 UFI: T9S2-00K9-400E E2EM				
		Country : SE / Language : EN			
SECTION 4: First aid measure	S				
4.1. Description of first aid measures					
· Inhalation · Skin contact	 Remove victim to uncontaminated area wearing s victim warm and rested. Call a doctor. Perform ca stopped. Adverse effects not expected from this product. 				
- Eye contact	: Adverse effects not expected from this product.				
- Ingestion	: Ingestion is not considered a potential route of exposure.				
4.2. Most important symptoms and eff	fects, both acute and delayed				
	See section 11.				
4.3. Indication of any immediate medi	cal attention and special treatment needed				
, ,,,,,,	None.				
SECTION 5: Firefighting meas	ures				
5.1. Extinguishing media					
- Suitable extinguishing media - Unsuitable extinguishing media	Water spray or fog.Carbon dioxide.Do not use water jet to extinguish.				
5.2. Special hazards arising from the	substance or mixture				
Specific hazards Hazardous combustion products	 Exposure to fire may cause containers to rupture/explode. Carbon monoxide. 				
5.3. Advice for firefighters					
Specific methods	 Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes if possible. Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosiv re-ignition may occur. Extinguish any other fire. Move containers away from the fire area if this can be done without risk. In confined space use self-contained breathing apparatus. Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire 				
Special protective equipment for fire fight	sewers and drainage systems. If possible, stop flow of product. Use water spray or fog to knock down fire fumes Do not extinguish a leaking gas flame unless abs re-ignition may occur. Extinguish any other fire. Move containers away from the fire area if this casters : In confined space use self-contained breathing a	if possible. olutely necessary. Spontaneous/explosive in be done without risk. oparatus.			

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures For non-emergency personnel : Act in accordance with local emergency plan. Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous. Stay upwind. See section 8 of the SDS for more information on personal protective equipment

	SAFETY DATA SHEET	Page : 4/12			
O Air Liquide		Revised edition no : 6.0			
		Revision date : 2024-02-02			
		Supersedes version of : 2023-01-2			
ALPHA	GAZ MIX CH4 10%/AR	NOAL_1005 UFI: T9S2-00K9-400E E2EM			
		Country : SE / Language : EN			
or emergency responders	: See section 5.3 of the SDS for more information.				
5.2. Environmental precautions					
	Try to stop release.				
.3. Methods and material for containn	nent and cleaning up				
	Ventilate area.				
4 Potoronoo to other costions					
6.4. Reference to other sections	Coo also contiano () and (2)				
	See also sections 8 and 13.				
SECTION 7: Handling and stora	age				
7.1. Precautions for safe handling					
afe use of the product	: Do not breathe gas.				
	Avoid release of product into atmosphere.				
		The product must be handled in accordance with good industrial hygiene and safety			
	procedures.	•			
	Only experienced and properly instructed persons	Only experienced and properly instructed persons should handle gases under pressure.			
		Consider pressure relief device(s) in gas installations.			
		Ensure the complete gas system was (or is regularily) checked for leaks before use.			
	Do not smoke while handling product.				
	Use only properly specified equipment which is suitable for this product, its supply pressure				
	and temperature. Contact your gas supplier if in doubt.				
	Avoid suck back of water, acid and alkalis.				
		Assess the risk of potentially explosive atmospheres and the need for explosion-proof			
	Purge air from system before introducing gas.	equipment. Purce air from system before introducing gas			
		Take precautionary measures against static discharge.			
	Keep away from ignition sources (including static d	-			
	Consider the use of only non-sparking tools.	S ,			
	Ensure equipment is adequately earthed.				
Safe handling of the gas receptacle	: Refer to supplier's container handling instructions.				
	Do not allow backfeed into the container.				
	Protect containers from physical damage; do not d	-			
	When moving cylinders, even for short distances, u	use a cart (trolley, hand truck, etc.)			
	designed to transport cylinders.				
	Leave valve protection caps in place until the conta	Leave valve protection caps in place until the container has been secured against either a			
	well or bonch or placed in a container stand and is	roady for use			
	wall or bench or placed in a container stand and is	-			
	If user experiences any difficulty operating valve di	iscontinue use and contact supplier.			
	If user experiences any difficulty operating valve di Never attempt to repair or modify container valves	iscontinue use and contact supplier. or safety relief devices.			
	If user experiences any difficulty operating valve di Never attempt to repair or modify container valves Damaged valves should be reported immediately t	iscontinue use and contact supplier. or safety relief devices. o the supplier.			
	If user experiences any difficulty operating valve di Never attempt to repair or modify container valves	iscontinue use and contact supplier. or safety relief devices. to the supplier. ontaminants particularly oil and water.			
	If user experiences any difficulty operating valve di Never attempt to repair or modify container valves Damaged valves should be reported immediately t Keep container valve outlets clean and free from c	iscontinue use and contact supplier. or safety relief devices. to the supplier. ontaminants particularly oil and water.			
	If user experiences any difficulty operating valve di Never attempt to repair or modify container valves Damaged valves should be reported immediately t Keep container valve outlets clean and free from c Replace valve outlet caps or plugs and container c	iscontinue use and contact supplier. or safety relief devices. to the supplier. contaminants particularly oil and water. caps where supplied as soon as containe			
	If user experiences any difficulty operating valve di Never attempt to repair or modify container valves Damaged valves should be reported immediately t Keep container valve outlets clean and free from c Replace valve outlet caps or plugs and container c is disconnected from equipment.	iscontinue use and contact supplier. or safety relief devices. to the supplier. contaminants particularly oil and water. caps where supplied as soon as containe apty, even if still connected to equipment.			
	If user experiences any difficulty operating valve di Never attempt to repair or modify container valves Damaged valves should be reported immediately to Keep container valve outlets clean and free from c Replace valve outlet caps or plugs and container c is disconnected from equipment. Close container valve after each use and when em Never attempt to transfer gases from one cylinder/ Never use direct flame or electrical heating devices	iscontinue use and contact supplier. or safety relief devices. to the supplier. contaminants particularly oil and water. caps where supplied as soon as containe upty, even if still connected to equipment. container to another. s to raise the pressure of a container.			
	If user experiences any difficulty operating valve di Never attempt to repair or modify container valves Damaged valves should be reported immediately to Keep container valve outlets clean and free from c Replace valve outlet caps or plugs and container c is disconnected from equipment. Close container valve after each use and when em Never attempt to transfer gases from one cylinder/ Never use direct flame or electrical heating devices Do not remove or deface labels provided by the su	iscontinue use and contact supplier. or safety relief devices. to the supplier. contaminants particularly oil and water. caps where supplied as soon as containe upty, even if still connected to equipment. container to another. s to raise the pressure of a container.			
	If user experiences any difficulty operating valve di Never attempt to repair or modify container valves Damaged valves should be reported immediately to Keep container valve outlets clean and free from o Replace valve outlet caps or plugs and container of is disconnected from equipment. Close container valve after each use and when em Never attempt to transfer gases from one cylinder/ Never use direct flame or electrical heating devices Do not remove or deface labels provided by the su of the container.	iscontinue use and contact supplier. or safety relief devices. to the supplier. contaminants particularly oil and water. caps where supplied as soon as containe hpty, even if still connected to equipment. container to another. s to raise the pressure of a container. upplier for the identification of the content			
	If user experiences any difficulty operating valve di Never attempt to repair or modify container valves Damaged valves should be reported immediately to Keep container valve outlets clean and free from c Replace valve outlet caps or plugs and container c is disconnected from equipment. Close container valve after each use and when em Never attempt to transfer gases from one cylinder/ Never use direct flame or electrical heating devices Do not remove or deface labels provided by the su	iscontinue use and contact supplier. or safety relief devices. to the supplier. contaminants particularly oil and water. caps where supplied as soon as containe hpty, even if still connected to equipment. container to another. s to raise the pressure of a container. upplier for the identification of the content			

Page : 5/12 Revised edition no : 6.0 Revision date : 2024-02-02 Supersedes version of : 2023-01-23 R NOAL_1005 UFI: T9S2-00K9-400E- E2EM Country : SE / Language : EN
Supersedes version of : 2023-01-23 NOAL_1005 UFI: T9S2-00K9-400E- E2EM
UFI: T9S2-00K9-400E- E2EM
UFI: T9S2-00K9-400E- E2EM
UFI: T9S2-00K9-400E- E2EM
E2EM
Country : SE / Language : EN
·
d local requirements regarding storage of containers. tored in conditions likely to encourage corrosion. caps should be in place. d in the vertical position and properly secured to prevent them e periodically checked for general condition and leakage. c in a well ventilated place. free from fire risk and away from sources of heat and ignition. ble materials. ses and other oxidants in store. he storage areas should be compatible with the risk of a
phere.
phere.

8.1. Control parameters

Methane (74-82-8)				
Belgium - Occupational Exposure Limits				
Local name Hydrocarbures aliphatiques sous forme gazeuse : (Alcanes C1-C4 Alifatische koolwaterstoffen in gas-vorm : Alkanen (C1-C4)				
OEL TWA [ppm]	1000 ppm			
Bulgaria - Occupational Exposure Limits				
Local name	Метан			
OEL TWA 500 mg/m ³				
Finland - Occupational Exposure Limits				
Local name	Metaani			
HTP (OEL TWA) [2] 1000 ppm				
Ireland - Occupational Exposure Limits				
Local name	Methane			
OEL TWA [2] 1000 ppm				
Romania - Occupational Exposure Limits				
Local name	Metan			
OEL TWA	1200 mg/m ³			
OEL TWA [ppm]	1834 ppm			
OEL STEL	1500 mg/m³			
OEL STEL [ppm] 2292 ppm				

\mathbf{O}	Air	Liq	uid	e

SAFETY DATA SHEET

Page : 6/12 Revised edition no : 6.0

Revision date : 2024-02-02

Supersedes version of : 2023-01-23

ALPHAGAZ MIX CH4 10%/AR

NOAL_1005 UFI: T9S2-00K9-400E-E2EM

Country : SE / Language : EN

Switzerland - Occupational Exposure Limits	6			
Local name		Methan		
MAK (OEL TWA) [1]		6700 mg/m ³		
MAK (OEL TWA) [2]	10000 ppm			
Remark		Formal ^{KT}		
DNEL (Derived-No Effect Level)	: None establis	shed.		
PNEC (Predicted No-Effect Concentration)	: None establis	shed.		
8.2. Exposure controls				
8.2.1. Appropriate engineering controls				
Provide adequate general and local exhaust ventilation. Product to be handled in a closed system. Systems under pressure should be regularily checked for leakages. Ensure exposure is below occupational exposure limits (where available). Gas detectors should be used when flammable gases/vapours may be released. Consider the use of a work permit system e.g. for maintenance activities.		e handled in a closed system. ler pressure should be regularily checked for leakages. sure is below occupational exposure limits (where available). s should be used when flammable gases/vapours may be released.		
8.2.2. Individual protection measures, e.g. personal protective equipment				
• Eye/face protection • Skin protection	 A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered: PPE compliant to the recommended EN/ISO standards should be selected. Wear safety glasses with side shields. Standard EN 166 - Personal eye-protection - specifications. 			
- Hand protection	: Wear working	: Wear working gloves when handling gas containers.		
	Standard EN	388 - Protective gloves against mechanical risk, performance level 1 or higher.		
- Other	Standard EN Standard EN Wear safety s	use of flame resistant anti-static safety clothing. ISO 14116 - Limited flame spread materials. 1149-5 - Protective clothing: Electrostatic properties. shoes while handling containers. ISO 20345 - Personal protective equipment - Safety footwear.		
Respiratory protection	contaminant(Use gas filter period, e.g. c Standard EN face mask. When indicat selection of th anticipated ex selected RPE Recommende Gas filters do Standard EN	 Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known. Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers. Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full 		
• Thermal hazards	expected, e.g	g. during maintenance activities on installation systems. tion to the above sections.		



SAFETY DATA SHEET

Page : 7/12

Revised edition no : 6.0 Revision date : 2024-02-02

Supersedes version of : 2023-01-23

ALPHAGAZ MIX CH4 10%/AR

NOAL_1005 UFI: T9S2-00K9-400E-E2EM

Country : SE / Language : EN

8.2.3. Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	
- Physical state at 20°C / 101.3kPa	: Gas
- Colour	: Colourless
Odour	: Odourless.
	Odour threshold is subjective and inadequate to warn of overexposure.
рН	: Not applicable for gases and gas mixtures.
Melting point / Freezing point	: Not applicable for gas mixtures.
Boiling point	: Not applicable for gas mixtures.
Flash point	: Not applicable for gases and gas mixtures.
Flammability	: Extremely flammable gas
Explosive limits	: Flammability range not available.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Vapour pressure [20°C]	: Not applicable.
Vapour pressure [50°C]	: Not applicable.
Density	: Not applicable
Vapour density	: Not applicable for gases and gas mixtures.
Relative density, liquid (water=1)	: Not applicable
Relative density, gas (air=1)	: Heavier than air.
Water solubility	: Solubility in water of component(s) of the mixture :
	Argon: 67.3 mg/l Methane: 26 mg/l
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for gas mixtures.
Auto-ignition temperature	: Not known.
Decomposition temperature	: Not applicable.
Viscosity, kinematic	: No reliable data available.
Particle characteristics	: Not applicable for gases and gas mixtures.

9.2. Other information

9.2.1. Information with regard to physical hazard classes

o , , ,	
Explosive properties	: Not applicable.
Oxidising properties	: Not applicable.
9.2.2. Other safety characteristics	
Molar mass	: Not applicable for gas mixtures.
Evaporation rate	: Not applicable for gases and gas mixtures.
Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability

Stable under normal conditions.

	SAFETY DATA SHEET	Page : 8/12
Air Liquide		Revised edition no : 6.0
e ni ciquide		Revision date : 2024-02-02
		Supersedes version of : 2023-01-2
ALPHA	GAZ MIX CH4 10%/AR	NOAL_1005
		UFI: T9S2-00K9-400E
		E2EM
		Country : SE / Language : EN
10.3. Possibility of hazardous reaction	<u>15</u>	
	Can form explosive mixture with air. May react violently with oxidants.	
Reactivity	 This mixture contains components with the follow with air. May react violently with oxidants. 	ving reactivity : Can form explosive mixture
10.4. Conditions to avoid		
	Keep away from heat, hot surfaces, sparks, oper smoking.	n flames and other ignition sources. No
	Avoid moisture in installation systems.	
10.5. Incompatible materials		
	Air, Oxidisers.	
	For additional information on compatibility refer to	o ISO 11114.
10.6. Hazardous decomposition produ	icts	
	Under normal conditions of storage and use, haz be produced.	ardous decomposition products should not

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity	: Toxicological effects not expected from this product if occupational exposure limit values are not exceeded.
Skin corrosion/irritation	: No known effects from this product.
Serious eye damage/irritation	: No known effects from this product.
Respiratory or skin sensitisation	: No known effects from this product.
Germ cell mutagenicity	: No known effects from this product.
Carcinogenicity	: No known effects from this product.
Toxic for reproduction : Fertility	: No known effects from this product.
Toxic for reproduction : unborn child	: No known effects from this product.
STOT-single exposure	: No known effects from this product.
STOT-repeated exposure	: No known effects from this product.
Aspiration hazard	: Not applicable for gases and gas mixtures.
11.2. Information on other hazards	
Other information	: The substance/mixture has no endocrine disrupting properties.

SECTION 12: Ecological information

12.1. Toxicity

Assessment	: Classification criteria are not met.
EC50 48h - Daphnia magna [mg/l]	: No data available.
EC50 72h - Algae [mg/l]	: No data available.
LC50 96 h - Fish [mg/l]	: No data available.

Methane (74-82-8)

EC50 48h - Daphnia magna [mg/l]	69.4 mg/l

	SAFETY DATA SHEET	Page : 9/12
O Air Liquide	OAI ETT DATA ONEET	Revised edition no : 6.0
C HII LIQUIDE		Revision date : 2024-02-02
		Supersedes version of : 2023-01-2
ALPHA	GAZ MIX CH4 10%/AR	NOAL_1005 UFI: T9S2-00K9-400E E2EM Country : SE / Language : EN
Methane (74-82-8)		Country . SE / Language . EN
EC50 72h - Algae [mg/l]	19.4 mg/l	
LC50 96 h - Fish [mg/l]	147.5 mg/l	
12.2. Persistence and degradability		
Assessment	: No data available.	
12.3. Bioaccumulative potential		
Assessment	: No data available.	
<u>12.4. Mobility in soil</u>		
Assessment	: Because of its high volatility, the product is un Partition into soil is unlikely.	nlikely to cause ground or water pollution.
12.5. Results of PBT and vPvB assess	sment	
Assessment	: Not classified as PBT or vPvB.	
12.6. Endocrine disrupting properties		
	The substance/mixture has no endocrine disr	upting properties.
12.7. Other adverse effects		
Other adverse effects	: No known effects from this product.	
Effect on the ozone layer	: None.	
Effect on global warming	: Contains greenhouse gas(es).	

SECTION 13: Disposal considerations

13.1.	Waste	treatment	methods
-------	-------	-----------	---------

	Contact supplier if guidance is required.
	Do not discharge into areas where there is a risk of forming an explosive mixture with air.
	Waste gas should be flared through a suitable burner with flash back arrestor.
	Do not discharge into any place where its accumulation could be dangerous.
	Ensure that the emission levels from local regulations or operating permits are not exceeded.
	Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at
	http://www.eiga.org for more guidance on suitable disposal methods.
	Return unused product in original container to supplier.
List of hazardous waste codes (from Commission Decision 2000/532/EC as amended)	: 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.
13.2. Additional information	
	External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information


14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN UN-No. : 1954

Air Liquide

SAFETY DATA SHEET

ALPHAGAZ MIX CH4 10%/AR



Page : 10/12

NOAL_1005 UFI: T9S2-00K9-400E-E2EM

Country : SE / Language : EN

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Transport by sea (IMDG)

14.3. Transport hazard class(es)



Transport by road/rail (ADR/RID)

Class Classification code Hazard identification number Tunnel Restriction

Transport by air (ICAO-TI / IATA-DGR) Class / Div. (Sub. risk(s))

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) Emergency Schedule (EmS) - Fire Emergency Schedule (EmS) - Spillage

14.4. Packing group

Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Transport by sea (IMDG)

14.5. Environmental hazards

Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Transport by sea (IMDG)

14.6. Special precautions for user

Packing Instruction(s) Transport by road/rail (ADR/RID) Transport by air (ICAO-TI / IATA-DGR) Passenger and Cargo Aircraft Cargo Aircraft only Transport by sea (IMDG)

Special transport precautions

- : COMPRESSED GAS, FLAMMABLE, N.O.S. (Methane, Argon)
- : Compressed gas, flammable, n.o.s. (Methane, Argon)
- : COMPRESSED GAS, FLAMMABLE, N.O.S. (Methane, Argon)



2.1 : Flammable gases.

- : 2
- : 1F
- : 23
- : B/D Tank carriage: Passage forbidden through tunnels of category B, C, D and E. Other carriage: Passage forbidden through tunnels of category D and E
- : 2.1
- : 2.1
- : F-D
- : S-U
- : Not established.
- : Not established.
- : Not established.
- : None.
- : None.
- : None.
- : P200
- : Forbidden.
- : 200.
- : P200
- : Avoid transport on vehicles where the load space is not separated from the driver's compartment.

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

- Before transporting product containers:
- Ensure there is adequate ventilation.
- Ensure that containers are firmly secured.
- Ensure valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.



SAFETY DATA SHEET

Page : 11/12

Revised edition no : 6.0 Revision date : 2024-02-02

Supersedes version of : 2023-01-23

ALPHAGAZ MIX CH4 10%/AR

NOAL_1005 UFI: T9S2-00K9-400E-E2EM

Country : SE / Language : EN

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture **EU-Regulations** Listed on REACH Annex XVII (Restriction Conditions). The following restrictions are applicable: Reference Applicable on code 40. ALPHAGAZ MIX CH4 10%/AR Restrictions on use : None. Contains no substance(s) listed on the REACH Candidate List National legislation Ensure all national/local regulations are observed. Seveso Directive : 2012/18/EU (Seveso III) Covered. National regulations Ensure all national/local regulations are observed. Germany Water hazard class (WGK) : WGK nwg, Non-hazardous to water (Classification according to AwSV, Annex 1) National Rules and Recommendations : [German regulations] BetriebssicherheitsV mit TRBSen insbesondere TRBS 3145 / TRGS 725 Ortsbewegliche Druckgasbehälter", TRBS 2141, BGRegel 500 Teil 2.33: "Umgang mit Gasen", GefahrstoffV mit Technischen Regeln Gefährliche Stoffe TRGS insbesondere TRGS 407 "Tätigkeiten mit Gasen - Gefährdungsbeurteilung", TRGS 400, 500, 510, 900." BGR 104, TRBS 2152. Netherlands SZW-lijst van kankerverwekkende stoffen : None of the components are listed SZW-lijst van mutagene stoffen None of the components are listed : SZW-lijst van reprotoxische stoffen - Borstvoeding : None of the components are listed SZW-lijst van reprotoxische stoffen -: None of the components are listed Vruchtbaarheid SZW-lijst van reprotoxische stoffen - Ontwikkeling : None of the components are listed Denmark **Danish National Regulations** : Young people below the age of 18 years are not allowed to use the product 15.2. Chemical safety assessment A CSA does not need to be carried out for this product.

SECTION 16: Other information

Indication of changes

: Safety data sheet in accordance with commission regulation (EU) No 2020/878.

Section	Changed item	Change	Comments
1.3	Company	Modified	Version 6.0. New address in Sweden. (This change only applies to the Swedish (SE) version of this SDS)

	SAFETY DATA SHEET	Page : 12/12
O Air Liquide	OAIEIT DATA ONEET	Revised edition no : 6.0
		Revision date : 2024-02-02
		Supersedes version of : 2023-01-23
ALPHA	GAZ MIX CH4 10%/AR	NOAL_1005 UFI: T9S2-00K9-400E- E2EM
		Country : SE / Language : EN
REACH - Registration, Evaluation, A (EC) No 1907/2006 EINECS - European Inventory of Exis CAS# - Chemical Abstract Service on PPE - Personal Protection Equipmen LC50 - Lethal Concentration to 50 % RMM - Risk Management Measures PBT - Persistent, Bioaccumulative ar vPvB - Very Persistent and Very Bioa STOT- SE : Specific Target Organ To CSA - Chemical Safety Assessment EN - European Standard UN - United Nations ADR - European Agreement concern Road IATA - International Air Transport Ass IMDG code - International Maritime I RID - Regulations concerning the Inter-		Country : SE / Language : EN regulation; Regulation (EC) No 1272/2008 horisation and Restriction of Chemicals Regulation ng Commercial Chemical Substances nber f a test population Toxic cumulative icity - Single Exposure g the International Carriage of Dangerous Goods by reiation
Training advice Further information	 Ensure operators understand the flammability haz Classification using data from databases maintain Association (EIGA). Data is maintained in EIGA d Guide', downloadable at : http://www.eiga.eu. Classification in accordance with the procedures a (EC) 1272/2008 (CLP). 	ed by the European Industrial Gases oc 169 : 'Classification and Labelling

Full text of H- and EUH-statements		
Flam. Gas 1A Flammable gases, Category 1A		
Flam. Gas 1B	Flammable gases, Category 1B	
H220	Extremely flammable gas.	
H221	Flammable gas.	
H280	Contains gas under pressure; may explode if heated.	
Press. Gas (Comp.)	Gases under pressure : Compressed gas	

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.

Details given in this document are believed to be correct at the time of going to press. Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document