

Phosphine**NOAL_0100**

Country : SE / Language : EN

SECTION 1: Identification of the substance/mixture and of the company/undertaking**1.1. Product identifier**

Trade name : Phosphine
SDS no : NOAL_0100
Other means of identification : Phosphine
CAS-No. : 7803-51-2
EC-No. : 232-260-8
EC Index-No. : 015-181-00-1
REACH registration No : 01-2119462840-39
Chemical formula : PH₃

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use.
Test gas/Calibration gas.
Laboratory use.
Contact supplier for more information on uses.
Uses advised against : Consumer use.
Uses other than those listed above are not supported, contact your supplier for more information on other uses.

1.3. Details of the supplier of the safety data sheet**Company identification****Supplier**

AIR LIQUIDE GAS AB
Lundavägen 151
212 09 Malmö - SWEDEN
T +46 40 38 10 00
info.sweden@airliquide.com


E-Mail address (competent person) : eunordic-sds@airliquide.com

1.4. Emergency telephone number

Emergency telephone number : 112
Availability
(24 / 7)

SECTION 2: Hazards identification**2.1. Classification of the substance or mixture****Classification according to Regulation (EC) No. 1272/2008 [CLP]**


Physical hazards	Flammable gases, Category 1A	H220
	Gases under pressure : Liquefied gas	H280
Health hazards	Acute toxicity (inhalation:gas) Category 1	H330
	Skin corrosion/irritation, Category 1, Sub-Category 1B	H314
	Serious eye damage/eye irritation, Category 1	H318
Environmental hazards	Hazardous to the aquatic environment – Acute Hazard, Category 1	H400

	SAFETY DATA SHEET	Page : 2/18
		Revised edition no : 5.0
		Revision date : 2023-01-21
		Supersedes version of : 2021-11-02
Phosphine		NOAL_0100
		Country : SE / Language : EN

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



Signal word (CLP) :

Danger

Hazard statements (CLP) :

H314 - Causes severe skin burns and eye damage.
 H220 - Extremely flammable gas.
 H280 - Contains gas under pressure; may explode if heated.
 H330 - Fatal if inhaled.
 H400 - Very toxic to aquatic life.
 EUH071 - Corrosive to the respiratory tract.

Precautionary statements (CLP)

- Prevention

: P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.
 P271 - Use only outdoors or in a well-ventilated area.
 P273 - Avoid release to the environment.
 P260 - Do not breathe dust/fume/gas/mist/vapours/spray.
 P284 - Wear respiratory protection.
 P264 - Wash hands, forearms and face thoroughly after handling.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

- Response

: P391 - Collect spillage.
 P321 - Specific treatment (see supplemental first aid instruction on this label).
 P320 - Specific treatment is urgent (see supplemental first aid instruction on this label).
 P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P310 - Immediately call a POISON CENTER or doctor.
 P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.
 P381 - In case of leakage, eliminate all ignition sources.
 P381 - In case of leakage, eliminate all ignition sources.
 P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
 P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .
 P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

- Storage

: P403+P233 - Store in a well-ventilated place. Keep container tightly closed.
 P405 - Store locked up.
 P403 - Store in a well-ventilated place.
 P410+P403 - Protect from sunlight. Store in a well-ventilated place.

- Disposal considerations


: P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards

May ignite spontaneously if exposed to air.
 The substance/mixture has no endocrine disrupting properties.

SECTION 3: Composition/information on ingredients

3.1. Substances

	SAFETY DATA SHEET		Page : 3/18
			Revised edition no : 5.0
			Revision date : 2023-01-21
			Supersedes version of : 2021-11-02
Phosphine			NOAL_0100
			Country : SE / Language : EN
Name	Product identifier	Composition [V-%]:	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Phosphine	CAS-No.: 7803-51-2 EC-No.: 232-260-8 EC Index-No.: 015-181-00-1 REACH registration No: 01-2119462840-39	100	Flam. Gas 1A, H220 Press. Gas (Liq.), H280 Acute Tox. 1 (Inhalation:gas), H330 Skin Corr. 1B, H314 Eye Dam. 1, H318 Aquatic Acute 1, H400

Contains no other components or impurities which will influence the classification of the product.

3.2. Mixtures

Not established.

SECTION 4: First aid measures

4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : Remove contaminated clothing. Drench affected area with water for at least 15 minutes. In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

4.2. Most important symptoms and effects, both acute and delayed

May cause severe chemical burns to skin and cornea. Suitable first-aid treatment should be immediately available. Seek medical advice before using product.
Material is destructive to tissue of the mucuous membranes and upper respiratory tract.
Cough, shortness of breath, headache, nausea.
See section 11.

4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.
Treat with corticosteroid spray as soon as possible after inhalation.


SECTION 5: Firefighting measures

5.1. Extinguishing media

- Suitable extinguishing media : Water spray or fog.
- Unsuitable extinguishing media : Carbon dioxide.
Do not use water jet to extinguish.

5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
Escaping gas cannot be extinguished.
- Hazardous combustion products : Phosphorus oxides/acids.

	SAFETY DATA SHEET	Page : 4/18
		Revised edition no : 5.0
		Revision date : 2023-01-21
		Supersedes version of : 2021-11-02
Phosphine		NOAL_0100
		Country : SE / Language : EN

5.3. Advice for firefighters

Specific methods	<p>: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.</p> <p>If possible, stop flow of product.</p> <p>Use water spray or fog to knock down fire fumes if possible.</p> <p>Do not extinguish a leaking gas flame unless absolutely necessary. Spontaneous/explosive re-ignition may occur. Extinguish any other fire.</p> <p>Move containers away from the fire area if this can be done without risk.</p>
Special protective equipment for fire fighters	<p>: Wear gas tight chemically protective clothing in combination with self contained breathing apparatus.</p> <p>Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Gas-tight chemical protective suits for emergency teams.</p> <p>Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.</p>

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel	<p>: Act in accordance with local emergency plan.</p> <p>Try to stop release.</p> <p>Evacuate area.</p> <p>Ensure adequate air ventilation.</p> <p>Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.</p> <p>Stay upwind.</p> <p>See section 8 of the SDS for more information on personal protective equipment</p>
For emergency responders	<p>: Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.</p> <p>Use chemically protective clothing.</p> <p>Monitor concentration of released product.</p> <p>See section 5.3 of the SDS for more information.</p>

6.2. Environmental precautions


Reduce vapour with fog or fine water spray.
Try to stop release.

6.3. Methods and material for containment and cleaning up

Hose down area with water.
Wash contaminated equipment or sites of leaks with copious quantities of water.

6.4. Reference to other sections

See also sections 8 and 13.

	SAFETY DATA SHEET	Page : 5/18
		Revised edition no : 5.0
		Revision date : 2023-01-21
		Supersedes version of : 2021-11-02
Phosphine		NOAL_0100
		Country : SE / Language : EN

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Safe use of the product

- : Do not breathe gas.
- Avoid release of product into atmosphere.
- The product must be handled in accordance with good industrial hygiene and safety procedures.
- Only experienced and properly instructed persons should handle gases under pressure.
- Consider pressure relief device(s) in gas installations.
- Ensure the complete gas system was (or is regularly) checked for leaks before use.
- Do not smoke while handling product.
- Avoid exposure, obtain special instructions before use.
- Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.
- Installation of a cross purge assembly between the container and the regulator is recommended.
- Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service.
- Avoid suck back of water, acid and alkalis.
- Assess the risk of potentially explosive atmospheres and the need for explosion-proof equipment.
- Purge air from system before introducing gas.
- Take precautionary measures against static discharge.
- Keep away from ignition sources (including static discharges).
- Consider the use of only non-sparking tools.
- Ensure equipment is adequately earthed.

Safe handling of the gas receptacle

- : Refer to supplier's container handling instructions.
- Do not allow backfeed into the container.
- Protect containers from physical damage; do not drag, roll, slide or drop.
- When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.
- Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.
- If user experiences any difficulty operating valve discontinue use and contact supplier.
- Never attempt to repair or modify container valves or safety relief devices.
- Damaged valves should be reported immediately to the supplier.
- Keep container valve outlets clean and free from contaminants particularly oil and water.
- Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.
- Close container valve after each use and when empty, even if still connected to equipment.
- Never attempt to transfer gases from one cylinder/container to another.
- Never use direct flame or electrical heating devices to raise the pressure of a container.
- Do not remove or deface labels provided by the supplier for the identification of the content of the container.
- Suck back of water into the container must be prevented.
- Open valve slowly to avoid pressure shock.

Phosphine**NOAL_0100**

Country : SE / Language : EN

7.2. Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers.
Containers should not be stored in conditions likely to encourage corrosion.
Container valve guards or caps should be in place.
Containers should be stored in the vertical position and properly secured to prevent them from falling over.
Stored containers should be periodically checked for general condition and leakage.
Keep container below 50°C in a well ventilated place.
Store containers in location free from fire risk and away from sources of heat and ignition.
Keep away from combustible materials.
Segregate from oxidant gases and other oxidants in store.
All electrical equipment in the storage areas should be compatible with the risk of a potentially explosive atmosphere.

7.3. Specific end use(s)

None.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Phosphine (7803-51-2)	
EU - Indicative Occupational Exposure Limit (IOEL)	
Local name	Phosphine
IOEL TWA	0.14 mg/m ³
IOEL TWA [ppm]	0.1 ppm
IOEL STEL	0.28 mg/m ³
IOEL STEL [ppm]	0.2 ppm
Austria - Occupational Exposure Limits	
Local name	Phosphorwasserstoff
MAK (mg/m ³)	0.15 mg/m ³
MAK (OEL TWA) [ppm]	0.1 ppm
MAK (OEL STEL)	0.3 mg/m ³
MAK (OEL STEL) [ppm]	0.2 ppm
Belgium - Occupational Exposure Limits	
Local name	Phosphine # Fosfine
OEL TWA	0.14 mg/m ³
OEL TWA [ppm]	0.1 ppm
OEL STEL	0.28 mg/m ³
OEL STEL [ppm]	0.2 ppm
Bulgaria - Occupational Exposure Limits	
Local name	Фосфороводород (фосфин)
OEL TWA	0.14 mg/m ³

Phosphine**NOAL_0100**

Country : SE / Language : EN

OEL TWA [ppm]	0.1 ppm
OEL STEL	0.28 mg/m ³
OEL STEL [ppm]	0.2 ppm
Remark	• (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)

Croatia - Occupational Exposure Limits

Local name	Fosfin (fosforovodik)
GVI (OEL TWA) [1]	0.14 mg/m ³
GVI (OEL TWA) [2]	0.1 ppm
KGVI (OEL STEL)	0.28 mg/m ³
KGVI (OEL STEL) [ppm]	0.2 ppm
Remark	EU** F+, T+, N

Czech Republic - Occupational Exposure Limits

Local name	Fosforovodik
PEL (OEL TWA)	0.1 mg/m ³
PEL (OEL TWA) [ppm]	0.072 ppm
NPK-P (OEL C)	0.2 mg/m ³
NPK-P (OEL C) [ppm]	0.144 ppm

Denmark - Occupational Exposure Limits

Local name	Hydrogenphosphid (Phosphin; Phosphorbrite; Phosphortrihydrid)
OEL TWA [1]	0.15 mg/m ³
OEL TWA [2]	0.1 ppm

Estonia - Occupational Exposure Limits

Local name	Vesinikfosfiid (fosfiin)
OEL TWA	0.14 mg/m ³
OEL TWA [ppm]	0.1 ppm
OEL STEL	0.28 mg/m ³
OEL STEL [ppm]	0.2 ppm

Finland - Occupational Exposure Limits

Local name	Fosfiini
HTP (OEL TWA) [1]	0.14 mg/m ³
HTP (OEL TWA) [2]	0.1 ppm
HTP (OEL STEL)	0.28 mg/m ³
HTP (OEL STEL) [ppm]	0.2 ppm

France - Occupational Exposure Limits

Local name	Hydrogène phosphoré (Phosphine)
------------	---------------------------------

Phosphine**NOAL_0100**

Country : SE / Language : EN

VME (OEL TWA)	0.14 mg/m ³
VME (OEL TWA) [ppm]	0.1 ppm
VLE (OEL C/STEL)	0.28 mg/m ³
VLE (OEL C/STEL) [ppm]	0.2 ppm
Remark	Valeurs réglementaires contraignantes

Germany - Occupational Exposure Limits (TRGS 900)

Local name	Phosphin
AGW (OEL TWA) [1]	0.14 mg/m ³
AGW (OEL TWA) [2]	0.1 ppm
Remark	EU,DFG,Y

Greece - Occupational Exposure Limits

OEL TWA	0.14 mg/m ³
OEL TWA [ppm]	0.1 ppm
OEL STEL	0.28 mg/m ³
OEL STEL [ppm]	0.2 ppm

Hungary - Occupational Exposure Limits

Local name	FOSZFIN
AK (OEL TWA)	0.14 mg/m ³
CK (OEL STEL)	0.28 mg/m ³

Ireland - Occupational Exposure Limits

Local name	Phosphine
OEL TWA [1]	0.14 mg/m ³
OEL TWA [2]	0.1 ppm
OEL STEL	0.28 mg/m ³
OEL STEL [ppm]	0.2 ppm

Italy - Occupational Exposure Limits

Local name	Fosfina
OEL TWA	0.14 mg/m ³
OEL TWA [ppm]	0.1 ppm
OEL STEL	0.28 mg/m ³
OEL STEL [ppm]	0.2 ppm

Latvia - Occupational Exposure Limits

Local name	Fosfins
OEL TWA	0.14 mg/m ³
OEL TWA [ppm]	0.1 ppm
OEL STEL	0.28 mg/m ³

Phosphine

NOAL_0100

Country : SE / Language : EN

OEL STEL [ppm]	0.2 ppm
Lithuania - Occupational Exposure Limits	
Local name	Fosfinas (fosfanas, vandenilio fosfidai)
IPRV (OEL TWA)	0.14 mg/m ³
IPRV (OEL TWA) [ppm]	0.1 ppm
TPRV (OEL STEL)	0.28 mg/m ³
TPRV (OEL STEL) [ppm]	0.2 ppm
Luxembourg - Occupational Exposure Limits	
Local name	Phosphine
OEL TWA	0.14 mg/m ³
OEL STEL	0.28 mg/m ³
OEL STEL [ppm]	0.2 ppm
Malta - Occupational Exposure Limits	
Local name	Phosphine
OEL TWA	0.14 mg/m ³
OEL TWA [ppm]	0.1 ppm
OEL STEL	0.28 mg/m ³
OEL STEL [ppm]	0.2 ppm
Netherlands - Occupational Exposure Limits	
Local name	Fosfine
TGG-8u (OEL TWA)	0.14 mg/m ³
TGG-15min (OEL STEL)	0.28 mg/m ³
Poland - Occupational Exposure Limits	
Local name	Fosfan
NDS (OEL TWA)	0.14 mg/m ³
NDSch (OEL STEL)	0.28 mg/m ³
Portugal - Occupational Exposure Limits	
Local name	Fosfina
OEL TWA [ppm]	0.3 ppm
OEL STEL [ppm]	1 ppm
Romania - Occupational Exposure Limits	
Local name	Fosfina
OEL TWA	0.14 mg/m ³
OEL TWA [ppm]	0.1 ppm
OEL STEL	0.28 mg/m ³
OEL STEL [ppm]	0.2 ppm

Phosphine

NOAL_0100

Country : SE / Language : EN

Slovakia - Occupational Exposure Limits

NPHV (OEL TWA) [1]	0.14 mg/m ³
NPHV (OEL TWA) [2]	0.1 ppm
NPHV (OEL STEL)	0.28 mg/m ³

Slovenia - Occupational Exposure Limits

Local name	fosfin
OEL TWA	0.14 mg/m ³
OEL TWA [ppm]	0.1 ppm
OEL STEL	0.28 mg/m ³
OEL STEL [ppm]	0.2 ppm

Spain - Occupational Exposure Limits

Local name	Hidruro de fósforo (Fosfamina)
VLA-ED (OEL TWA) [1]	0.14 mg/m ³
VLA-ED (OEL TWA) [2]	0.1 ppm
VLA-EC (OEL STEL)	0.28 mg/m ³
VLA-EC (OEL STEL) [ppm]	0.2 ppm
Remark	VLI (Agente químico para el que la U.E. estableció en su día un valor límite indicativo. Todos estos agentes químicos figuran al menos en una de las directivas de valores límite indicativos publicadas hasta ahora (ver Anexo C. Bibliografía). Los estados miembros disponen de un tiempo fijado en dichas directivas para su transposición a los valores límites de cada país miembro. Una vez adoptados, estos valores tienen la misma validez que el resto de los valores adoptados por el país).

Sweden - Occupational Exposure Limits

Local name	Fosfin
NGV (OEL TWA)	0.14 mg/m ³ 0.14 mg/m ³
NGV (OEL TWA) [ppm]	0.1 ppm 0.1 ppm
KTV (OEL STEL)	0.28 mg/m ³ 0.28 mg/m ³
KTV (OEL STEL) [ppm]	0.2 ppm 0.2 ppm

United Kingdom - Occupational Exposure Limits

Local name	Phosphine
WEL TWA (OEL TWA) [1]	0.14 mg/m ³
WEL TWA (OEL TWA) [2]	0.1 ppm
WEL STEL (OEL STEL)	0.28 mg/m ³
WEL STEL (OEL STEL) [ppm]	0.2 ppm

Phosphine**NOAL_0100**

Country : SE / Language : EN

Iceland - Occupational Exposure Limits

Local name	Fosfin (fosfórtrihýdríð, fosfórvetni, vetnisfosfíð)
OEL TWA	0.14 mg/m ³
OEL TWA [ppm]	0.1 ppm
OEL STEL	0.28 mg/m ³
OEL STEL [ppm]	0.2 ppm

Norway - Occupational Exposure Limits

Local name	Fosfin
Grenseverdi (OEL TWA) [1]	0.15 mg/m ³
Grenseverdi (OEL TWA) [2]	0.1 ppm

Switzerland - Occupational Exposure Limits

Local name	Phosphin (s. Phosphorwasserstoff)
MAK (OEL TWA) [1]	0.15 mg/m ³ 0.15 mg/m ³
MAK (OEL TWA) [2]	0.1 ppm 0.1 ppm
KZGW (OEL STEL)	0.3 mg/m ³ 0.3 mg/m ³
KZGW (OEL STEL) [ppm]	0.2 ppm 0.2 ppm
Remark	SS _C - OAW, GIT, ZNS - NIOSH


USA - ACGIH - Occupational Exposure Limits

Local name	Phosphine
ACGIH OEL TWA [ppm]	0.1 ppm
ACGIH OEL C [ppm]	0.5 ppm
Remark (ACGIH)	URT irr; lung edema; card toxicity

Phosphine (7803-51-2)

DNEL: Derived no effect level (Workers)	
Acute - systemic effects, inhalation	0.28 mg/m ³
Long-term - systemic effects, inhalation	0.14 mg/m ³

PNEC (Predicted No-Effect Concentration) : None established.

	SAFETY DATA SHEET	Page : 12/18
		Revised edition no : 5.0
		Revision date : 2023-01-21
		Supersedes version of : 2021-11-02
Phosphine		NOAL_0100
		Country : SE / Language : EN

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Product to be handled in a closed system and under strictly controlled conditions.
 Provide adequate general and local exhaust ventilation.
 Preferably use permanent leak-tight installations (e.g. welded pipes).
 Systems under pressure should be regularly checked for leakages.
 Ensure exposure is below occupational exposure limits (where available).
 Gas detectors should be used when toxic gases may be released.
 Consider the use of a work permit system e.g. for maintenance activities.

8.2.2. Individual protection measures, e.g. personal protective equipment

A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk.

The following recommendations should be considered:

PPE compliant to the recommended EN/ISO standards should be selected.

- Eye/face protection : Wear goggles and a face shield when transfilling or breaking transfer connections.
Standard EN 166 - Personal eye-protection - specifications.
Provide readily accessible eye wash stations and safety showers.
- Skin protection
 - Hand protection : Wear chemically resistant protective gloves.
Wear working gloves when handling gas containers.
Standard EN 388 - Protective gloves against mechanical risk, performance level 1 or higher.
Standard EN 511 - Cold insulating gloves.
Standard EN 374 - Protective gloves against chemicals.
Consult glove manufacturer's product information on material suitability and material thickness.
 - Other : The breakthrough time of the selected gloves must be greater than the intended use period.
: Keep suitable chemically resistant protective clothing readily available for emergency use.
Standard EN943-1 - Full protective suits against liquid, solid and gaseous chemicals.
Consider the use of flame resistant anti-static safety clothing.
Standard EN ISO 14116 - Limited flame spread materials.
Standard EN 1149-5 - Protective clothing: Electrostatic properties.
Wear safety shoes while handling containers.
Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
- Respiratory protection : Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
Consult respiratory device supplier's product information for the selection of the appropriate device.
Keep self contained breathing apparatus readily available for emergency use.
Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
- Thermal hazards : None in addition to the above sections.

8.2.3. Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

- Physical state at 20°C / 101.3kPa : Gas
- Colour : Colourless.

Odour

- : Odourless.
- Odour threshold is subjective and inadequate to warn of overexposure.

pH

- : Not applicable for gases and gas mixtures.

Phosphine**NOAL_0100**

Country : SE / Language : EN

Melting point / Freezing point	: -134 °C
	-134 °C
Boiling point	: -88 °C
Flash point	: Not applicable for gases and gas mixtures.
Flammability	: Extremely flammable gas
Explosive limits	: Pyrophoric.
Lower explosion limit	: Not available
Upper explosion limit	: Not available
Vapour pressure [20°C]	: 34.6 bar(a)
Vapour pressure [50°C]	: 62 bar(a)
Density	: Not applicable
Vapour density	: Not applicable for gases and gas mixtures.
Relative density, liquid (water=1)	: 0.74
Relative density, gas (air=1)	: 1.2
Water solubility	: 300 mg/l
Partition coefficient n-octanol/water (Log Kow)	: Not applicable for inorganic products.
Auto-ignition temperature	: 38 °C
Decomposition temperature	: Not applicable.
Viscosity, kinematic	: No reliable data available.
Particle characteristics	: Not applicable for gases and gas mixtures.

9.2. Other information**9.2.1. Information with regard to physical hazard classes**

Explosive properties	: Not applicable.
Oxidising properties	: No oxidising properties.
Tci	: 1.7 %
Critical temperature [°C]	: 51.6 °C

9.2.2. Other safety characteristics

Molar mass	: 34 g/mol
Evaporation rate	: Not applicable for gases and gas mixtures.
Gas group	: Press. Gas (Liq.)
Other data	: Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level.

SECTION 10: Stability and reactivity**10.1. Reactivity**

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability


Stable under normal conditions.

10.3. Possibility of hazardous reactions

None.
Can form explosive mixture with air.
May react violently with oxidants.

10.4. Conditions to avoid

Avoid moisture in installation systems.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

	SAFETY DATA SHEET	Page : 14/18
		Revised edition no : 5.0
		Revision date : 2023-01-21
		Supersedes version of : 2021-11-02
Phosphine		NOAL_0100
		Country : SE / Language : EN

10.5. Incompatible materials

With water causes rapid corrosion of some metals.
 Reacts with water to form corrosive acids.
 May react violently with alkalis.
 Air, Oxidisers.
 For additional information on compatibility refer to ISO 11114.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity : Fatal if inhaled.

LC50 Inhalation - Rat [ppm]	10 ppm/4h
-----------------------------	-----------

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitisation : No known effects from this product.

Germ cell mutagenicity : No known effects from this product.

Carcinogenicity : No known effects from this product.

Toxic for reproduction : Fertility : No known effects from this product.

Toxic for reproduction : unborn child : No known effects from this product.

STOT-single exposure : Severe corrosion to the respiratory tract at high concentrations.

STOT-repeated exposure : No known effects from this product.

Aspiration hazard : Not applicable for gases and gas mixtures.

11.2. Information on other hazards

Other information : The substance/mixture has no endocrine disrupting properties.

SECTION 12: Ecological information

12.1. Toxicity

Assessment : Very toxic to aquatic life.

EC50 48h - Daphnia magna [mg/l] : No data available.

EC50 72h - Algae [mg/l] : No data available.

LC50 96 h - Fish [mg/l] : No data available.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential


No additional information available

12.4. Mobility in soil

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.
 Partition into soil is unlikely.

12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.

	SAFETY DATA SHEET	Page : 15/18
		Revised edition no : 5.0
		Revision date : 2023-01-21
		Supersedes version of : 2021-11-02
Phosphine		NOAL_0100
		Country : SE / Language : EN

12.6. Endocrine disrupting properties

The substance/mixture has no endocrine disrupting properties.

12.7. Other adverse effects

Other adverse effects : May cause pH changes in aqueous ecological systems.
Effect on the ozone layer : No effect on the ozone layer.
Effect on global warming : No known effects from this product.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Contact supplier if guidance is required.
Must not be discharged to atmosphere.
Ensure that the emission levels from local regulations or operating permits are not exceeded.
Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods.
Return unused product in original container to supplier.

List of hazardous waste codes (from Commission Decision 2000/532/EC as amended) : 16 05 04 *: Gases in pressure containers (including halons) containing hazardous substances.

13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

SECTION 14: Transport information



14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN
UN-No. : 2199

14.2. UN proper shipping name

Transport by road/rail (ADR/RID) : PHOSPHINE
Transport by air (ICAO-TI / IATA-DGR) : Phosphine
Transport by sea (IMDG) : PHOSPHINE

14.3. Transport hazard class(es)

Labelling :   

2.3 : Toxic gases.
2.1 : Flammable gases.

Transport by road/rail (ADR/RID)


Class : 2
Classification code : 2TF
Tunnel Restriction : D - Passage forbidden through tunnels of category D and E

Transport by sea (IMDG)

Class / Div. (Sub. risk(s)) : 2.3 (2.1)
Emergency Schedule (EmS) - Fire : F-D
Emergency Schedule (EmS) - Spillage : S-U

14.4. Packing group

Transport by road/rail (ADR/RID) : Not established.
Transport by air (ICAO-TI / IATA-DGR) : Not established.

	SAFETY DATA SHEET	Page : 16/18
		Revised edition no : 5.0
		Revision date : 2023-01-21
		Supersedes version of : 2021-11-02
Phosphine		NOAL_0100
		Country : SE / Language : EN

Transport by sea (IMDG) : Not established.

14.5. Environmental hazards

Transport by road/rail (ADR/RID) : Environmentally hazardous substance / mixture.
 Transport by air (ICAO-TI / IATA-DGR) : Environmentally hazardous substance / mixture.
 Transport by sea (IMDG) : Marine pollutant

14.6. Special precautions for user

Packing Instruction(s)

Transport by road/rail (ADR/RID) : P200
 Transport by air (ICAO-TI / IATA-DGR)
 Passenger and Cargo Aircraft : Forbidden.
 Cargo Aircraft only : Forbidden.
 Transport by sea (IMDG) : P200

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment.
 Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.
 Before transporting product containers:
 - Ensure there is adequate ventilation.
 - Ensure that containers are firmly secured.
 - Ensure valve is closed and not leaking.
 - Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
 - Ensure valve protection device (where provided) is correctly fitted.

14.7. Maritime transport in bulk according to IMO instruments

Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU-Regulations

Restrictions on use : None.
 Seveso Directive : 2012/18/EU (Seveso III) : Covered.

National regulations

Ensure all national/local regulations are observed.

Germany

Water hazard class (WGK) : WGK 2, Significantly hazardous to water (Classification according to AwSV)
 National Rules and Recommendations : [German regulations] BetriebssicherheitsV mit TRBSen insbesondere TRBS 3145 / TRGS 725 Ortsbewegliche Druckgasbehälter", TRBS 2141, BGR Regel 500 Teil 2.33: "Umgang mit Gasen", GefahrstoffV mit Technischen Regeln Gefährliche Stoffe TRGS insbesondere TRGS 407 "Tätigkeiten mit Gasen - Gefährdungsbeurteilung", TRGS 400, 500, 510, 900." BGR 104, TRBS 2152.

Netherlands


SZW-lijst van kankerverwekkende stoffen : The substance is not listed
 SZW-lijst van mutagene stoffen : The substance is not listed
 SZW-lijst van reprotoxische stoffen – Borstvoeding : The substance is not listed
 SZW-lijst van reprotoxische stoffen – Vruchtbaarheid : The substance is not listed
 SZW-lijst van reprotoxische stoffen – Ontwikkeling : The substance is not listed

Denmark

Danish National Regulations : Young people below the age of 18 years are not allowed to use the product

Switzerland

Storage class (LK) : LK 2 - Liquefied or pressurized gases

	SAFETY DATA SHEET	Page : 17/18
		Revised edition no : 5.0
		Revision date : 2023-01-21
		Supersedes version of : 2021-11-02
Phosphine		NOAL_0100
		Country : SE / Language : EN


15.2. Chemical safety assessment

A CSA does not need to be carried out for this product.

SECTION 16: Other information

Indication of changes	: Safety data sheet in accordance with commission regulation (EU) No 2020/878.
Abbreviations and acronyms	: ATE - Acute Toxicity Estimate CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008 REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006 EINECS - European Inventory of Existing Commercial Chemical Substances CAS# - Chemical Abstract Service number PPE - Personal Protection Equipment LC50 - Lethal Concentration to 50 % of a test population RMM - Risk Management Measures PBT - Persistent, Bioaccumulative and Toxic vPvB - Very Persistent and Very Bioaccumulative STOT- SE : Specific Target Organ Toxicity - Single Exposure CSA - Chemical Safety Assessment EN - European Standard UN - United Nations ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road IATA - International Air Transport Association IMDG code - International Maritime Dangerous Goods RID - Regulations concerning the International Carriage of Dangerous Goods by Rail WGK - Water Hazard Class STOT - RE : Specific Target Organ Toxicity - Repeated Exposure UFI : Unique Formula Identifier
Training advice	: Users of breathing apparatus must be trained. Ensure operators understand the flammability hazard. Ensure operators understand the toxicity hazard.
Further information	: Classification in accordance with the procedures and calculation methods of Regulation (EC) 1272/2008 (CLP). Key literature references and sources of data are maintained in EIGA doc 169 : 'Classification and Labelling Guide', downloadable at http://www.Eiga.eu .

Full text of H- and EUH-statements	
Acute Tox. 1 (Inhalation:gas)	Acute toxicity (inhalation:gas) Category 1
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
EUH071	Corrosive to the respiratory tract.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Flam. Gas 1A	Flammable gases, Category 1A
H220	Extremely flammable gas.
H280	Contains gas under pressure; may explode if heated.
H314	Causes severe skin burns and eye damage.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.

	SAFETY DATA SHEET	Page : 18/18
		Revised edition no : 5.0
		Revision date : 2023-01-21
		Supersedes version of : 2021-11-02
Phosphine		NOAL_0100
		Country : SE / Language : EN
Press. Gas (Liq.)	Gases under pressure : Liquefied gas	
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B	

DISCLAIMER OF LIABILITY

: Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.
 Details given in this document are believed to be correct at the time of going to press.
 Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted.

End of document