



# SAFETY DATA SHEET

Page : 1/11

Revised edition no : 7.0

Revision date : 2025-03-04

Supersedes version of : 2024-05-24

**Sulphur dioxide****NOAL\_0113**

Country : SE / Language : EN

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

Trade name : Sulphur dioxide  
SDS no : NOAL\_0113  
Other means of identification : Sulphur dioxide  
CAS-No. : 7446-09-5  
EC-No. : 231-195-2  
EC Index-No. : 016-011-00-9  
REACH registration No : 01-2119485028-34  
Chemical formula : SO<sub>2</sub>

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses : Industrial and professional uses. Perform risk assessment prior to use.  
See the list of identified uses and exposure scenarios in the annex of the safety data sheet.  
Contact supplier for more information on uses.  
Uses advised against : Consumer use.

### 1.3. Details of the supplier of the safety data sheet

#### Company identification

##### Supplier

AIR LIQUIDE GAS AB  
Pulpetgatan 20  
215 37 Malmö - SWEDEN  
T +46 40 38 10 00

E-Mail address (competent person) : eunordic-sds@airliquide.com

### 1.4. Emergency telephone number


| Country | Organisation/Company      | Address                            | Emergency number            | Comment |
|---------|---------------------------|------------------------------------|-----------------------------|---------|
| Sweden  | Giftinformationscentralen | Solna Strandväg 21<br>171 54 Solna | 112 – begär Giftinformation |         |

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

#### Classification according to Regulation (EC) No. 1272/2008 [CLP]





|                  |  |      |
|------------------|--|------|
| Physical hazards | Gases under pressure : Liquefied gas                         | H280 |
| Health hazards   | Acute toxicity (inhalation:gas) Category 3                   | H331 |
|                  | Skin corrosion/irritation, Category 1, Sub-Category 1B       | H314 |
|                  | Serious eye damage/eye irritation, Category 1                | H318 |
|                  | Specific target organ toxicity – single exposure, Category 1 | H370 |

|   |                   |                                    |
|---|-------------------|------------------------------------|
|  | SAFETY DATA SHEET | Page : 2/11                        |
|   |                   | Revised edition no : 7.0           |
|   |                   | Revision date : 2025-03-04         |
|   |                   | Supersedes version of : 2024-05-24 |
| Sulphur dioxide   |                   | NOAL_0113                          |
|   |                   | Country : SE / Language : EN       |

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)

GHS04

GHS05

GHS06

GHS08

Signal word (CLP)

: Danger

Hazard statements (CLP)

: H314 - Causes severe skin burns and eye damage.  
H280 - Contains gas under pressure; may explode if heated.  
H331 - Toxic if inhaled.  
H370 - Causes damage to organs.

Precautionary statements (CLP)

- Prevention

: P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection.  
P271 - Use only outdoors or in a well-ventilated area.  
P260 - Do not breathe dust/fume/gas/mist/vapours/spray.  
P264 - Wash hands, forearms and face thoroughly after handling.  
P270 - Do not eat, drink or smoke when using this product.  
P308+P311 - IF exposed or concerned: Call a POISON CENTER or doctor.  
P321 - Specific treatment (see supplemental first aid instruction on this label).  
P304+P340 - IF INHALED: Remove person to fresh air and keep comfortable for breathing.  
P310 - Immediately call a POISON CENTER or doctor.  
P301+P330+P331 - IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.  
P303+P361+P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water .  
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

- Storage

: P403+P233 - Store in a well-ventilated place. Keep container tightly closed.  
P405 - Store locked up.  
P410+P403 - Protect from sunlight. Store in a well-ventilated place.

- Disposal considerations

: P501 - Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

2.3. Other hazards


None.  
Not classified as PBT or vPvB.

SECTION 3: Composition/information on ingredients

3.1. Substances

| Name            | Product identifier   | Composition [V-%]: | Classification according to Regulation (EC) No. 1272/2008 [CLP]  |
|-----------------|--|--------------------|--|
| Sulphur dioxide | CAS-No.: 7446-09-5<br>EC-No.: 231-195-2<br>EC Index-No.: 016-011-00-9<br>REACH registration No: 01-2119485028-34 | 100                | Press. Gas (Liq.), H280<br>Acute Tox. 3 (Inhalation:gas), H331<br>Skin Corr. 1B, H314<br>Eye Dam. 1, H318<br>STOT SE 1, H370 |

Contains no other components or impurities which will influence the classification of the product.

|   |                              |                                    |
|---|------------------------------|------------------------------------|
|  | <b>SAFETY DATA SHEET</b>     | Page : 3/11                        |
|   |                              | Revised edition no : 7.0           |
|   |                              | Revision date : 2025-03-04         |
|   |                              | Supersedes version of : 2024-05-24 |
| <b>Sulphur dioxide</b>  | <b>NOAL_0113</b>             |                                    |
|   | Country : SE / Language : EN |                                    |

### 3.2. Mixtures

Not established.

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

- Inhalation : Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Perform cardiopulmonary resuscitation if breathing stopped.
- Skin contact : Remove contaminated clothing. Drench affected area with water for at least 15 minutes. In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.
- Eye contact : Immediately flush eyes thoroughly with water for at least 15 minutes.
- Ingestion : Ingestion is not considered a potential route of exposure.

### 4.2. Most important symptoms and effects, both acute and delayed

May cause severe chemical burns to skin and cornea. Suitable first-aid treatment should be immediately available. Seek medical advice before using product.  
Prolonged exposure to small concentrations may result in pulmonary oedema.  
Material is destructive to tissue of the mucuous membranes and upper respiratory tract.  
Cough, shortness of breath, headache, nausea.  
See section 11.

### 4.3. Indication of any immediate medical attention and special treatment needed

Obtain medical assistance.  
Treat with corticosteroid spray as soon as possible after inhalation.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media


- Suitable extinguishing media : Water spray or fog.
- Unsuitable extinguishing media : Do not use water jet to extinguish.

### 5.2. Special hazards arising from the substance or mixture

- Specific hazards : Exposure to fire may cause containers to rupture/explode.
- Hazardous combustion products : None that are more hazardous than the product itself.

### 5.3. Advice for firefighters

- Specific methods : Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas receptacles to rupture. Cool endangered receptacles with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.  
If possible, stop flow of product.  
Use water spray or fog to knock down fire fumes if possible.  
Move containers away from the fire area if this can be done without risk.
- Special protective equipment for fire fighters : Wear gas tight chemically protective clothing in combination with self contained breathing apparatus.  
Standard EN 943-2: Protective clothing against liquid and gaseous chemicals, aerosols and solid particles. Gas-tight chemical protective suits for emergency teams.  
Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.

|   |                              |                                    |
|---|------------------------------|------------------------------------|
|  | <b>SAFETY DATA SHEET</b>     | Page : 4/11                        |
|   |                              | Revised edition no : 7.0           |
|   |                              | Revision date : 2025-03-04         |
|   |                              | Supersedes version of : 2024-05-24 |
| <b>Sulphur dioxide</b>  | <b>NOAL_0113</b>             |                                    |
|   | Country : SE / Language : EN |                                    |

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

Try to stop release.  
 Evacuate area.  
 Monitor concentration of released product.  
 Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.  
 Use chemically protective clothing.  
 Ensure adequate air ventilation.  
 Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.  
 Act in accordance with local emergency plan.  
 Stay upwind.

### 6.2. Environmental precautions

Reduce vapour with fog or fine water spray.  
 Try to stop release.

### 6.3. Methods and material for containment and cleaning up

Hose down area with water.  
 Keep area evacuated and free from ignition sources until any spilled liquid has evaporated (ground free from frost).  
 Wash contaminated equipment or sites of leaks with copious quantities of water.

### 6.4. Reference to other sections


See also sections 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Safe use of the product

: Do not breathe gas.  
 Avoid release of product into atmosphere.  
 The product must be handled in accordance with good industrial hygiene and safety procedures.  
 Only experienced and properly instructed persons should handle gases under pressure.  
 Consider pressure relief device(s) in gas installations.  
 Ensure the complete gas system was (or is regularly) checked for leaks before use.  
 Do not smoke while handling product.  
 Avoid exposure, obtain special instructions before use.  
 Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Contact your gas supplier if in doubt.  
 Installation of a cross purge assembly between the container and the regulator is recommended.  
 Purge system with dry inert gas (e.g. helium or nitrogen) before gas is introduced and when system is placed out of service.  
 Avoid suck back of water, acid and alkalis.

|   |                   |                                    |
|---|-------------------|------------------------------------|
|  | SAFETY DATA SHEET | Page : 5/11                        |
|   |                   | Revised edition no : 7.0           |
|   |                   | Revision date : 2025-03-04         |
|   |                   | Supersedes version of : 2024-05-24 |
| Sulphur dioxide   | NOAL_0113         | Country : SE / Language : EN       |

Safe handling of the gas receptacle

: Refer to supplier's container handling instructions.  
Do not allow backfeed into the container.  
Protect containers from physical damage; do not drag, roll, slide or drop.  
When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders.  
Leave valve protection caps in place until the container has been secured against either a wall or bench or placed in a container stand and is ready for use.  
If user experiences any difficulty operating valve discontinue use and contact supplier.  
Never attempt to repair or modify container valves or safety relief devices.  
Damaged valves should be reported immediately to the supplier.  
Keep container valve outlets clean and free from contaminants particularly oil and water.  
Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.  
Close container valve after each use and when empty, even if still connected to equipment.  
Never attempt to transfer gases from one cylinder/container to another.  
Never use direct flame or electrical heating devices to raise the pressure of a container.  
Do not remove or deface labels provided by the supplier for the identification of the content of the container.  
Suck back of water into the container must be prevented.  
Open valve slowly to avoid pressure shock.

7.2. Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers.  
Containers should not be stored in conditions likely to encourage corrosion.  
Container valve guards or caps should be in place.  
Containers should be stored in the vertical position and properly secured to prevent them from falling over.  
Stored containers should be periodically checked for general condition and leakage.  
Keep container below 50°C in a well ventilated place.  
Store containers in location free from fire risk and away from sources of heat and ignition.  
Keep away from combustible materials.

7.3. Specific end use(s)


None.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

|  |              |
|--|--------------|
| <b>Sulphur dioxide (7446-09-5)</b>           |              |
| <b>Sweden - Occupational Exposure Limits</b> |              |
| Local name                                   | Svaveldioxid |
| NGV (OEL TWA)                                | 1.3 mg/m³    |
|  | 0.5 ppm      |
| KGV (OEL STEL)                               | 2.7 mg/m³    |
|  | 1 ppm        |

|   |           |
|---|-----------|
| <b>Sulphur dioxide (7446-09-5)</b>      |           |
| DNEL: Derived no effect level (Workers) |           |
| Acute - local effects, inhalation       | 2.7 mg/m³ |
| Long-term - local effects, inhalation   | 1.3 mg/m³ |

|   |                            |                                    |
|---|----------------------------|------------------------------------|
|  | <h1>SAFETY DATA SHEET</h1> | Page : 6/11                        |
|   |                            | Revised edition no : 7.0           |
|   |                            | Revision date : 2025-03-04         |
|   |                            | Supersedes version of : 2024-05-24 |
| <h2>Sulphur dioxide</h2>  | <h3>NOAL_0113</h3>         | Country : SE / Language : EN       |

PNEC (Predicted No-Effect Concentration) : None established.

### 8.2. Exposure controls

#### 8.2.1. Appropriate engineering controls

Provide adequate general and local exhaust ventilation.  
Product to be handled in a closed system.  
Systems under pressure should be regularly checked for leakages.  
Ensure exposure is below occupational exposure limits (where available).  
Gas detectors should be used when toxic gases may be released.  
Consider the use of a work permit system e.g. for maintenance activities.

#### 8.2.2. Individual protection measures, e.g. personal protective equipment

- A risk assessment should be conducted and documented in each work area to assess the risks related to the use of the product and to select the PPE that matches the relevant risk. The following recommendations should be considered:  
PPE compliant to the recommended EN/ISO standards should be selected.
- Eye/face protection :
    - Wear goggles and a face shield when transfilling or breaking transfer connections.
    - Standard EN 166 - Personal eye-protection - specifications.
    - Provide readily accessible eye wash stations and safety showers.
  - Skin protection
    - Hand protection :
      - Wear working gloves when handling gas containers.
      - Wear chemically resistant protective gloves.
      - Standard EN 388 - Protective gloves against mechanical risks, performance level 1 or higher. Recommended types include wrist gloves from leather or synthetic material with equivalent performance, fabric gloves, fabric gloves with leather palms.
      - Wear cold insulating gloves when transfilling or breaking transfer connections.
      - Standard EN 511 - Cold insulating gloves, performance level 1 or higher. Recommended types include insulated gauntlets or gloves specifically selected to prevent liquid penetration and ingress of cryogenic liquids and to provide mechanical resistance.
      - Standard EN 374 - Protective gloves against chemicals.
      - Chloroprene rubber (Neoprene®) (CR).
    - Other :
      - Keep suitable chemically resistant protective clothing readily available for emergency use.
      - Standard EN943-1 - Full protective suits against liquid, solid and gaseous chemicals.
      - Wear safety shoes while handling containers.
      - Standard EN ISO 20345 - Personal protective equipment - Safety footwear.
  - Respiratory protection :
    - Gas filters may be used if all surrounding conditions e.g. type and concentration of the contaminant(s) and duration of use are known.
    - Use gas filters with full face mask, where exposure limits may be exceeded for a short-term period, e.g. connecting or disconnecting containers.
    - Standard EN 137 - Self-contained open-circuit compressed air breathing apparatus with full face mask.
    - Recommended: Filter E (yellow).
    - Gas filters do not protect against oxygen deficiency.
    - Standard EN 14387 - Gas filter(s), combined filter(s) and standard EN136, full face masks .
    - Keep self contained breathing apparatus readily available for emergency use.
    - Self contained breathing apparatus is recommended, where unknown exposure may be expected, e.g. during maintenance activities on installation systems.
  - Thermal hazards : None in addition to the above sections.


#### 8.2.3. Environmental exposure controls

Refer to local regulations for restriction of emissions to the atmosphere. See section 13 for specific methods for waste gas treatment.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Appearance

|   |                   |                                    |
|---|-------------------|------------------------------------|
|  | SAFETY DATA SHEET | Page : 7/11                        |
|   |                   | Revised edition no : 7.0           |
|   |                   | Revision date : 2025-03-04         |
|   |                   | Supersedes version of : 2024-05-24 |
| Sulphur dioxide   | NOAL_0113         |                                    |
|   |                   | Country : SE / Language : EN       |

|   |   |
|---|---|
| - Physical state at 20°C / 101.3kPa             | : Gas   |
| - Colour  | : Colourless.   |
| Odour   | : Pungent.  |
|   | Odour threshold is subjective and inadequate to warn of overexposure. |
| pH  | : If dissolved in water pH-value will be affected.                    |
| Melting point / Freezing point                  | : -75.5 °C  |
|   | -75.5 °C  |
| Boiling point                                   | : -10 °C  |
| Flash point                                     | : Not applicable for gases and gas mixtures.                          |
| Flammability                                    | : Non flammable.  |
| Explosive limits                                | : Non flammable.  |
| Lower explosion limit                           | : Not available   |
| Upper explosion limit                           | : Not available   |
| Vapour pressure [20°C]                          | : 3.3 bar(a)  |
| Vapour pressure [50°C]                          | : 8.4 bar(a)  |
| Density   | : Not applicable  |
| Vapour density                                  | : Not applicable.   |
| Relative density, liquid (water=1)              | : 1.5   |
| Relative density, gas (air=1)                   | : 2.3   |
| Water solubility                                | : Completely soluble.   |
| Partition coefficient n-octanol/water (Log Kow) | : Not applicable for inorganic products.                              |
| Auto-ignition temperature                       | : Non flammable.  |
| Decomposition temperature                       | : Not applicable.   |
| Viscosity, kinematic                            | : No reliable data available.   |
| Particle characteristics                        | : Not applicable  |

9.2. Other information

9.2.1. Information with regard to physical hazard classes

|                           |                   |
|---------------------------|-------------------|
| Explosive properties      | : Not applicable. |
| Oxidising properties      | : Not applicable. |
| Critical temperature [°C] | : 158 °C          |

9.2.2. Other safety characteristics

|                  |  |
|------------------|--|
| Molar mass       | : 64 g/mol   |
| Evaporation rate | : Not applicable for gases and gas mixtures.   |
| Gas group        | : Press. Gas (Liq.)  |
| Other data       | : Gas/vapour heavier than air. May accumulate in confined spaces, particularly at or below ground level. |

SECTION 10: Stability and reactivity

10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

10.2. Chemical stability


Stable under normal conditions.

10.3. Possibility of hazardous reactions

None.

10.4. Conditions to avoid

Avoid moisture in installation systems.

|   |                              |                                    |
|---|------------------------------|------------------------------------|
|  | <b>SAFETY DATA SHEET</b>     | Page : 8/11                        |
|   |                              | Revised edition no : 7.0           |
|   |                              | Revision date : 2025-03-04         |
|   |                              | Supersedes version of : 2024-05-24 |
| <b>Sulphur dioxide</b>  | <b>NOAL_0113</b>             |                                    |
|   | Country : SE / Language : EN |                                    |

#### 10.5. Incompatible materials

Reacts with water to form corrosive acids.  
 May react violently with alkalis.  
 Reacts with most metals in the presence of moisture, liberating hydrogen, an extremely flammable gas.  
 With water causes rapid corrosion of some metals.  
 Moisture.  
 For additional information on compatibility refer to ISO 11114.

#### 10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

### SECTION 11: Toxicological information

#### 11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

**Acute toxicity** : Toxic if inhaled.  
 Delayed fatal pulmonary oedema possible.

|                             |             |
|-----------------------------|-------------|
| LC50 Inhalation - Rat [ppm] | 1260 ppm/4h |
|-----------------------------|-------------|

**Skin corrosion/irritation** : Causes severe skin burns and eye damage.  
**Serious eye damage/irritation** : Causes serious eye damage.  
**Respiratory or skin sensitisation** : No known effects from this product.  
**Germ cell mutagenicity** : No known effects from this product.  
**Carcinogenicity** : No known effects from this product.  
**Toxic for reproduction : Fertility** : No known effects from this product.  
**Toxic for reproduction : unborn child** : No known effects from this product.  
**STOT-single exposure** : Severe corrosion to the respiratory tract at high concentrations.  
**STOT-repeated exposure** : No known effects from this product.  
**Aspiration hazard** : Not applicable for gases and gas mixtures.

#### 11.2. Information on other hazards

Other information : The substance/mixture has no endocrine disrupting properties.

### SECTION 12: Ecological information

#### 12.1. Toxicity

Assessment : Classification criteria are not met.  
 EC50 48h - Daphnia magna [mg/l] : 89 mg/l  
 EC50 72h - Algae [mg/l] : 48.1 mg/l  
 LC50 96 h - Fish [mg/l] : No data available.

#### 12.2. Persistence and degradability

Assessment : Not applicable for inorganic products.

#### 12.3. Bioaccumulative potential

Assessment : Product is an inorganic gas with a low potential to bioaccumulate in aquatic species.


#### 12.4. Mobility in soil

Assessment : Because of its high volatility, the product is unlikely to cause ground or water pollution.  
 Partition into soil is unlikely.

#### 12.5. Results of PBT and vPvB assessment

Assessment : Not classified as PBT or vPvB.



|   |                              |                                    |
|---|------------------------------|------------------------------------|
|  | <b>SAFETY DATA SHEET</b>     | Page : 9/11                        |
|   |                              | Revised edition no : 7.0           |
|   |                              | Revision date : 2025-03-04         |
|   |                              | Supersedes version of : 2024-05-24 |
| <b>Sulphur dioxide</b>  | <b>NOAL_0113</b>             |                                    |
|   | Country : SE / Language : EN |                                    |

#### Sulphur dioxide (7446-09-5)

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

#### 12.6. Endocrine disrupting properties

No additional information available

#### 12.7. Other adverse effects

Other adverse effects : May cause pH changes in aqueous ecological systems.  
Effect on the ozone layer : None.  
Effect on global warming : No known effects from this product.

### SECTION 13: Disposal considerations

#### 13.1. Waste treatment methods

Contact supplier if guidance is required.  
Must not be discharged to atmosphere.  
Gas may be scrubbed in alkaline solution under controlled conditions to avoid violent reaction.  
Ensure that the emission levels from local regulations or operating permits are not exceeded.  
Refer to the EIGA code of practice Doc.30 "Disposal of Gases", downloadable at <http://www.eiga.org> for more guidance on suitable disposal methods.  
Return unused product in original container to supplier.  
List of hazardous waste codes (from Commission Decision 2000/532/EC as amended) : 16 05 04 \*: Gases in pressure containers (including halons) containing hazardous substances.

#### 13.2. Additional information

External treatment and disposal of waste should comply with applicable local and/or national regulations.

### SECTION 14: Transport information

#### 14.1. UN number or ID number

In accordance with ADR / RID / IMDG / IATA / ADN  
UN-No. : 1079

#### 14.2. UN proper shipping name


Transport by road/rail/inland waterways (ADR/RID/ADN) : SULPHUR DIOXIDE  
Transport by air (ICAO-TI / IATA-DGR) : Sulphur dioxide  
Transport by sea (IMDG) : SULPHUR DIOXIDE

#### 14.3. Transport hazard class(es)

Labelling



2.3 : Toxic gases.  
8 : Corrosive substances.

|   |                              |                                    |
|---|------------------------------|------------------------------------|
|  | <b>SAFETY DATA SHEET</b>     | Page : 10/11                       |
|   |                              | Revised edition no : 7.0           |
|   |                              | Revision date : 2025-03-04         |
|   |                              | Supersedes version of : 2024-05-24 |
| <b>Sulphur dioxide</b>  | <b>NOAL_0113</b>             |                                    |
|   | Country : SE / Language : EN |                                    |

**Transport by road/rail/inland waterways  
(ADR/RID/ADN)**

Class : 2  
Classification code : 2TC  
Hazard identification number : 268  
Tunnel Restriction : C/D - Tank carriage: Passage forbidden through tunnels of category C, D and E. Other carriage: Passage forbidden through tunnels of category D and E

**Transport by sea (IMDG)**

Class / Div. (Sub. risk(s)) : 2.3 (8)  
Emergency Schedule (EmS) - Fire : F-C  
Emergency Schedule (EmS) - Spillage : S-U

**14.4. Packing group**

Transport by road/rail/inland waterways (ADR/RID/ADN) : Not established.  
Transport by air (ICAO-TI / IATA-DGR) : Not established.  
Transport by sea (IMDG) : Not established.

**14.5. Environmental hazards**

Transport by road/rail/inland waterways (ADR/RID/ADN) : None.  
Transport by air (ICAO-TI / IATA-DGR) : None.  
Transport by sea (IMDG) : None.

**14.6. Special precautions for user**

**Packing Instruction(s)**

Transport by road/rail/inland waterways (ADR/RID/ADN) : P200  
Transport by air (ICAO-TI / IATA-DGR)  
Passenger and Cargo Aircraft : Forbidden.  
Cargo Aircraft only : Forbidden.  
Transport by sea (IMDG) : P200

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment.  
Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.  
Before transporting product containers:  
- Ensure there is adequate ventilation.  
- Ensure that containers are firmly secured.  
- Ensure valve is closed and not leaking.  
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.  
- Ensure valve protection device (where provided) is correctly fitted.

**14.7. Maritime transport in bulk according to IMO instruments**

Not applicable.

**SECTION 15: Regulatory information**


**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture**

**EU-Regulations**

Restrictions on use : None.  
National legislation : Ensure all national/local regulations are observed.  
Seveso Directive : 2012/18/EU (Seveso III) : Covered.

**National regulations**

No additional information available

|   |                   |                                    |
|---|-------------------|------------------------------------|
|  | SAFETY DATA SHEET | Page : 11/11                       |
|   |                   | Revised edition no : 7.0           |
|   |                   | Revision date : 2025-03-04         |
|   |                   | Supersedes version of : 2024-05-24 |
| Sulphur dioxide   |                   | NOAL_0113                          |
|   |                   | Country : SE / Language : EN       |

**15.2. Chemical safety assessment**

A CSA has been carried out.

**SECTION 16: Other information**

|                            |   |
|----------------------------|---|
| Indication of changes      | : Safety data sheet in accordance with commission regulation (EU) No 2020/878.  |
| Abbreviations and acronyms | : ATE - Acute Toxicity Estimate<br>CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008<br>REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006<br>EINECS - European Inventory of Existing Commercial Chemical Substances<br>CAS# - Chemical Abstract Service number<br>PPE - Personal Protection Equipment<br>LC50 - Lethal Concentration to 50 % of a test population<br>RMM - Risk Management Measures<br>PBT - Persistent, Bioaccumulative and Toxic<br>vPvB - Very Persistent and Very Bioaccumulative<br>STOT- SE : Specific Target Organ Toxicity - Single Exposure<br>CSA - Chemical Safety Assessment<br>EN - European Standard<br>UN - United Nations<br>ADR - Agreement concerning the International Carriage of Dangerous Goods by Road<br>IATA - International Air Transport Association<br>IMDG code - International Maritime Dangerous Goods<br>RID - Regulations concerning the International Carriage of Dangerous Goods by Rail<br>WGK - Water Hazard Class<br>STOT - RE : Specific Target Organ Toxicity - Repeated Exposure |
| Training advice            | : Users of breathing apparatus must be trained.<br>Ensure operators understand the toxicity hazard.   |

| Full text of H- and EUH-statements |  |
|------------------------------------|--|
| Acute Tox. 3 (Inhalation:gas)      | Acute toxicity (inhalation:gas) Category 3                   |
| Eye Dam. 1                         | Serious eye damage/eye irritation, Category 1                |
| H280                               | Contains gas under pressure; may explode if heated.          |
| H314                               | Causes severe skin burns and eye damage.                     |
| H318                               | Causes serious eye damage.                                   |
| H331                               | Toxic if inhaled.  |
| H370                               | Causes damage to organs.                                     |
| Press. Gas (Liq.)                  | Gases under pressure : Liquefied gas                         |
| Skin Corr. 1B                      | Skin corrosion/irritation, Category 1, Sub-Category 1B       |
| STOT SE 1                          | Specific target organ toxicity – single exposure, Category 1 |

|                         |   |
|-------------------------|---|
| DISCLAIMER OF LIABILITY | : Before using this product in any new process or experiment, a thorough material compatibility and safety study should be carried out.<br>Details given in this document are believed to be correct at the time of going to press.<br>Whilst proper care has been taken in the preparation of this document, no liability for injury or damage resulting from its use can be accepted. |
| <b>End of document</b>  |   |